NASA

MODEL AERODYNAMIC TEST RESULTS FOR TWO VARIABLE CYCLE ENGINE COANNULAR EXHAUST SYSTEMS AT SIMULATED TAKEOFF AND CRUISE CONDITIONS

COMPREHENSIVE DATE REPORT
VOLUME II
TABULATED AERODYNAMIC DATA
BOOK 1

By D.P. Nelson

Commercial Products Division
Pratt & Whitney Aircraft Group
United Technologies Corporation

Prepared for
NATIONAL AERONAUTICS AND SPACE ADMINISTRATION
Lewis Research Center
Under
Contract NAS3-20061

1 Report No	2 Government Accession No	3 Recipient's Catalog No
CR-159819		

4 Title and Subtitle	5 Report Date
Model Aerodynamic Test Results for Two Variable Cycle Engine Coannular Exhaust Systems at Takeoff and Cruise Conditions - Comprehesive Data Report	January 1981
	6 Performing Organization Code

7. Author(s)	8. Performing Organization Report No.
D.P. Nelson	PWA-5550-50
	10. Work Unit No

9 Performing Organization Name and Address	
Pratt & Whitney Aircraft Group Commercial Products Division United Technologies Corporation East Hartford, Connecticut 06108	11. Contract or Grant No.
	NAS3-20061
	13. Type of Report and Period Covered

12 Sponsoring Agency Name and Address	Contractor Report
NASA Lewis Research Center Cleveland, Ohio 44135	14. Sponsoring Agency Code

15. Supplementary Notes

Project Manager: A. G. Powers, NASA Lewis Research Center

16 Abstract

Wind tunnel tests were conducted to evaluate the aerodynamic performance of an advanced coannular exhaust nozzle for a future supersonic propulsion system. Tests were conducted with two test configurations: 1) a short flap mechanism for fan stream control with an isentropic contoured flow splitter, and 2) an iris fan nozzle with a conical flow splitter. Both designs feature a translating primary plug and an auxiliary inlet ejector.

Tests were conducted at takeoff and simulated cruise conditions. Data were acquired at Mach numbers of 0, 0.36, 0.9, and 2.0 for a wide range of nozzle operating conditions. At simulated supersonic cruise, both configurations demonstrated good performance, comparable to levels assumed in earlier advanced supersonic propulsion studies. However, at subsonic cruise, both configurations exhibited performance that was 6 to 7.5 percent less than the study assumptions. At take-off conditions, the iris configuration performance approached the assumed levels, while the short flap design was 4 to 6 percent less.

17. Key Words (Suggested by Author(s))	18. Distribution Statement
Short Flap Ejector Iris Flap Ejector Coannular Exhaust Nozzle Inverted Velocity Profile	

19. Security Classif (of this report)	20. Security Classif. (of this page)	21. No. of Pages	22. Price*
Unclassified	Unclassified	2226	

NASA-C-168 (Rev 10-75)

FOREWORD

This report documents the work performed during the Nozzle Performance Tests (Task III) of Contract NAS3-20061. Because of the large amount of information, this report is presented in three Volumes to facilitate its use.

Volume I contains the design layouts and detailed design drawings of the nozzle models.

Volume II contains the tabular aerodynamic data generated in this program.

Volume III contains a graphical presentation of the data.

A complete description of the test hardware and test facilities is contained in the companion Task III Final Report, CR-159818. Significant test results and conclusions are also included in the Final Report.

TABLE OF CONTENTS

iii

1. Introduction

Tabulated aerodynamic data presented in this volume were acquired during the scale model nozzle performance wind tunnel test.

Section 2 contains an index that can be used to locate the tabulated data obtained during this program.

Section 3 provides a description of the tabulated data parameters.

The aerodynamic data presented in Section 5 include:

- o   Nozzle thrust coefficient parameters
- o   Nozzle discharge coefficients
- o   Static pressure tap measurements

2. Tabulated Data Index

The tabulated data are organized by run number sequence with each run number representing a specific test configuration. Each run is comprised of a sequence of reading numbers that represent specific data points for discrete nozzle operating conditions and tunnel Mach number.

A data matrix is provided in Table 2-I which relates each test configuration and nominal Mach number to the corresponding run number and reading numbers comprising that run. For example, to locate the data for the short flap nozzle subsonic cruise configuration C_2 tested at an ejector inlet position of 0.46 and clamshell angle of 17° at 0.9 Mach number, we find the desired run number is 30 and the reading numbers are (1718-1751).

TABLE 2-I

DATA MATRIX GUIDE

o **Supersonic Cruise Data**

- Short flap nozzle-supersonic cruise configuration C_1

$M_0 = 2.0$

W_s corr	0	0.02	0.04
Run No. (RD'G No.)	14 (1039-1070)	15 (1071-1102)	16 (1103-1144)

- Iris flap nozzle-supersonic cruise configuration A_1

$M_0 = 2.0$

W_s corr	0	0.02	0.04
Run No. (RD'G No.)	18 (1155-1184)	20 (1248-1277)	19 (1205-1235)

o **Subsonic Cruise Data**

- Short flap nozzle-subsonic cruise configuration C_2

Ejector Inlet Position A_{inlet}/A_9	M_0	13°	Clamshell angle 17°	21°	Removed
(Mid) 0.46	0.9	29(1685-1717)	30(1718-1751)	31(1752-1785)	46(2265-2278)
(Mid) 0.46	0 & 0.9	-	-	-	47(2279-2292)
(Mid) 0.46	vary 0 to 0.95	-	45(2224-2264)	-	-
(Min) 0.36	0 & 0.9	-	-	32(1786-1828)	-

TABLE 2-1 (Cont'd)

- Iris flap nozzle-subsonic cruise configuration A_2

Ejector Inlet Position A_{inlet}/A_9	M_o	13°	Clamshell angle 17°	21°	Removed
(Mid) 0.63	0.9	-	-	33(1829-1863)	-
(Mid) 0.63	0 & 0.9				38(2001-2058)
(Mid) 0.63	vary 0 to 0.95	-	44(2171-2223)		
(Modified) 0.42	0.9	-	-	-	39(2059-2090)
Ejector Removed	vary 0 to 0.95				63(2771-2820)

o   Takeoff Data

- Short flap nozzle-takeoff configuration C_3 plug extended
                                        C_{33} plug retracted

Ejector Inlet Position	Primary Plug				Clamshell angle	

A_{inlet}/A_9	Position	M_o	13°	17°	21°	Removed
(Max) 0.60	extended	0 & 0.36	26(1528-1592)	-	-	-
(Mid) 0.46	extended	0 & 0.36	24(1438-1498)	22(1348-1407)	23(1408-1437) 25(1499-1527)	57(2592-2627)
(Mid) 0.46 modified*	extended	0 & 0.36	59(2658-2693)	-	-	60(2694-2710)
(Min) 0.36	extended	0 & 0.36	27(1593-1653)	-	-	-
(Min) 0.36	retracted	0.36	28(1654-1684)	-	-	-
Removed	extended	0				58(2628-2657)
Removed Modified*	extended	0				61(2711-2727)

* 20° segment inlet flap removed

- Iris flap nozzle-takeoff configuration A_3 plug extended
                                         A_{33} plug retracted

Ejector Inlet Position A_{inlet}/A_9	Primary Plug Position	M_o	13°	Clamshell angle 17°	21°	Removed
(Mid) 0.80	extended	0 & 0.36	37(1940-2000)	-	-	65(2873-2893)
(Mid) 0.80	retracted	0 & 0.36	35(1864-1927)	-	-	-

3. Data Identification Guide

A set of tabulated data for each run consists of tunnel Mach number, nozzle operating conditions, discharge coefficients, thrust coefficients and surface static pressures. The nozzle operating conditions and performance coefficients for each reading of the run are summarized at the beginning of the data set followed by static pressure measurements for each reading. We will use the data set for run 30 listed on pages 585-619 book 2 and previous identified in the data matrix, as an example, to describe the information presented. The configuration description is listed at the top of the summary page. Directly below the description, the nozzle operating conditions and coefficients are tabulated by reading number (RDG) which appears on the extreme left of the page. Proceeding from left to right the parameters are; tunnel Mach number (MO), fan-to-primary stream pressure split (PTF/PTP), fan nozzle pressure ratio (PTF/PO), primary nozzle pressure ratio (PTP/PO), secondary flow (OMEGA), secondary-to-fan total pressure pumping characteristic (PTS/PTF), (note that the secondary flow and pumping characteristic parameters only apply to the supersonic cruise configuration), fan nozzle discharge coefficient (CDF), primary nozzle discharge coefficient (CDP), nozzle gross thrust coefficient as defined in Ref. 1, but including the external skin friction drag of the model (CF1), nozzle efficiency coefficient as defined in Ref. 1, but including external skin friction drag (ETA1), nozzle efficiency coefficient as defined in Ref. 1 (ETA1, INT), nozzle gross thrust coefficient as defined in Ref. 1 (CFP1), nozzle gross thrust coefficient as defined in Ref. 1, adjusted for the estimated internal duct friction losses from the charging station to nozzle exit plane (CFP2), stream thrust coefficient (F9). The definition of the additional thrust parameters not included in Ref. 1 are provided on page viii.

Following the run summary the model surface static pressure measurements are presented for each reading. These data are identified by the run and reading (RDG) number on the upper right hand corner of the page. The pressure measurements are grouped together for each model surface as identified by the heading such as; primary plug, flow splitter outer diameter, flow splitter inner diameter. Reading from left to right for each grouping the pressures are expressed in terms of absolute pressure, psia, (PL), normalized by ambient pressure (PL/PO), normalized by fan total pressure (PL/PTF), and normalized by primary total pressure (PL/PTP). (X/DMAX) describes the normalized axial location of each tap relative to the common model connection flange*. It should be noted that not all of the static tap instrumentation listed was applicable to all of test configurations. For cases that do not apply, the information is lined out.

*For the short flap nozzle configurations C_2, C_3 and C_{33}, the correct axial location (X/Dmax) of the last inlet flap tap, #48, identified as AVD word 142 is 0.558 and not 0.588 as shown.

Additional Thrust Parameters

Gross thrust coef. CF1 $= \dfrac{(F-Dex)-Dsm}{m_f V_{1f} + m_p V_{1p}}$

Efficiency coef. ETA1 $= \dfrac{(F-Dex) - Dsm}{m_f V_{1f} + m_p V_{1p} + m_s V_{1s}}$

Gross Thrust Coef. CFP2 $=$

$$\frac{F - Dex}{m_f V_{1f} + m_p V_{1p}} \quad + \quad \frac{\Delta C_{fp_f} \; m_f V_{1f} + \Delta C_{fp_p} \, m_p V_{1p}}{m_f V_{1f} + m_p V_{1p}}$$

where $\quad \Delta Cfp \quad = \left[\dfrac{P_t}{P_0} \; \dfrac{\gamma-1}{2} - 1 \right]^{\frac{\gamma-1}{2\gamma}} \left(\dfrac{\Delta P_t}{P_t} \right)$

and $\quad \dfrac{\Delta P_t}{P_t} \quad$ is the estimated duct friction loss from the instrumentation charging station to nozzle exit plane

Stream thrust Coef. F9 $= \dfrac{(F-Dex) + P_0 A_9}{P_{tf} A_f + P_{tp} A_p}$

4. References

1. Nelson, D.P., "Model Aerodynamic Test Results for Two Variable Cycle Engine Coannualar Exhaust Systems at Takeoff and Cruise Conditions," NASA CR-159818, 1980.

NOZZLE TYPE	P+W BASE EJECTOR NOZZLE (MODEL C)
FLIGHT CONDITIONS	SUPER SONIC CRUISE (MS=0)
NOZZLE CONFIGURATION	C1
PRIMARY-NOZZLE PLUG	SPLIT PLUG (RETRACTED)
FLOW SPLITTER	ISENTROPIC SPLITTER
FAN NOZZLE	SHORT FLAP
CLAMSHELL POSITION	
EJECTOR INLET OPENING	

PDG	MD	PTF/PTP	PTF/PO	PTP/PO	OMEGA	PTS/PTF	CDF	CDP	CF1	ETA1	ETA1,INT	CFP1	CFP2	FG
1039	1.964	2.30	20.16	10.10	0.000	0.043	0.974	0.981	0.9699	0.9699	0.9729	0.9729	0.9734	1.4594
1040	1.962	2.31	20.05	8.70	0.000	0.043	0.974	0.981	0.9701	0.9701	0.9734	0.9734	0.9739	1.4452
1041	1.961	2.43	20.17	7.72	0.000	0.043	0.973	0.979	0.9711	0.9711	0.9745	0.9745	0.9750	1.4702
1042	1.962	2.33	22.57	11.31	0.000	0.043	0.974	0.982	0.9760	0.9760	0.9787	0.9787	0.9792	1.4443
1043	1.963	2.31	22.65	9.42	0.000	0.043	0.974	0.981	0.9765	0.9765	0.9793	0.9793	0.9798	1.4674

NOZZLE TYPE	P+W BASE EJECTOR NOZZLE (MODEL C)
FLIGHT CONDITIONS	SUPER SONIC CRUISE (VS=0)
NOZZLE CONFIGURATION	C1
PRIMARY-NOZZLE PLUG	SPLIT PLUG (RETRACTED)
FLOW SPLITTER	ISENTROPIC SPLITTER
FAN NOZZLE	SHORT FLAP
CLAMSHELL POSITION	
EJECTOR INLET OPENING	

RDG	MD	PTF/PTP	PTF/PO	PTP/PO	OMEGA	PTS/PTF	CDF	CDP	CF1	ETA1	ETA1.INT	CFP1	CFP2	F9
1044	1.563	2.59	22.55	8.71	0.000	0.262	0.973	0.980	0.9763	0.9763	0.9793	0.9793	0.9798	1.4785
1045	1.959	2.00	25.11	12.53	0.000	0.042	0.975	0.980	0.9794	0.9794	0.9818	0.9818	0.9822	1.4653
1046	1.961	2.33	25.04	10.76	0.000	0.042	0.974	0.982	0.9794	0.9794	0.9819	0.9819	0.9824	1.5689
1047	1.964	2.63	25.92	9.62	0.000	0.043	0.973	0.980	0.9796	0.9796	0.9823	0.9823	0.9827	1.4711
1048	1.962	2.04	27.51	13.47	0.000	0.042	0.975	0.982	0.9824	0.9824	0.9846	0.9846	0.9851	1.4697
1049	1.962	2.32	27.47	11.90	0.000	0.042	0.974	0.980	0.9832	0.9832	0.9855	0.9855	0.9859	1.4717
1050	1.962	2.63	27.71	10.67	0.000	0.042	0.976	0.981	0.9819	0.9819	0.9863	0.9863	0.9867	1.4739
1051	1.962	2.32	29.93	12.99	0.000	0.042	0.974	0.981	0.9832	0.9832	0.9853	0.9853	0.9857	1.4783
1052	1.962	2.60	30.11	11.58	0.000	0.042	0.977	0.981	0.9833	0.9833	0.9854	0.9854	0.9858	1.4763
1053	1.961	2.65	30.10	11.54	0.000	0.042	0.974	0.980	0.9835	0.9835	0.9857	0.9857	0.9861	1.4728
1054	1.962	2.32	29.85	12.87	0.000	0.042	0.975	0.984	0.9797	0.9797	0.9818	0.9818	0.9822	1.4684
1055	1.962	2.59	28.04	10.91	0.000	0.042	0.974	0.978	0.9833	0.9833	0.9956	0.9856	0.9860	1.4724
1056	1.962	2.35	27.52	11.77	0.000	0.042	0.974	0.981	0.9818	0.9818	0.9861	0.9861	0.9846	1.4703
1057	1.963	2.04	27.63	13.55	0.000	0.042	0.975	0.981	0.9828	0.9828	0.9850	0.9850	0.9856	1.4691
1058	1.962	2.60	25.07	9.65	0.000	0.043	0.977	0.982	0.9773	0.9773	0.9800	0.9800	0.9804	1.4715
1059	1.962	2.33	24.98	10.67	0.000	0.042	0.972	0.982	0.9803	0.9803	0.9829	0.9829	0.9834	1.4693
1060	1.962	2.01	24.98	12.45	0.000	0.043	0.974	0.981	0.9787	0.9787	0.9811	0.9811	0.9816	1.4663
1061	1.962	2.60	22.55	8.69	0.000	0.043	0.973	0.980	0.9774	0.9774	0.9804	0.9804	0.9809	1.4726
1062	1.963	2.31	22.53	9.73	0.000	0.042	0.972	0.981	0.9795	0.9795	0.9823	0.9823	0.9828	1.4706
1063	1.962	2.01	22.50	11.21	0.000	0.042	0.973	0.980	0.9786	0.9786	0.9813	0.9813	0.9818	1.4661
1064	1.962	2.60	20.07	7.73	0.000	0.043	0.971	0.980	0.9698	0.9698	0.9733	0.9733	0.9738	1.4674
1065	1.962	2.31	20.07	8.67	0.000	0.043	0.973	0.980	0.9727	0.9727	0.9760	0.9760	0.9765	1.4674
1066	1.962	2.00	20.07	10.03	0.000	0.043	0.972	0.980	0.9780	0.9780	0.9811	0.9811	0.9816	1.4687
1067	0.939	1.40	4.39	2.92	0.000	0.215	0.972	0.980	0.9177	0.9177	0.9177	0.9177	0.9193	1.7165
1068	0.935	1.59	4.54	2.87	0.000	0.196	0.973	0.979	0.9211	0.9211	0.9211	0.9211	0.9226	1.6995
1069	0.952	1.78	5.03	2.83	0.000	0.177	0.972	0.979	0.9268	0.9269	0.9268	0.9269	0.9283	1.6829
1070	0.952	1.98	5.51	2.79	0.000	0.158	0.972	0.979	0.9264	0.9264	0.9264	0.9264	0.9277	1.6647

2

NASA-LEWIS   PRELIMINARY DATA   07/07/79   CADDEII   REC 1G/07/79 02:15:24.090   FAC BX6X1   PG4 C034   RDG 1039

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.856	4.3114	0.21394	0.42670	0.43200
37	7.2137	2.2415	0.11117	0.22189	0.53000
47	12.966	4.0345	0.20010	0.39937	0.62900
52	9.3651	2.9140	0.14453	0.28846	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.651	3.3140	0.16437	0.32805	0.42200
67	7.4589	2.3209	0.11511	0.22975	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	26.754	8.3247	0.41289	0.82407	0.50800
82	13.176	4.0998	0.20334	0.40584	0.58300
92	3.4695	1.0796	0.053544	0.10687	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.4721	1.7027	0.084449	0.16855	0.62400
112	3.9051	1.2151	0.060267	0.12028	0.83000
122	3.7950	1.1808	0.058567	0.11689	0.96000
127	3.4495	1.0733	0.053235	0.10625	1.0900
137	3.5847	1.1154	0.055321	0.11041	1.2200
142	3.3193	1.0328	0.051225	0.10224	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.4721	1.7027	0.084449	0.16855	-1.0000
-112	3.9051	1.2151	0.060267	0.12028	-1.0000
-122	3.7950	1.1808	0.058567	0.11689	-1.0000
-127	3.4495	1.0733	0.053235	0.10625	-1.0000
-137	3.5847	1.1154	0.055321	0.11041	-1.0000
-142	3.3193	1.0328	0.051225	0.10224	-1.0000
-152	3.4244	1.0655	0.052848	0.10548	-1.0000
-157	3.4194	1.0640	0.052771	0.10532	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4244	1.0655	0.052848	0.10548	-1.0000
-157	3.4194	1.0640	0.052771	0.10532	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4294	1.0671	0.052926	0.10563	-1.0000
-172	3.4244	1.0655	0.052848	0.10548	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.7900	1.1762	0.058335	0.11643	-1.0000
-187	3.6798	1.1450	0.056789	0.11334	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

3

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.965	3.7116	0.18509	0.42670	0.43200
37	6.2551	1.9404	0.096766	0.22308	0.53000
47	11.170	3.4651	0.17282	0.39836	0.62900
52	8.1404	2.5253	0.12593	0.29031	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	9.2053	2.8557	0.14241	0.32829	0.42200
67	6.5301	2.0165	0.10056	0.23182	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	26.644	8.2653	0.41218	0.95020	0.50800
82	13.116	4.0682	0.20287	0.46760	0.58300
92	3.4734	1.0775	0.053734	0.12387	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.4597	1.6937	0.084463	0.19471	0.62400
112	3.8337	1.2379	0.060236	0.13886	0.83000
122	3.7786	1.1722	0.058456	0.13476	0.96000
127	3.4584	1.0728	0.053501	0.12334	1.0900
137	3.2432	1.0061	0.050172	0.11566	1.2200
142	2.9579	0.91759	0.045759	0.10549	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.4597	1.6937	0.084463	0.19471	-1.0000
-112	3.8337	1.2379	0.060236	0.13886	-1.0000
-122	3.7786	1.1722	0.058456	0.13476	-1.0000
-127	3.4584	1.0728	0.053501	0.12334	-1.0000
-137	3.2432	1.0061	0.050172	0.11566	-1.0000
-142	2.9579	0.91759	0.045759	0.10549	-1.0000
-152	3.4333	1.0651	0.053114	0.12244	-1.0000
-157	3.4293	1.0635	0.053037	0.12227	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4333	1.0651	0.053114	0.12244	-1.0000
-157	3.4293	1.0635	0.053037	0.12227	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4333	1.0651	0.053114	0.12244	-1.0000
-172	3.4333	1.0651	0.053114	0.12244	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.8337	1.1903	0.058943	0.13565	-1.0000
-187	3.7476	1.1613	0.057914	0.13361	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

4

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.573	3.2917	0.16395	0.42615	0.43200
37	5.5563	1.7298	0.086176	0.22394	0.53000
47	9.9193	3.3880	0.15384	0.35978	0.62900
52	7.1036	2.213X	0.11013	0.28620	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	9.1549	2.5399	0.12645	0.32869	0.42200
67	5.1259	1.7527	0.088812	0.23080	0.67900

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	26.505	8.2520	0.41111	1.0683	0.50800
82	13.370	4.0691	0.20272	0.52691	0.58300
92	3.4660	1.0791	0.053760	0.13971	0.67600

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.4411	1.6940	0.084393	0.21931	0.62600
112	3.8861	1.2099	0.060276	0.15664	0.83000
122	3.7711	1.1741	0.059492	0.15200	0.96000
127	3.4460	1.0729	0.053450	0.13890	1.0500
137	3.0759	0.95766	0.047719	0.12398	1.2200
142	2.6759	0.83308	0.041504	0.10785	1.3500

>ADDITIONAL PRESSURE RATIOS , FREEDOM INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.4411	1.6940	0.084393	0.21931	-1.0000
-112	3.8861	1.2099	0.060276	0.15664	-1.0000
-122	3.7711	1.1741	0.059492	0.15200	-1.0000
-127	3.4460	1.0729	0.053450	0.13890	-1.0000
-137	3.0759	0.95766	0.047719	0.12398	-1.0000
-142	2.6759	0.83308	0.041534	0.10785	-1.0000
-152	3.4160	1.0635	0.052585	0.13769	-1.0000
-157	3.4210	1.0651	0.052062	0.13780	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4160	1.0635	0.052085	0.13769	-1.0000
-157	3.4210	1.0651	0.052062	0.13789	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4160	1.0635	0.052085	0.13769	-1.0000
-172	3.4210	1.0651	0.052062	0.13789	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.7961	1.1819	0.058875	0.15301	-1.0000
-187	3.7361	1.1632	0.057943	0.15059	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.471	4.8289	0.21396	0.42708	0.43200
37	9.0177	2.5025	0.11CRP	0.22133	0.53000
47	14.596	4.5528	0.20173	0.40266	0.62900
52	10.358	3.2330	0.14325	0.28593	J.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.893	3.7120	0.16447	0.32820	J.42200
67	8.3177	2.5962	0.11503	0.22561	0.67003

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	29.744	9.2901	0.41163	0.82162	0.50800
82	14.706	4.5903	0.20229	0.40597	0.58300
92	3.4598	1.0799	0.047849	0.095508	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.1169	1.9093	0.084596	0.16886	0.62500
112	4.3607	1.3611	0.060308	0.12038	0.83000
122	4.2256	1.3189	0.058439	0.11665	0.96000
127	3.4398	1.0737	0.047572	0.094956	1.0900
137	4.0056	1.2502	0.055353	0.11057	1.2200
142	3.7371	1.1549	0.051171	0.10214	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.1169	1.9093	0.084596	0.16886	-1.0000
-112	4.3607	1.3611	0.060308	0.12038	-1.0000
-122	4.2256	1.3189	0.058439	0.11665	-1.0000
-127	3.4398	1.0737	0.047572	0.094956	-1.0000
-137	4.0056	1.2502	0.055353	0.11057	-1.0000
-142	3.7371	1.1549	0.051171	0.10214	-1.0000
-152	3.4098	1.0643	0.047156	0.094126	-1.0000
-157	3.4148	1.0658	0.047226	0.094265	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE EXP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4098	1.0643	0.047156	0.094126	-1.0000
-157	3.4148	1.0658	0.047226	0.094265	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4398	1.0643	0.047156	0.054126	-1.0000
-177	3.4148	1.0658	0.047226	0.094265	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.8352	1.1971	0.053040	0.10587	-1.0000
-187	3.7451	1.1699	0.051796	0.10338	-1.0000

>SECTIONS , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	13.545	4.1941	0.18515	0.42708	0.43200
37	7.0724	2.1899	0.096675	0.22300	0.53000
47	12.730	3.9417	0.17401	0.40138	0.62900
52	9.0788	2.8112	0.12610	0.28626	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	10.414	3.2247	0.14236	0.32837	0.42200
67	7.2876	2.2565	0.095617	0.22578	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	30.024	9.2968	0.41041	0.94668	0.50800
82	14.835	4.5935	0.20278	0.46775	0.58300
92	3.4932	1.0785	0.047613	0.10983	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	6.1816	1.9141	0.084498	0.19491	0.62400
112	4.4045	1.3638	0.060207	0.13888	0.83000
122	4.2944	1.3266	0.058564	0.13509	0.96000
127	3.4682	1.0739	0.047408	0.10935	1.0900
137	3.6835	1.1406	0.050351	0.11614	1.2200
142	3.3530	1.0382	0.045833	0.10572	1.3500

>ADDITIONAL PRESSURE RATIOS , FREEDROW INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	6.1816	1.9141	0.084498	0.19491	-1.0000
-112	4.4045	1.3638	0.060207	0.13888	-1.0000
-122	4.2944	1.3266	0.058564	0.13509	-1.0000
-127	3.4682	1.0739	0.047408	0.10935	-1.0000
-137	3.6835	1.1406	0.050351	0.11614	-1.0000
-142	3.3530	1.0382	0.045833	0.10572	-1.0000
-152	3.4431	1.0661	0.047065	0.10856	-1.0000
-157	3.4381	1.0646	0.046597	0.10841	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	3.4431	1.0661	0.047065	0.10856	-1.0000
-157	3.4381	1.0646	0.046597	0.10841	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-167	3.4431	1.0661	0.047065	0.10856	-1.0000
-172	3.4431	1.0661	0.047065	0.10856	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-182	3.9038	1.2089	0.053363	0.12309	-1.0000
-187	3.8397	1.1896	0.052473	0.12104	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.337	3.7176	0.16459	0.42734	0.43200
37	6.2925	1.9492	0.086245	0.22379	0.53000
47	11.337	3.5101	0.15539	0.40320	0.62900
52	8.0395	2.4991	0.11019	0.28592	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	9.2456	2.8625	0.12672	0.32882	0.42200
67	6.4677	2.0025	0.088666	0.23002	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	29.948	9.2721	0.41047	1.0651	0.50800
82	14.819	4.5880	0.20310	0.52702	3.58300
92	3.4780	1.0768	0.047670	0.12369	0.67800

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.1723	1.9110	0.084598	0.21952	0.62400
112	4.3946	1.3606	0.060233	0.15629	0.83000
122	4.2744	1.3234	0.058596	0.15202	0.96000
127	3.4683	1.0737	0.047533	0.12334	1.0900
137	3.4930	1.0784	0.047739	0.12387	1.2200
142	3.0221	0.93568	0.041422	0.10748	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.1723	1.9110	0.084598	0.21952	-1.0000
-112	4.3946	1.3606	0.060233	0.15629	-1.0000
-122	4.2744	1.3234	0.058596	0.15202	-1.0000
-127	3.4683	1.0737	0.047533	0.12336	-1.0000
-137	3.4830	1.0784	0.047739	0.12387	-1.0000
-142	3.0221	0.93568	0.041422	0.10748	-1.0000
-152	3.4429	1.0660	0.047189	0.12245	-1.0000
-157	3.4683	1.0675	0.047259	0.12263	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4429	1.0660	0.047189	0.12245	-1.0000
-157	3.4490	1.0675	0.047259	0.12263	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4530	1.0691	0.047327	0.12280	-1.0000
-172	3.4603	1.0706	0.047395	0.12296	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.8988	1.2071	0.053437	0.13866	-1.0000
-187	3.8136	1.1807	0.052279	0.13569	-1.0000

>OPTIONS , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	17.426	5.3542	0.21226	0.42735	0.43200
37	8.9913	2.7627	0.11004	0.22650	0.53000
47	16.636	5.1124	0.20323	0.40725	0.62500
52	11.612	3.5679	0.14211	0.28477	1.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.402	4.1178	0.16401	0.32867	0.42200
67	9.3464	2.8719	0.11438	0.22921	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	33.450	10.278	0.40937	0.82033	0.50800
82	16.651	5.1162	0.20378	0.40835	0.58300
92	3.5118	1.0790	0.042978	0.086123	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.9352	2.1309	0.084876	0.17008	0.62400
112	4.9435	1.5189	0.060500	0.12123	0.83000
122	4.7933	1.4728	0.058663	0.11755	0.96000
127	3.5069	1.0775	0.042917	0.086080	1.0900
137	4.5130	1.3867	0.055232	0.11068	1.2200
142	4.1826	1.2852	0.051199	0.10258	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.9352	2.1309	0.084876	0.17008	-1.0000
-112	4.9435	1.5189	0.060500	0.12123	-1.0000
-122	4.7933	1.4728	0.058663	0.11755	-1.0000
-127	3.5069	1.0775	0.042517	0.086000	-1.0000
-137	4.5130	1.3867	0.055232	0.11068	-1.0000
-142	4.1826	1.2852	0.051199	0.10258	-1.0000
-152	3.4667	1.0652	0.042427	0.085019	-1.0000
-157	3.4717	1.0667	0.042488	0.085141	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4667	1.0652	0.042427	0.085018	-1.0000
-157	3.4717	1.0667	0.042488	0.085141	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4667	1.0652	0.042427	0.085018	-1.0000
-172	3.4717	1.0667	0.042488	0.085141	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.9974	1.2252	0.048799	0.097787	-1.0000
-187	3.9373	1.2096	0.047819	0.095823	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.785	4.5334	0.18341	0.42705	0.43200
37	7.6702	2.3493	0.095404	0.22213	0.53000
47	13.905	4.3201	0.17250	0.40164	0.62900
52	9.9137	3.0791	0.12295	0.28627	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.356	3.5291	0.14007	0.32800	0.42200
67	7.9453	2.4695	0.098568	0.22950	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.739	10.162	0.40578	0.94478	0.50800
82	16.344	5.0778	0.20276	0.47208	3.56300
92	3.4622	1.0757	0.042951	0.10000	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.3139	2.1189	0.084606	0.19695	0.62400
112	4.9436	1.5048	0.060088	0.13990	0.83000
122	4.7235	1.4675	0.058559	0.13644	0.56000
127	3.4622	1.0757	0.042951	0.10000	1.0900
137	4.0428	1.2561	0.050154	0.11678	1.2200
142	3.4624	1.1379	0.045435	0.10579	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.8199	2.1189	0.084606	0.19699	-1.0000
-112	4.9436	1.5048	0.060088	0.13990	-1.0000
-122	4.7235	1.4675	0.058559	0.13644	-1.0000
-127	3.4622	1.0757	0.042951	0.10000	-1.0000
-137	4.0428	1.2561	0.050154	0.11678	-1.0000
-142	3.4624	1.1379	0.045435	0.10579	-1.0000
-152	3.4221	1.0632	0.042454	0.098847	-1.0000
-157	3.4221	1.0632	0.042454	0.098847	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4221	1.0632	0.042454	0.098847	-1.0000
-157	3.4221	1.0632	0.042454	0.098847	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4171	1.0617	0.042392	0.098703	-1.0000
-172	3.4171	1.0617	0.042392	0.098703	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.9777	1.2358	0.049347	0.11490	-1.0000
-187	3.9177	1.2172	0.048602	0.11316	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

10

NASA-LEWIS   PRELIMINARY DATA   07/07/79   CADDETT   REC 10/07/79 02:25:11.720   FAC 9X6V1   PGM F934   PRG 1047

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.212	4.1130	0.16441	0.42754	0.43200
37	6.9027	2.1488	0.085894	0.22324	0.53000
47	12.493	3.8930	0.15565	0.40425	0.62500
52	8.8431	2.7529	0.11034	0.28615	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.148	3.1591	0.12629	0.32838	0.42200
67	7.1127	2.2142	0.088509	0.23016	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.669	10.170	0.40652	1.0571	0.50800
82	16.311	5.0775	0.20296	0.52780	0.58300
92	3.4612	1.0772	0.043057	0.11197	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.9076	2.1192	0.084711	0.22029	0.52400
112	4.8415	1.5071	0.060245	0.15666	0.83000
122	4.7114	1.4666	0.058626	0.15245	0.96000
127	3.4602	1.0772	0.043057	0.11197	1.0900
137	3.8356	1.1940	0.047728	0.12411	1.2200
142	3.3351	1.0382	0.041509	0.10792	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.8076	2.1192	0.084711	0.22029	-1.0000
-112	4.8415	1.5071	0.060245	0.15666	-1.0000
-122	4.7114	1.4666	0.058626	0.15245	-1.0000
-127	3.4602	1.0772	0.043057	0.11197	-1.0000
-137	3.8356	1.1940	0.047728	0.12411	-1.0000
-142	3.3351	1.0382	0.041509	0.10792	-1.0000
-152	3.4201	1.0647	0.042559	0.11067	-1.0000
-157	3.4201	1.0647	0.042559	0.11067	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4201	1.0647	0.042559	0.11067	-1.0000
-157	3.4201	1.0647	0.042559	0.11067	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4201	1.0647	0.042559	0.11067	-1.0000
-172	3.4201	1.0647	0.042559	0.11067	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.9507	1.2298	0.049161	0.12784	-1.0000
-187	3.8956	1.2126	0.048351	0.12573	-1.0000

>OPTIONS , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	18.602	5.7558	0.20525	0.42732	0.43200
37	9.5940	2.9654	0.10701	0.22016	0.53000
47	17.658	5.4635	0.19862	0.40562	0.62900
52	12.309	3.8395	0.13959	0.28505	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	14.326	4.4320	0.16112	0.32904	0.42200
67	9.9991	3.0937	0.11236	0.22546	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	35.986	11.134	0.40477	0.82659	0.50800
82	18.392	5.5900	0.20351	0.41561	0.58300
92	3.4756	1.0766	0.034141	0.079031	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	7.5392	2.3324	0.084795	0.17316	0.62400
112	5.3617	1.6590	0.060311	0.12316	0.83000
122	5.2215	1.6156	0.058735	0.11994	0.96000
127	3.4946	1.0782	0.039197	0.080045	1.0900
137	4.9262	1.4933	0.054288	0.11036	1.2200
142	4.4958	1.3880	0.050459	0.10306	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	7.5392	2.3324	0.084795	0.17316	-1.0000
-112	5.3617	1.6590	0.060311	0.12316	-1.0000
-122	5.2215	1.6156	0.058735	0.11994	-1.0000
-127	3.4946	1.0782	0.039197	0.080045	-1.0000
-137	4.9262	1.4933	0.054288	0.11036	-1.0000
-142	4.4958	1.3880	0.050459	0.10306	-1.0000
-152	3.4395	1.0642	0.038690	0.079010	-1.0000
-157	3.4446	1.0658	0.038746	0.079125	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	3.4395	1.0642	0.038690	0.079010	-1.0000
-157	3.4446	1.0658	0.038746	0.079125	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-167	3.4395	1.0642	0.038690	0.079010	-1.0000
-172	3.4345	1.0627	0.038624	0.078895	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-182	4.0453	1.2579	0.045729	0.093385	-1.0000
-187	4.0153	1.2424	0.045166	0.092225	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

12

NASA-LEWIS   PRELIMINARY DATA   07/07/79   CADDELL   REC 10/07/79 02:27:23.749   FAC 8X6X1   PGM C034   PPG 1849

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	16.481	5.0085	0.18388	0.42750	0.43200
37	8.5301	2.6336	0.095171	0.22126	0.53000
47	15.636	4.8184	0.17412	0.40481	0.62900
52	11.016	3.4012	0.12291	0.28575	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.661	3.9092	0.14126	0.32842	0.42200
67	8.9553	2.7349	0.099799	0.22970	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	36.281	11.202	0.40470	0.94110	0.50800
82	18.261	5.6380	0.20274	0.47366	0.58300
92	3.4949	1.0791	0.038993	0.090655	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	7.6095	2.3494	0.094899	0.19728	0.62500
112	5.4124	1.6711	0.060307	0.14039	0.83000
122	5.2723	1.6278	0.058823	0.13676	0.96000
127	3.5000	1.0806	0.039049	0.090785	1.0900
137	4.5166	1.3944	0.050390	0.11715	1.2200
142	4.0939	1.2639	0.045641	0.10611	1.3500

>ADDITIONAL PRESSURE RATIOS , SECONDARY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.6095	2.3494	0.094899	0.19738	-1.0000
-112	5.4124	1.6711	0.060307	0.14039	-1.0000
-122	5.2723	1.6278	0.058823	0.13676	-1.0000
-127	3.5000	1.0806	0.039049	0.090785	-1.0000
-137	4.5164	1.3944	0.050390	0.11715	-1.0000
-142	4.0939	1.2630	0.045641	0.10611	-1.0000
-152	3.4499	1.0651	0.038491	0.089486	-1.0000
-157	3.4499	1.0651	0.038491	0.089486	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4499	1.0651	0.038491	0.089486	-1.0000
-157	3.4499	1.0651	0.038491	0.089486	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-162	3.4499	1.0651	0.038491	0.089486	-1.0000
-172	3.4499	1.0651	0.038491	0.089486	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	4.3759	1.2584	0.045474	0.10572	-1.0000
-187	4.0237	1.2414	0.044859	0.10429	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   07/07/79   CADRE11   REC 10/07/79 C2:28:01.086   FAC 9X6X1   PG* C034   RDG 1050

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.706	4.5624	3.16463	0.42766	0.43200
37	7.5965	2.3705	0.085536	0.22220	0.53000
47	14.304	4.3198	0.15594	0.40482	0.62900
52	9.3279	3.0619	0.11949	0.28702	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.358	3.5029	0.12640	0.32825	0.62700
67	7.9517	2.6523	0.098497	0.22987	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	36.310	11.198	0.40406	1.0497	0.50000
82	18.298	5.6432	0.20363	0.52897	0.59300
92	3.4967	1.0784	0.038912	0.10108	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	7.6315	2.3536	0.084924	0.22061	3.62400
112	5.4343	1.6760	0.060474	0.15710	0.83000
122	5.2902	1.6312	0.058858	0.15290	0.96000
127	3.4967	1.0784	0.038912	0.10108	1.0900
137	4.2929	1.3239	0.047771	0.12410	1.2200
142	3.7371	1.1525	0.041596	0.10803	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.6315	2.3536	0.084924	0.22061	-1.0000
-112	5.4343	1.6760	0.060474	0.15710	-1.0000
-122	5.2902	1.6312	0.058858	0.15290	-1.0000
-127	3.4967	1.0784	0.038912	0.10108	-1.0000
-137	4.2929	1.3239	0.047771	0.12410	-1.0000
-142	3.7371	1.1525	0.041596	0.10803	-1.0000
-152	3.4516	1.0645	0.038410	0.099780	-1.0000
-157	3.4516	1.0645	0.038410	0.099780	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4516	1.0645	0.038410	0.099780	-1.0000
-157	3.4516	1.0645	0.038410	0.099780	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4516	1.0645	0.038410	0.099780	-1.0000
-172	3.4516	1.0645	0.038410	0.099780	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	4.3976	1.2637	0.045508	0.11845	-1.0000
-187	4.0475	1.2483	0.045041	0.11701	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

14

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	17.937	5.5201	0.18444	0.43911	0.43200
37	9.2371	2.8476	0.095142	0.27084	0.53930
47	16.736	5.1770	0.17298	0.40151	0.62930
52	11.933	3.6918	0.12301	0.29553	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.785	4.2494	0.14199	0.32956	0.42200
67	9.6167	2.9644	0.095051	0.22951	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	38.896	11.990	0.40062	0.92089	0.50800
82	19.734	6.0831	0.20326	0.47178	0.50300
92	3.4868	1.0768	0.035913	0.083355	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.2383	2.5395	0.084855	0.19696	0.62500
112	5.8636	1.8066	0.060364	0.14011	0.83000
122	5.7107	1.7604	0.058820	0.13653	0.96000
127	3.5018	1.0794	0.036068	0.083717	1.0500
137	4.9012	1.5108	0.050482	0.11717	1.2200
142	4.4364	1.3676	0.045695	0.10404	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	8.2383	2.5395	0.084855	0.19696	-1.0000
-112	5.8606	1.8066	0.060364	0.14011	-1.0000
-122	5.7107	1.7604	0.058820	0.13653	-1.0000
-127	3.5018	1.0794	0.036068	0.083717	-1.0000
-137	4.9012	1.5108	0.050482	0.11717	-1.0000
-142	4.4364	1.3676	0.045695	0.10404	-1.0000
-152	3.4468	1.0625	0.035502	0.082403	-1.0000
-157	3.4469	1.0625	0.035502	0.082403	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4468	1.0625	0.035502	0.082403	-1.0000
-157	3.4469	1.0625	0.035502	0.082403	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4518	1.0640	0.035553	0.082522	-1.0000
-172	3.4518	1.0640	0.035553	0.082522	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	4.2765	1.3183	0.044048	0.10224	-1.0000
-187	4.2715	1.3167	0.043996	0.10212	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

:[]

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	16.359	4.9448	0.16425	0.47494	0.43200
37	8.3019	2.5578	0.084959	0.22079	3.53000
47	15.190	4.6798	0.15545	0.40356	3.62900
52	10.748	3.3115	0.11000	0.28585	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.329	3.7985	0.12617	0.32785	0.42200
67	8.6222	2.6565	0.088235	0.22930	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	39.115	12.051	0.40029	1.0402	0.50800
82	19.910	6.1340	0.20375	0.52949	0.58300
92	3.5010	1.0786	0.035928	0.093100	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	8.3019	2.5578	0.094959	0.22079	0.67400
112	5.9095	1.8207	0.060476	0.15716	0.83000
122	5.7593	1.7744	0.058939	0.15317	0.96000
127	3.5110	1.0817	0.035931	0.093375	1.0900
137	4.6729	1.4397	0.047821	0.12427	1.2200
142	4.0619	1.2515	0.041569	0.10803	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	8.3019	2.5578	0.094959	0.22079	-1.0000
-112	5.9395	1.8207	0.060476	0.15716	-1.0000
-122	5.7593	1.7744	0.058939	0.15317	-1.0000
-127	3.5110	1.0817	0.035931	0.093375	-1.0000
-137	4.6729	1.4397	0.047821	0.12427	-1.0000
-142	4.0619	1.2515	0.041569	0.10803	-1.0000
-152	3.4610	1.0663	0.035418	0.092043	-1.0000
-157	3.4563	1.0648	0.035367	0.091910	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4610	1.0663	0.035418	0.092043	-1.0000
-157	3.4563	1.0648	0.035367	0.091910	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4610	1.0663	0.035419	0.092043	-1.0000
-172	3.4560	1.0648	0.035367	0.091910	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	4.3123	1.3286	0.044131	0.11468	-1.0000
-187	4.3123	1.3286	0.044131	0.11468	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

16

NASA-LEWIS   PRELIMINARY DATA   07/07/79   CADDFII   REC 10/07/79 02:30:34.647   FAC RX6X1   PGM F034   RDG 1053

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.898	4.9332	0.16352	0.42745	0.43700
37	9.2419	2.5591	0.095032	0.22174	0.53000
47	15.308	4.6600	0.15484	0.40378	0.62500
52	10.658	3.3092	0.10506	0.28674	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.209	3.7906	0.12555	0.32845	0.42700
67	8.5421	2.6523	0.098129	0.22982	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	54.771	12.039	0.40000	1.0431	0.50800
82	19.732	6.1267	0.20357	0.53087	0.58300
92	3.4772	1.0797	0.035874	0.093552	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	8.2319	2.5560	0.084928	0.22147	0.62400
112	5.8551	1.8180	0.060407	0.15753	0.83000
122	5.7049	1.7714	0.058858	0.15349	0.56000
127	3.4822	1.0812	0.035926	0.093686	1.0500
137	4.6237	1.4357	0.047703	0.12440	1.2200
142	4.0230	1.2491	0.041505	0.10824	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	8.2319	2.5560	0.084928	0.22147	-1.0000
-112	5.8551	1.8180	0.060407	0.15753	-1.0000
-122	5.7049	1.7714	0.058858	0.15349	-1.0000
-127	3.4822	1.0812	0.035926	0.093686	-1.0000
-137	4.6237	1.4357	0.047703	0.12440	-1.0000
-142	4.0230	1.2491	0.041505	0.10824	-1.0000
-152	3.4321	1.0657	0.035409	0.092339	-1.0000
-157	3.4321	1.0657	0.035409	0.092339	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4321	1.0657	0.035409	0.092339	-1.0000
-157	3.4321	1.0657	0.035409	0.092339	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4321	1.0657	0.035409	0.092339	-1.0000
-172	3.4271	1.0641	0.035355	0.092284	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	4.2332	1.3144	0.043674	0.11389	-1.0000
-187	4.1982	1.3035	0.043313	0.11295	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   07/07/79   CARDFII   PEC 10/07/79 02:31:30.790   FAC 9X6X1   PGR C034   PDG 1854

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	17.755	5.5168	0.18483	0.42858	0.43200
37	9.1619	2.8464	0.095362	0.22113	0.53000
47	16.935	5.2217	0.17494	0.40566	0.47900
52	11.966	3.6908	0.12322	0.28595	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.651	4.2416	0.14211	0.32952	0.42200
67	9.5312	2.9414	0.095215	0.22024	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	38.467	11.746	0.40022	0.92805	0.50800
82	19.579	6.0936	0.20392	0.47262	0.58300
92	3.4662	1.0770	0.036082	0.083668	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	8.1554	2.5340	0.084896	0.19686	0.62600
112	5.8389	1.8149	0.060469	0.14022	0.83000
122	5.6486	1.7551	0.058801	0.13635	0.96000
127	3.4817	1.0817	0.036238	0.084031	1.0900
137	4.8528	1.5379	0.050517	0.11714	1.2200
142	4.3973	1.3663	0.045775	0.10615	1.3500

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	8.1554	2.5340	0.084896	0.19686	-1.0000
-112	5.8389	1.8149	0.060469	0.14022	-1.0000
-122	5.6486	1.7551	0.058801	0.13635	-1.0000
-127	3.4817	1.0817	0.036238	0.084031	-1.0000
-137	4.8528	1.5379	0.050517	0.11714	-1.0000
-142	4.3973	1.3663	0.045775	0.10615	-1.0000
-152	3.4311	1.0661	0.035717	0.082822	-1.0000
-157	3.4311	1.0661	0.035717	0.082822	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4311	1.0661	0.035717	0.082822	-1.0000
-157	3.4311	1.0661	0.035717	0.082822	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4311	1.0661	0.035717	0.082822	-1.0000
-172	3.4311	1.0661	0.035717	0.082822	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	4.1921	1.3035	0.043630	0.10119	-1.0000
-187	4.1921	1.2961	0.043232	0.10022	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

18

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.836	4.6355	0.16436	0.42634	0.43200
37	7.7173	2.3365	0.38545?	0.22165	0.53600
47	14.371	4.3563	0.15537	0.40292	0.62900
52	10.010	3.1100	0.11605	0.28765	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.400	3.5431	0.12630	0.32761	0.42200
67	7.3795	2.4759	0.088350	0.22927	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	36.144	11.230	0.40042	1.0387	0.50800
82	18.351	5.7016	0.20339	0.52734	0.58300
92	3.4691	1.0775	0.038421	0.059660	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	7.6733	2.3340	0.085009	0.22050	0.62400
112	5.4559	1.6951	0.060644	0.15678	0.83000
122	5.3158	1.6516	0.058851	0.15276	0.96000
127	3.4731	1.0791	0.038477	0.099804	1.0300
137	4.3144	1.3405	0.047757	0.12398	1.2200
142	3.7535	1.1662	0.041594	0.10796	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.6733	2.3440	0.085009	0.22050	-1.0000
-112	5.4559	1.6951	0.060444	0.15678	-1.0000
-122	5.3158	1.6516	0.058851	0.15276	-1.0000
-127	3.4731	1.0791	0.038477	0.099804	-1.0000
-137	4.3144	1.3405	0.047757	0.12398	-1.0000
-142	3.7535	1.1662	0.041594	0.10786	-1.0000
-152	3.4237	1.0635	0.037922	0.058364	-1.0000
-157	3.4280	1.0651	0.037577	0.098508	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4237	1.0635	0.037922	0.058364	-1.0000
-157	3.4280	1.0651	0.037577	0.098508	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4290	1.0651	0.037577	0.098508	-1.0000
-172	3.4280	1.0651	0.037577	0.098508	-1.0000

>ADDITIONAL PRESSURE RATIOS , 60 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	4.1091	1.2767	0.045523	0.11808	-1.0000
-187	4.0490	1.2580	0.044857	0.11635	-1.0000

>SUBTICLE , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   07/07/79   CADDETT   REC 10/07/79 02:33:30.986   FAC 8X6X1   PGM C334   PRG 1856

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	16.376	5.0363	0.15304	0.42781	0.43200
37	8.4517	2.6104	0.094873	0.22175	0.53000
47	15.496	4.7831	0.17384	0.43690	0.62900
52	10.947	3.3812	0.12288	0.28722	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.527	3.8691	0.14062	0.32667	0.42200
67	8.7669	2.7378	0.098410	0.23091	0.67800

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	35.714	11.031	0.40091	0.93704	0.50800
82	18.110	5.5935	0.20329	0.47514	0.58300
92	3.488	1.0773	0.039154	0.091515	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	7.5664	2.3370	0.084935	0.19852	0.62400
112	5.3833	1.6617	0.060392	0.14115	0.83000
122	5.2348	1.6169	0.058763	0.13735	0.96000
127	3.4930	1.0789	0.039213	0.091646	1.0900
137	4.4741	1.3819	0.050273	0.11739	1.2200
142	4.1497	1.2505	0.045448	0.10622	1.3500

>ADDITIONAL PRESSURE RATIOS , SCREECON INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.5664	2.3370	0.084935	0.19852	-1.0000
-112	5.3833	1.6617	0.060392	0.14115	-1.0000
-122	5.2348	1.6169	0.058763	0.13735	-1.0000
-127	3.4930	1.0789	0.039213	0.091646	-1.0000
-137	4.4741	1.3819	0.050223	0.11739	-1.0000
-142	4.1497	1.2505	0.045448	0.10622	-1.0000
-152	3.4483	1.0650	0.038705	0.090464	-1.0000
-157	3.4483	1.0650	0.038705	0.090464	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4483	1.0650	0.038705	0.090464	-1.0000
-157	3.4483	1.0650	0.038705	0.090464	-1.0000

>ADDITIONAL PRESSURE RATIOS , 30 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4483	1.0650	0.038705	0.090464	-1.0000
-172	3.4430	1.0636	0.038648	0.090333	-1.0000

>ADDITIONAL PRESSURE RATIOS , 30 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	4.1187	1.2721	0.046234	0.10806	-1.0000
-187	4.1527	1.2529	0.045594	0.11636	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

Row 14

NASA-LEWIS   PRELIMINARY DATA   07/07/79   CADDE11   REC 10/07/79 02:35:23.246   FSC 9X6X1   PGM C034   PDG 1057

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	19.779	5.7897	0.20549	0.42721	0.43200
37	9.6736	2.9823	0.10792	0.22307	0.53000
47	17.653	5.4433	0.19659	0.40172	0.62500
52	12.536	3.8663	0.13985	0.28519	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.492	4.4642	0.16156	0.32946	0.42200
67	10.194	3.1095	0.11245	0.22941	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	35.959	11.085	0.40114	0.81804	0.50000
82	18.228	5.6191	0.20335	0.41469	0.58300
92	3.4995	1.0757	0.038928	0.079385	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	7.6163	2.3478	0.084965	0.17327	0.62400
112	5.4131	1.6686	0.060397	0.12315	0.83300
122	5.2678	1.6239	0.058767	0.11984	0.96000
127	3.4995	1.0788	0.039040	0.079613	1.0500
137	4.8822	1.5050	0.054464	0.11107	1.2200
142	4.5315	1.3969	0.050553	0.10309	1.3500

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.6163	2.3478	0.084965	0.17327	-1.0000
-112	5.4131	1.6686	0.060397	0.12315	-1.0000
-122	5.2678	1.6239	0.058767	0.11984	-1.0000
-127	3.4995	1.0788	0.039040	0.079613	-1.0000
-137	4.8822	1.5050	0.054464	0.11107	-1.0000
-142	4.5315	1.3969	0.050553	0.10309	-1.0000
-152	3.4494	1.0633	0.038491	0.078473	-1.0000
-157	3.4494	1.0633	0.038491	0.078473	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4494	1.0633	0.038491	0.078473	-1.0000
-157	3.4494	1.0633	0.038491	0.078473	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4564	1.0649	0.038537	0.078567	-1.0000
-172	3.4494	1.0633	0.038491	0.078473	-1.0000

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	4.1333	1.2734	0.046092	0.093974	-1.0000
-187	4.0707	1.2549	0.045411	0.092606	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

21

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.255	4.1172	0.16420	0.42659	0.43200
37	6.9053	2.1449	0.085540	0.22224	0.53000
47	12.559	3.9012	0.15559	0.40422	0.62900
52	9.0322	2.8356	0.11189	0.29070	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.193	3.1662	0.12627	0.32806	0.42200
67	7.1303	2.2148	0.088331	0.22945	0.67900

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.521	10.102	0.40288	1.0467	0.53900
82	16.415	5.0990	0.20336	0.52832	0.58300
92	3.4749	1.0794	0.043048	0.11184	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.8500	2.1278	0.094858	0.22046	0.62400
112	4.9773	1.5150	0.060421	0.15697	0.83000
122	4.7371	1.4714	0.058683	0.15246	0.96000
127	3.4699	1.0778	0.042996	0.11168	1.0900
137	3.9506	1.1961	0.047792	0.12393	1.2200
142	3.3497	1.0405	0.041496	0.10781	1.3500

>ADDITIONAL PRESSURE RATIOS , SECONDARY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.8500	2.1278	0.094858	0.22046	-1.0000
-112	4.9773	1.5150	0.060420	0.15697	-1.0000
-122	4.7371	1.4714	0.058683	0.15246	-1.0000
-127	3.4699	1.0778	0.042996	0.11168	-1.0000
-137	3.9506	1.1961	0.047792	0.12393	-1.0000
-142	3.3497	1.0405	0.041496	0.10781	-1.0000
-152	3.4299	1.0654	0.042489	0.11039	-1.0000
-157	3.4299	1.0654	0.042489	0.11039	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4299	1.0654	0.042489	0.11039	-1.0000
-157	3.4299	1.0654	0.042489	0.11039	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4299	1.0654	0.042489	0.11039	-1.0000
-172	3.4299	1.0654	0.042489	0.11039	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.9958	1.2412	0.049501	0.12860	-1.0000
-187	3.9157	1.2163	0.048528	0.12603	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

22

23

NASA-LEWIS   PRELIMINARY DATA   07/37/79   CADDELL   REC 10/37/79 02:37:32.P75   F8C 8N6X1   PGM C034   RDG 1859

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.758	4.5770	0.18307	0.42881	0.43200
37	7.6719	2.3702	0.095634	0.22201	0.53000
47	13.368	4.3218	0.17412	0.40584	0.62900
52	9.9447	3.0841	0.12398	0.28894	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.331	3.5140	0.14125	0.32922	0.42200
67	7.9423	2.4631	0.099004	0.23076	0.67900

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.335	13.028	0.40308	0.93951	0.53800
82	16.299	5.0568	0.20318	0.47358	0.58300
92	3.4745	1.0775	0.043312	0.10095	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.8356	2.1106	0.084836	0.19774	0.62400
112	4.8373	1.5002	0.060299	0.14055	0.83000
122	4.7073	1.4599	0.058676	0.13676	0.96000
127	3.4745	1.0775	0.043312	0.10095	1.0400
137	4.0337	1.2500	0.050245	0.11711	1.2200
142	3.6560	1.1335	0.045560	0.10619	1.3500

>ADDITIONAL PRESSURE RATIOS , SHROUD INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.8056	2.1106	0.084836	0.19774	-1.0000
-112	4.8373	1.5002	0.060299	0.14055	-1.0000
-122	4.7070	1.4599	0.058676	0.13676	-1.0000
-127	3.4745	1.0775	0.043312	0.10095	-1.0000
-137	4.0337	1.2500	0.050245	0.11711	-1.0000
-142	3.6560	1.1335	0.045560	0.10619	-1.0000
-152	3.4234	1.0636	0.042750	0.099643	-1.0000
-157	3.4344	1.0651	0.042812	0.099780	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4234	1.0636	0.042750	0.099643	-1.0000
-157	3.4344	1.0651	0.042812	0.099780	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4344	1.0651	0.042812	0.099780	-1.0000
-172	3.4344	1.0651	0.042812	0.099780	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.9056	1.2391	0.045908	0.11609	-1.0000
-187	3.9205	1.2158	0.048971	0.11391	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	17.134	5.3270	0.21325	0.42774	0.43200
37	8.8531	2.7524	0.11019	0.22102	0.53000
47	16.294	5.0628	0.20267	0.40654	0.62900
52	11.469	3.5654	0.14274	0.28633	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.159	4.0913	0.16378	0.32853	0.42200
67	9.2033	2.8613	0.11454	0.22976	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.426	10.081	0.40356	0.80952	0.50800
82	16.333	5.0799	0.20325	0.40792	0.58300
92	3.4724	1.0794	0.043216	0.086650	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.8266	2.1224	0.084960	0.17043	0.62400
112	4.9544	1.5392	0.060416	0.12119	0.83000
122	4.7142	1.4656	0.058671	0.11769	0.96000
127	3.4775	1.0811	0.043279	0.086815	1.0000
137	4.4689	1.3831	0.055369	0.11107	1.2200
142	4.1134	1.2789	0.051193	0.10269	1.3500

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.8266	2.1224	0.084960	0.17043	-1.0000
-112	4.8544	1.5392	0.063416	0.12119	-1.0000
-122	4.7142	1.4656	0.058671	0.11769	-1.0000
-127	3.4775	1.0811	0.043279	0.086815	-1.0000
-137	4.4689	1.3831	0.055369	0.11107	-1.0000
-142	4.1134	1.2789	0.051193	0.10269	-1.0000
-152	3.4324	1.0671	0.042718	0.085650	-1.0000
-157	3.4324	1.0671	0.042718	0.085690	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4324	1.0671	0.042718	0.085690	-1.0000
-157	3.4324	1.0671	0.042718	0.085650	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4324	1.0671	0.042718	0.085690	-1.0000
-172	3.4324	1.0671	0.042718	0.085690	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.9732	1.2353	0.049449	0.099192	-1.0000
-187	3.3931	1.2198	0.048389	0.097167	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

24

NASA-LEWIS   PRELIMINARY DATA   07/07/79   CADDELL   REC 10/07/79 02:40:29.495   FAC 8X6X1   PGM C034   RDG 1061

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.177	3.7125	0.16466	0.42745	0.43200
37	6.3373	1.9465	0.094333	0.22411	0.53000
47	11.432	3.5142	0.15687	0.40461	0.62600
52	8.2643	2.5405	0.11268	0.25259	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	9.3002	2.8589	0.12680	0.32517	0.42200
67	6.5123	2.0319	0.088750	0.23049	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	29.863	9.1799	0.40716	1.0570	0.50800
82	14.893	4.5782	0.20306	0.52713	0.58300
92	3.5125	1.0798	0.047891	0.12432	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.2319	1.9157	0.084968	0.22057	0.62400
112	4.4292	1.3615	0.060389	0.15676	0.83000
122	4.3099	1.3246	0.058750	0.15251	0.96000
127	3.4975	1.0751	0.047696	0.12379	1.0500
137	3.5075	1.0782	0.047923	0.12414	1.2200
142	3.0516	0.93808	0.041607	0.10801	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.2319	1.9157	0.084968	0.22057	-1.0000
-112	4.4292	1.3615	0.060389	0.15676	-1.0000
-122	4.3099	1.3246	0.058750	0.15251	-1.0000
-127	3.4975	1.0751	0.047696	0.12379	-1.0000
-137	3.5075	1.0782	0.047923	0.12414	-1.0000
-142	3.0516	0.93808	0.041607	0.10801	-1.0000
-152	3.4624	1.0644	0.047209	0.12255	-1.0000
-157	3.4624	1.0644	0.047209	0.12255	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4624	1.0644	0.047209	0.12255	-1.0000
-157	3.4624	1.0644	0.047209	0.12255	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4674	1.0659	0.047276	0.12272	-1.0000
-172	3.4674	1.0659	0.047276	0.12272	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.9383	1.2108	0.053696	0.13930	-1.0000
-187	3.8592	1.1960	0.052604	0.13655	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PN	PL/PTF	PL/PTP	X/DMAX
32	13.531	4.1620	0.18475	0.42761	0.43200
37	7.3595	2.1713	0.C96386	0.22309	0.53000
47	12.931	3.9619	0.17587	C.40706	0.62900
52	9.1373	2.9104	0.12476	0.28075	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PN	PL/PTF	PL/PTP	X/DMAX
62	10.799	3.1984	0.14199	0.32861	0.42200
67	7.2748	2.2376	0.CS5326	0.22585	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PN	PL/PTF	PL/PTP	X/DMAX
77	29.827	9.1741	0.40724	0.94256	0.50800
82	14.867	4.5729	0.20259	0.46582	0.58300
92	3.5079	1.0790	0.047895	0.11086	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PN	PL/PTF	PL/PTP	X/DMAX
107	6.2381	1.9095	0.084762	0.19619	0.62400
112	4.4049	1.3548	0.060141	0.13920	0.83000
122	4.2896	1.3194	0.058567	0.13556	0.96000
127	3.4929	1.0743	0.047690	0.11039	1.0500
137	3.6783	1.1314	0.050221	0.11624	1.2200
142	3.3576	1.0327	0.045843	0.10610	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PN	PL/PTF	PL/PTP	X/DMAX
-107	6.2381	1.9095	0.084762	0.19619	-1.0000
-112	4.4049	1.3548	0.060141	0.13920	-1.0000
-122	4.2896	1.3194	0.058567	0.13556	-1.0000
-127	3.4929	1.0743	0.047690	0.11039	-1.0000
-137	3.6783	1.1314	0.050221	0.11624	-1.0000
-142	3.3576	1.0327	0.045843	0.10610	-1.0000
-152	3.4623	1.0651	0.047279	0.10943	-1.0000
-157	3.4578	1.0636	0.047211	0.10927	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PN	PL/PTF	PL/PTP	X/DMAX
-152	3.4623	1.0651	0.047279	0.10943	-1.0000
-157	3.4578	1.0636	0.047211	0.10927	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PN	PL/PTF	PL/PTP	X/DMAX
-167	3.4623	1.0651	0.047279	0.10943	-1.0000
-172	3.4623	1.0651	0.047279	0.10943	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PN	PL/PTF	PL/PTP	X/DMAX
-17?	3.9338	1.2100	0.053719	0.17431	-1.0000
-182	3.8537	1.1852	0.052616	0.12179	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

26

placeholder

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.597	4.7902	0.21289	0.42717	3.43200
37	8.0957	2.4865	0.11053	0.22173	0.53000
47	16.961	4.5351	0.23422	0.49977	3.62500
52	13.478	3.2183	0.14302	0.29659	0.72300

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.984	3.6809	0.16358	0.32824	3.42280
67	8.3861	2.5757	3.11447	0.22968	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTEP O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	29.884	9.1784	0.40790	0.81848	0.50800
82	14.931	4.5767	0.23340	0.40913	0.58300
92	3.5082	1.0775	0.047886	0.096086	3.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOP SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.2191	1.9099	0.084875	0.17031	0.62500
112	4.4250	1.3591	0.060400	0.12120	3.83000
122	4.2898	1.3175	0.058554	0.11749	0.56000
127	3.5032	1.0760	0.047817	0.095949	1.0900
137	4.0493	1.2437	0.055271	0.11051	1.2200
142	3.7487	1.1514	0.051168	0.10267	1.3500

>ADDITIONAL PRESSURE RATIOS , EJECTOP HALES

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.2191	1.9099	0.084875	0.17031	-1.0000
-112	4.4250	1.3591	0.060400	0.12120	-1.0000
-122	4.2898	1.3175	0.058554	0.11749	-1.0000
-127	3.5032	1.0760	0.047817	0.095949	-1.0000
-137	4.0493	1.2437	0.055271	0.11051	-1.0000
-142	3.7487	1.1514	0.051168	0.10267	-1.0000
-152	3.4681	1.0652	0.047339	0.094988	-1.0000
-157	3.4681	1.0652	0.047339	0.094988	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZIE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4681	1.0652	0.047339	0.094988	-1.0000
-157	3.4681	1.0652	0.047339	0.094988	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHPCOP LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4681	1.0652	0.047339	0.094988	-1.0000
-172	3.4681	1.0652	0.047339	0.094988	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHPCUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.9140	1.2021	0.053425	0.10720	-1.0000
-187	3.8133	1.1729	0.052126	0.13459	-1.0000

>SECTION 3 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	10.652	3.2988	0.16436	0.42664	0.43200
37	5.5912	1.7316	0.094274	0.22395	0.53000
47	10.151	3.1439	0.15444	0.40660	0.62900
52	7.3285	2.2697	0.11308	0.29354	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	8.2945	2.5410	0.12660	0.32862	0.42200
67	5.7416	1.7782	0.088594	0.22997	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	26.501	8.2076	0.40963	1.0615	0.50000
92	13.153	4.0735	0.23296	0.52683	0.58300
97	3.4877	1.0802	0.053818	0.13970	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.4760	1.6960	0.084499	0.21934	0.62400
112	3.9035	1.2399	0.060233	0.15635	0.83000
122	3.7893	1.1732	0.058455	0.15174	0.96000
127	3.4627	1.0724	0.053431	0.13865	1.0900
137	3.3919	0.95759	0.047711	0.12384	1.2200
142	2.6911	0.83346	0.041526	0.10779	1.3500

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.4760	1.6960	0.084499	0.21934	-1.0000
-112	3.9035	1.2399	0.060233	0.15635	-1.0000
-122	3.7893	1.1732	0.058455	0.15174	-1.0000
-127	3.4627	1.0724	0.053431	0.13865	-1.0000
-137	3.3919	0.95759	0.047711	0.12384	-1.0000
-142	2.6911	0.83346	0.041526	0.10779	-1.0000
-152	3.4426	1.0662	0.053122	0.13789	-1.0000
-157	3.4376	1.0646	0.053045	0.13769	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4426	1.0662	0.053122	0.13789	-1.0000
-157	3.4376	1.0646	0.053045	0.13769	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4426	1.0662	0.053122	0.13789	-1.0000
-172	3.4426	1.0662	0.053122	0.13789	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.9133	1.1810	0.058842	0.15274	-1.0000
-187	3.4781	1.1391	0.056755	0.14732	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.944	3.6383	0.18425	0.42651	0.43200
37	6.2434	1.9331	0.09631	0.22296	0.53933
47	11.433	3.5333	0.17400	0.40740	0.62400
52	8.1536	2.5237	0.12574	0.29137	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	9.1866	2.8444	0.14172	0.32806	0.42700
67	6.4237	1.9889	0.099099	0.22925	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	26.527	8.2135	0.40924	7.94730	0.50400
82	13.139	4.0682	0.20270	0.46521	0.58300
92	3.4790	1.0772	0.053672	0.12424	0.67800

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.4723	1.6944	0.094423	0.19542	0.62400
112	3.3938	1.2075	0.060163	0.13926	0.83000
122	3.7846	1.1718	0.058386	0.13515	0.96000
127	3.4593	1.0710	0.053362	0.12352	1.0900
137	3.2486	1.0359	0.050117	0.11601	1.2200
142	2.9533	0.91433	0.045557	0.10545	1.3500

>ADDITIONAL PRESSURE RATIOS , EJECTOR FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.4723	1.6944	0.094423	0.19542	-1.0000
-112	3.3998	1.2075	0.060163	0.13926	-1.0000
-122	3.7846	1.1718	0.058386	0.13515	-1.0000
-127	3.4593	1.0710	0.053362	0.12352	-1.0000
-137	3.2486	1.0059	0.050117	0.11601	-1.0000
-142	2.9533	0.91433	0.045557	0.10545	-1.0000
-152	3.4239	1.0617	0.052899	0.12245	-1.0000
-157	3.4239	1.0617	0.052899	0.12245	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4239	1.0617	0.052899	0.12245	-1.0000
-157	3.4239	1.0617	0.052899	0.12245	-1.0000

>ADDITIONAL PRESSURE RATIOS , 70 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4239	1.0617	0.052899	0.12245	-1.0000
-172	3.4239	1.0617	0.052899	0.12245	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.9247	1.1942	0.059036	0.13658	-1.0000
-187	3.7044	1.1470	0.057149	0.13229	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

29

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.856	4.2844	0.21347	0.42713	0.43280
37	7.2123	2.2330	0.11111	0.22232	0.53000
47	13.295	4.1111	0.20493	0.40985	0.62500
52	9.3835	2.9306	0.14452	0.28917	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.657	3.2954	0.16419	0.32853	0.42200
67	7.5474	2.3228	0.11574	0.22958	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	26.592	8.2225	0.40969	0.81974	0.50800
82	13.182	4.0755	0.20306	0.40630	0.58300
92	3.4890	1.0788	0.053754	0.10756	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.4886	1.6971	0.084560	0.16920	0.62400
112	3.9151	1.2106	0.060317	0.12069	0.83000
122	3.7999	1.1749	0.058541	0.11714	0.96000
127	3.4693	1.0726	0.053445	0.10694	1.0900
137	3.5842	1.1083	0.055221	0.11049	1.2200
142	3.3196	1.0261	0.051128	0.10230	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.4886	1.6971	0.084560	0.16920	-1.0000
-112	3.9151	1.2106	0.060317	0.12069	-1.0000
-122	3.7999	1.1749	0.058541	0.11714	-1.0000
-127	3.4693	1.0726	0.053465	0.10694	-1.0000
-137	3.5842	1.1083	0.055221	0.11049	-1.0000
-142	3.3196	1.0261	0.051128	0.10230	-1.0000
-152	3.4439	1.0649	0.053059	0.10616	-1.0000
-157	3.4439	1.0649	0.053059	0.10616	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4439	1.0649	0.053059	0.10616	-1.0000
-157	3.4439	1.0649	0.053059	0.10616	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4289	1.0533	0.052981	0.10601	-1.0000
-172	3.4439	1.0649	0.053059	0.10616	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.8248	1.1827	0.058927	0.11791	-1.0000
-187	3.7095	1.1470	0.057151	0.11435	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS . PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	22.243	1.5703	0.28434	0.53864	0.43200
37	17.913	1.2576	0.30779	0.43136	0.53000
47	18.143	1.2738	0.31176	0.43653	0.62900
52	11.767	0.83072	0.20332	0.28455	0.72700

>ADDITIONAL PRESSURE RATIOS . FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.758	0.97126	0.23772	0.33315	0.42200
67	9.4457	0.66684	0.16321	0.22874	0.67000

>ADDITIONAL PRESSURE RATIOS . FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	25.034	1.7673	0.43255	0.60621	0.50400
82	13.368	0.94372	0.23097	0.32371	0.59300
92	14.198	1.0016	0.24515	0.34357	0.67000

>ADDITIONAL PRESSURE RATIOS . EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	12.222	0.86286	0.21118	0.29597	0.62400
112	12.207	0.86180	0.21092	0.29561	0.83000
122	12.232	0.86357	0.21136	0.29621	0.96000
127	14.153	0.99915	0.24454	0.34272	1.0900
137	12.617	0.89076	0.21801	0.30554	1.2200
142	12.947	0.91406	0.22372	0.31353	1.3500

>ADDITIONAL PRESSURE RATIOS . FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	12.222	0.86286	0.21118	0.29597	-1.0000
-112	12.207	0.86180	0.21092	0.29561	-1.0000
-122	12.232	0.86357	0.21136	0.29621	-1.0000
-127	14.153	0.99915	0.24454	0.34272	-1.0000
-137	13.017	0.89076	0.21801	0.30554	-1.0000
-142	12.947	0.91406	0.22372	0.31353	-1.0000
-152	14.183	1.0013	0.24506	0.34345	-1.0000
-157	14.178	1.0009	0.24497	0.34333	-1.0000

>ADDITIONAL PRESSURE RATIOS . FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.183	1.0013	0.24506	0.34345	-1.0000
-157	14.178	1.0009	0.24497	0.34333	-1.0000

>ADDITIONAL PRESSURE RATIOS . 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	14.183	1.0013	0.24506	0.34345	-1.0000
-172	14.183	1.0013	0.24506	0.34345	-1.0000

>ADDITIONAL PRESSURE RATIOS . 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	14.193	1.0020	0.24523	0.34369	-1.0000
-187	14.193	1.0020	0.24523	0.34369	-1.0000

>OPTION 5 . MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   07/07/79   CADDEII   REC 10/07/79 03:32:17.245   FAC 9XEV1   PGM C324

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	21.237	1.5482	0.34111	0.53949	0.43200
37	17.490	1.2421	0.27367	0.43274	0.53300
47	17.917	1.2570	0.27694	0.43752	0.62900
52	11.696	0.82547	0.18197	0.28760	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.577	0.95826	0.21113	0.33386	0.42200
67	9.3296	0.65629	0.14475	0.22889	0.67900

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	27.753	1.9585	0.43151	0.68235	0.50800
82	13.322	0.94025	0.20716	0.32758	0.58300
92	14.198	1.0013	0.22062	0.34887	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	12.176	0.85928	0.18934	0.29941	0.62400
112	12.176	0.85928	0.18934	0.29941	0.83000
122	12.196	0.86005	0.18950	0.29966	0.56000
127	14.159	0.99922	0.22015	0.34813	1.0900
137	12.512	0.88304	0.19455	0.30765	1.2200
142	12.947	0.99670	0.19977	0.31590	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	12.176	0.85934	0.18934	0.29941	-1.0000
-112	12.176	0.85938	0.18934	0.29941	-1.0000
-122	12.196	0.86009	0.18951	0.29966	-1.0000
-127	14.159	0.99922	0.22015	0.34813	-1.0000
-137	12.512	0.89304	0.19455	0.30765	-1.0000
-142	12.947	0.93670	0.19977	0.31590	-1.0000
-152	14.198	1.0013	0.22062	0.34887	-1.0000
-157	14.198	1.0013	0.22062	0.34887	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.198	1.0013	0.22062	0.34887	-1.0000
-157	14.198	1.0013	0.22062	0.34887	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	14.192	1.0010	0.22054	0.34875	-1.0000
-172	14.192	1.0013	0.22054	0.34875	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	14.193	1.0017	0.22070	0.34899	-1.0000
-187	14.193	1.0020	0.22077	0.34911	-1.0000

>SORTICN 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	21.545	1.5227	0.30287	0.53843	0.43200
37	17.316	1.2237	0.24343	0.43271	0.53000
47	17.513	1.2375	0.24614	0.43758	0.62500
52	12.328	0.85306	0.16509	0.30959	0.72730

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.342	0.94304	0.18757	0.32347	0.42200
67	9.1659	0.64779	0.12885	0.22906	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	30.619	2.1640	0.43042	0.76520	0.50500
82	14.649	1.0353	0.20592	0.36609	0.50300
92	14.174	1.0017	0.19925	0.35422	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	12.083	0.85395	0.16985	0.30196	0.62500
112	12.068	0.85289	0.16964	0.30159	0.83000
122	12.109	0.85572	0.17029	0.30259	0.96300
127	14.139	0.99925	0.19875	0.35334	1.0900
137	12.438	0.87905	0.17485	0.31084	1.2200
142	12.753	0.90133	0.17928	0.31871	1.3500

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	12.083	0.85395	0.16985	0.30196	-1.0000
-112	12.068	0.85289	0.16964	0.30159	-1.0000
-122	12.109	0.85572	0.17029	0.30259	-1.0000
-127	14.139	0.99925	0.19875	0.35334	-1.0000
-137	12.438	0.87905	0.17485	0.31084	-1.0000
-142	12.753	0.90133	0.17928	0.31871	-1.0000
-152	14.164	1.0010	0.19910	0.35397	-1.0000
-157	14.169	1.0014	0.19918	0.35409	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.164	1.0010	0.19910	0.35397	-1.0000
-157	14.169	1.0014	0.19919	0.35409	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	14.169	1.0014	0.19918	0.35409	-1.0000
-172	14.164	1.0010	0.19913	0.35397	-1.0000

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	14.199	1.0029	0.19946	0.35459	-1.0000
-187	14.199	1.0029	0.19946	0.35459	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	21.191	1.4974	0.27181	0.53911	0.43200
37	17.335	1.2322	0.21923	0.43293	0.53000
47	17.210	1.7167	0.22686	0.43805	0.62900
52	11.498	0.89657	0.14643	0.29037	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	13.109	0.92674	0.16823	0.33366	0.42200
67	9.0012	0.63635	0.11551	0.22911	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	33.417	2.3625	0.42885	0.85059	0.50900
82	16.030	1.1332	0.20571	0.40801	0.50300
92	14.164	1.0014	0.18177	0.36053	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	11.853	0.83798	0.15211	0.30171	0.62400
112	11.803	0.83444	0.15147	0.30043	0.83000
122	12.003	0.84959	0.15404	0.30553	0.96000
127	14.124	0.99852	0.18126	0.35951	1.0900
137	12.319	0.87087	0.15809	0.31355	1.2200
142	12.534	0.89315	0.16213	0.37157	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	11.853	0.83798	0.15211	0.30171	-1.0000
-112	11.803	0.83444	0.15147	0.30043	-1.0000
-122	12.003	0.84959	0.15404	0.30553	-1.0000
-127	14.124	0.99852	0.18126	0.35951	-1.0000
-137	12.319	0.87087	0.15809	0.31355	-1.0000
-142	12.534	0.89315	0.16213	0.32157	-1.0000
-152	14.159	1.0010	0.18171	0.36040	-1.0000
-157	14.159	1.0010	0.18171	0.36040	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	14.159	1.0010	0.18171	0.36040	-1.0000
-157	14.159	1.0010	0.18171	0.36040	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-167	14.159	1.0010	0.18171	0.36040	-1.0000
-172	14.164	1.0026	0.18164	0.36027	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-182	14.194	1.0035	0.18214	0.36129	-1.0000
-187	14.194	1.0035	0.18214	0.36129	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

34

35

NOZZLE TYPE	P&W RISE EJECTOR NOZZLE (MODEL C)	
FLIGHT CONDITIONS	SUPER SONIC CRUISE (NS=.02 WT)	
NOZZLE CONFIGURATION	C1	
PRIMARY-NOZZLE PLUG	SPLIT PLUG (RETRACTED)	
FLOW SPLITTER	ISENTROPIC SPLITTER	
FAN NOZZLE	SHORT FLAP	
CLAMSHELL POSITION		
EJECTOR INLET OPENING		

PD3	WT	PTF/PTP	PTF/PC	PTP/PD	OMEGA	PTS/PTF	CDF	CDP	CF1	ETA1	ETA1.INT	CFP1	CFP2	F9
1071	1.964	2.30	19.75	8.57	0.000	0.134	1.003	0.979	0.9749	0.9749	0.9781	0.9781	0.9786	1.4968
1072	1.959	2.32	22.08	9.53	0.000	0.133	1.004	0.981	0.9802	0.9802	0.9830	0.9830	0.9835	1.4992
1073	1.959	2.32	24.83	10.70	0.000	0.133	1.005	0.981	0.9828	0.9828	0.9853	0.9853	0.9858	1.4992
1074	1.959	2.32	27.67	11.91	0.000	0.133	1.006	0.981	0.9840	0.9840	0.9862	0.9862	0.9866	1.4987
1077	1.961	2.33	27.58	11.84	0.000	0.133	1.005	0.983	0.9833	0.9839	0.9856	0.9856	0.9860	1.4995
1078	1.960	2.33	24.55	10.72	0.000	0.134	1.003	0.982	0.9855	0.9855	0.9879	0.9879	0.9884	1.5015
1079	1.959	2.31	22.18	9.62	0.000	0.134	1.004	0.982	0.9839	0.9839	0.9867	0.9867	0.9872	1.5037
1080	1.963	2.31	19.69	8.53	0.000	0.134	1.002	0.980	0.9812	0.9812	0.9844	0.9844	0.9850	1.5032
1081	1.957	2.31	29.20	12.62	0.000	0.134	1.006	0.981	0.9876	0.9876	0.9897	0.9897	0.9901	1.5031
1082	1.961	2.31	29.41	12.75	0.000	0.134	1.005	0.984	0.9865	0.9865	0.9885	0.9885	0.9890	1.5026
1083	1.959	1.99	20.01	10.03	0.018	0.134	0.974	0.982	0.9948	0.9831	0.9962	0.9978	0.9984	1.4923
1084	1.957	2.31	19.60	8.50	0.019	0.133	0.972	0.981	0.9938	0.9814	0.9867	0.9971	0.9976	1.4960
1085	1.958	2.31	19.91	8.63	0.019	0.134	0.977	0.982	0.9937	0.9813	0.9866	0.9970	0.9975	1.4990
1086	1.959	2.50	19.89	7.66	0.020	0.133	0.972	0.980	0.9943	0.9812	0.9867	0.9978	0.9983	1.5000
1087	1.958	2.00	22.33	11.14	0.018	0.133	0.974	0.983	0.9993	0.9872	0.9890	1.0029	1.0025	1.4956
1088	1.959	2.31	22.46	9.72	0.019	0.134	0.974	0.982	0.9974	0.9844	0.9873	1.0002	1.0007	1.4985
1089	1.959	2.60	22.46	8.65	0.019	0.133	0.974	0.981	0.9973	0.9837	0.9867	1.0003	1.0008	1.4995
1090	1.960	2.03	24.94	12.46	0.018	0.134	0.975	0.983	1.0000	0.9876	0.9900	1.0024	1.0029	1.4981
1091	1.960	2.33	24.84	10.67	0.019	0.134	0.973	0.982	1.0039	0.9905	0.9931	1.0065	1.0069	1.5006
1092	1.961	2.59	24.84	9.58	0.019	0.134	0.972	0.981	1.0055	0.9914	0.9941	1.0082	1.0086	1.5068
1093	1.963	2.02	27.39	13.53	0.018	0.134	0.978	0.985	1.0020	0.9892	0.9914	1.0042	1.0046	1.4995
1094	1.959	2.33	27.34	11.75	0.019	0.133	0.973	0.982	1.0088	0.9951	0.9974	1.0111	1.0116	1.5053
1095	1.961	2.60	27.38	10.52	0.020	0.133	0.974	0.983	1.0040	0.9897	0.9921	1.0066	1.0068	1.5125
1096	1.963	2.32	29.47	12.87	0.019	0.134	0.977	0.984	1.0030	0.9891	0.9912	1.0051	1.0055	1.5005
1097	1.960	2.60	29.96	11.53	0.019	0.134	0.974	0.981	1.0040	0.9914	0.9936	1.0042	1.0086	1.5139
1098	1.960	2.33	29.84	12.87	0.019	0.134	0.975	0.981	1.0047	0.9908	0.9929	1.0068	1.0072	1.5014
1099	1.963	2.33	27.48	11.80	0.019	0.134	0.973	0.982	1.0049	0.9912	0.9935	1.0072	1.0076	1.5007
1100	1.963	2.32	24.41	10.71	0.019	0.133	0.975	0.984	1.0010	0.9877	0.9903	1.0036	1.0041	1.5001
1101	1.960	2.31	22.41	9.70	0.019	0.134	0.972	0.981	1.0024	0.9893	0.9922	1.0052	1.0057	1.5012
1102	1.961	2.31	19.96	8.65	0.019	0.134	0.973	0.982	0.9954	0.9829	0.9962	0.9997	0.9992	1.4983

NASA-LEWIS   PRELIMINARY DATA   06/10/79   CAODEII   REC 10/11/79 03:33:24.247   FAC RN6X1   PGM C034   RDG 1071   *RUN 15*

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.341	3.6959	0.18709	0.43106	0.43200
37	6.5331	1.9566	0.099047	0.22820	0.53000
47	8.3479	2.4792	0.12504	0.28813	0.62900
52	8.2729	2.4777	0.12542	0.28927	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
52	9.3925	2.8130	0.14240	0.37808	0.42200
67	6.5931	1.9746	0.099957	0.23030	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	26.851	8.0416	0.40707	0.93789	0.50800
82	13.235	3.9638	0.20065	0.46230	0.58300
52	3.5823	1.0729	0.054311	0.12513	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	3.9825	1.1927	0.060379	0.13911	0.62400
112	3.9275	1.1763	0.059544	0.13719	0.83000
122	3.8675	1.1523	0.058331	0.13439	0.96000
127	3.5723	1.0699	0.054159	0.12478	1.0900
137	3.2621	0.97698	0.049456	0.11395	1.2200
142	3.2171	0.96350	0.048774	0.11237	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INNER

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	3.9825	1.1927	0.060379	0.13911	-1.0000
-112	3.9275	1.1763	0.059544	0.13719	-1.0000
-122	3.8675	1.1523	0.058331	0.13439	-1.0000
-127	3.5723	1.0699	0.054159	0.12478	-1.0000
-137	3.2621	0.97698	0.049456	0.11395	-1.0000
-142	3.2171	0.96350	0.048774	0.11237	-1.0000
-152	3.5473	1.0624	0.053780	0.12391	-1.0000
-157	3.5473	1.0624	0.053780	0.12391	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-162	3.5473	1.0624	0.053780	0.12391	-1.0000
-157	3.5473	1.0624	0.053780	0.12391	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5523	1.0639	0.053856	0.12408	-1.0000
-172	3.5523	1.0639	0.053856	0.12408	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3970	0.92756	0.046953	0.10818	-1.0000
-187	3.1571	0.94552	0.047863	0.11028	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

36

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.836	4.1164	0.18647	0.43212	0.43200
37	7.2908	2.1691	0.098257	0.22770	0.53000
47	9.2415	2.7494	0.12455	0.28862	0.62900
52	9.2665	2.7569	0.12488	0.28941	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.532	3.1333	0.14193	0.32892	0.42200
67	7.3909	2.1989	0.099606	0.23083	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	30.588	9.0995	0.41220	0.95523	0.50800
82	14.921	4.4391	0.20109	0.46600	0.58300
87	3.6078	1.0733	0.048621	0.11268	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.5088	1.3414	0.060764	0.14081	0.62400
112	4.4437	1.3220	0.059887	0.13878	0.83000
122	4.3486	1.2937	0.058605	0.13581	0.96000
127	3.5978	1.0704	0.048486	0.11236	1.0900
137	3.6528	1.0867	0.049228	0.11408	1.2200
142	3.6178	1.0763	0.048756	0.11299	1.3500

>ADDITIONAL PRESSURE RATIOS , FAN FRAME INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.5088	1.3414	0.060764	0.14081	-1.0000
-112	4.4437	1.3220	0.059887	0.13878	-1.0000
-122	4.3486	1.2937	0.058605	0.13581	-1.0000
-127	3.5978	1.0704	0.048486	0.11236	-1.0000
-137	3.6528	1.0867	0.049228	0.11408	-1.0000
-142	3.6178	1.0763	0.048756	0.11299	-1.0000
-152	3.5727	1.0629	0.048149	0.11158	-1.0000
-157	3.5727	1.0629	0.048149	0.11158	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE/FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5727	1.0629	0.049149	0.11158	-1.0000
-157	3.5727	1.0629	0.048149	0.11158	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5727	1.0629	0.048149	0.11158	-1.0000
-172	3.5727	1.0629	0.048149	0.11158	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.1971	0.92143	0.041740	0.096728	-1.0000
-187	3.1672	0.94228	0.042684	0.099917	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

37

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.548	4.6199	0.18604	0.43147	0.43200
37	8.1581	2.4241	0.097615	0.22665	0.53000
47	10.359	3.0780	0.12395	0.28779	0.62900
52	10.409	3.0938	0.12454	0.28918	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.824	3.5133	0.14148	0.32850	0.42200
67	8.2892	2.4627	0.099171	0.23027	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	34.261	10.180	0.40995	0.95187	0.50800
82	16.798	4.9912	0.20099	0.46668	0.58300
92	3.6094	1.0725	0.043197	0.10028	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.0860	1.5112	0.060856	0.14130	0.62400
112	5.0159	1.4904	0.060018	0.13936	0.83000
122	4.9058	1.4577	0.058700	0.13630	0.96000
127	3.6044	1.0710	0.043127	0.10014	1.0900
137	4.1033	1.2183	0.049058	0.11391	1.2200
142	4.0649	1.2093	0.048699	0.11307	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.0860	1.5112	0.060856	0.14130	-1.0000
-112	5.0159	1.4904	0.060018	0.13936	-1.0000
-122	4.9058	1.4577	0.058700	0.13630	-1.0000
-127	3.6044	1.0710	0.043127	0.10014	-1.0000
-137	4.1000	1.2183	0.049058	0.11341	-1.0000
-142	4.0649	1.2093	0.048699	0.11307	-1.0000
-152	3.5843	1.0650	0.042888	0.099582	-1.0000
-157	3.5793	1.0636	0.042828	0.099443	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5843	1.0650	0.042888	0.099582	-1.0000
-157	3.5793	1.0636	0.042828	0.099443	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5793	1.0636	0.042828	0.099443	-1.0000
-172	3.5843	1.0650	0.042888	0.099582	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-192	3.1137	0.92520	0.037257	0.086597	-1.0000
-197	3.1838	0.94603	0.038095	0.088454	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	17.267	5.1348	0.18559	0.43112	0.43200
37	9.0451	2.6898	0.097222	0.22584	0.53000
47	11.510	3.4728	0.12371	0.28738	0.62900
52	11.565	3.4391	0.12430	0.28875	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.149	3.9193	0.14133	0.32831	0.42200
67	9.2051	2.7374	0.098941	0.22984	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	37.620	11.187	0.40436	0.93930	0.50800
82	18.706	5.5627	0.20106	0.46705	0.58300
87	3.6075	1.0728	0.038775	0.090073	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.6441	1.6784	0.060666	0.14092	0.62400
112	5.5740	1.6576	0.059913	0.13917	0.83000
122	5.4589	1.6234	0.058676	0.13630	0.96000
127	3.6175	1.0758	0.038883	0.090323	1.0900
137	4.5583	1.3555	0.048995	0.11381	1.2200
142	4.5283	1.3466	0.048673	0.11306	1.3500

>ADDITIONAL PRESSURE RATIOS , FAIRING INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.6441	1.6784	0.060666	0.14092	-1.0000
-112	5.5740	1.6576	0.059913	0.13917	-1.0000
-122	5.4589	1.6234	0.058676	0.13630	-1.0000
-127	3.6175	1.0758	0.038883	0.090323	-1.0000
-137	4.5583	1.3555	0.048995	0.11381	-1.0000
-142	4.5283	1.3466	0.048673	0.11306	-1.0000
-152	3.5724	1.0624	0.038398	0.089198	-1.0000
-157	3.5724	1.0624	0.038398	0.089198	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE STEP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5724	1.0624	0.038398	0.089198	-1.0000
-157	3.5724	1.0624	0.038398	0.089198	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5774	1.0639	0.038452	0.089323	-1.0000
-172	3.5724	1.0624	0.038398	0.089198	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.1119	0.92543	0.033449	0.077700	-1.0000
-187	3.1820	0.94627	0.034202	0.079450	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

39

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	17.177	5.1140	0.18544	0.43203	0.43200
37	8.9986	2.6730	0.097143	0.22632	0.53300
47	11.439	3.4055	0.12349	0.28770	0.62900
52	11.499	3.6234	0.12414	0.28921	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.084	3.8952	0.14124	0.32907	0.42200
67	9.1585	2.7266	1.098871	0.23035	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	36.910	10.989	0.39846	0.92832	0.50800
82	18.612	5.5410	0.20092	0.46811	0.58300
87	3.6044	1.3731	0.038911	0.090054	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.6165	1.6721	0.060633	0.14126	0.62400
112	5.5464	1.6513	0.059877	0.13950	0.83000
122	5.4313	1.6170	0.058634	0.13660	0.96000
127	3.6144	1.3761	0.038019	0.090905	1.0900
137	4.5306	1.3488	0.048938	0.11395	1.2200
142	4.5004	1.3398	0.048584	0.11319	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.6165	1.6721	0.060633	0.14126	-1.0000
-112	5.5464	1.6513	0.059877	0.13950	-1.0000
-122	5.4313	1.6170	0.058634	0.13660	-1.0000
-127	3.6144	1.3761	0.038019	0.090905	-1.0000
-137	4.5306	1.3488	0.048908	0.11395	-1.0000
-142	4.5004	1.3398	0.048584	0.11319	-1.0000
-152	3.5743	1.0641	0.038587	0.089898	-1.0000
-157	3.5743	1.0641	0.038587	0.089898	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/TMAX
-152	3.5743	1.0641	0.038587	0.089898	-1.0000
-157	3.5743	1.0641	0.038587	0.089898	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/TMAX
-167	3.5743	1.0641	0.038587	0.089898	-1.0000
-172	3.5743	1.0641	0.038587	0.089898	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-132	3.1237	0.92998	0.033722	0.078565	-1.0000
-137	3.1899	0.94936	0.034425	0.080202	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

40

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.529	4.6757	0.18538	0.43144	0.43200
37	8.1928	2.4374	0.097683	0.22736	0.53000
47	10.357	3.0951	0.12364	0.28775	0.62900
52	10.492	3.0985	0.12418	0.28900	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.812	3.5196	0.14100	0.32816	0.42200
67	8.2878	2.4687	0.098936	0.23025	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	33.454	9.9648	0.39936	0.92941	0.50800
82	16.763	4.9933	0.20011	0.46572	0.58300
92	3.5912	1.0697	0.042870	0.099760	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.0771	1.5123	0.060608	0.14105	0.62400
112	4.9971	1.4885	0.059653	0.13883	0.83000
122	4.8970	1.4587	0.058458	0.13605	0.96000
127	3.5962	1.0712	0.042929	0.099908	1.0900
137	4.0865	1.2172	0.048783	0.11353	1.2200
142	4.0515	1.2068	0.048365	0.11256	1.3500

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.0771	1.5123	0.060608	0.14105	-1.0000
-112	4.9971	1.4885	0.059653	0.13883	-1.0000
-122	4.8970	1.4587	0.058458	0.13605	-1.0000
-127	3.5962	1.0712	0.042929	0.099908	-1.0000
-137	4.0865	1.2172	0.048783	0.11353	-1.0000
-142	4.0515	1.2068	0.048365	0.11256	-1.0000
-152	3.5661	1.0622	0.042571	0.099074	-1.0000
-157	3.5661	1.0622	0.042571	0.099074	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5661	1.0622	0.042571	0.099074	-1.0000
-157	3.5661	1.0622	0.042571	0.099074	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5661	1.0622	0.042571	0.099074	-1.0000
-172	3.5617	1.0607	0.042511	0.098935	-1.0000

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-192	3.1608	0.94150	0.037732	0.087813	-1.0000
-197	3.2208	0.95938	0.038449	0.089481	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/10/79   CADDEII   REC 10/11/79 03:42:26.803   FAC RX6X1   PGM C034   PRG 1079

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.930	4.1475	0.19701	0.43125	0.43200
37	7.3439	2.1866	0.098536	0.22736	0.53000
47	9.3317	2.7696	0.12489	0.28798	0.62400
52	9.3317	2.7785	0.12529	0.28850	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.590	3.1531	0.14219	0.32784	0.42200
67	7.6389	2.2149	0.099870	0.23030	0.67700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	29.746	8.8686	0.39988	0.92215	0.50900
82	14.913	4.4403	0.20021	0.46169	0.58700
92	3.5913	1.0693	0.048215	0.11115	0.67800

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.5060	1.3417	0.060495	0.13950	0.62400
112	4.4413	1.3223	0.059623	0.13749	0.83000
122	4.3461	1.2940	0.058348	0.13455	0.96000
127	3.5863	1.0678	0.048148	0.11103	1.0900
137	3.6663	1.0916	0.049222	0.11351	1.2200
142	3.6213	1.0782	0.048618	0.11211	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.5060	1.3417	0.060495	0.13950	-1.0000
-112	4.4410	1.3223	0.059623	0.13740	-1.0000
-122	4.3461	1.2940	0.058348	0.13455	-1.0000
-127	3.5863	1.0678	0.048148	0.11103	-1.0000
-137	3.6663	1.0916	0.049222	0.11351	-1.0000
-142	3.6213	1.0782	0.048618	0.11211	-1.0000
-152	3.5664	1.0619	0.047880	0.11041	-1.0000
-157	3.5614	1.0604	0.047813	0.11026	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5664	1.0619	0.047880	0.11041	-1.0000
-157	3.5614	1.0604	0.047813	0.11026	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5664	1.0619	0.047880	0.11041	-1.0000
-172	3.5614	1.0604	0.047813	0.11026	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.1366	0.93387	0.042190	0.097103	-1.0000
-187	3.2364	0.95471	0.043048	0.099270	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.332	3.6759	0.18669	0.43103	0.43200
37	6.5219	1.9440	0.098730	0.22755	0.53000
47	8.2475	2.4584	0.12485	0.28826	0.62900
52	8.2675	2.4643	0.12516	0.28856	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	9.3976	2.8012	0.14226	0.32846	0.42200
67	6.5919	1.9649	0.099790	0.23040	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	26.389	7.8660	0.39949	0.92235	0.50400
82	13.247	3.9486	0.20054	0.46300	0.58300
92	4.5446	1.0715	0.054416	0.12564	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	3.9700	1.1834	0.060099	0.13876	0.62400
113	3.9299	1.1714	0.059493	0.13736	0.83000
122	3.8499	1.1476	0.058281	0.13456	0.96000
127	3.5796	1.0670	0.054189	0.12511	1.0940
137	3.2392	0.96553	0.049036	0.11322	1.2200
142	3.2192	0.95658	0.048582	0.11217	1.3500

>ADDITIONAL PRESSURE RATIOS , FAN FRAME INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	3.9700	1.1834	0.060099	0.13876	-1.0000
-112	3.9299	1.1714	0.059493	0.13736	-1.0000
-122	3.8499	1.1476	0.058281	0.13456	-1.0000
-127	3.5796	1.0670	0.054189	0.12511	-1.0000
-137	3.2392	0.96553	0.049036	0.11322	-1.0000
-142	3.2192	0.95658	0.048582	0.11217	-1.0000
-152	3.5596	1.0610	0.053886	0.12441	-1.0000
-157	3.5646	1.0625	0.053962	0.12459	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5596	1.0610	0.053886	0.12441	-1.0000
-157	3.5646	1.0625	0.053962	0.12450	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-162	3.5596	1.0610	0.053886	0.12441	-1.0000
-172	3.5646	1.0625	0.053962	0.12450	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.1241	0.93121	0.047294	0.10919	-1.0000
-187	3.1042	0.95210	0.048354	0.11164	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

43

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVO WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
32	19.221	5.4468	0.14655	0.43174	0.43200
37	9.5590	2.9550	0.097782	0.22631	0.53000
47	12.112	3.6705	0.12403	0.29659	0.62900
52	12.192	3.6444	0.12482	0.28888	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVO WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
62	13.847	4.1392	0.14176	0.32809	0.42200
67	9.7913	2.8999	0.099318	0.22986	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVO WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
77	38.856	11.615	0.39781	0.92049	0.50000
82	19.601	5.8592	0.20067	0.46443	0.58300
92	3.5834	1.0703	0.036656	0.084838	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVO WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
107	5.9133	1.7677	0.060540	0.14011	0.62400
112	5.8483	1.7482	0.059874	0.13857	0.83000
122	5.7331	1.7138	0.058696	0.13585	0.96000
127	3.5854	1.0718	0.036708	0.084956	1.0900
137	4.7971	1.4340	0.049112	0.11367	1.2200
142	4.7670	1.4250	0.048805	0.11295	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVO WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-107	5.9133	1.7677	0.060540	0.14011	-1.0000
-112	5.8483	1.7482	0.059874	0.13857	-1.0000
-122	5.7331	1.7138	0.058696	0.13585	-1.0000
-127	3.5454	1.0718	0.036708	0.084956	-1.0000
-137	4.7971	1.4340	0.049112	0.11367	-1.0000
-142	4.7670	1.4250	0.048805	0.11295	-1.0000
-152	3.5454	1.0598	0.036259	0.094007	-1.0000
-157	3.5454	1.0598	0.036259	0.084007	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVO WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-152	3.5454	1.0598	0.036259	0.084007	-1.0000
-157	3.5454	1.0598	0.036259	0.084007	-1.0000

>ADDITIONAL PRESSURE RATIOS , 28 DEG SHROUD LOCATION

AVO WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-167	3.5454	1.0598	0.036259	0.084007	-1.0000
-172	3.5454	1.0598	0.036259	0.084007	-1.0000

>ADDITIONAL PRESSURE RATIOS , 63 DEG SHROUD LOCATION

AVO WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-182	3.1649	0.94635	0.032401	0.074989	-1.0000
-187	3.1849	0.95204	0.032606	0.075464	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

44

NASA-LEWIS   PRELIMINARY DATA   06/10/79   CADDFIT   REC 10/11/79 03:54:40.576   FAC 9X6X1   PGM C034   RDG 1082

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	19.444	5.5301	0.18700	0.43129	0.43200
37	9.6589	2.8804	0.097927	0.22586	0.53000
47	12.273	2.6599	0.12443	0.28699	0.62900
52	12.343	3.6808	0.12514	0.28863	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.067	4.1949	0.14262	0.32894	0.42200
67	9.8289	2.9310	0.099651	0.22984	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	39.083	11.655	0.39625	0.91391	0.50800
82	19.783	5.8994	0.20057	0.46260	0.58300
92	3.5968	1.0726	0.036467	0.084107	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.9584	1.7768	0.060410	0.13933	0.62400
112	5.9034	1.7604	0.059852	0.13804	0.83000
122	5.7833	1.7246	0.058635	0.13524	0.96000
127	3.6168	1.0786	0.036670	0.084575	1.0900
137	4.9578	1.4486	0.049251	0.11359	1.2700
142	4.8278	1.4397	0.048947	0.11289	1.3500

>ADDITIONAL PRESSURE RATIOS , COREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.9584	1.7768	0.060410	0.13933	-1.0000
-112	5.9034	1.7604	0.059852	0.13804	-1.0000
-122	5.7833	1.7246	0.058635	0.13524	-1.0000
-127	3.6168	1.0786	0.036670	0.084575	-1.0000
-137	4.9578	1.4486	0.049251	0.11359	-1.0000
-142	4.8278	1.4397	0.048947	0.11289	-1.0000
-152	3.5768	1.0666	0.036264	0.083639	-1.0000
-157	3.5768	1.0666	0.036264	0.083639	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5768	1.0666	0.036264	0.083639	-1.0000
-157	3.5768	1.0666	0.036264	0.083639	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5768	1.0666	0.036264	0.083639	-1.0000
-172	3.5818	1.0681	0.036314	0.083756	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-187	3.2064	0.95619	0.032509	0.074979	-1.0000
-192	3.2115	0.95768	0.032560	0.075096	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

45

CASE-LEWIS   PRELIMINARY DATA   06/10/79   CADWELL   PEC 10/11/79 04:05:47.209   FAE 9X6X1   PG* C034   PDG 1893

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
22	13.527	4.3165	0.21562	0.43095	0.43200
32	7.3513	2.2773	0.11381	0.22659	0.53000
47	6.2972	2.8771	0.14379	0.28677	3.67200
52	5.3272	2.8894	0.14441	0.28831	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.693	3.2945	0.16415	0.32730	0.42200
67	7.4414	2.3052	0.11521	0.22977	0.67300

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	25.354	8.3301	0.40027	0.79831	0.50800
82	12.948	4.0236	0.20109	0.40103	0.58300
52	3.4375	1.0549	0.053220	0.10614	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	3.8931	1.2029	0.060118	0.11950	0.62400
117	3.8390	1.1390	0.059421	0.11851	0.83000
122	3.7479	1.1611	0.058026	0.11573	0.96000
127	3.4325	1.0633	0.053142	0.10599	1.0900
132	3.5827	1.1099	0.055468	0.11063	1.2200
142	3.5226	1.0913	0.054537	0.10877	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	3.8931	1.2029	3.060118	0.11990	-1.0000
-117	2.8390	1.1990	0.059421	0.11851	-1.0000
-122	3.7479	1.1611	0.058026	0.11573	-1.0000
-127	3.4325	1.0633	0.053142	0.10599	-1.0030
-137	3.5827	1.1390	0.055468	0.11063	-1.0000
-142	3.5226	1.0913	0.054537	0.10877	-1.0030
-152	3.4225	1.0602	0.052997	0.10568	-1.0000
-157	3.4225	1.0602	0.052997	0.10568	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4225	1.0602	0.052997	0.10568	-1.0000
-157	3.4225	1.0602	0.052997	0.10568	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4225	1.0602	0.052997	0.10568	-1.0000
-177	3.4225	1.0602	0.052997	0.10568	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-157	2.9369	0.92839	0.046398	0.092538	-1.0000
-167	3.0410	0.96235	0.047396	0.093929	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/10/79   CADDFIT   REC 10/11/79 04:37:06.519   FOC RX6R1   PGM C034

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD JCPD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.968	3.6614	0.18677	0.43077	3.43200
37	6.3412	1.9430	0.098963	0.22824	3.53500
47	8.0373	2.4497	0.12496	0.28821	3.62500
52	8.0321	2.4533	0.12525	0.28911	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD JCPD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	9.1327	2.7940	0.14252	0.32872	3.42200
67	6.4113	1.9614	0.10005	0.23076	3.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD JCPD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	25.724	7.8697	0.40144	0.92588	0.50800
82	12.918	3.9521	0.20160	0.46496	0.58300
92	3.4933	1.0687	0.054516	0.12573	3.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD JCPD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	3.8738	1.1851	0.060453	0.13943	3.62400
117	3.8337	1.1729	0.059828	0.13799	2.83000
122	3.7386	1.1438	0.058344	0.13456	0.96000
127	3.4893	1.0672	0.054437	0.12555	1.0500
132	3.1478	0.96302	0.049124	0.11330	1.2200
142	3.1225	0.95536	0.048734	0.11240	1.3500

>ADDITIONAL PRESSURE RATIOS , ECTEADDY INLEY

AVD JCPD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	3.8738	1.1851	0.060453	0.13943	-1.0000
-112	3.8337	1.1729	0.059828	0.13799	-1.0000
-122	3.7386	1.1438	0.058344	0.13456	-1.0000
-127	3.4893	1.0672	0.054437	0.12555	-1.0000
-132	3.1478	0.96302	0.049124	0.11330	-1.0000
-142	3.1225	0.95536	0.048734	0.11240	-1.0000
-152	3.4733	1.0626	0.054203	0.12501	-1.0000
-157	3.4733	1.0626	0.054203	0.12501	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD JOPC	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4733	1.0626	0.054203	0.12501	-1.0000
-157	3.4733	1.0626	0.054203	0.12501	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD JCPD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4793	1.0641	0.054281	0.12519	-1.0000
-177	3.4733	1.0626	0.054203	0.12501	-1.0000

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD JCPD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-187	3.0176	0.92319	0.047093	0.10861	-1.0000
-197	3.0727	0.94004	0.047952	0.11060	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WCPD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	12.090	3.7218	0.19647	0.43302	0.43200
37	6.3867	1.9624	0.098588	0.22736	0.53000
47	8.0791	2.4822	0.12479	0.28757	0.62900
52	8.0881	2.4952	0.12495	0.29792	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WCPD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	9.2138	2.8311	0.14223	0.32809	0.42200
67	6.4517	1.9824	0.099592	0.22967	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WCPD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	26.094	9.0178	0.40279	0.92889	0.50800
82	13.075	4.0176	0.20183	0.46545	0.58300
82	3.4780	1.0687	0.053689	0.12381	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WCPD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	3.9137	1.2026	0.060414	0.13932	0.62400
112	3.8736	1.1903	0.059795	0.13790	0.83000
122	3.7785	1.1610	0.058327	0.13451	0.96300
127	3.4630	1.0641	0.053457	0.12328	1.0900
137	3.1826	0.97791	0.049128	0.11329	1.2200
142	3.1475	0.96714	0.048587	0.11205	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WCPD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	3.9137	1.2026	0.060414	0.13932	-1.0000
-112	3.8736	1.1903	0.059795	0.13790	-1.0000
-122	3.7785	1.1610	0.058327	0.13451	-1.0000
-127	3.4630	1.0641	0.053457	0.12328	-1.0000
-137	3.1826	0.97791	0.049128	0.11329	-1.0000
-142	3.1475	0.96714	0.048587	0.11205	-1.0000
-152	3.4530	1.0610	0.053302	0.12292	-1.0000
-157	3.4580	1.0625	0.053380	0.12310	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WCPD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	3.4530	1.0610	0.053302	0.12292	-1.0000
-157	3.4580	1.0625	0.053380	0.12310	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WCPD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-167	3.4580	1.0625	0.053380	0.12310	-1.0000
-172	3.4580	1.0625	0.053380	0.12310	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WCPD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-182	2.9973	0.92357	0.046267	0.10670	-1.0000
-187	3.0473	0.93636	0.047041	0.10848	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/10/79   CADDELL   REC 10/11/79 04:39:21.094   FAC 8X6X1   PGM C034   RDG 1086

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	12.718	3.2933	0.16559	0.42966	0.43200
37	5.6825	1.7460	0.087792	0.22780	0.53900
47	7.1631	2.2010	0.11067	0.28715	0.62900
52	7.1781	2.2356	0.11090	0.28775	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	8.1783	2.5129	0.12635	0.32784	0.42200
67	5.7376	1.7630	0.088642	0.23000	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	26.073	8.0113	0.40281	1.0452	0.50800
82	13.052	4.0105	0.20165	0.52322	0.58300
92	3.4759	1.0690	0.053701	0.13934	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	3.9063	1.2003	0.060351	0.15659	0.62400
112	3.8663	1.1880	0.059732	0.15499	0.83000
122	3.7762	1.1603	0.058340	0.15138	0.96000
127	3.4709	1.0665	0.053624	0.13914	1.0900
137	2.8653	0.88042	0.044268	0.11486	1.2200
142	2.8153	0.86504	0.043494	0.11286	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	3.9063	1.2003	0.060351	0.15659	-1.0000
-112	3.8663	1.1880	0.059732	0.15499	-1.0000
-122	3.7762	1.1603	0.058340	0.15138	-1.0000
-127	3.4709	1.0665	0.053624	0.13914	-1.0000
-137	2.8653	0.88042	0.044268	0.11486	-1.0000
-142	2.8153	0.86504	0.043494	0.11286	-1.0000
-152	3.4609	1.0634	0.053469	0.13874	-1.0000
-157	3.4609	1.0634	0.053469	0.13874	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	3.4609	1.0634	0.053469	0.13874	-1.0000
-157	3.4609	1.0634	0.053469	0.13874	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-167	3.4609	1.0634	0.053469	0.13874	-1.0000
-172	3.4659	1.0650	0.053547	0.13894	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-192	2.9905	0.91987	0.046201	0.11988	-1.0000
-197	3.0455	0.93578	0.047051	0.12209	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

49

NASA-LEWIS   PRELIMINARY DATA   06/10/79   CADDELL   PFC 10/11/79 04:10:43.867   FAC RX6X1   PGM C034   PDG 1097

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PC	PL/PTF	PL/PTP	X/DMAX
32	15.533	4.8065	0.21528	0.43158	0.43200
37	8.1732	2.5210	0.11291	0.22636	0.53080
47	10.359	3.1951	0.14311	0.28689	0.62500
52	10.399	3.2075	0.14366	0.28800	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.969	3.6609	0.16397	0.32871	0.42200
67	8.2933	2.5580	0.11457	0.22968	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	29.394	9.0634	0.40595	0.81380	0.50800
82	14.593	4.5013	0.20161	0.40417	0.58300
92	3.4692	1.0701	0.047929	0.096081	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.3853	1.3526	0.060584	0.12145	0.62400
112	4.3353	1.3372	0.058893	0.12007	0.83000
122	4.2251	1.3032	0.058371	0.11702	0.96000
127	3.4642	1.0685	0.047859	0.095942	1.0900
137	4.0199	1.2399	0.055536	0.11133	1.2200
142	3.9549	1.2198	0.054637	0.10953	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.3853	1.3526	0.060584	0.12145	-1.0000
-112	4.3353	1.3372	0.058893	0.12007	-1.0000
-122	4.2251	1.3032	0.058371	0.11702	-1.0000
-127	3.4642	1.0685	0.047859	0.095942	-1.0000
-137	4.0199	1.2399	0.055536	0.11133	-1.0000
-142	3.9549	1.2198	0.054637	0.10953	-1.0000
-152	3.4442	1.0623	0.047582	0.095388	-1.0000
-157	3.4492	1.0639	0.047651	0.095526	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4442	1.0623	0.047582	0.095388	-1.0000
-157	3.4492	1.0639	0.047651	0.095526	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4492	1.0639	0.047651	0.095526	-1.0000
-172	3.4492	1.0639	0.047651	0.095526	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	2.9996	0.92181	0.041288	0.082769	-1.0000
-187	3.0396	0.93725	0.041979	0.084156	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/10/79   CANOELL   REC 10/11/79 04:11:50.906   FAC RXAX1   PGM C034   RDG 1008

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.542	4.1811	0.18589	0.43013	0.43200
37	7.1498	2.2071	0.098137	0.22705	0.53000
47	9.0439	2.7922	0.12414	0.28725	0.62900
52	9.0689	2.7990	0.12449	0.28804	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.314	3.1843	0.14157	0.32758	0.42200
67	7.2338	2.2334	0.099297	0.22976	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	29.527	9.1161	0.40531	0.937A2	0.50800
92	14.677	4.5313	0.20146	0.46615	0.58300
62	3.4567	1.0672	0.047449	0.10979	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.4125	1.3623	0.060569	0.14015	0.62400
112	4.3624	1.3469	0.059882	0.13856	0.83000
122	4.2524	1.3129	0.058371	0.13506	0.96000
127	3.4667	1.0703	0.047587	0.11011	1.0500
137	3.5668	1.1012	0.048960	0.11329	1.2200
142	3.5368	1.0919	0.048548	0.11233	1.3500

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.4125	1.3623	0.060569	0.14015	-1.0000
-112	4.3624	1.3469	0.059882	0.13856	-1.0000
-122	4.2524	1.3129	0.058371	0.13506	-1.0000
-127	3.4667	1.0703	0.047587	0.11011	-1.0000
-137	3.5668	1.1012	0.048960	0.11329	-1.0000
-142	3.5368	1.0919	0.048548	0.11233	-1.0000
-152	3.4417	1.0626	0.047243	0.10931	-1.0000
-157	3.4417	1.0626	0.047243	0.10931	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4417	1.0626	0.047243	0.10931	-1.0000
-157	3.4417	1.0626	0.047243	0.10931	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-162	3.4467	1.0641	0.047312	0.10947	-1.0000
-172	3.4467	1.0641	0.047312	0.10947	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	2.9962	0.92505	0.041129	0.095164	-1.0000
-187	3.0463	0.94051	0.041816	0.096754	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	12.071	3.7265	0.16590	0.43068	0.43200
37	6.3891	1.9725	0.087811	0.22797	0.53000
47	8.0650	2.4890	0.11084	0.28776	0.62400
52	8.0350	2.4891	0.11126	0.28884	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	9.2304	2.8404	0.12645	0.32827	0.42200
67	6.4592	1.9941	0.088774	0.23047	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	29.455	9.0935	0.40483	1.0510	0.50800
82	14.655	4.5244	0.20142	0.52250	0.58300
92	3.4613	1.0686	0.047572	0.12350	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	4.4024	1.3591	0.060506	0.15709	0.62400
112	4.3523	1.3437	0.059819	0.15529	0.83000
122	4.2522	1.3128	0.058442	0.15172	0.96000
127	3.4563	1.0670	0.047503	0.12332	1.0630
132	3.2210	0.99440	0.044269	0.11493	1.2200
142	3.1769	0.98049	0.043649	0.11332	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	4.4024	1.3591	0.060506	0.15708	-1.0000
-112	4.3523	1.3437	0.059819	0.15529	-1.0000
-122	4.2522	1.3128	0.058442	0.15172	-1.0000
-127	3.4563	1.0670	0.047503	0.12332	-1.0000
-132	3.2210	0.99440	0.044269	0.11493	-1.0000
-142	3.1769	0.98049	0.043649	0.11332	-1.0000
-152	3.4413	1.0624	0.047296	0.12279	-1.0000
-157	3.4413	1.0624	0.047296	0.12279	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	3.4413	1.0624	0.047296	0.12279	-1.0000
-157	3.4413	1.0624	0.047296	0.12279	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-167	3.4413	1.0624	0.047296	0.12279	-1.0000
-172	3.4413	1.0624	0.047296	0.12279	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-182	2.9957	0.92484	0.041177	0.10689	-1.0000
-187	3.3457	1.04030	0.041863	0.13967	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	17.469	5.3604	0.21546	0.43004	0.43200
37	9.1668	2.8139	0.11307	0.22569	0.53000
47	11.621	3.5662	0.14334	0.28612	0.62900
52	11.686	3.5962	0.14415	0.28772	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.331	4.0816	0.16406	0.32746	0.42200
67	9.3368	2.8560	0.11479	0.22913	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.801	10.066	0.40459	0.80757	0.50800
82	16.284	4.9970	0.20085	0.40091	0.58300
92	3.4942	1.0492	0.042977	0.085782	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.9304	1.5038	0.060445	0.12065	0.62400
112	4.8404	1.4854	0.059704	0.11917	0.83000
122	4.7303	1.4516	0.058346	0.11646	0.96000
127	3.4893	1.0707	0.043034	0.085905	1.0900
137	4.5101	1.3840	0.055631	0.11104	1.2200
142	4.4401	1.3625	0.054766	0.10932	1.3500

>ADDITIONAL PRESSURE RATIOS , FORWARD INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.9304	1.5038	0.060445	0.12065	-1.0000
-112	4.8414	1.4854	0.059704	0.11917	-1.0000
-122	4.7303	1.4516	0.058346	0.11646	-1.0000
-127	3.4893	1.0707	0.043034	0.085905	-1.0000
-137	4.5101	1.3840	0.055631	0.11104	-1.0000
-142	4.4401	1.3625	0.054766	0.10932	-1.0000
-152	3.4592	1.0615	0.042668	0.085166	-1.0000
-157	3.4642	1.0631	0.042730	0.085289	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4592	1.0615	0.042668	0.085166	-1.0000
-157	3.4642	1.0631	0.042730	0.085289	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4642	1.0631	0.042730	0.085289	-1.0000
-172	3.4592	1.0615	0.042668	0.085166	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.0338	0.93097	0.037420	0.074692	-1.0000
-187	3.0799	0.94480	0.037976	0.075801	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

53

NASA-LEWIS   PRELIMINARY DATA   06/10/79   CADDFII   REC 10/11/79 04:15:39,669   FAC 8Y6X1   PGM C034   RDG 1991

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.003	4.5969	0.18509	0.43063	0.43200
37	7.9121	2.4243	0.097611	0.22711	0.53000
47	10.303	3.0649	0.12349	0.28712	0.62500
52	10.048	3.0787	0.12396	0.28861	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.413	3.4970	0.14080	0.32760	0.42200
67	8.0072	2.4534	0.098783	0.22983	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.655	10.006	0.40286	0.93732	0.50090
82	16.252	4.9798	0.20050	0.46650	0.58300
92	3.4831	1.0672	0.042971	0.099978	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.8968	1.4998	0.060386	0.14050	0.62400
112	4.8368	1.4814	0.059645	0.13877	0.83000
122	4.7296	1.4492	0.058349	0.13576	0.96000
127	3.4831	1.0672	0.042971	0.099978	1.0900
137	3.9287	1.2038	0.048468	0.11277	1.2200
142	3.9137	1.1992	0.048292	0.11234	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.8968	1.4998	0.060386	0.14050	-1.0000
-112	4.8368	1.4814	0.059645	0.13877	-1.0000
-122	4.7296	1.4492	0.058349	0.13576	-1.0000
-127	3.4831	1.0672	0.042971	0.099978	-1.0000
-137	3.9287	1.2038	0.048468	0.11277	-1.0000
-142	3.9137	1.1992	0.048292	0.11234	-1.0000
-152	3.4631	1.0611	0.042724	0.099403	-1.0000
-157	3.4631	1.0611	0.042724	0.099403	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4631	1.0611	0.042724	0.099403	-1.0000
-157	3.4631	1.0611	0.042724	0.099403	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4631	1.0611	0.042724	0.099403	-1.0000
-172	3.4631	1.0611	0.042724	0.099403	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.0475	3.93377	0.037597	0.087475	-1.0000
-187	3.0976	0.94911	0.038215	0.088912	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
22	13.465	4.1255	0.16605	0.43047	0.43200
37	7.1094	2.1783	0.097677	0.22729	0.53600
47	8.9950	2.7561	0.11092	0.28757	0.62500
52	9.0233	2.7637	0.11124	0.28837	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.250	3.1406	0.12641	0.32770	0.42200
67	7.1944	2.2013	0.088602	0.22969	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.689	10.016	0.40313	1.0451	0.50800
82	16.273	4.9861	0.20069	0.52026	0.58300
92	3.4815	1.0667	0.042935	0.11130	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.8979	1.5007	0.060404	0.15659	0.62400
112	4.8329	1.4808	0.059601	0.15451	0.83000
122	4.7178	1.4455	0.058182	0.15083	0.96000
127	3.4815	1.0667	0.042935	0.11130	1.0900
137	3.5716	1.0943	0.044047	0.11418	1.2200
142	3.5365	1.0836	0.043615	0.11306	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.8979	1.5007	0.060404	0.15659	-1.0000
-112	4.8329	1.4808	0.059601	0.15451	-1.0000
-122	4.7178	1.4455	0.058182	0.15083	-1.0000
-127	3.4815	1.0667	0.042935	0.11130	-1.0000
-137	3.5716	1.0943	0.044047	0.11418	-1.0000
-142	3.5365	1.0836	0.043615	0.11306	-1.0000
-152	3.4665	1.0621	0.042750	0.11082	-1.0000
-157	3.4665	1.0621	0.042750	0.11082	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4665	1.0621	0.042750	0.11082	-1.0000
-157	3.4665	1.0621	0.042750	0.11082	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4665	1.0621	0.042750	0.11082	-1.0000
-172	3.4715	1.0637	0.042812	0.11098	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.0309	0.92868	0.037379	0.096900	-1.0000
-187	3.1910	0.54401	0.037996	0.098500	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	19.422	5.8164	0.21236	0.42986	0.43200
37	9.8544	3.0452	0.11118	0.22505	0.53000
47	12.524	3.8703	0.14131	0.28603	0.62900
52	12.589	3.8903	0.14204	0.28752	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.369	4.4493	0.16212	0.32816	3.42200
67	10.029	3.0993	0.11316	0.22905	3.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	35.593	10.996	0.40147	0.81265	0.50800
82	17.833	5.5106	0.20120	0.40726	0.58300
92	3.4550	1.0676	0.038981	0.078903	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.3721	1.6601	0.060610	0.12269	0.62400
112	5.3220	1.6446	0.060046	0.12154	0.83000
122	5.1919	1.6044	0.058579	0.11857	0.96000
127	3.4750	1.0738	0.039207	0.079361	1.0900
137	4.8916	1.5116	0.055189	0.11171	1.2200
142	4.8165	1.4884	0.054342	0.11000	1.3500

>ADDITIONAL PRESSURE RATIOS , FAREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.3721	1.6601	0.060610	0.12269	-1.0000
-112	5.3220	1.6446	0.060046	0.12154	-1.0000
-122	5.1919	1.6044	0.058578	0.11857	-1.0000
-127	3.4750	1.0738	0.039207	0.079361	-1.0000
-137	4.8916	1.5116	0.055189	0.11171	-1.0000
-142	4.8165	1.4884	0.054342	0.11000	-1.0000
-152	3.4449	1.0645	0.038868	0.078675	-1.0000
-157	3.4399	1.0630	0.038811	0.078560	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4449	1.0645	0.038868	0.078675	-1.0000
-157	3.4399	1.0630	0.038811	0.078560	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4399	1.0630	0.038811	0.078560	-1.0000
-172	3.4369	1.0614	0.038755	0.078446	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.0244	0.93458	0.034123	0.069070	-1.0000
-184	3.0795	0.95160	0.034744	0.070328	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	16.396	5.0647	0.18524	0.43114	0.43200
37	8.6160	2.6614	0.C97344	0.22656	C.53000
47	10.935	3.3778	0.12355	0.28754	0.62900
52	10.985	3.3933	0.12411	0.28886	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.479	3.8548	0.14099	0.32815	0.42200
67	8.7510	2.7031	0.098869	0.23011	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	35.461	10.954	0.40064	0.93245	0.50800
82	17.795	5.4967	0.20105	0.46792	0.58300
87	3.4546	1.0671	0.C39031	0.090840	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.3607	1.6559	0.060565	0.14096	0.62400
112	5.3057	1.6373	0.C59887	0.13938	0.83000
122	5.1806	1.6003	0.058531	0.13623	0.96000
127	3.4696	1.0717	0.C39200	0.091235	1.0900
137	4.3102	1.3314	0.C48657	0.11334	1.2200
142	4.2852	1.3237	0.048414	0.11268	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.3607	1.6559	0.060565	0.14096	-1.0000
-112	5.3057	1.6373	0.C59887	0.13938	-1.0000
-122	5.1806	1.6003	0.058531	0.13623	-1.0000
-127	3.4696	1.0717	0.C39200	0.091235	-1.0000
-137	4.3102	1.3314	0.048657	0.11534	-1.0000
-142	4.2852	1.3237	0.048414	0.11268	-1.0000
-152	3.4396	1.0625	0.038861	0.090446	-1.0000
-157	3.4396	1.0625	0.038861	0.090446	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4396	1.0625	0.038861	0.090446	-1.0000
-157	3.4396	1.0625	0.038861	0.090446	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4396	1.0625	0.038861	0.090446	-1.0000
-172	3.4396	1.0625	0.038861	0.C90446	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.0043	0.92800	0.033942	0.078598	-1.0000
-187	3.0503	0.94520	0.034566	0.080445	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

57

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	14.773	4.5340	0.16562	0.43115	0.43200
37	7.7696	2.3846	0.087106	0.22675	0.53000
47	9.9598	3.0261	0.11054	0.28775	0.62900
52	9.8908	3.0353	0.11088	0.28863	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	11.235	3.4480	0.12595	0.32788	0.42200
67	7.8797	2.4183	0.088339	0.22996	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	35.743	10.970	0.40071	1.0431	0.50800
82	17.936	5.5348	0.20109	0.52344	0.58300
92	3.4770	1.0671	0.038981	0.10147	0.67300

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	5.3936	1.6553	0.060468	0.15741	0.62400
112	5.3486	1.6415	0.059963	0.15609	0.83000
122	5.2135	1.6001	0.058449	0.15215	0.96000
127	3.4870	1.0702	0.039093	0.10177	1.0900
137	3.9374	1.2084	0.044143	0.11491	1.2200
142	3.8874	1.1931	0.043582	0.11345	1.3500

>ADDITIONAL PRESSURE RATIOS , FREESTREAM INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	5.3936	1.6553	0.060468	0.15741	-1.0000
-112	5.3486	1.6415	0.059963	0.15609	-1.0000
-122	5.2135	1.6001	0.058449	0.15215	-1.0000
-127	3.4870	1.0702	0.039093	0.10177	-1.0000
-137	3.9374	1.2084	0.044143	0.11491	-1.0000
-142	3.8874	1.1931	0.043582	0.11345	-1.0000
-152	3.4620	1.0625	0.038812	0.10104	-1.0000
-157	3.4569	1.0610	0.038756	0.10089	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	3.4620	1.0625	0.038812	0.10104	-1.0000
-157	3.4569	1.0610	0.038756	0.10089	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-167	3.4620	1.0625	0.038812	0.10104	-1.0000
-172	3.4569	1.0610	0.038756	0.10089	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-182	3.0215	0.92732	0.033874	0.088180	-1.0000
-187	3.0765	0.94422	0.034491	0.089787	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	18.106	5.5505	0.19582	0.43133	0.43200
37	9.4829	2.9071	0.097325	0.22591	0.53000
47	12.038	3.6904	0.12355	0.28678	0.62900
52	12.398	3.7987	0.12416	0.28821	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	13.792	4.2283	0.14155	0.32858	0.42200
67	9.6429	2.9561	0.098967	0.22972	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	38.729	11.873	0.39740	0.92266	0.50800
82	19.610	6.0116	0.20126	0.46717	0.58300
92	3.4840	1.0681	0.035757	0.083000	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	5.8913	1.8030	0.060361	0.14011	0.62400
112	5.8463	1.7923	0.060002	0.13928	0.83000
122	5.7062	1.7493	0.058564	0.13594	0.96000
127	3.5040	1.0742	0.035963	0.083477	1.0400
137	4.7604	1.4594	0.048857	0.11341	1.2200
142	4.7303	1.4501	0.048549	0.11269	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLEY

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	5.8913	1.8030	0.060361	0.14011	-1.0000
-112	5.8463	1.7923	0.060002	0.13928	-1.0000
-122	5.707	1.7493	0.058564	0.13594	-1.0000
-127	3.5040	1.0742	0.035963	0.083477	-1.0000
-137	4.7604	1.4594	0.048857	0.11341	-1.0000
-142	4.7303	1.4501	0.048549	0.11269	-1.0000
-152	3.4590	1.0604	0.035500	0.082404	-1.0000
-157	3.4690	1.0635	0.035603	0.082642	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	3.4590	1.0604	0.035500	0.082404	-1.0000
-157	3.4690	1.0635	0.035603	0.082642	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-167	3.4690	1.0635	0.035603	0.082642	-1.0000
-172	3.4690	1.0635	0.035603	0.082642	-1.0000

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-182	3.0435	0.93301	0.031236	0.072505	-1.0000
-187	3.0395	0.94989	0.031801	0.073917	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFII   REC 10/11/79 24:22:32.13A   FAC RX6X1   PGM C034   PDG 1097

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	16.178	4.9590	0.16549	0.43099	0.43200
37	8.5339	2.6267	0.096592	0.22608	0.53020
47	11.783	3.3053	0.11030	0.28666	0.62900
52	10.928	3.3190	0.11076	0.28786	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.307	3.7724	0.12589	0.32717	0.42200
67	8.6239	2.6435	0.088219	0.22927	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	38.747	11.877	0.39637	1.0301	0.50800
82	19.659	6.0261	0.20110	0.52263	0.58300
92	3.4984	1.0693	0.035686	0.092740	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.8992	1.8083	0.060347	0.15683	0.62400
117	5.8692	1.7991	0.060049	0.15603	0.83000
122	5.7342	1.7577	0.058659	0.15244	0.96000
127	3.5334	1.0739	0.035839	0.093139	1.0900
132	4.3238	1.3254	0.044231	0.11495	1.2200
142	4.2789	1.3116	0.043771	0.11375	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.8992	1.8083	0.060347	0.15683	-1.0000
-112	5.8692	1.7991	0.060049	0.15603	-1.0000
-122	5.7342	1.7577	0.058659	0.15244	-1.0000
-127	3.5334	1.0739	0.035839	0.093139	-1.0000
-132	4.3238	1.3254	0.044231	0.11495	-1.0000
-142	4.2789	1.3116	0.043771	0.11375	-1.0000
-152	3.4634	1.0616	0.035439	0.092075	-1.0000
-157	3.4634	1.0616	0.035439	0.092075	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4634	1.0616	0.035439	0.092075	-1.0000
-157	3.4634	1.0616	0.035439	0.092075	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4634	1.0632	0.035481	0.092208	-1.0000
-172	3.4634	1.0616	0.035439	0.092075	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-177	3.0281	0.92822	0.030977	0.080503	-1.0000
-182	3.0732	0.94203	0.031438	0.081701	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

60

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	19.112	5.5466	0.18527	0.43096	0.43200
37	9.4792	2.5029	0.096544	0.22555	0.53000
47	12.156	3.6921	0.12332	0.28687	0.62900
52	12.111	3.7389	0.12380	0.28817	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.834	4.2272	0.14129	0.32845	0.42200
67	9.6490	2.9549	0.098702	0.22959	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	38.708	11.854	0.39595	0.92101	0.50800
82	19.640	6.0143	0.20090	0.46730	0.58300
92	3.4872	1.0679	0.035671	0.082974	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.8818	1.8012	0.060165	0.13995	0.62400
112	5.8518	1.7920	0.059859	0.13924	0.83000
122	5.7218	1.7522	0.058529	0.13614	0.96000
127	3.5022	1.0725	0.035824	0.083330	1.0900
137	4.7571	1.4568	0.048661	0.11319	1.2200
142	4.7321	1.4491	0.048405	0.11260	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.8818	1.8012	0.060165	0.13995	-1.0000
-112	5.8518	1.7920	0.059859	0.13924	-1.0000
-122	5.7218	1.7522	0.058529	0.13614	-1.0000
-127	3.5022	1.0725	0.035824	0.083330	-1.0000
-137	4.7571	1.4568	0.048661	0.11319	-1.0000
-142	4.7321	1.4491	0.048405	0.11260	-1.0000
-152	3.4672	1.0618	0.035466	0.082498	-1.0000
-157	3.4672	1.0618	0.035466	0.082498	-1.0000

>ADDITIONAL PRESSURE RATIOS , TAB NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4672	1.0618	0.035466	0.082498	-1.0000
-157	3.4672	1.0618	0.035466	0.082498	-1.0000

>ADDITIONAL PRESSURE RATIOS , 2A DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4672	1.0618	0.035466	0.082498	-1.0000
-172	3.4672	1.0618	0.035466	0.082498	-1.0000

>ADDITIONAL PRESSURE RATIOS , NO DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.0421	0.93161	0.031119	0.072384	-1.0000
-187	3.1521	1.04602	0.031699	0.073574	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	16.446	5.0791	0.18481	0.43047	0.43200
37	8.6289	2.6649	0.096962	0.22586	0.53000
47	10.969	3.3475	0.12326	0.28710	0.62900
52	11.024	3.4045	0.12387	0.28854	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.533	3.8707	0.14084	0.32805	0.42200
67	8.7789	2.7112	0.098648	0.22978	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	35.397	10.932	0.39775	0.92649	0.50800
82	17.890	5.5251	0.20103	0.46827	0.58300
92	3.4610	1.0689	0.038891	0.090589	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.3826	1.6623	0.060485	0.14089	0.62400
112	5.3226	1.6438	0.059810	0.13932	0.83000
122	5.2075	1.6082	0.058517	0.13630	0.96000
127	3.4710	1.0719	0.035004	0.090851	1.0900
137	4.3318	1.3378	0.048677	0.11338	1.2200
142	4.3118	1.3316	0.048452	0.11286	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.3826	1.6623	0.060485	0.14089	-1.0000
-112	5.3226	1.6438	0.059810	0.13932	-1.0000
-122	5.2075	1.6082	0.058517	0.13630	-1.0000
-127	3.4710	1.0719	0.035004	0.090851	-1.0000
-137	4.3318	1.3378	0.048677	0.11338	-1.0000
-142	4.3118	1.3316	0.048452	0.11286	-1.0000
-152	3.4413	1.0627	0.038666	0.090065	-1.0000
-157	3.4461	1.0642	0.038722	0.090196	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4413	1.0627	0.038666	0.090065	-1.0000
-157	3.4461	1.0642	0.038722	0.090196	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4313	1.0611	0.078610	0.089934	-1.0000
-172	3.4410	1.0627	0.038665	0.090065	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-187	3.0055	0.92819	0.032773	0.078667	-1.0000
-192	3.1555	0.94364	0.034335	0.079077	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

62

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.906	4.6107	0.18585	0.43056	0.43200
37	7.9372	2.4239	0.097714	0.22637	3.57000
47	9.9474	3.0766	0.12402	0.28733	0.62900
52	9.9774	3.0959	0.12440	0.28820	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.347	3.5096	0.14148	0.32776	0.42200
67	7.9572	2.4611	0.099210	0.22984	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.114	9.9324	0.40040	0.92760	0.50800
82	16.150	4.9951	0.20136	0.46650	0.58300
92	3.4643	1.0715	0.043193	0.10006	9.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.8606	1.5033	0.060602	0.14040	0.62400
112	4.8056	1.4863	0.059916	0.13881	0.83000
122	4.6905	1.4507	0.058481	0.13548	0.96000
127	3.4643	1.0715	0.043193	0.10006	1.0900
137	3.9248	1.2139	0.048934	0.11337	1.2200
142	3.8947	1.2046	0.048559	0.11250	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.8606	1.5033	0.060602	0.14040	-1.0000
-112	4.8056	1.4863	0.059916	0.13881	-1.0000
-122	4.6905	1.4507	0.058481	0.13548	-1.0000
-127	3.4643	1.0715	0.043193	0.10006	-1.0000
-137	3.9248	1.2139	0.048934	0.11337	-1.0000
-142	3.8947	1.2046	0.048559	0.11250	-1.0000
-152	3.4393	1.0637	0.042881	0.099342	-1.0000
-157	3.4393	1.0637	0.042881	0.099342	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4393	1.0637	0.042881	0.099342	-1.0000
-157	3.4393	1.0637	0.042881	0.099342	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4467	1.0653	0.042943	0.099486	-1.0000
-172	3.4443	1.0653	0.042943	0.099486	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	2.9999	0.92747	0.037398	0.086618	-1.0000
-187	3.0538	0.94450	0.038075	0.088209	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/10/79   CADDELL   REC 10/11/79 04:25:29.194   FAC 8X6X1   PGM C934

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	13.541	4.1824	0.18463	0.43130	0.43200
37	7.1574	2.2091	0.098576	0.22780	0.53000
47	9.0392	2.7918	0.12458	0.28763	0.62900
52	9.1742	2.8026	0.12506	0.28901	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	10.315	3.1859	0.14216	0.32854	0.42200
67	7.2325	2.2338	0.099680	0.23036	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	29.014	9.9612	0.39988	0.92411	0.50800
87	14.597	4.5083	0.20118	0.46491	0.58300
92	3.4572	1.0662	0.047578	0.10995	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	4.3837	1.3539	0.060418	0.13962	0.62400
112	4.3387	1.3400	0.059796	0.13819	0.83000
122	4.2285	1.3060	0.058279	0.13468	0.96000
127	3.4522	1.0662	0.047578	0.10995	1.0900
137	3.5623	1.1003	0.049097	0.11346	1.2200
142	3.5223	1.0879	0.048545	0.11218	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	4.3837	1.3539	0.060418	0.13962	-1.0000
-112	4.3387	1.3400	0.059796	0.13819	-1.0000
-122	4.2285	1.3060	0.058279	0.13468	-1.0000
-127	3.4522	1.0662	0.047578	0.10995	-1.0000
-137	3.5623	1.1003	0.049097	0.11346	-1.0000
-142	3.5223	1.0879	0.048545	0.11218	-1.0000
-152	3.4371	1.0616	0.047371	0.10947	-1.0000
-157	3.4421	1.0631	0.047440	0.10963	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	3.4371	1.0616	0.047371	0.13947	-1.0000
-157	3.4421	1.0631	0.047440	0.10963	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-167	3.4421	1.0631	0.047440	0.10963	-1.0000
-172	3.4421	1.0631	0.047440	0.10963	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-182	3.0113	0.93307	0.041503	0.095912	-1.0000
-187	3.0465	0.94395	0.042243	0.097667	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

64

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.136	3.7231	0.14653	0.43028	0.43200
37	6.3780	1.9728	0.098825	0.22800	0.53000
47	8.0530	2.4910	0.12478	0.28788	0.62900
52	8.0787	2.4987	0.12517	0.28878	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
52	9.1828	2.8404	0.14228	0.32827	0.42200
67	6.4530	1.9960	0.099987	0.23068	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	25.769	7.9708	0.39928	0.92119	0.50800
82	13.001	4.0214	0.20144	0.46476	0.58300
92	3.4614	1.0708	0.053639	0.12375	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	3.8970	1.2054	0.060383	0.13931	0.62400
112	3.8520	1.1915	0.059686	0.13770	0.83000
122	3.7670	1.1652	0.058368	0.13466	0.96000
127	3.4467	1.0661	0.053406	0.12322	1.0900
137	3.1765	0.98257	0.049219	0.11356	1.2200
142	3.1365	0.97019	0.048599	0.11213	1.3500

>ADDITIONAL PRESSURE RATIOS , ENGEARCH VELEY

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	3.8970	1.2054	0.060383	0.13931	-1.0000
-112	3.8520	1.1915	0.059686	0.13770	-1.0000
-122	3.7670	1.1652	0.058369	0.13466	-1.0000
-127	3.4467	1.0661	0.053406	0.12322	-1.0000
-137	3.1765	0.98257	0.049219	0.11356	-1.0000
-142	3.1165	0.97019	0.048599	0.11213	-1.0000
-152	3.4367	1.0631	0.053251	0.12286	-1.0000
-157	3.4417	1.0646	0.053329	0.12304	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4367	1.3631	0.053251	0.12286	-1.0000
-157	3.4417	1.0646	0.053329	0.12304	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4417	1.0646	0.053329	0.12304	-1.0000
-172	3.4417	1.0646	0.053329	0.12304	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-192	2.9364	0.92685	0.046628	0.10712	-1.0000
-197	3.0514	0.94387	0.047291	0.10908	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

65

NASA-LEWIS PRELIMINARY DATA CADDE-II FACILITY   PXEX1   PROGRAM C036 RDGS   1103 TO 1144
TIME AND DATE PROCESSED 21:30:40 JUN 11 1979

NOZZLE TYPE	P&W BASE EJECTOR NOZZLE (MODEL C)
FLIGHT CONDITIONS	SUPER SONIC CRUISE (WS=.04 WT)
NOZZLE CONFIGURATION	C1
PRIMARY-NOZZLE PLUG	SPLIT PLUG (RETRACTED)
FLOW SPLITTER	ISENTROPIC SPLITTER
FAN NOZZLE	SHORT FLAP
CLAMSHELL POSITION	
EJECTOR INLET OPENING	

RDG	MN	PTF/PTP	PTF/P0	PTP/P0	OMEGA	PTS/PTF	CDF	CDP	CFI	ETA1	ETA1.INT	CFP1	CFP2	F9
1103	1.957	2.32	19.73	8.51	0.000	0.242	1.035	0.980	0.9707	0.9707	0.9739	0.9739	0.9744	1.5156
1104	1.955	2.31	22.25	9.62	0.000	0.242	1.036	0.982	0.9747	0.9747	0.9774	0.9774	0.9779	1.5171
1105	1.958	2.33	25.02	10.73	0.000	0.243	1.037	0.981	0.9787	0.9787	0.9811	0.9811	0.9816	1.5199
1106	1.953	2.33	27.65	11.88	0.000	0.243	1.037	0.981	0.9794	0.9794	0.9816	0.9816	0.9820	1.5190
1108	1.960	0.70	9.03	12.94	0.000	0.807	3.453	0.985	1.0680	1.0680	1.0702	1.0702	1.0706	2.6097
1109	1.954	2.31	29.14	12.60	0.000	0.243	1.040	0.982	0.9799	0.9799	0.9820	0.9820	0.9824	1.9223
1110	1.957	2.32	29.21	12.59	0.000	0.244	1.038	0.982	0.9793	0.9793	0.9813	0.9813	0.9817	1.5190
1111	1.957	2.32	27.69	11.93	0.000	0.243	1.039	0.983	0.9790	0.9790	0.9811	0.9811	0.9816	1.5214
1112	1.958	2.33	24.93	10.72	0.000	0.243	1.037	0.982	0.9808	0.9808	0.9832	0.9832	0.9837	1.5225
1113	1.958	2.31	22.17	9.63	0.000	0.243	1.038	0.983	0.9726	0.9726	0.9754	0.9754	0.9759	1.5167
1114	1.959	2.30	19.56	8.49	0.000	0.243	1.036	0.980	0.9720	0.9720	0.9752	0.9752	0.9757	1.5168
1115	1.960	2.30	19.92	9.93	0.036	0.243	0.973	0.982	1.0081	0.9746	0.9817	1.0112	1.0117	1.5099
1116	1.953	2.31	19.84	8.60	0.039	0.243	0.975	0.982	1.0062	0.9748	0.9781	1.0095	1.0100	1.5139
1117	1.959	2.59	19.79	7.63	0.041	0.243	0.974	0.981	1.0093	0.9763	0.9798	1.0128	1.0133	1.5218
1118	1.960	2.31	22.24	11.07	0.037	0.242	0.973	0.984	1.0123	0.9823	0.9850	1.0150	1.0155	1.5124
1119	1.954	2.31	22.49	9.75	0.039	0.244	0.975	0.981	1.0114	0.9794	0.9823	1.0143	1.0148	1.5152
1120	1.959	2.31	22.32	9.67	0.039	0.244	0.974	0.982	1.0109	0.9790	0.9819	1.0138	1.0143	1.5142
1121	1.959	2.60	22.28	8.58	0.041	0.244	0.976	0.982	1.0114	0.9779	0.9809	1.0144	1.0149	1.5205
1122	1.956	2.31	24.92	12.34	0.037	0.243	0.975	0.984	1.0126	0.9820	0.9844	1.0149	1.0153	1.5117
1123	1.959	2.32	24.86	10.70	0.039	0.243	0.974	0.981	1.0180	0.9854	0.9879	1.0206	1.0210	1.5195
1124	1.959	2.60	24.72	9.52	0.041	0.243	0.974	0.982	1.0151	0.9811	0.9838	1.0179	1.0183	1.5202
1125	1.959	2.30	27.35	13.67	0.036	0.244	0.974	0.984	1.0162	0.9854	0.9876	1.0193	1.0188	1.5149
1126	1.961	2.33	27.38	11.76	0.039	0.244	0.977	0.983	1.0159	0.9831	0.9854	1.0192	1.0187	1.5195
1127	1.958	2.61	27.31	10.49	0.041	0.243	0.973	0.982	1.0165	0.9821	0.9845	1.0189	1.0194	1.5183
1128	1.956	2.32	29.81	12.86	0.039	0.244	0.975	0.983	1.0182	0.9851	0.9872	1.0203	1.0207	1.5200
1129	1.955	2.60	29.49	11.50	0.041	0.244	0.977	0.983	1.0170	0.9824	0.9846	1.0192	1.0196	1.5217
1130	1.955	2.61	29.72	11.41	0.041	0.243	0.974	0.983	1.0223	0.9875	0.9897	1.0246	1.0250	1.5267
1131	1.955	2.33	29.68	12.74	0.039	0.243	0.974	0.985	1.0175	0.9844	0.9865	1.0196	1.0201	1.5198
1132	1.956	2.61	27.45	10.55	0.041	0.244	0.973	0.983	1.0212	0.9867	0.9851	1.0237	1.0241	1.5251
1133	1.956	2.34	27.26	11.66	0.039	0.243	0.974	0.984	1.0168	0.9834	0.9862	1.0191	1.0196	1.5178
1134	1.956	2.32	27.43	13.55	0.037	0.244	0.974	0.983	1.0145	0.9837	0.9858	1.0167	1.0171	1.5125
1135	1.956	2.61	24.82	12.35	0.037	0.244	0.973	0.982	1.0172	0.9867	0.9861	1.0197	1.0201	1.5152
1136	1.955	2.32	24.74	10.67	0.039	0.243	0.975	0.985	1.0137	0.9813	0.9839	1.0162	1.0167	1.5169
1137	1.954	2.60	24.82	9.55	0.041	0.243	0.975	0.983	1.0183	0.9842	0.9869	1.0210	1.0214	1.5249
1138	1.956	2.60	22.32	8.59	0.041	0.243	0.974	0.982	1.0138	0.9802	0.9832	1.0168	1.0173	1.5214
1139	1.956	2.31	22.32	9.66	0.039	0.243	0.973	0.983	1.0124	0.9804	0.9833	1.0153	1.0157	1.5158
1140	1.956	2.31	22.45	11.15	0.037	0.243	0.975	0.983	1.0109	0.9808	0.9835	1.0136	1.0141	1.5117
1141	1.957	2.59	19.91	7.64	0.041	0.243	0.971	0.981	1.0132	0.9799	0.9833	1.0166	1.0171	1.5249

TIME AND DATE PROCESSED 31:00:40 JUN 11 1979

NOZZLE TYPE	P+W BASE EJECTOR NOZZLE (MODEL C)	
FLIGHT CONDITIONS	SUPER SONIC CRUISE (MS=.04 WT)	
NOZZLE CONFIGURATION	C1	
PRIMARY-NOZZLE PLUG	SPLIT PLUG (RETRACTED)	
FLOW SPLITTER	ISENTROPIC SPLITTER	
FAN NOZZLE	SHORT FLAP	
CLAMSHELL POSITION		
EJECTOR INLET OPENING		

PDG	MO	PTF/PTP	PTF/PO	PTP/PO	OMEGA	PTS/PTF	CDF	CDP	CF1	ETA1	ETA1.INT	CFP1	CFP2	F9
1142	1.957	2.30	19.85	8.61	0.039	0.243	0.976	0.983	1.0072	0.9758	0.9791	1.0105	1.0111	1.5150
1143	1.957	2.33	19.97	9.08	0.037	0.243	0.972	0.983	1.0084	0.9788	0.9819	1.0115	1.0120	1.5087
1144	1.956	2.32	24.77	10.68	0.039	0.242	0.974	0.982	1.0134	0.9810	0.9835	1.0160	1.0164	1.5145

67

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.323	3.6730	0.18619	0.43170	0.43200
37	6.5333	1.9472	0.098711	0.22886	1.53000
47	8.3924	2.4119	0.12227	0.28348	0.62900
52	8.1274	2.4432	0.12395	0.28716	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	9.3815	2.7961	0.14174	0.32864	0.42200
67	6.6082	1.9696	0.099844	0.23149	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	27.382	8.1611	0.41371	0.95920	0.50800
82	13.342	3.9766	0.20159	0.46738	0.58300
95	3.6187	1.0785	0.054674	0.12676	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
102	4.4397	1.3230	0.067065	0.15549	0.67400
112	4.1237	1.2291	0.062305	0.14446	0.83000
122	3.8237	1.1396	0.057772	0.13395	0.96000
127	3.5987	1.0726	0.054372	0.12606	1.0500
137	3.4086	1.0159	0.051501	0.11941	1.2200
142	3.2986	0.98315	0.049834	0.11555	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-102	4.4397	1.3230	0.067065	0.15549	-1.0000
-112	4.1237	1.2291	0.062305	0.14446	-1.0000
-122	3.8237	1.1396	0.057772	0.13395	-1.0000
-127	3.5987	1.0726	0.054372	0.12606	-1.0000
-137	3.4086	1.0159	0.051501	0.11941	-1.0000
-142	3.2986	0.98315	0.049834	0.11555	-1.0000
-152	3.5687	1.0636	0.053919	0.12501	-1.0000
-157	3.5737	1.0651	0.053994	0.12519	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5687	1.0636	0.053919	0.12501	-1.0000
-157	3.5737	1.0651	0.053994	0.12519	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5687	1.0636	0.053919	0.12501	-1.0000
-172	3.5647	1.0621	0.053843	0.12484	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.1096	0.92650	0.046967	0.10889	-1.0000
-187	3.1336	0.93396	0.047345	0.10977	-1.0000

>ADDITIONAL , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.826	4.1499	0.18647	0.43128	0.43200
37	7.3320	2.1978	0.098754	0.22840	0.53000
47	9.0659	2.7212	0.12227	0.28280	0.62900
52	9.1859	2.7572	0.12389	0.28654	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.500	3.1515	0.14161	0.32753	0.42200
67	7.4070	2.2233	0.099909	0.23105	0.67200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	30.708	9.2172	0.41417	0.95791	0.50800
82	14.934	4.4826	0.20142	0.46586	0.58300
92	3.5827	1.0754	0.048321	0.11176	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.9978	1.5001	0.067406	0.15590	0.62400
112	4.6328	1.3906	0.062484	0.14452	0.83000
122	4.2878	1.2870	0.057830	0.13375	0.96000
127	3.5627	1.0694	0.048051	0.11114	1.0900
137	3.8228	1.1474	0.051558	0.11925	1.2200
142	3.7027	1.1114	0.049940	0.11550	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.9978	1.5001	0.067406	0.15590	-1.0000
-112	4.6328	1.3906	0.062484	0.14452	-1.0000
-122	4.2878	1.2870	0.057830	0.13375	-1.0000
-127	3.5627	1.0694	0.048051	0.11114	-1.0000
-137	3.8228	1.1474	0.051558	0.11925	-1.0000
-142	3.7027	1.1114	0.049940	0.11550	-1.0000
-152	3.5327	1.0604	0.047646	0.11020	-1.0000
-157	3.5327	1.0604	0.047646	0.11020	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5327	1.0604	0.047646	0.11020	-1.0000
-157	3.5327	1.0604	0.047646	0.11020	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5327	1.0604	0.047646	0.11020	-1.0000
-172	3.5327	1.0604	0.047646	0.11020	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.0826	0.92526	0.041576	0.096159	-1.0000
-187	3.1176	0.93527	0.041983	0.097095	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
42	15.426	4.6329	0.18514	0.43170	0.43200
37	8.1596	2.4506	0.097931	0.22835	0.53000
47	10.098	3.3297	0.12108	0.28231	0.62900
52	10.238	3.0747	0.12287	0.28650	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.721	3.5202	0.14068	0.32801	0.42200
67	8.2545	2.4791	0.099071	0.23100	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	34.128	10.250	0.40960	0.95506	0.50800
82	16.774	5.0378	0.20132	0.46942	0.58300
92	3.5961	1.0800	0.043161	0.10064	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	/PO	PL/PTF	PL/PTP	X/DMAX
107	5.6309	.6911	0.067582	0.15758	0.62400
112	5.2163	1.5665	0.062603	0.14597	0.83000
122	4.8361	1.4524	0.058043	0.13534	0.96000
127	3.5411	1.0755	0.042981	0.10022	1.3900
137	4.2661	1.2813	0.051202	0.11939	1.2200
142	4.1461	1.2452	0.049762	0.11603	1.3500

>ADDITIONAL PRESSURE RATIOS , SCREECH INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.6309	1.6911	0.067582	0.15758	-1.0000
-112	5.2163	1.5665	0.062603	0.14597	-1.0000
-122	4.8361	1.4524	0.058043	0.13534	-1.0000
-127	3.5411	1.0755	0.042981	0.10022	-1.0000
-137	4.2661	1.2813	0.051202	0.11939	-1.0000
-142	4.1461	1.2452	0.049762	0.11603	-1.0000
-152	3.5411	1.0635	0.042501	0.099098	-1.0000
-157	3.5411	1.0635	0.042501	0.099098	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5411	1.0635	0.042501	0.099098	-1.0000
-157	3.5411	1.0635	0.042501	0.099098	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5361	1.0620	0.042440	0.098958	-1.0000
-172	3.5411	1.0635	0.042501	0.099098	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-162	3.3063	0.92984	0.037159	0.086642	-1.0000
-167	3.1461	0.94486	0.037759	0.088042	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	17.136	5.1296	0.18553	0.43168	0.43200
37	8.9907	2.7398	0.098012	0.22894	0.53000
47	11.148	3.3567	0.12141	0.28248	0.62900
52	11.308	3.4048	0.12315	0.28653	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.941	3.8966	0.14094	0.32792	0.42200
67	9.1147	2.7444	0.099264	0.23096	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	37.180	11.195	0.40491	0.94210	0.50800
82	18.494	5.5686	0.20141	0.46863	0.58300
92	3.5857	1.0796	0.039052	0.090858	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.2009	1.8671	0.067531	0.15712	0.62400
112	5.7559	1.7331	0.062686	0.14585	0.83000
122	5.3210	1.6021	0.057949	0.13483	0.96000
127	3.5857	1.0796	0.039052	0.090858	1.0900
137	4.7109	1.4185	0.051305	0.11937	1.2200
142	4.5759	1.3778	0.049835	0.11595	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.2009	1.8671	0.067531	0.15712	-1.0000
-112	5.7559	1.7331	0.062686	0.14585	-1.0000
-122	5.3210	1.6021	0.057949	0.13483	-1.0000
-127	3.5857	1.0796	0.039052	0.090858	-1.0000
-137	4.7109	1.4185	0.051305	0.11937	-1.0000
-142	4.5759	1.3778	0.049835	0.11595	-1.0000
-152	3.5357	1.0646	0.038596	0.089591	-1.0000
-157	3.5407	1.0661	0.038563	0.089718	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5357	1.0646	0.038596	0.089591	-1.0000
-157	3.5407	1.0661	0.038560	0.089718	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5407	1.0661	0.038562	0.089718	-1.0000
-172	3.5307	1.0631	0.038451	0.089464	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.0505	0.92151	0.033331	0.077559	-1.0000
-187	3.1255	0.94139	0.034032	0.079198	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

71

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	18.715	5.5908	0.61939	0.43206	0.43200
37	9.8830	2.9515	0.32659	0.22809	0.53000
47	12.229	3.6533	0.40474	0.28233	0.62500
52	12.404	3.7055	0.41053	0.28637	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.263	4.2609	0.47206	0.32928	0.42700
67	10.005	2.9888	0.33113	0.23098	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	39.831	11.890	1.3182	0.91954	0.50800
82	20.209	6.0370	0.66882	0.46654	0.58300
92	3.6129	1.0793	0.11957	0.083407	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.7648	2.0208	0.22389	0.15617	0.62400
112	6.2896	1.8789	0.20816	0.14520	0.83000
122	5.8194	1.7384	0.19260	0.13435	0.96000
127	3.6179	1.0808	0.11974	0.083522	1.0900
137	5.1691	1.5442	0.17107	0.11933	1.2200
142	5.6193	1.4993	0.16611	0.11587	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.7648	2.0208	0.22389	0.15617	-1.0000
-112	6.2896	1.8789	0.20816	0.14520	-1.0000
-122	5.8194	1.7384	0.19260	0.13435	-1.0000
-127	3.6179	1.0808	0.11974	0.083522	-1.0000
-137	5.1691	1.5442	0.17107	0.11933	-1.0000
-142	5.0193	1.4993	0.16611	0.11587	-1.0000
-152	3.5628	1.0643	0.11791	0.082251	-1.0000
-157	3.5628	1.0643	0.11791	0.082251	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5628	1.0643	0.11791	0.082251	-1.0000
-157	3.5628	1.0643	0.11791	0.082251	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-162	3.5578	1.0628	0.11775	0.082136	-1.0000
-172	3.5628	1.0643	0.11791	0.082251	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.1124	0.92976	0.10301	0.071853	-1.0000
-187	3.1174	0.93126	0.10317	0.071968	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

72

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	18.244	5.4332	0.18643	0.43126	0.43200
37	0.6317	2.8684	0.099428	0.22768	0.53000
47	11.920	3.5530	0.12181	0.28178	0.62900
52	12.080	3.5976	0.12345	0.28556	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.878	4.1332	0.14183	0.32807	0.42200
67	9.7566	2.9056	0.099705	0.23064	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	38.904	11.586	0.39757	0.91965	0.50800
82	19.737	5.8778	0.20169	0.46656	0.58300
87	3.6120	1.0757	0.036913	0.085384	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.6076	1.9678	0.067525	0.15620	0.62400
112	6.1426	1.8294	0.062773	0.14521	0.83000
122	5.6926	1.6953	0.058174	0.13457	0.96000
127	3.6220	1.0787	0.037014	0.085620	1.0900
137	5.0525	1.5047	0.051633	0.11944	1.2200
142	4.8975	1.4585	0.050048	0.11577	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.6076	1.9678	0.067525	0.15620	-1.0000
-112	6.1426	1.8294	0.062773	0.14521	-1.0000
-122	5.6926	1.6953	0.058174	0.13457	-1.0000
-127	3.6220	1.0787	0.037014	0.085620	-1.0000
-137	5.0525	1.5047	0.051633	0.11944	-1.0000
-142	4.8975	1.4585	0.050048	0.11577	-1.0000
-152	3.5670	1.0623	0.036452	0.084320	-1.0000
-157	3.5670	1.0623	0.036452	0.084320	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5670	1.0623	0.036452	0.084320	-1.0000
-157	3.5670	1.0623	0.036452	0.084320	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5620	1.0608	0.036400	0.084201	-1.0000
-172	3.5620	1.0608	0.036400	0.084201	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-192	3.1167	0.92819	0.031850	0.073676	-1.0000
-197	3.1417	0.93564	0.032106	0.074267	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

73

ok

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	17.105	5.1444	0.18577	0.43125	0.43200
37	9.0439	2.7199	0.098219	0.22801	0.53000
47	11.232	3.3691	0.12166	0.28242	0.62500
52	11.357	3.4156	0.12334	0.28633	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.105	3.9114	0.14124	0.32788	0.42200
67	9.1637	2.7560	0.099521	0.23103	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	36.669	11.028	0.39924	0.92448	0.50800
82	18.563	5.5829	0.20160	0.46801	0.58300
92	3.5797	1.0766	0.038877	0.090250	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.2349	1.8752	0.067713	0.15719	0.62400
112	5.7930	1.7413	0.062881	0.14597	0.83000
122	5.3530	1.6090	0.058103	0.13488	0.96000
127	3.5797	1.0766	0.038877	0.090250	1.0500
137	4.7530	1.4286	0.051586	0.11975	1.2200
142	4.6300	1.3925	0.050283	0.11673	1.3500

>ADDITIONAL PRESSURE RATIOS , OREGON INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.2349	1.8752	0.067713	0.15719	-1.0000
-112	5.7930	1.7413	0.062881	0.14597	-1.0000
-122	5.3530	1.6090	0.058103	0.13488	-1.0000
-127	3.5797	1.0766	0.038877	0.090250	-1.0000
-137	4.7500	1.4286	0.051586	0.11975	-1.0000
-142	4.6300	1.3925	0.050283	0.11673	-1.0000
-152	3.5297	1.0616	0.038334	0.088989	-1.0000
-157	3.5347	1.0631	0.038388	0.089115	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5297	1.0616	0.038334	0.088989	-1.0000
-157	3.5347	1.0631	0.038388	0.089115	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5347	1.0631	0.038388	0.089115	-1.0000
-172	3.5347	1.0631	0.038388	0.089115	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.0895	0.92918	0.033553	0.077891	-1.0000
-187	3.0895	1.32617	0.033445	0.277639	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.374	4.6295	0.18569	0.43195	0.43200
37	8.1344	2.4494	0.098246	0.22854	0.53000
47	10.362	3.0290	0.12153	0.28270	0.62900
52	10.192	3.0690	0.12310	0.28635	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.665	3.5126	0.14089	0.32774	0.42200
67	8.2293	2.4780	0.099393	0.23121	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	33.147	9.9811	0.40034	0.93128	0.50800
82	16.682	5.0232	0.20148	0.46869	0.58300
92	3.5769	1.0771	0.043202	0.10050	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.6063	1.6881	0.067712	0.15751	0.62400
112	5.1915	1.5632	0.062702	0.14586	0.83000
122	4.7916	1.4428	0.057873	0.13462	0.96000
127	3.5719	1.0756	0.043142	0.10036	1.0900
137	4.2418	1.2773	0.051232	0.11918	1.2200
142	4.1314	1.2442	0.049904	0.11609	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.6063	1.6881	0.067712	0.15751	-1.0000
-112	5.1915	1.5632	0.062702	0.14586	-1.0000
-122	4.7916	1.4428	0.057873	0.13462	-1.0000
-127	3.5719	1.0756	0.043142	0.10036	-1.0000
-137	4.2418	1.2773	0.051232	0.11918	-1.0000
-142	4.1314	1.2442	0.049904	0.11609	-1.0000
-152	3.5319	1.0635	0.042658	0.099232	-1.0000
-157	3.5319	1.0635	0.042658	0.099232	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5319	1.0635	0.042658	0.099232	-1.0000
-157	3.5319	1.0635	0.042658	0.099232	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5319	1.0635	0.042658	0.099232	-1.0000
-172	3.5369	1.0650	0.042719	0.099372	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.0570	0.92051	0.036922	0.085887	-1.0000
-182	3.1129	0.93797	0.037546	0.087432	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
37	13.826	4.1499	0.18647	0.43128	0.43200
27	7.3320	2.1978	0.098754	0.22840	0.53000
47	9.3659	2.7212	0.12227	0.28280	0.62900
52	9.1858	2.7572	0.12389	0.28654	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.500	3.1515	0.14161	0.32753	0.42200
67	7.4070	2.2233	0.099909	0.23105	0.67300

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	30.708	9.2172	0.41417	0.95791	0.50800
82	14.934	4.4826	0.20142	0.46586	0.58300
92	3.5827	1.0754	0.048321	0.11176	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.9978	1.5001	0.067406	0.15590	0.62400
112	4.6328	1.3906	0.062484	0.14452	0.83000
122	4.2878	1.2870	0.057830	0.13375	0.96000
127	3.5627	1.0694	0.048051	0.11114	1.0900
137	3.8228	1.1474	0.051558	0.11925	1.2200
142	3.7027	1.1114	0.049940	0.11550	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.9978	1.5001	0.067406	0.15590	-1.0000
-112	4.6328	1.3906	0.062484	0.14452	-1.0000
-122	4.2878	1.2870	0.057830	0.13375	-1.0000
-127	3.5627	1.0694	0.048051	0.11114	-1.0000
-137	3.8228	1.1474	0.051558	0.11925	-1.0000
-142	3.7027	1.1114	0.049940	0.11550	-1.0000
-152	3.5327	1.0604	0.047646	0.11020	-1.0000
-157	3.5327	1.0604	0.047646	0.11020	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5327	1.0604	0.047646	0.11020	-1.0000
-157	3.5327	1.0604	0.047646	0.11020	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5327	1.0604	0.047646	0.11020	-1.0000
-172	3.5327	1.0604	0.047646	0.11020	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.0826	0.92526	0.041576	0.096159	-1.0000
-187	3.1176	0.93627	0.042198	0.097095	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

69

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
42	15.426	4.6329	0.18514	0.43170	0.43200
37	8.1596	2.4506	0.097931	0.22835	0.53000
47	10.098	3.3297	0.12138	0.28231	0.62900
52	10.238	3.0747	0.12287	0.28650	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	11.721	3.5202	0.14068	0.32801	0.42200
67	8.2545	2.4791	0.099071	0.23100	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	34.128	10.250	0.40960	0.95506	0.50800
82	16.774	5.0378	0.20132	0.46942	0.58300
92	3.5561	1.0800	0.043161	0.10064	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	/P0	PL/PTF	PL/PTP	X/DMAX
107	5.6309	.6911	0.067582	0.15758	0.62400
112	5.2163	1.5665	0.062603	0.14597	0.83000
122	4.8361	1.4524	0.058043	0.13534	0.96000
127	3.5411	1.0755	0.042981	0.10022	1.3900
137	4.2661	1.2813	0.051202	0.11939	1.2200
142	4.1461	1.2452	0.049762	0.11603	1.3500

>ADDITIONAL PRESSURE RATIOS , ECREACTOR INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	5.6309	1.6911	0.067582	0.15758	-1.0000
-112	5.2163	1.5665	0.062603	0.14597	-1.0000
-122	4.8361	1.4524	0.058043	0.13534	-1.0000
-127	3.5411	1.3755	0.042981	0.10022	-1.0000
-137	4.2661	1.2813	0.051202	0.11939	-1.0000
-142	4.1461	1.2452	0.049762	0.11603	-1.0000
-152	3.5411	1.0635	0.042501	0.099098	-1.0000
-157	3.5411	1.0635	0.042501	0.099098	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	3.5411	1.0635	0.042501	0.099098	-1.0000
-157	3.5411	1.0635	0.042501	0.099098	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-167	3.5361	1.0620	0.042440	0.098958	-1.0000
-172	3.5411	1.0635	0.042501	0.099098	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-162	3.3063	0.92984	0.037159	0.086642	-1.0000
-167	3.1461	0.94486	0.037759	0.088042	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	18.715	5.5908	0.61939	0.43206	0.43200
37	9.8830	2.9515	0.32659	0.22809	0.53000
47	12.229	3.6533	0.40474	0.28233	0.62500
52	12.404	3.7055	0.41053	0.28637	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.263	4.2609	0.47206	0.32928	0.42700
67	10.005	2.9888	0.33113	0.23098	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	39.831	11.890	1.3182	0.91954	0.50800
82	20.209	6.0370	0.66882	0.46654	0.58300
92	3.6129	1.0793	0.11957	0.083407	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.7648	2.0208	0.22389	0.15617	0.62400
112	6.2896	1.8789	0.20816	0.14520	0.83000
122	5.8194	1.7384	0.19260	0.13435	0.96000
127	3.6179	1.0808	0.11974	0.083522	1.0900
137	5.1691	1.5442	0.17107	0.11933	1.2200
142	5.0193	1.4993	0.16611	0.11587	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.7648	2.0208	0.22389	0.15617	-1.0000
-112	6.2896	1.8789	0.20816	0.14520	-1.0000
-122	5.8194	1.7384	0.19260	0.13435	-1.0000
-127	3.6179	1.0808	0.11974	0.083522	-1.0000
-137	5.1691	1.5442	0.17107	0.11933	-1.0000
-142	5.0193	1.4993	0.16611	0.11587	-1.0000
-152	3.5628	1.0643	0.11791	0.082251	-1.0000
-157	3.5628	1.0643	0.11791	0.082251	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5628	1.0643	0.11791	0.082251	-1.0000
-157	3.5628	1.0643	0.11791	0.082251	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5578	1.0628	0.11775	0.082136	-1.0000
-172	3.5628	1.0643	0.11791	0.082251	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.1124	0.92976	0.10301	0.071853	-1.0000
-187	3.1174	0.93126	0.10317	0.071968	-1.0000

>ADDITIONAL , MEASURED THRUST PARAMETERS

72

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	18.244	5.4332	0.18643	0.43126	0.43200
37	9.6317	2.8684	0.099428	0.22768	0.53000
47	11.920	3.5530	0.12181	0.28178	0.62900
52	12.080	3.5976	0.12345	0.28556	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.878	4.1332	0.14183	0.32807	0.42200
67	9.7566	2.9056	0.099705	0.23064	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	38.904	11.586	0.39757	0.91965	0.50800
82	19.737	5.8778	0.20169	0.46656	0.58300
87	3.6120	1.0757	0.036912	0.085384	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.6076	1.9678	0.067525	0.15620	0.62400
112	6.1426	1.8294	0.062773	0.14521	0.83000
122	5.6926	1.6953	0.058174	0.13457	0.96000
127	3.6220	1.0787	0.037014	0.085620	1.0900
137	5.0525	1.5047	0.051633	0.11944	1.2200
142	4.8975	1.4585	0.050048	0.11577	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.6076	1.9678	0.067525	0.15620	-1.0000
-112	6.1426	1.8294	0.062773	0.14521	-1.0000
-122	5.6926	1.6953	0.058174	0.13457	-1.0000
-127	3.6220	1.0787	0.037014	0.085620	-1.0000
-137	5.0525	1.5047	0.051633	0.11944	-1.0000
-142	4.8975	1.4585	0.050048	0.11577	-1.0000
-152	3.5670	1.0623	0.036452	0.084320	-1.0000
-157	3.5670	1.0623	0.036452	0.084320	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5670	1.0623	0.036452	0.084320	-1.0000
-157	3.5670	1.0623	0.036452	0.084320	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5620	1.0608	0.036400	0.084201	-1.0000
-172	3.5620	1.0608	0.036400	0.084201	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.1167	0.92819	0.031850	0.073676	-1.0000
-187	3.1417	0.93564	0.032106	0.074267	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

73

NASA-LEWIS   PRELIMINARY DATA   06/11/79   CADDEII   REC 10/13/79 01:41:31.283   FAC RX6X1   PGM CO34   PPG 1110

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	18.069	5.4350	0.18604	0.43169	0.43200
37	9.5354	2.8696	0.098223	0.22792	0.53000
47	11.807	3.5532	0.12162	0.28222	0.62930
52	11.967	3.6012	0.12327	0.28604	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.744	4.1360	0.14157	0.32851	0.42200
67	9.6692	2.9071	0.099509	0.23091	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	38.563	11.605	0.39723	0.92176	0.50800
82	19.572	5.8900	0.20161	0.46783	0.58300
92	3.5856	1.0790	0.036935	0.085706	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.5588	1.9738	0.067561	0.15677	0.62400
112	6.0942	1.8340	0.062775	0.14567	0.83000
122	5.6445	1.6986	0.058143	0.13492	0.96000
127	3.5936	1.0815	0.036986	0.085825	1.0900
137	5.0000	1.5047	0.051504	0.11951	1.2230
142	4.8600	1.4626	0.050063	0.11617	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.5588	1.9738	0.067561	0.15677	-1.0000
-112	6.0942	1.8340	0.062775	0.14567	-1.0000
-122	5.6445	1.6986	0.058143	0.13492	-1.0000
-127	3.5936	1.0815	0.036986	0.085825	-1.0000
-137	5.0000	1.5047	0.051504	0.11951	-1.0000
-142	4.8600	1.4626	0.050063	0.11617	-1.0000
-152	3.5306	1.0625	0.036369	0.084392	-1.0000
-157	3.5356	1.0640	0.036420	0.084511	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5306	1.0625	0.036369	0.084392	-1.0000
-157	3.5356	1.0640	0.036420	0.084511	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5356	1.0640	0.036420	0.084511	-1.0000
-172	3.5356	1.0640	0.036420	0.084511	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.0658	0.92260	0.031580	0.073280	-1.0000
-187	3.1157	0.93764	0.032095	0.074475	-1.0000

>ADDITIONALS , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/11/79   CADDEII   REC 10/13/79 01:43:13.827   FAC RX6X1   PGM C934   PDG 1112

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	15.374	4.6295	0.18569	0.43195	0.43200
37	8.1344	2.4494	0.098246	0.22854	0.53000
47	10.062	3.0299	0.12153	0.28270	0.62900
52	10.192	3.0690	0.12310	0.28635	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	11.665	3.5126	0.14089	0.32774	0.42200
67	8.2293	2.4780	0.099393	0.23121	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	33.147	9.9811	0.40034	0.93128	0.50800
82	16.682	5.0232	0.20148	0.46869	0.58300
92	3.5769	1.0771	0.043202	0.10050	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	5.6063	1.6881	0.067712	0.15751	0.62400
112	5.1915	1.5632	0.062702	0.14586	0.83000
122	4.7916	1.4428	0.057873	0.13462	0.96000
127	3.5719	1.0756	0.043142	0.10036	1.0900
137	4.2418	1.2773	0.051232	0.11918	1.2200
142	4.1314	1.2442	0.049904	0.11609	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	5.6063	1.6881	0.067712	0.15751	-1.0000
-112	5.1915	1.5632	0.062702	0.14586	-1.0000
-122	4.7916	1.4428	0.057873	0.13462	-1.0000
-127	3.5719	1.0756	0.043142	0.10036	-1.0000
-137	4.2418	1.2773	0.051232	0.11918	-1.0000
-142	4.1314	1.2442	0.049904	0.11609	-1.0000
-152	3.5319	1.0635	0.042658	0.099232	-1.0000
-157	3.5319	1.0635	0.042658	0.099232	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	3.5319	1.0635	0.042658	0.099232	-1.0000
-157	3.5319	1.0635	0.042658	0.099232	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-167	3.5319	1.0635	0.042658	0.099232	-1.0000
-172	3.5369	1.0650	0.042719	0.099372	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-182	3.0570	0.92051	0.036922	0.085887	-1.0000
-187	3.1120	0.93707	0.037596	0.087432	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.739	4.1420	0.18484	0.43150	0.43200
37	7.2766	2.1941	0.098935	0.22853	0.53000
47	9.0015	2.7143	0.12241	0.28271	0.62900
52	9.1315	2.7534	0.12418	0.28675	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.441	3.1483	0.14199	0.37792	0.42200
67	7.3816	2.2258	0.10038	0.23183	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	29.597	8.9244	0.40249	0.92953	0.50800
82	14.833	4.4728	0.20172	0.46587	0.58300
92	3.5750	1.0780	0.048617	0.11228	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.9559	1.4944	0.067396	0.15565	0.62400
112	4.6107	1.3903	0.062702	0.14481	0.83000
122	4.2555	1.2832	0.057871	0.13365	0.96000
127	3.5550	1.0720	0.048345	0.11165	1.0930
137	3.7952	1.1444	0.051611	0.11919	1.2200
142	3.6851	1.1112	0.050114	0.11574	1.3500

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.9559	1.4944	0.067396	0.15565	-1.0000
-112	4.6107	1.3903	0.062702	0.14481	-1.0000
-122	4.2555	1.2832	0.057871	0.13365	-1.0000
-127	3.5550	1.0720	0.048345	0.11165	-1.0000
-137	3.7952	1.1444	0.051611	0.11919	-1.0000
-142	3.6851	1.1112	0.050114	0.11574	-1.0000
-152	3.5250	1.0629	0.047937	0.11071	-1.0000
-157	3.5300	1.0644	0.048005	0.11087	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5250	1.0629	0.047937	0.11071	-1.0000
-157	3.5300	1.0644	0.048005	0.11087	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD ITERATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5250	1.0629	0.047937	0.11071	-1.0000
-172	3.5250	1.0629	0.047937	0.11071	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD ITERATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.0446	0.91805	0.041404	0.095620	-1.0000
-187	3.0546	0.92107	0.041540	0.095935	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
32	12.217	3.6645	0.19739	0.43137	0.47200
37	6.4757	1.9432	0.029367	0.22874	0.53000
47	8.0131	2.4036	0.12291	0.28295	0.62900
52	8.1201	2.4366	0.12460	0.28683	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
62	9.2944	2.7860	0.14247	0.32756	0.42200
67	6.5436	1.9627	0.10036	0.23104	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
77	26.254	7.8781	0.40286	0.92738	0.50800
82	13.141	3.9432	0.23164	0.46418	0.58300
92	3.5855	1.0759	0.055019	0.12665	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
107	4.3707	1.3115	0.067067	0.15439	0.62400
115	4.0757	1.2230	0.062540	0.14397	0.83000
122	3.7606	1.1284	0.057705	0.13294	0.96000
127	3.5735	1.0714	0.054789	0.12612	1.0900
137	3.3754	1.0129	0.051795	0.11923	1.2200
142	3.2454	0.97585	0.050107	0.11535	1.3500

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-107	4.3707	1.3115	0.067067	0.15439	-1.0000
-112	4.0757	1.2230	0.062540	0.14397	-1.0000
-122	3.7606	1.1284	0.057705	0.13294	-1.0000
-127	3.5735	1.0714	0.054789	0.12612	-1.0000
-137	3.3754	1.0129	0.051795	0.11923	-1.0000
-142	3.2654	0.97985	0.050107	0.11535	-1.0000
-152	3.5355	1.0609	0.054251	0.12489	-1.0000
-157	3.5405	1.0624	0.054328	0.12506	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-152	3.5355	1.0609	0.054251	0.12499	-1.0000
-157	3.5405	1.0624	0.054328	0.12506	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-167	3.5405	1.0624	0.054328	0.12506	-1.0000
-172	3.5405	1.0624	0.054328	0.12506	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-102	3.0553	0.91681	0.046883	0.10792	-1.0000
-107	3.0853	0.92582	0.047343	0.10898	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   0(/11/79   CADDFII   REC 10/13/79 01:57:31.855   FAC 9X6X1   PGM C034   PDG 1115

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
4?	13.669	4.2858	0.21615	0.43160	0.43200
37	7.2393	2.2698	0.11449	0.22958	0.53000
47	8.9649	2.8138	0.14178	0.28306	0.62900
5?	9.0849	2.8484	0.14368	0.28695	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
6?	10.390	3.2576	0.16432	0.32906	0.42200
67	7.3294	2.2980	0.11592	0.23142	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	25.533	9.0056	0.40382	0.80620	0.50800
8?	12.780	4.0069	0.20212	0.40351	0.58300
92	3.4114	1.0696	0.053952	0.10771	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.2372	1.3285	0.067014	0.13379	0.62400
11?	3.9670	1.2438	0.062739	0.12526	0.83000
12?	3.6416	1.1418	0.057594	0.11498	0.96000
127	3.4063	1.0680	0.053873	0.10755	1.09
13?	3.6867	1.1559	0.058306	0.11641	1.2290
14?	3.5265	1.1057	0.055773	0.11135	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.2372	1.3285	0.067014	0.13379	-1.0000
-11?	3.9670	1.2438	0.062739	0.12526	1.0000
-12?	3.6416	1.1418	0.057594	0.11498	-1.0000
-12?	3.4063	1.0690	0.053873	0.10755	-1.0000
-13?	3.6867	1.1559	0.058306	0.11641	-1.0000
-14?	3.5265	1.1057	0.055773	0.11135	-1.0000
-15?	3.3963	1.0649	0.053715	0.10724	-1.0000
-15?	3.3963	1.0649	0.053715	0.10724	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-15?	3.3963	1.0649	0.053715	0.10724	-1.0000
-15?	3.3963	1.0649	0.053715	0.10724	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-16?	3.3963	1.0649	0.053715	0.10724	-1.0000
-17?	3.3963	1.0649	0.053715	0.10724	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-18?	2.9357	0.93702	0.045797	0.091432	-1.0000
-187	2.9638	0.92933	0.046827	0.093487	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.902	3.7079	0.18650	0.43101	0.43200
37	6.3172	1.9655	0.099129	0.22869	0.53000
47	7.8126	2.4329	0.12262	0.28280	0.62900
52	7.9177	2.4697	0.12444	0.28697	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	9.0377	2.8180	0.14204	0.32756	0.42200
67	6.3773	1.9884	0.10023	0.23114	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
72	25.618	7.3876	0.40262	0.92846	0.50800
82	12.922	3.9978	0.20151	0.46471	0.58300
63	3.4253	1.0680	0.053836	0.12415	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.2610	1.3286	0.066969	0.15444	0.62400
112	3.9958	1.2438	0.062644	0.14446	0.83000
122	3.6605	1.1413	0.057531	0.13267	0.96000
127	3.4153	1.0649	0.053677	0.12378	1.0900
137	3.2852	1.0243	0.051632	0.11907	1.2290
142	3.1801	0.99164	0.049980	0.11526	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.2610	1.3286	0.066969	0.15444	-1.0000
-112	3.9958	1.2438	0.062644	0.14446	-1.0000
-122	3.6605	1.1413	0.057531	0.13267	-1.0000
-127	3.4153	1.0649	0.053677	0.12378	-1.0000
-137	3.2852	1.0243	0.051632	0.11907	-1.0000
-142	3.1801	0.99164	0.049980	0.11526	-1.0000
-152	3.4153	1.0618	0.053523	0.12342	-1.0000
-157	3.4103	1.0633	0.053598	0.12360	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4153	1.0618	0.053523	0.12342	-1.0000
-157	3.4103	1.0633	0.053598	0.12360	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4718	1.0802	0.053441	0.12324	-1.0000
-172	3.4153	1.0618	0.053523	0.12342	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	2.9249	0.91195	0.045969	0.10601	-1.0000
-192	2.9340	0.93069	0.046912	0.10818	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVR WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	10.546	3.2878	0.16618	0.43109	0.43200
37	5.6368	1.7473	0.088315	0.22510	0.53000
47	6.9255	2.1591	0.10913	0.28308	0.62900
52	7.0326	2.1318	0.11078	0.28738	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVR WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	8.0439	2.5968	0.12670	0.32868	0.42200
67	5.6798	1.7707	0.089498	0.23217	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVR WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	25.534	7.9602	0.40233	1.0437	0.50800
92	12.801	3.9907	0.20170	0.52323	0.58300
62	3.4279	1.0647	0.054013	0.14012	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR ,HPCUD

AVR WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.2537	1.3261	0.067026	0.17387	0.62400
117	3.9694	1.2372	0.062531	0.16221	0.83000
122	3.6581	1.1404	0.057641	0.14953	0.96000
127	3.4178	1.0655	0.053855	0.13971	1.0900
137	2.8972	0.90323	0.045652	0.11843	1.2200
142	2.9223	0.91104	0.046046	0.11945	1.3500

>ADDITIONAL PRESSURE RATIOS , FORFARON INLET

AVR WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.2537	1.3261	0.067026	0.17387	-1.0000
-117	3.9694	1.2372	0.062531	0.16221	-1.0000
-122	3.6581	1.1404	0.057641	0.14953	-1.0000
-127	3.4178	1.0655	0.053855	0.13971	-1.0000
-137	2.8972	0.90323	0.045652	0.11843	-1.0000
-142	2.9223	0.91104	0.046046	0.11945	-1.0000
-152	3.4128	1.0640	0.053776	0.13950	-1.0000
-157	3.4178	1.0624	0.053698	0.13930	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVR WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4128	1.0640	0.053776	0.13950	-1.0000
-157	3.4178	1.0624	0.053658	0.13930	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVR WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4178	1.0624	0.053698	0.13930	-1.0000
-172	3.4128	1.0640	0.053776	0.13950	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVR WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	2.9323	0.91416	0.046204	0.11986	-1.0000
-187	2.9974	0.93445	0.047239	0.12252	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.313	4.7769	0.21480	0.43167	0.43200
37	8.1155	2.5333	0.11391	0.22892	0.53000
47	10.034	3.1322	0.14084	0.29304	0.62930
52	13.164	3.1727	0.14266	0.28671	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.623	3.6280	0.16314	0.32785	0.42200
67	8.1954	2.5582	0.11503	0.23118	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	29.055	9.0794	0.40441	0.81676	0.50900
82	14.384	4.4901	0.20199	0.40576	0.58300
92	3.4313	1.0711	0.34F161	0.096789	0.67030

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.7965	1.4972	0.067323	0.13530	0.62400
112	4.4765	1.3973	0.062832	0.12627	0.83000
122	4.1114	1.2834	0.057708	0.11597	0.96000
127	3.4263	1.0695	0.048091	0.096648	1.0900
137	4.1464	1.2943	0.058199	0.11696	1.2200
142	3.9614	1.2366	0.055602	0.11174	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.7965	1.4972	0.067323	0.13530	-1.0000
-112	4.4765	1.3973	0.062832	0.12627	-1.0000
-122	4.1114	1.2834	0.057708	0.11597	-1.0000
-127	3.4263	1.0695	0.048091	0.096648	-1.0000
-137	4.1464	1.2943	0.058199	0.11696	-1.0000
-142	3.9614	1.2366	0.055602	0.11174	-1.0000
-152	3.4113	1.0648	0.047891	0.096225	-1.0000
-157	3.4113	1.0648	0.047891	0.096225	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLSP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4113	1.0648	0.047891	0.096225	-1.0000
-157	3.4113	1.0648	0.047891	0.096225	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4113	1.0664	0.047951	0.096366	-1.0000
-172	3.4113	1.0648	0.047891	0.096225	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
	2.9361	0.90714	0.040790	0.081975	-1.0000
	2.9711	0.92744	0.041703	0.083809	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/11/79   CADDELL   REC 10/13/79 02:31:18.193   FAC 8X6X1   PGM C034   RDG 1119

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
42	13.351	4.1920	1.19637	0.43309	0.43200
37	7.1744	2.2213	0.958755	0.32790	0.53000
47	8.7530	2.7502	0.12227	0.28216	0.62900
52	8.8739	2.7863	0.12387	0.28587	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.163	3.1911	0.14187	0.32740	0.42200
67	7.1644	2.2495	0.10001	0.23080	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	29.104	9.1384	0.40628	0.93757	0.50800
82	14.450	4.5370	0.20171	0.46549	0.58300
92	3.4037	1.0687	0.047513	0.10965	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.8193	1.5132	0.067274	0.15525	0.62400
117	4.4992	1.4127	0.062806	0.14494	0.83000
122	4.1341	1.2980	0.057709	0.13318	0.96000
127	3.3997	1.0671	0.047444	0.10949	1.0900
137	3.6989	1.1614	0.051634	0.11916	1.2200
147	3.5889	1.1268	0.050097	0.11561	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.8193	1.5132	0.067274	0.15525	-1.0000
-112	4.4992	1.4127	0.062806	0.14494	-1.0900
-122	4.1341	1.2980	0.057709	0.13318	-1.0000
-127	3.3997	1.0671	0.047444	0.10949	-1.0000
-137	3.6989	1.1614	0.051634	0.11916	-1.0000
-147	3.5889	1.1268	0.050097	0.11561	-1.0000
-152	3.3837	1.0624	0.047234	0.10900	-1.0000
-157	3.3787	1.0609	0.047164	0.10884	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.3837	1.0624	0.047234	0.10900	-1.0000
-157	3.3787	1.0609	0.047164	0.10884	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.3837	1.0624	0.047234	0.10900	-1.0000
-172	3.3787	1.0609	0.047164	0.10884	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	2.8386	0.91906	0.040460	0.093369	-1.0000
-187	2.9536	0.92891	0.041228	0.095303	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
42	13.351	4.1920	0.19637	0.43109	0.43200
37	7.0744	2.2213	0.058755	0.22790	0.53000
47	8.7530	2.7502	0.12227	0.28216	0.62900
52	8.8729	2.7863	0.12387	0.28587	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.163	3.1911	0.14187	0.32740	0.42200
67	7.1644	2.2495	0.10001	0.23080	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	29.104	9.1384	0.40628	0.93757	0.50800
82	14.450	4.5370	0.20171	0.46549	0.58300
92	3.4037	1.0687	0.047513	0.10965	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.8193	1.5132	0.067274	0.15525	0.62400
117	4.4992	1.4127	0.062806	0.14494	0.83000
122	4.1341	1.2980	0.057709	0.13318	0.96000
127	3.3997	1.0671	0.047444	0.10949	1.0900
137	3.6989	1.1614	0.051634	0.11916	1.2200
142	3.5988	1.1268	0.050097	0.11561	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.8193	1.5132	0.067274	0.15525	-1.0000
-112	4.4992	1.4127	0.062806	0.14494	-1.0000
-122	4.1341	1.2980	0.057709	0.13318	-1.0000
-127	3.3997	1.0671	0.047444	0.10949	-1.0000
-137	3.6989	1.1614	0.051634	0.11916	-1.0000
-142	3.5988	1.1268	0.050097	0.11561	-1.0000
-152	3.3837	1.0624	0.047234	0.10900	-1.0000
-157	3.3787	1.0609	0.047164	0.10884	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.3837	1.0624	0.047234	0.10900	-1.0000
-157	3.3787	1.0609	0.047164	0.10884	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.3837	1.0624	0.047234	0.10900	-1.0000
-172	3.3787	1.0609	0.047164	0.10884	-1.0000

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	2.8986	0.91006	0.040460	0.093369	-1.0000
-192	2.9534	0.92801	0.041228	0.095303	-1.0000

>STATION 9 , MEASURED THRUST PARAMETERS

83

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.754	3.6970	0.16591	0.43066	0.43200
37	6.2410	1.9631	0.088057	0.22867	0.53000
47	7.7737	2.4285	0.10869	0.28286	0.62900
52	7.8307	2.4631	0.11054	0.28692	0.72703

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	8.9533	2.8153	0.12634	0.32794	0.42200
67	6.3163	1.9867	0.089156	0.23142	0.67003

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	28.775	9.0512	0.43619	1.0543	0.50800
82	14.331	4.4984	0.20187	0.52400	0.58300
92	3.3952	1.0680	0.047927	0.12440	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.7758	1.5022	0.067415	0.17499	0.62400
112	4.4507	1.4000	0.062826	0.16308	0.83000
122	4.0856	1.2851	0.057672	0.14970	0.96000
127	3.3952	1.0680	0.047927	0.12440	1.0900
137	3.2301	1.0160	0.045597	0.11835	1.2200
142	3.2602	1.0255	0.046020	0.11945	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.7758	1.5022	0.067415	0.17499	-1.0000
-112	4.4507	1.4300	0.062826	0.16308	-1.0000
-122	4.0856	1.2851	0.057672	0.14970	-1.0000
-127	3.3952	1.0680	0.047927	0.12440	-1.0000
-137	3.2301	1.0160	0.045597	0.11835	-1.0000
-142	3.2602	1.0255	0.046020	0.11945	-1.0000
-152	3.3402	1.0632	0.047715	0.12385	-1.0000
-157	3.3952	1.0648	0.047786	0.12404	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.3802	1.0632	0.047715	0.12385	-1.0000
-157	3.3952	1.0648	0.047786	0.12404	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.3756	1.0617	0.047645	0.12367	-1.0000
-172	3.3752	1.0617	0.047645	0.12367	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	2.9999	0.93902	0.040794	0.10589	-1.0000
-187	2.3530	0.92751	0.041642	0.10839	-1.0000

>SECTION C , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
12	17.363	5.3192	0.21430	0.43103	0.43200
22	9.0087	2.8084	0.11313	0.22757	0.53000
42	11.149	3.4752	0.14001	0.28161	0.62900
52	11.319	3.5292	0.14214	0.28590	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
42	12.977	4.0453	0.16298	0.32781	0.42200
67	9.1337	2.8473	0.11471	0.23073	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.341	10.092	0.40618	0.81658	0.50800
82	16.344	5.0315	0.20150	0.40529	0.58300
62	3.4278	1.0686	0.043051	0.086592	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.3738	1.6752	0.067491	0.13575	0.62400
112	5.0037	1.5598	0.062842	0.12640	0.83500
122	4.6035	1.4351	0.057817	0.11629	0.96000
127	3.4428	1.0733	0.043243	0.086971	1.0900
137	4.6285	1.4429	0.058131	0.11692	1.2200
142	4.4284	1.3805	0.055618	0.11187	1.3500

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.3738	1.6752	0.067491	0.13575	-1.0000
-112	5.0037	1.5598	0.062842	0.12640	-1.0000
-122	4.6035	1.4351	0.057817	0.11629	-1.0000
-127	3.4428	1.0733	0.043243	0.086971	-1.0000
-137	4.6285	1.4429	0.058131	0.11692	-1.0000
-142	4.4284	1.3805	0.055618	0.11187	-1.0000
-152	3.4128	1.0639	0.042842	0.086213	-1.0000
-157	3.4128	1.0639	0.042842	0.086213	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4128	1.0639	0.042842	0.086213	-1.0000
-157	3.4128	1.0639	0.042842	0.086213	-1.0000

>ADDITIONAL PRESSURE RATIOS , 30 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4178	1.0655	0.042925	0.086330	-1.0000
-172	3.4178	1.0655	0.042925	0.086330	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	2.9475	0.91895	0.037018	0.074457	-1.0000
-187	3.3075	0.93757	0.037772	0.075974	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

96

C-2

87

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	14.747	4.6120	0.18554	0.43094	0.43200
37	7.9135	2.4426	0.098270	0.22924	0.53000
47	9.6602	3.0211	0.12154	0.28229	0.62500
52	9.7951	3.0633	0.12324	0.28623	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	11.205	3.5041	0.14097	0.32742	0.42200
67	7.9055	2.4723	0.099465	0.23101	0.47000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	32.254	10.087	0.40582	0.94259	0.50800
82	16.126	5.0119	0.20164	0.46831	0.58300
92	3.4290	1.0724	0.043143	0.10020	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	5.3701	1.6794	0.067565	0.15693	0.62400
112	4.9950	1.5621	0.062846	0.14596	0.83000
122	4.5998	1.4354	0.057748	0.13412	0.96900
127	3.4290	1.0724	0.043143	0.10020	1.0900
137	4.0795	1.2758	0.051327	0.11921	1.2200
142	3.9694	1.2414	0.049942	0.11599	1.3503

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	5.3701	1.6794	0.067556	0.15693	-1.0000
-112	4.9950	1.5621	0.062846	0.14596	-1.0000
-122	4.5998	1.4354	0.057748	0.13412	-1.0500
-127	3.4290	1.0724	0.043143	0.10020	-1.0000
-137	4.0795	1.2758	0.051327	0.11921	-1.0000
-142	3.9694	1.2414	0.049942	0.11599	-1.0000
-152	3.4040	1.0646	0.042829	0.099472	-1.0000
-157	3.4100	1.0661	0.042892	0.099618	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	3.4040	1.0646	0.042829	0.099472	-1.0000
-157	3.4100	1.0661	0.042892	0.099618	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-167	3.4040	1.0646	0.042829	0.099472	-1.0000
-172	3.4040	1.0646	0.042829	0.099472	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-182	2.9136	0.91119	0.036658	0.085141	-1.0000
-187	2.9136	0.91119	0.036658	0.085141	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   36/11/79   CARDELL   WEC 10/13/79 02:06:11.463   FAC 8XAX1   PGM C034   ROG 1124

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.134	4.1255	0.16695	0.43124	3.43700
37	6.9637	2.1751	0.097072	0.22847	0.53000
47	9.6106	2.6906	0.10992	0.28262	0.62900
52	8.7356	2.7297	0.11040	0.28672	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
52	9.9902	3.1217	0.12624	0.32790	0.42200
67	7.0557	2.2947	0.099173	0.23159	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.134	19.033	0.40581	1.0539	0.50800
82	15.956	4.9860	0.20166	0.52372	0.58300
92	3.4192	1.0684	0.043213	0.11223	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.3403	1.6687	0.067493	0.17528	0.62400
112	4.9751	1.5546	0.062878	0.16330	0.83000
122	4.5699	1.4280	0.057757	0.15000	0.96000
127	3.4242	1.0700	0.043277	0.11230	1.0900
132	3.5993	1.1247	0.045490	0.11814	1.2200
142	3.6344	1.1357	0.045933	0.11929	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.3403	1.6687	0.067493	0.17528	-1.0000
-112	4.9751	1.5546	0.062878	0.16330	-1.0000
-122	4.5699	1.4280	0.057757	0.15000	-1.0000
-127	3.4242	1.0700	0.043277	0.11230	-1.0000
-132	3.5993	1.1247	0.045490	0.11814	-1.0000
-142	3.6344	1.1357	0.045933	0.11929	-1.0000
-152	3.4342	1.0637	0.043024	0.11173	-1.0000
-167	3.4042	1.0637	0.043024	0.11173	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4042	1.0637	0.043024	0.11173	-1.0000
-167	3.4042	1.0637	0.043024	0.11173	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.3392	1.0422	0.042960	0.11157	-1.0000
-172	3.4042	1.0637	0.043024	0.11173	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-177	2.9188	0.91206	0.036889	0.095802	-1.0000
-182	2.9393	0.91832	0.037142	0.096459	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	18.747	5.8977	0.21562	0.43157	0.43200
37	9.8890	3.1109	0.11374	0.22765	0.53000
47	12.243	3.8514	0.14081	0.28183	0.62900
52	12.413	3.9049	0.14276	0.28574	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.262	4.4865	0.16493	0.32830	0.42200
67	10.029	3.1550	0.11535	0.23087	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	35.014	11.015	0.40271	0.80603	0.50800
82	17.534	5.5158	0.20164	0.40362	0.58300
92	3.4078	1.0721	0.039195	0.078448	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.8892	1.8526	0.067733	0.13557	0.62400
112	5.4740	1.7221	0.062958	0.12601	0.83000
122	5.0338	1.5836	0.057896	0.11588	0.96000
127	3.4229	1.0768	0.039367	0.078794	1.0900
137	5.0789	1.5977	0.058414	0.11692	1.2200
142	4.9688	1.5316	0.055997	0.11208	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.8892	1.8526	0.067733	0.13557	-1.0000
-112	5.4740	1.7221	0.062958	0.12601	1.0030
-122	5.0338	1.5836	0.057895	0.11588	-1.0000
-127	3.4229	1.0768	0.039367	0.078794	-1.0000
-137	5.0789	1.5977	0.058414	0.11692	-1.0000
-142	4.9688	1.5316	0.055997	0.11208	-1.0000
-152	3.3978	1.0658	0.038964	0.077988	-1.0000
-157	3.3978	1.0658	0.038964	0.077988	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.3978	1.0658	0.038964	0.077988	-1.0000
-157	3.3978	1.0658	0.038964	0.077988	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.3928	1.0642	0.039007	0.077872	-1.0000
-172	3.3928	1.0642	0.039007	0.077872	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	2.9176	0.91463	0.033439	0.066929	-1.0000
-187	2.9324	0.92253	0.033727	0.067505	-1.0000

>OPTIONS , MEASURED THRUST PARAMETERS

68

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	16.029	5.0556	0.18477	0.43026	0.43200
37	8.4656	2.6721	0.397584	0.22723	0.53030
47	10.479	3.3078	0.12080	0.28129	0.62900
52	10.639	3.3582	0.12264	0.28559	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	12.173	3.8424	0.14032	0.32676	0.42200
67	8.5756	2.7068	0.098852	0.23019	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	34.934	11.027	0.40269	0.93771	0.50900
82	17.492	5.5215	0.20164	0.46956	0.58300
87	3.3902	1.0701	0.039089	0.091002	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	5.8559	1.8484	0.067503	0.15719	0.62400
112	5.4605	1.7237	0.062956	0.14658	0.83300
122	5.0158	1.5832	0.057819	0.13464	0.96000
127	3.3952	1.0717	0.039139	0.091137	1.0900
137	6.4357	1.4001	0.051132	0.11906	1.2200
142	4.3156	1.3622	0.049748	0.11584	1.3500

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	5.8559	1.8484	0.067503	0.15719	-1.0000
-112	5.4605	1.7237	0.062956	0.14658	-1.0000
-122	5.0158	1.5932	0.057819	0.13464	-1.0000
-127	3.3952	1.0717	0.039139	0.091147	-1.0000
-137	4.4357	1.4001	0.051132	0.11906	-1.0000
-142	4.3156	1.3622	0.049748	0.11584	-1.0000
-152	3.3652	1.0622	0.038792	0.090331	-1.0900
-157	3.3652	1.0622	0.038792	0.090331	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	3.3652	1.0622	0.038792	0.090331	-1.0000
-157	3.3652	1.0622	0.038792	0.090331	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-167	3.3652	1.0622	0.038792	0.090331	-1.0000
-172	3.3652	1.0622	0.038792	0.090331	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-182	2.8939	0.91221	0.033313	0.077573	-1.0000
-187	2.7242	0.02376	0.033717	0.078513	-1.0000

>SECTION 4 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
52	14.425	4.5258	0.16575	0.43204	0.43200
57	7.6381	2.3964	0.087763	0.22816	0.53000
67	9.4629	2.9626	0.13850	0.28791	0.62900
52	9.5778	3.0350	0.11005	0.28686	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	10.967	3.4346	0.12575	0.32787	0.42200
67	7.7331	2.4262	0.098854	0.23160	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	34.989	10.977	0.40203	1.0479	0.50800
82	17.543	5.5038	0.20157	0.52540	0.58300
87	3.4063	1.0687	0.039139	0.10202	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	5.9777	1.8641	0.067536	0.17604	0.62400
112	5.4726	1.7170	0.062881	0.16390	0.83000
122	5.0274	1.5773	0.057766	0.15057	0.96000
127	3.4213	1.0734	0.039312	0.10247	1.0900
137	3.9667	1.2383	0.045349	0.11820	1.2200
142	4.0018	1.2555	0.065981	0.11985	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	5.9777	1.8641	0.067536	0.17604	-1.0000
-112	5.4726	1.7170	0.062881	0.16390	-1.0000
-122	5.0274	1.5773	0.057766	0.15057	-1.0000
-127	3.4213	1.0734	0.039312	0.10247	-1.0000
-137	3.9667	1.2383	0.045349	0.11820	-1.0000
-142	4.0018	1.2555	0.045991	0.11985	-1.0000
-152	3.3963	1.0656	0.039024	0.10172	-1.0000
-157	3.3963	1.0656	0.039024	0.10172	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	3.3963	1.0656	0.039024	0.10172	-1.0000
-157	3.3963	1.0656	0.039024	0.10172	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-167	3.3963	1.0656	0.039024	0.10172	-1.0000
-172	3.3013	1.0360	0.038967	0.10157	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-177	2.9159	0.91496	0.033504	0.087331	-1.0000
-182	2.9550	0.92740	0.033964	0.088530	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	17.930	5.5509	0.18619	0.43161	0.43200
37	9.4218	2.9317	0.098334	0.22705	0.53000
47	11.665	3.6298	0.12175	0.29224	0.62900
52	11.825	3.6796	0.12342	0.28611	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.559	4.2190	0.14151	0.32805	0.42200
67	9.5517	2.9721	0.099690	0.23110	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER D.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	38.115	11.860	0.39786	0.92216	0.50800
82	19.313	6.0093	0.20156	0.46726	0.58300
92	3.4366	1.3693	0.035867	0.083147	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.4725	2.0140	0.067552	0.15660	0.62400
112	6.0275	1.8755	0.062908	0.14583	0.83000
122	5.5474	1.7261	0.057869	0.13422	0.56000
127	3.4516	1.0743	0.036024	0.083510	1.0400
137	4.9373	1.5363	0.051530	0.11945	1.2200
142	4.7972	1.4927	0.050068	0.11607	1.3500

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.4725	2.0140	0.067552	0.15660	-1.0000
-112	6.0275	1.8755	0.062908	0.14583	-1.0000
-122	5.5474	1.7261	0.057869	0.13422	-1.0000
-127	3.4516	1.0743	0.036024	0.083510	-1.0000
-137	4.9373	1.5363	0.051530	0.11965	-1.0000
-142	4.7972	1.4927	0.050068	0.11607	-1.0000
-152	3.4166	1.0631	0.035659	0.082663	-1.0000
-157	3.4166	1.0631	0.035659	0.082663	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4166	1.0631	0.035659	0.082663	-1.0000
-157	3.4166	1.0631	0.035659	0.082663	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4166	1.0631	0.035659	0.082663	-1.0000
-172	3.4215	1.0647	0.035711	0.082786	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	2.9663	0.92300	0.030959	0.071760	-1.0000
-187	3.0113	0.93701	0.031429	0.072850	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

92

NASA-LEWIS   PRELIMINARY DATA   06/11/79   CFDDFII   REC 10/13/79 02:14:02.459   FAC RX6T1   PGM C034   PRG 1129

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.871	4.5544	0.16574	0.43049	0.43200
37	8.3966	2.4211	0.087685	0.22785	0.53000
47	10.396	3.2621	0.10946	0.28183	0.62500
52	10.536	3.2889	0.11002	0.28599	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.060	3.7646	0.12594	0.32726	0.42200
67	8.5266	2.6554	0.098833	0.23086	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	38.105	11.895	0.39792	1.0340	0.50000
82	19.312	6.0286	0.20168	0.52407	0.58300
92	3.4259	1.0694	0.035776	0.092966	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.4618	2.0172	0.067480	0.17535	0.62400
112	6.0318	1.8829	0.062990	0.16368	0.83000
122	5.5667	1.7315	0.057924	0.15052	0.96000
127	3.4409	1.0741	0.035933	0.093373	1.0900
137	4.3514	1.3583	0.045441	0.11808	1.2200
142	4.4166	1.3786	0.046120	0.11984	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREFAN INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.4618	2.0172	0.067480	0.17535	-1.0000
-112	6.0318	1.8829	0.062990	0.16368	-1.0000
-122	5.5667	1.7315	0.057924	0.15052	-1.0000
-127	3.4409	1.0741	0.035933	0.093373	-1.0000
-137	4.3514	1.3583	0.045441	0.11808	-1.0000
-142	4.4166	1.3786	0.046120	0.11984	-1.0000
-152	3.4009	1.0616	0.035515	0.092287	-1.0000
-157	3.4359	1.0632	0.035567	0.092423	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4009	1.0616	0.035515	0.092287	-1.0000
-157	3.4359	1.0632	0.035567	0.092423	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4359	1.0632	0.035567	0.092423	-1.0000
-172	3.4009	1.0616	0.035515	0.092287	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	2.9355	0.91637	0.030656	0.079660	-1.0000
-187	2.9356	0.91700	0.031170	0.081018	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.723	4.0255	0.16571	0.43167	0.43200
37	8.3131	2.6741	0.C87609	0.22873	0.53300
47	10.277	3.2195	0.10631	0.28215	0.62500
52	10.437	3.2696	0.11000	0.28655	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
~2	11.922	3.7345	0.12564	0.32729	0.42200
67	8.4180	2.6370	0.088716	0.23111	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	37.743	11.823	0.39777	1.0362	0.50000
92	19.135	5.9962	0.20166	0.52533	0.58300
92	3.4019	1.0657	0.035851	0.093394	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.3981	2.0063	0.067428	0.17565	0.62400
112	5.9730	1.8711	0.062568	0.16398	0.83000
122	5.4929	1.7207	0.057888	0.15080	0.96000
127	3.4219	1.0719	0.036062	0.093944	1.0900
137	4.2924	1.3446	0.045237	0.11784	1.2230
142	4.3625	1.3666	0.045975	0.11977	1.3500

>ADDITIONAL PRESSURE RATIOS , FORWARD INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.3981	2.0063	0.067428	0.17565	-1.0000
-112	5.9730	1.8711	0.062948	0.16398	-1.0000
-122	5.4929	1.7207	0.057899	0.15080	-1.0000
-127	3.4219	1.0719	0.036062	0.093944	-1.0000
-137	4.2924	1.3446	0.045237	0.11784	-1.0000
-142	4.3625	1.3666	0.045975	0.11977	-1.0000
-152	3.3969	1.3613	0.035653	0.092982	-1.0000
-157	3.3969	1.3610	0.035693	0.092982	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.3969	1.0610	0.035693	0.092982	-1.0000
-157	3.3969	1.3610	0.035693	0.092982	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.3969	1.0610	0.035693	0.092982	-1.0000
-172	3.3969	1.0610	0.035693	0.092982	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	2.9315	0.91931	0.030894	0.080491	-1.0000
-187	2.9766	0.93242	0.031369	0.081718	-1.0000

>SECTION 5 . MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	17.609	5.5089	0.18558	0.43229	0.43200
37	9.3080	2.9120	0.098099	0.22851	0.53000
47	11.516	3.6029	0.12137	0.28272	0.62900
52	11.671	3.6513	0.12300	0.28652	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.399	4.1919	0.14122	0.32895	3.42200
67	9.4329	2.9511	0.099416	0.23158	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	37.702	11.820	0.39820	0.92756	0.50800
82	19.156	5.9931	0.20189	0.47029	0.58300
92	3.4143	1.0682	0.035985	0.083623	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.4144	2.0068	0.067603	0.15747	0.62400
112	5.9895	1.8738	0.063125	0.14704	0.83000
122	5.4996	1.7206	0.057962	0.13502	0.96000
127	3.4343	1.0744	0.036196	0.084314	1.0400
137	4.8596	1.5203	0.051217	0.11930	1.2200
142	4.7396	1.4828	0.049952	0.11636	1.3500

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.4144	2.0068	0.067603	0.15747	-1.0000
-112	5.9895	1.8738	0.063125	0.14704	-1.0000
-122	5.4996	1.7206	0.057962	0.13502	-1.0000
-127	3.4343	1.0744	0.036196	0.084314	-1.0000
-137	4.8596	1.5203	0.051217	0.11930	-1.0000
-142	4.7396	1.4828	0.049952	0.11636	-1.0000
-152	3.4043	1.0651	0.035879	0.083577	-1.0000
-157	3.4143	1.0651	0.035879	0.083577	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4143	1.0651	0.035879	0.083577	-1.0000
-157	3.4143	1.0651	0.035879	0.083577	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4143	1.0651	0.035879	0.083577	-1.0000
-172	3.3003	1.0635	0.035827	0.082454	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-187	2.9191	0.91327	0.030766	0.071666	-1.0000
-197	2.9742	0.93068	0.031346	0.073016	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.531	4.5491	0.14571	0.43121	0.43200
37	7.6795	2.4392	0.097759	0.22837	0.53000
47	9.4960	2.9784	0.10849	0.28233	0.62900
52	9.6339	0.0223	0.11009	0.28649	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.013	3.4551	0.12586	0.32751	1.42200
67	7.7795	2.4606	0.088901	0.23134	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	34.996	10.944	0.39867	1.0374	0.50800
82	17.632	5.5316	0.20150	0.52434	0.58300
92	3.4134	1.0708	0.039007	0.10150	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.9044	1.8523	0.067474	0.17558	0.62400
112	5.4993	1.7252	0.062845	0.16354	0.83000
122	5.0592	1.5872	0.057815	0.15045	0.96000
127	3.4234	1.0740	0.039121	0.10190	1.0900
137	3.9687	1.2451	0.045353	0.11802	1.2700
142	4.0234	1.2623	0.045582	0.11946	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.9044	1.8523	0.067474	0.17558	-1.0000
-112	5.4993	1.7252	0.062845	0.16354	-1.0000
-122	5.0592	1.5872	0.057815	0.15045	-1.0000
-127	3.4234	1.0740	0.039121	0.10190	-1.0000
-137	3.9687	1.2451	0.045353	0.11802	-1.0000
-142	4.0234	1.2623	0.045582	0.11946	-1.0000
-152	3.3934	1.0646	0.038778	0.10091	-1.0000
-157	3.3944	1.0661	0.038836	0.10106	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.3934	1.0646	0.038778	0.10091	-1.0000
-157	3.3944	1.0661	0.038836	0.10106	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.3934	1.0646	0.038778	0.10091	-1.0000
-172	3.3934	1.0646	0.038778	0.10091	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	2.9330	0.92014	0.033518	0.087221	-1.0000
-187	2.9671	0.92956	0.033861	0.088113	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	16.146	5.0310	0.18456	0.43164	0.43200
37	8.5314	2.6589	0.097522	0.22808	3.53000
47	10.555	3.2897	0.12066	0.29219	0.62900
52	10.715	3.3395	0.12249	0.28647	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	12.274	3.8254	0.14031	0.32815	0.42200
67	8.6463	2.6947	0.098836	0.23115	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	34.947	10.892	0.39948	0.93429	0.50800
82	17.656	5.5020	0.20180	0.47197	0.58300
92	3.4257	1.0676	0.039150	0.091583	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	5.9066	1.8408	0.067518	0.15791	0.62400
112	5.5065	1.7162	0.062945	0.14721	0.83000
122	5.0614	1.5774	0.057857	0.13531	0.96000
127	3.4357	1.0708	0.039273	0.091850	1.0900
137	4.4562	1.3888	0.050939	0.11913	1.2200
142	4.3462	1.3545	0.049681	0.11619	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	5.9066	1.8408	0.067518	0.15791	-1.0000
-112	5.5065	1.7162	0.062945	0.14721	-1.0000
-122	5.0614	1.5774	0.057857	0.13531	-1.0000
-127	3.4357	1.0708	0.039273	0.091850	-1.0000
-137	4.4562	1.3888	0.050939	0.11913	-1.0000
-142	4.3462	1.3545	0.049681	0.11619	-1.0000
-152	3.4107	1.0630	0.038997	0.091182	-1.0000
-157	3.4107	1.0630	0.038997	0.091182	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	3.4107	1.0630	0.038997	0.091182	-1.0000
-157	3.4107	1.0630	0.038997	0.091182	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-167	3.4107	1.0630	0.038997	0.091182	-1.0000
-177	3.4057	1.0614	0.038930	0.091048	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-187	2.9233	0.91014	0.033392	0.078073	-1.0000
-197	2.9654	0.92418	0.033867	0.079277	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

97

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	18.924	5.8427	0.21304	0.43133	0.43200
37	9.9359	3.0960	0.11245	0.22767	0.53000
47	12.395	3.9152	0.13926	0.28195	0.62900
52	12.470	3.8704	0.14112	0.28573	0.72793

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.358	4.4566	0.16250	0.37900	0.42200
67	10.076	3.1274	0.11403	0.23088	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	35.316	10.961	0.39968	0.80972	0.50400
82	17.845	5.5388	0.20196	0.40858	0.58300
87	4.4430	1.0677	0.038932	0.078824	0.67800

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.9762	1.8549	0.067636	0.13694	0.62400
112	5.5761	1.7337	0.063108	0.12777	0.83000
122	5.1159	1.5879	0.057900	0.11723	0.96000
127	3.4600	1.0739	0.039159	0.079293	1.0900
137	5.1159	1.5879	0.057900	0.11723	1.2200
142	4.9009	1.5212	0.055466	0.11230	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.9762	1.8549	0.067636	0.13694	-1.0000
-112	5.5761	1.7337	0.063108	0.12777	-1.0000
-122	5.1159	1.5879	0.057900	0.11723	-1.0000
-127	3.4600	1.0739	0.039159	0.079293	-1.0000
-137	5.1159	1.5879	0.057900	0.11723	-1.0000
-142	4.9009	1.5212	0.055466	0.11230	-1.0000
-152	3.4250	1.0631	0.038762	0.078480	-1.0000
-157	3.4290	1.0615	0.038706	0.078365	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4250	1.0631	0.038762	0.078480	-1.0000
-157	3.4290	1.0615	0.038706	0.078365	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4250	1.0631	0.038762	0.078480	-1.0000
-172	3.4250	1.0631	0.038762	0.078480	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-184	2.9346	0.91356	0.033326	0.067473	-1.0000
-187	2.9346	0.92439	0.033779	0.068390	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

86

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	17.399	5.3251	0.21450	0.43113	0.43200
37	9.0327	2.8132	0.11332	0.22776	0.53000
47	11.172	3.4795	0.14016	0.28171	0.62900
52	11.337	3.5309	0.14223	0.28587	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER T.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	3.306	4.0507	0.16317	0.32796	0.42200
67	9.1527	2.8506	0.11482	0.23079	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	.253	2.9517	0.40087	0.80572	0.50A00
82	16.23	5.0077	0.20172	0.40544	0.58300
92	3.4310	1.0686	0.043043	0.086515	1.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	5.3822	1.6763	0.067522	0.13572	0.62400
112	5.0121	1.5610	0.062678	0.12638	0.83000
122	4.6319	1.4332	0.057732	0.11604	.96000
127	3.4310	1.0686	0.043043	0.086515	1.0900
137	4.6318	1.4426	0.058109	0.11679	1.2200
142	4.4267	1.3787	0.055535	0.11162	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	5.3822	1.6763	0.067522	0.13572	-1.0000
-112	5.0121	1.5610	0.062879	0.12638	-1.0000
-122	4.6318	1.4332	0.057732	0.11604	-1.0000
-127	3.4313	1.0686	0.043043	0.086515	-1.0000
-137	4.6318	1.4426	0.058109	0.11679	-1.0000
-142	4.4267	1.3797	0.055535	0.11162	-1.0000
-152	3.4162	1.0639	0.042855	0.086136	-1.0000
-157	3.4110	1.0623	0.042792	0.086010	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	3.4160	1.0639	0.042855	0.086136	-1.0000
-157	3.4110	1.0623	0.042792	0.086010	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-167	3.4110	1.0623	0.042792	0.086010	-1.0000
-172	3.4110	1.0623	0.042792	0.086010	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-182	2.9255	0.91115	0.036702	0.073760	-1.0000
-187	2.9856	0.92985	0.037456	0.075284	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   04/11/79   GADDETI   REC 10/13/79 02:20:26.036   FAC 9X6X1   PGM C034   PDG 1156

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.759	4.6362	0.18621	0.43160	0.43200
37	7.8157	2.4393	0.098607	0.22956	0.53000
47	9.6658	3.0167	0.12195	0.28266	0.62900
52	9.8398	3.0588	0.12365	0.28661	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.210	3.4988	0.14144	0.32789	0.42200
67	7.9207	2.4720	0.099932	0.23163	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	31.870	9.9466	0.40209	0.93169	0.50000
82	16.003	4.9945	0.20190	0.46799	0.58300
87	3.4232	1.0684	0.043189	0.10011	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.3547	1.6712	0.067558	0.15659	0.62400
112	4.9945	1.5588	0.063013	0.14606	0.83000
122	4.5792	1.4292	0.057774	0.13391	0.96000
127	3.4332	1.0715	0.043315	0.10040	1.0900
137	4.0738	1.2714	0.051397	0.11913	1.2200
142	3.9547	1.2355	0.049945	0.11577	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.3547	1.6712	0.067558	0.15659	-1.0000
-112	4.9945	1.5588	0.063013	0.14606	-1.0000
-122	4.5792	1.4292	0.057774	0.13391	-1.0000
-127	3.4332	1.0715	0.043315	0.10040	-1.0000
-137	4.0738	1.2714	0.051397	0.11913	-1.0000
-142	3.9547	1.2355	0.049945	0.11577	-1.0000
-152	3.4032	1.0621	0.042936	0.099520	-1.0000
-157	3.4392	1.0637	0.042999	0.099667	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4032	1.0621	0.042936	0.099520	-1.0000
-157	3.4392	1.0637	0.042999	0.099667	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-162	3.4032	1.0621	0.042936	0.099520	-1.0000
-172	3.3392	1.0406	0.042873	0.098374	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	2.9326	0.93500	0.036621	0.084883	-1.0000
-187	3.0637	0.92465	0.037370	0.086640	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

100

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.117	4.1110	0.16565	0.43046	3.43200
37	6.9579	2.1897	0.087970	0.22934	0.53000
47	8.5980	2.6947	0.10858	0.28217	0.62900
52	8.7191	2.7323	0.11010	0.28611	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	9.9779	3.1272	0.12601	0.32745	0.42200
67	7.0478	2.2089	0.095007	0.23129	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	31.401	9.5669	0.49162	1.0436	0.50800
82	15.973	5.0052	0.20169	0.52410	0.58300
92	3.4137	1.0689	0.043073	0.11193	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.3471	1.6759	0.067529	0.17548	0.62400
112	4.9819	1.5614	0.062917	0.16349	0.83000
122	4.5666	1.4312	0.057672	0.14987	0.96000
127	3.4137	1.0689	0.043073	0.11193	1.0900
137	3.5958	1.1270	0.045412	0.11801	1.2200
142	3.6359	1.1395	0.045917	0.11932	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.3471	1.6759	0.067529	0.17548	-1.0000
-112	4.9819	1.5614	0.062917	0.16349	-1.0000
-122	4.5666	1.4312	0.057672	0.14987	-1.0000
-127	3.4137	1.0689	0.043073	0.11193	-1.0000
-137	3.5958	1.1270	0.045412	0.11801	-1.0000
-142	3.6359	1.1395	0.045917	0.11932	-1.0000
-152	3.3906	1.0627	0.042820	0.11127	-1.0000
-157	3.3906	1.0627	0.042820	0.11127	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.3906	1.0627	0.042820	0.11127	-1.0000
-157	3.3906	1.0627	0.042920	0.11127	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.3352	1.0642	0.042884	0.11144	-1.0000
-172	3.3906	1.0627	0.042820	0.11127	-1.0000

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-192	2.9052	0.91051	0.036689	0.095340	-1.0000
-197	2.9702	0.93091	0.037511	0.097476	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.292	4.1686	0.18678	0.43147	0.43200
37	7.0475	2.2191	0.099033	0.22877	0.53093
47	8.7190	2.7339	0.12251	0.28295	0.62900
52	8.8330	2.7709	0.12612	0.29672	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.098	3.1667	0.14190	0.32770	0.42200
67	7.1226	2.2336	0.10009	0.23120	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	28.686	8.9952	0.40307	0.93109	0.50800
82	14.367	4.5054	0.20188	0.46635	0.58300
92	3.4049	1.0678	0.047847	0.11053	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.7912	1.5025	0.067327	0.15553	0.62400
112	4.4760	1.4037	0.062897	0.14529	0.83000
122	4.1336	1.2960	0.057623	0.13311	0.96000
127	3.3999	1.0662	0.047776	0.11036	1.0400
137	3.6652	1.1494	0.051504	0.11897	1.2200
142	3.5601	1.1164	0.050027	0.11556	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.7912	1.5025	0.067327	0.15553	-1.0000
-112	4.4760	1.4037	0.062897	0.14529	-1.0000
-122	4.1336	1.2960	0.057623	0.13311	-1.0000
-127	3.3999	1.0662	0.047776	0.11036	-1.0000
-137	3.6652	1.1494	0.051504	0.11897	-1.0000
-142	3.5601	1.1164	0.050027	0.11556	-1.0000
-152	3.3849	1.0615	0.047565	0.10988	-1.0000
-157	3.3849	1.0615	0.047565	0.10988	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.3849	1.0615	0.047565	0.10988	-1.0000
-157	3.3849	1.0615	0.047565	0.10988	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-162	3.3849	1.0615	0.047565	0.10988	-1.0000
-172	3.3139	1.0391	0.047636	0.11004	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	2.9736	0.99610	0.040602	0.093799	-1.0000
-187	2.3564	0.92653	0.061516	0.095903	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
22	15.442	4.8081	0.21471	0.43118	0.43200
37	9.1531	2.5407	0.11319	0.22785	0.53000
47	10.303	3.1416	0.13596	0.29173	0.62500
52	10.245	3.1899	0.14211	0.29404	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.729	3.6521	0.16279	0.32751	0.42200
67	8.2701	2.5750	0.11672	0.23092	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	29.098	9.0568	0.40363	0.81247	0.50800
82	14.538	4.5265	0.20166	0.40593	0.58300
87	3.4333	1.0689	0.047621	0.095857	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.8541	1.5114	0.067333	0.13554	0.62400
112	4.5334	1.4117	0.062891	0.12660	0.83000
122	4.1536	1.2933	0.057617	0.11598	0.96000
127	3.4333	1.0689	0.047621	0.095857	1.1900
137	4.1936	1.3026	0.058033	0.11692	1.2200
142	3.9785	1.2450	0.055465	0.11165	1.3500

>SECTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   04/11/79   CARRELL   REC 10/13/79 02:25:44.651   FAC SK6X1   PGM C934   PRG 1141

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	10.555	3.2922	0.16534	0.43068	0.43200
37	5.6135	1.7500	0.097891	0.22993	0.53900
47	6.9357	2.1634	0.13865	0.29331	0.62900
52	7.0357	2.1946	0.11022	0.28709	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	8.0436	2.5080	0.12596	0.32809	0.42200
67	5.6824	1.7719	0.089999	0.23179	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	25.650	9.0008	0.40182	1.0466	0.50800
82	12.968	4.0138	0.20158	0.52508	0.58300
52	3.4156	1.0666	0.053569	0.13953	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.2701	1.3319	0.066892	0.17424	0.62400
112	3.9949	1.2461	0.062582	0.16301	0.83000
122	3.6647	1.1431	0.057413	0.14954	0.96000
127	3.4146	1.0651	0.053491	0.13933	1.0900
137	2.8992	0.90432	0.045417	0.11830	1.2200
142	2.9192	0.91056	0.045731	0.11912	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.2701	1.3319	0.066892	0.17424	-1.0000
-112	3.9949	1.2461	0.062582	0.16301	-1.0000
-122	3.6647	1.1431	0.057410	0.14954	-1.0000
-127	3.4146	1.0651	0.053491	0.13933	-1.0000
-137	2.8992	0.90432	0.045417	0.11830	-1.0000
-142	2.9192	0.91056	0.045731	0.11912	-1.0000
-152	3.4046	1.0620	0.053334	0.13892	-1.0000
-157	3.4046	1.0629	0.053334	0.13892	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4046	1.0620	0.053334	0.13892	-1.0000
-157	3.4046	1.0620	0.053334	0.13892	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4046	1.0620	0.053334	0.13892	-1.0000
-172	3.2396	1.0104	0.053256	0.13872	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	2.9392	0.90744	0.045574	0.11871	-1.0000
-187	2.9633	0.92617	0.046515	0.12116	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

105

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	11.912	3.7066	0.18678	0.43042	0.43200
37	6.2691	1.9670	0.09511	0.22841	0.53000
47	7.7532	2.4344	0.12268	0.28271	0.62900
52	7.8631	2.4675	0.12434	0.28654	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	9.9929	2.9221	0.14221	0.32771	0.42200
67	6.3631	1.9905	0.10030	0.23115	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	25.539	8.0144	0.40385	0.93965	0.50800
82	12.731	4.0108	0.20211	0.46575	0.58300
92	3.4319	1.0676	0.053794	0.12397	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	4.2374	1.3297	0.067006	0.15441	0.62400
112	3.9673	1.2450	0.062734	0.14457	0.83000
122	3.6370	1.1413	0.057513	0.13254	0.96000
127	3.3969	1.0660	0.053715	0.12378	1.0900
137	3.2618	1.0236	0.051579	0.11886	1.2200
142	3.1667	0.99375	0.050075	0.11540	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	4.2374	1.3297	0.067006	0.15441	-1.0000
-112	3.9673	1.2450	0.062734	0.14457	-1.0000
-122	3.6370	1.1413	0.057513	0.13254	-1.0000
-127	3.3969	1.0660	0.053715	0.12378	-1.0000
-137	3.2618	1.0236	0.051579	0.11886	-1.0000
-142	3.1667	0.99375	0.050075	0.11540	-1.0000
-152	3.3969	1.0628	0.053557	0.12342	-1.0000
-157	3.3969	1.0628	0.053557	0.12342	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	3.3969	1.0628	0.053557	0.12342	-1.0000
-157	3.3969	1.0628	0.053557	0.12342	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-167	3.3969	1.0628	0.053557	0.12342	-1.0000
-172	3.3969	1.0628	0.053557	0.12342	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-182	2.9965	0.93581	0.065644	0.10519	-1.0000
-187	2.9965	0.92466	0.066596	0.10737	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.703	4.3024	0.21540	0.43097	0.43200
37	7.2569	2.2785	0.11408	0.22824	0.53000
47	8.9763	2.8184	0.14110	0.28232	0.62900
52	9.1012	2.8576	0.14307	0.28625	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.400	3.2656	0.16349	0.32711	0.42200
67	7.3369	2.3036	0.11533	0.23076	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	25.644	8.0516	0.40311	0.80654	0.50800
82	12.929	4.0279	0.20166	0.40348	0.58300
92	3.4064	1.0695	0.053547	0.10714	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	4.2518	1.3350	0.066836	0.13372	0.62400
112	3.9917	1.2533	0.062748	0.12554	0.83000
122	3.6515	1.1465	0.057401	0.11485	0.96000
127	3.3464	1.0464	0.053390	0.10242	1.0900
137	3.7015	1.1622	0.058187	0.11642	1.2200
142	3.5165	1.1104	0.055592	0.11123	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	4.2518	1.3350	0.066836	0.13372	-1.0000
-112	3.9917	1.2533	0.062748	0.12554	-1.0000
-122	3.6515	1.1465	0.057401	0.11485	-1.0000
-127	3.3464	1.0664	0.053390	0.10642	-1.0000
-137	3.7015	1.1622	0.058187	0.11642	-1.0000
-142	3.5165	1.1104	0.055592	0.11123	-1.0000
-152	3.3864	1.0633	0.053233	0.10651	-1.0000
-157	3.3864	1.0633	0.053233	0.10651	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.3864	1.0633	0.053233	0.10651	-1.0000
-157	3.3864	1.0633	0.053233	0.10651	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.3814	1.0617	0.053154	0.10635	-1.0000
-172	3.3864	1.0633	0.053233	0.10651	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	2.8911	0.90775	0.045447	0.090930	-1.0000
-187	2.9561	0.92814	0.046470	0.092976	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

107

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	14.649	4.5074	0.18561	0.43057	0.43200
37	7.7593	2.6352	0.098317	0.22807	0.53000
47	9.5934	3.0138	0.12156	0.28198	0.62900
52	9.7293	3.0532	0.12327	0.28596	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	11.127	3.4922	0.14099	0.32706	0.42200
67	7.8563	2.4650	0.099520	0.23086	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	32.050	10.359	0.42610	0.94205	0.50900
82	15.917	4.9956	0.20168	0.46786	0.58300
92	3.3992	1.0668	0.043071	0.099513	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	5.3247	1.6711	0.067469	0.15651	0.62400
112	4.9697	1.5557	0.062970	0.14607	0.83000
122	4.5546	1.4294	0.057710	0.13387	0.94000
127	3.6042	1.0684	0.043134	0.10006	1.0900
137	4.0545	1.2725	0.051373	0.11917	1.2200
142	3.9395	1.2364	0.049916	0.11579	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	5.3247	1.6711	0.067469	0.15651	-1.0000
-112	4.9697	1.5557	0.062970	0.14607	-1.0000
-122	4.5546	1.4294	0.057710	0.13387	-1.0000
-127	3.6042	1.0684	0.043134	0.10006	-1.0000
-137	4.0545	1.2725	0.051373	0.11917	-1.0000
-142	3.9395	1.2364	0.049916	0.11579	-1.0000
-152	3.3842	1.0621	0.042891	0.099472	-1.0000
-157	3.3842	1.0621	0.042891	0.099472	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	3.3842	1.0621	0.042891	0.099472	-1.0000
-157	3.3842	1.0621	0.042891	0.099472	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-167	3.3799	1.0694	0.042817	0.099325	-1.0000
-172	3.3792	1.0606	0.042817	0.099325	-1.0000

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-182	2.9993	0.93669	0.036636	0.084515	-1.0000
-187	2.9563	0.92719	0.037439	0.086827	-1.3000

>SECTION 5 . MEASURED THRUST PARAMETERS

Run 18

NASA-LEWIS PRELIMINARY DATA CADDE-II FACILITY   RX6X1   PROGRAM CO.4 RDGS 1155 TO 1194
TIME AND DATE PROCESSED 02:01:50 JUN 11 1975

109

	NOZZLE TYPE	P+W EJECTOR NOZZLE (MODEL A)
	FLIGHT CONDITIONS	SUPER SONIC CRUISE (MS=0)
	NOZZLE CONFIGURATION	A1
	PRIMARY-NOZZLE PLUG	SPLIT PLUG (RETRACTED)
	FLOW SPLITTER	CONICAL SPLITTER
	FAN NOZZLE	IRIS
	CLAMSHELL POSITION	
	EJECTOR INLET OPENING	

RDG	MO	PTF/PTP	PTF/PO	PTP/PO	OMEGA	PTS/PTF	COS	FNP	CF1	ETA1	ETA1.IMT	CFP1	CFP2	F9
1155	1.970	1.99	19.88	9.96	0.000	0.057	0.960	0.991	0.9678	0.9678	0.9709	9.9709	0.9714	1.4593
1156	1.968	2.31	19.95	9.60	0.000	0.057	0.962	0.990	0.9668	0.9668	0.9691	0.9691	0.9686	1.4568
1157	1.970	2.59	19.94	7.69	0.000	0.058	0.962	0.987	0.9626	0.9626	0.9661	0.9661	0.9666	1.4569
1158	1.966	2.01	22.37	11.12	0.000	0.057	0.962	0.991	0.9715	0.9715	0.9742	0.9742	0.9747	1.4556
1159	1.963	2.31	22.35	9.70	0.000	0.057	0.961	0.990	0.9697	0.9697	0.9726	0.9726	0.9731	1.4561
1160	1.962	2.59	22.36	8.64	0.005	0.057	0.961	0.988	0.9709	0.9709	0.9735	0.9739	0.9744	1.4585
1161	1.962	2.01	24.78	12.35	0.000	0.057	0.962	0.992	0.9772	0.9772	0.9796	0.9796	0.9801	1.4582
1162	1.959	2.33	24.86	10.64	0.000	0.057	0.962	0.989	0.9743	0.9743	0.9769	0.9769	0.9774	1.4575
1163	1.961	2.59	24.86	9.59	0.000	0.057	0.963	0.990	0.9716	0.9716	0.9743	0.9743	0.9748	1.4571
1164	1.961	2.03	27.45	13.47	0.000	0.057	0.961	0.991	0.9800	0.9800	0.9822	0.9822	0.9824	1.4609
1165	1.963	2.33	27.48	11.81	0.000	0.057	0.963	0.991	0.9766	0.9766	0.9789	0.9749	0.9793	1.4590
1166	1.963	2.60	27.59	10.62	0.000	0.057	0.962	0.990	0.9755	0.9755	0.9779	0.9779	0.9783	1.4582
1167	1.962	2.31	29.92	12.96	0.000	0.056	0.962	0.994	0.9762	0.9762	0.9783	0.9783	0.9787	1.4612
1168	1.962	2.65	30.00	11.54	0.000	0.056	0.962	0.991	0.9789	0.9789	0.9811	0.9811	0.9815	1.4614
1169	1.962	2.61	29.96	11.48	0.000	0.056	0.962	0.992	0.9756	0.9756	0.9778	0.9778	0.9782	1.4580
1170	1.961	2.32	29.97	12.92	0.000	0.057	0.965	0.992	0.9757	0.9757	0.9778	0.9778	0.9782	1.4585
1171	1.963	2.05	27.47	13.39	0.000	0.057	0.963	0.995	0.9740	0.9740	0.9761	0.9761	0.9766	1.4559
1172	1.965	2.33	27.58	11.46	0.000	0.057	0.962	0.991	0.9786	0.9786	0.9804	0.9804	0.9813	1.4411
1173	1.962	2.60	27.53	10.57	0.000	0.057	0.961	0.990	0.9791	0.9791	0.9815	0.9915	0.9919	1.4617
1174	1.963	2.01	24.88	12.37	0.000	0.057	0.960	0.990	0.9776	0.9776	0.9800	0.9800	0.9805	1.4578
1175	1.964	2.33	25.03	10.76	0.000	0.057	0.963	0.991	0.9763	0.9763	0.9788	0.9788	0.9793	1.4400
1176	1.963	2.59	25.01	9.65	0.000	0.057	0.962	0.990	0.9741	0.9741	0.9768	0.9768	0.9773	1.4592
1177	1.963	2.02	22.52	11.19	0.000	0.057	0.960	0.989	0.9752	0.9752	0.9779	0.9779	0.9784	1.4567
1178	1.963	2.31	22.46	9.75	0.000	0.057	0.961	0.990	0.9718	0.9718	0.9747	0.9747	0.9752	1.4567
1179	1.962	2.59	22.52	8.71	0.000	0.057	0.962	0.990	0.9688	0.9688	0.9718	0.9718	0.9723	1.4562
1180	1.969	2.59	19.95	7.69	0.005	0.058	0.960	0.988	0.9631	0.9631	0.9666	0.9666	0.9671	1.4566
1181	1.962	2.31	19.94	8.65	0.000	0.057	0.960	0.989	0.9674	0.9676	0.9708	0.9708	0.9714	1.4556
1182	1.963	1.99	19.90	9.58	0.000	0.058	0.961	0.992	0.9661	0.9661	0.9692	0.9692	0.9697	1.4521
1183	1.964	2.60	27.47	10.55	0.000	0.057	0.961	0.990	0.9762	0.9762	0.9787	0.9787	0.9791	1.4584
1184	1.962	2.00	19.97	9.97	0.000	0.058	0.960	0.989	0.9728	0.9728	0.9759	0.9759	0.9764	1.4585

ORIGINAL PAGE IS OF POOR QUALITY

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.393	4.3475	0.21871	0.43631	9.43200
37	7.7671	2.3978	0.12063	0.24064	0.53000
47	9.0966	2.8083	0.14128	0.28183	0.62900
52	9.2815	2.8653	0.14415	0.28756	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.671	3.2918	0.16510	0.32936	0.42200
67	15.671	4.8378	0.24338	0.48552	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	25.309	7.8133	0.39307	0.78414	0.56400
82	7.8971	2.4340	0.12249	0.24436	3.63500
92	3.4719	1.0718	0.053920	0.10756	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.8174	1.7959	0.090349	0.18024	0.62400
112	3.6569	1.1289	0.056795	0.11330	0.83000
122	2.1259	0.65631	0.033019	0.065867	0.96000
127	3.4419	1.0625	0.053454	0.10663	1.0900
137	3.4769	1.0733	0.053999	0.10772	1.2200
142	3.5249	1.0888	0.054775	0.10921	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.8174	1.7959	0.090349	0.18024	-1.0000
-112	3.6569	1.1289	0.056795	0.11330	-1.0000
-122	2.1259	0.65631	0.033019	0.065867	-1.0000
-127	3.4419	1.0625	0.053454	0.10663	-1.0000
-137	3.4769	1.0733	0.053599	0.10772	-1.0000
-142	3.5269	1.0888	0.054775	0.10927	-1.0000
-152	3.4519	1.0656	0.053609	0.10694	-1.0000
-157	3.4518	1.0656	0.053609	0.10694	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4518	1.0656	0.053609	0.10694	-1.0000
-157	3.4518	1.0656	0.053609	0.10694	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4519	1.0656	0.053609	0.10694	-1.0000
-172	3.4568	1.0641	0.053532	0.10679	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-187	3.3668	1.0394	0.052288	0.10431	-1.0000
-197	3.1365	0.96833	0.048714	0.097188	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

110

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	12.336	3.7687	0.18887	0.43565	0.43200
37	6.6864	2.0723	0.10441	0.24083	0.53300
47	7.9316	2.4272	0.12229	0.28268	0.62500
52	7.9966	2.4752	0.12471	0.28766	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	9.2115	2.8568	0.14386	0.33178	0.42200
67	15.608	4.8373	0.24373	0.56217	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	25.235	7.8209	0.39405	0.90891	0.56400
82	7.8566	2.4349	0.12268	0.28298	0.63500
52	3.4447	1.0676	0.053789	0.12407	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	5.7811	1.7917	0.090274	0.20822	0.62400
112	3.6746	1.1389	0.057344	0.13236	0.83000
122	2.1193	0.65652	0.033078	0.076298	0.96000
127	3.4197	1.0598	0.053349	0.12317	1.0900
137	3.1744	0.98382	0.049570	0.11434	1.2200
142	3.0143	0.93574	0.047147	0.10875	1.3500

>ADDITIONAL PRESSURE RATIOS , TAILPIPE INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	5.7811	1.7917	0.090274	0.20822	-1.0000
-112	3.6746	1.1389	0.057344	0.13236	-1.0000
-122	2.1193	0.65652	0.033078	0.076298	-1.3000
-127	3.4197	1.0598	0.053349	0.12317	-1.0000
-137	3.1744	0.98382	0.049570	0.11434	-1.0000
-142	3.0143	0.93574	0.047147	0.10875	-1.0000
-152	3.4247	1.0614	0.053477	0.12335	-1.0000
-157	3.4287	1.0629	0.053555	0.12353	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	3.4247	1.0614	0.053477	0.12335	-1.0000
-157	3.4287	1.0629	0.053555	0.12353	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-167	3.4287	1.0629	0.053555	0.12353	-1.0000
-172	3.4287	1.0629	0.053555	0.12353	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-182	3.3696	1.0381	0.052305	0.12064	-1.0000
-197	3.1244	0.96831	0.048789	0.11253	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	10.434	3.3408	2.16759	0.43447	0.43200
37	5.9728	1.8469	0.302645	0.24020	1.53000
47	6.6932	2.1674	0.10847	0.28124	0.62900
52	7.1632	2.2088	0.11090	0.29727	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	8.2286	2.5444	0.12763	0.33092	0.42200
67	15.542	4.8057	0.24107	0.62502	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	25.405	7.8557	0.39407	1.0217	0.56400
82	7.8985	2.4423	0.12252	0.31765	0.63500
92	3.4558	1.0686	0.053603	0.13900	1.04200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.8427	1.8067	0.090627	0.23497	0.62400
112	3.7010	1.1444	0.057407	0.14886	0.83000
122	2.1342	0.65992	0.033104	0.085828	0.96000
127	3.4257	1.0593	0.053137	0.13777	1.0400
137	3.0453	0.94166	0.047236	0.12247	1.2200
142	2.7400	0.84724	0.042500	0.11019	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.8427	1.8067	0.090627	0.23497	-1.0000
-112	3.7010	1.1444	0.057407	0.14886	-1.0000
-122	2.1342	0.65992	0.033104	0.085828	-1.0000
-127	3.4257	1.0593	0.053137	0.13777	-1.0000
-137	3.0453	0.94166	0.047236	0.12247	-1.0000
-142	2.7400	0.84724	0.042500	0.11019	-1.0000
-152	3.4407	1.0639	0.053371	0.13837	-1.0000
-157	3.4407	1.0639	0.053370	0.13837	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4407	1.0639	0.053370	0.13837	-1.0000
-157	3.4407	1.0639	0.053370	0.13837	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4407	1.0639	0.053370	0.13837	-1.0000
-172	3.4407	1.0639	0.053370	0.13837	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3707	1.0423	0.052283	0.13555	-1.0000
-187	2.1404	0.97107	0.048712	0.12629	-1.0000

>ADDITIONS , MEASURED THRUST PARAMETERS

112

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.753	4.8552	0.21704	0.43672	0.43200
37	8.6793	2.4750	0.11958	0.24062	0.53000
47	10.154	3.1297	0.13991	0.28151	0.62900
52	10.369	3.1959	0.14287	0.28747	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.904	3.6690	0.16402	0.33002	0.42200
67	15.503	4.7782	0.21360	0.42979	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	28.442	8.7784	0.39242	0.78961	0.56400
82	8.8843	2.7382	0.12241	0.24630	0.63500
87	3.4734	1.0647	0.047821	0.096222	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.4634	1.9921	0.049052	0.17919	0.62400
112	4.1266	1.2718	0.056855	0.11440	0.83000
122	2.3945	0.73900	0.032951	0.066382	0.96000
127	3.4558	1.0651	0.047614	0.095806	1.0900
137	3.9963	1.2009	0.053683	0.10802	1.2200
142	3.9514	1.2178	0.054442	0.10954	1.3500

>ADDITIONAL PRESSURE RATIOS , CORE FLOW INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.4634	1.9921	0.049052	0.17919	-1.0000
-112	4.1266	1.2718	0.056855	0.11440	-1.0000
-122	2.3945	0.73900	0.032991	0.066382	-1.0000
-127	3.4558	1.0651	0.047614	0.095806	-1.0000
-137	3.9963	1.2009	0.053683	0.10802	-1.0000
-142	3.9514	1.2178	0.054442	0.10954	-1.0000
-152	3.4508	1.0636	0.047545	0.095667	-1.0000
-157	3.4558	1.0651	0.047614	0.095806	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4508	1.0636	0.047545	0.095667	-1.0000
-157	3.4558	1.0651	0.047614	0.095806	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4558	1.0651	0.047614	0.095806	-1.0000
-172	3.4558	1.0651	0.047614	0.095806	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.4359	1.0589	0.047339	0.095251	-1.0000
-187	3.2317	0.99569	0.044513	0.089561	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

113

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
22	13.942	4.2314	0.18896	0.43508	0.43200
37	7.6405	2.3356	0.10430	0.24070	0.53000
47	8.9413	2.7332	0.12206	0.28168	0.63500
52	9.1314	2.7913	0.12465	0.28767	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.492	3.2072	0.14322	0.33053	0.42700
67	15.457	4.7250	0.21100	0.48695	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	2C.740	8.7855	0.39233	0.90541	0.56400
82	8.9713	2.7424	0.12247	0.28262	0.63500
92	3.4861	1.0656	0.047587	0.10982	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.4996	1.9938	0.088598	0.20444	0.62400
112	4.1420	1.2561	0.056541	0.13049	0.83000
122	2.4093	0.73650	0.032889	0.075902	0.96000
127	3.4710	1.0610	0.047382	0.10935	1.0900
137	3.6263	1.1085	0.049501	0.11424	1.2200
142	3.4560	1.0565	0.047177	0.10888	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.4996	1.9938	0.088598	0.20444	-1.0000
-112	4.1420	1.2561	0.056541	0.13049	-1.0000
-122	2.4093	0.73650	0.032889	0.075902	-1.0000
-127	3.4710	1.0610	0.047382	0.10935	-1.0000
-137	3.6263	1.1085	0.049501	0.11424	-1.0000
-142	3.4560	1.0565	0.047177	0.10888	-1.0000
-152	3.4760	1.0626	0.047451	0.10951	-1.0000
-157	3.4760	1.0626	0.047451	0.10951	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4760	1.0626	0.047451	0.10951	-1.0000
-157	3.4760	1.0626	0.047451	0.10951	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4811	1.0641	0.047519	0.10966	-1.0000
-172	3.4760	1.0626	0.047451	0.10951	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.4360	1.0503	0.046904	0.10824	-1.0000
-187	3.3457	1.00217	0.044306	0.10225	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

114

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.422	3.7597	0.16861	0.43619	0.43200
37	6.8635	2.0823	0.093138	0.24094	0.53000
47	8.0391	2.4393	0.13911	0.29225	0.62900
52	8.1993	2.4879	0.11129	0.28788	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	9.4207	2.8586	0.12796	0.33076	0.42200
67	15.405	4.6744	0.20908	0.54987	2.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	28.932	8.7788	0.39266	1.0158	0.56400
82	9.0302	2.7401	0.12256	0.31705	0.63500
92	3.5167	1.0671	0.047728	0.12347	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.5320	1.9920	0.088653	0.22934	0.62400
112	4.1680	1.2647	0.056567	0.14634	0.83000
122	2.4393	0.74016	0.033106	0.085642	0.96000
127	3.4966	1.0610	0.047456	0.12276	1.0900
137	3.4966	1.0610	0.047456	0.12276	1.2200
142	3.1408	0.95304	0.042627	0.11027	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.5320	1.9920	0.088653	0.22934	-1.0000
-112	4.1680	1.2647	0.056567	0.14634	-1.0000
-122	2.4393	0.74016	0.033106	0.085642	-1.0000
-127	3.4966	1.0610	0.047456	0.12276	-1.0000
-137	3.4966	1.0610	0.047456	0.12276	-1.0000
-142	3.1408	0.95304	0.042627	0.11027	-1.0000
-152	3.5066	1.0640	0.047592	0.12312	-1.0000
-157	3.5066	1.0640	0.047592	0.12312	-1.0005

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5066	1.0640	0.047592	0.12312	-1.0000
-157	3.5066	1.0640	0.047592	0.12312	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5016	1.0625	0.047524	0.12294	-1.0000
-172	3.5016	1.0625	0.047524	0.12294	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.4764	1.0549	0.047184	0.12206	-1.0000
-187	3.2912	0.99865	0.044668	0.11555	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

115

NASA-LEWIS   PRELIMINARY DATA   06/11/79   CFDDELL   FEC 10/17/79 02:07:05.052   FAC RX6X1   PGM C934   PRG 1161

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	17.845	5.3977	0.21789	0.43713	0.43200
37	5.8137	2.9684	0.11977	0.24039	0.53000
47	11.489	3.4749	0.14021	0.28142	0.62500
52	11.743	3.5520	0.14333	0.28766	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.503	4.0842	0.16480	0.33076	0.42700
67	15.352	4.6435	0.18737	0.37605	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	31.935	9.6592	0.38975	0.78225	0.56400
82	10.019	3.0304	0.12229	0.24541	0.63500
92	3.5350	1.0695	0.043154	0.086613	0.65200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	7.1483	2.1622	0.087244	0.17510	0.62400
112	4.6769	1.4146	0.057081	0.11456	0.83000
122	2.6959	0.81664	0.032952	0.066136	0.96000
127	3.5159	1.0634	0.042910	0.086122	1.0900
137	4.4117	1.3344	0.053844	0.10807	1.2200
142	4.4717	1.3526	0.054577	0.10954	1.3500

>ADDITIONAL PRESSURE RATIOS , PRIMARY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.1483	2.1622	0.087244	0.17510	-1.0000
-112	4.6769	1.4146	0.057081	0.11456	-1.0000
-122	2.6999	0.81664	0.032952	0.066136	-1.0000
-127	3.5159	1.0634	0.042910	0.086122	-1.0000
-137	4.4117	1.3344	0.053844	0.10807	-1.0000
-142	4.4717	1.3526	0.054577	0.10954	-1.0000
-152	3.5159	1.0634	0.042910	0.086122	-1.0000
-157	3.5159	1.0634	0.042910	0.086122	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5159	1.0634	0.042910	0.086122	-1.0000
-157	3.5159	1.0634	0.042910	0.086122	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5159	1.0634	0.042910	0.086122	-1.0000
-172	3.5159	1.0634	0.042910	0.086122	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.6510	1.1043	0.044559	0.089432	-1.0000
-187	3.5008	1.0599	0.042727	0.085754	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.407	4.6532	0.18721	0.43533	0.43200
37	8.4962	2.5660	0.10323	0.24006	0.53000
47	9.9519	3.0056	0.12002	0.28119	0.63500
52	10.152	3.3660	0.12335	0.28684	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.647	3.5176	0.14152	0.32909	0.42200
67	15.327	4.6290	0.18624	0.43307	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.062	9.6831	0.38957	0.90590	0.56400
82	10.077	3.0434	0.12244	0.28472	0.63500
92	3.5213	1.0635	0.042786	0.099493	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	7.1803	2.1686	0.087245	0.20288	0.62400
112	4.7079	1.4218	0.057203	0.13302	0.83000
122	2.7100	0.81846	0.032928	0.076571	0.96000
127	3.5063	1.0589	0.042603	0.099068	1.0900
137	4.0871	1.2364	0.049660	0.11548	1.2200
142	3.8568	1.1648	0.046862	0.10897	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.1803	2.1686	0.087245	0.20288	-1.0000
-112	4.7079	1.4218	0.057203	0.13302	-1.0000
-122	2.7100	0.81846	0.032928	0.076571	-1.0000
-127	3.5063	1.0589	0.042603	0.099068	-1.0000
-137	4.0871	1.2364	0.049660	0.11548	-1.0000
-142	3.8568	1.1648	0.046862	0.10897	-1.0000
-152	3.5063	1.0589	0.042603	0.099068	-1.0000
-157	3.5113	1.0605	0.042664	0.099210	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5063	1.0589	0.042603	0.099068	-1.0000
-157	3.5113	1.0605	0.042664	0.099210	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SIDEWALL LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5113	1.0605	0.042664	0.099210	-1.0000
-172	3.5013	1.0574	0.042547	0.098927	-1.0000

>ADDITIONAL PRESSURE RATIOS , 90 DEG SIDEWALL LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.6345	1.0983	0.044195	0.10275	-1.0000
-187	3.4762	1.0505	0.042238	0.098219	-1.0000

>OPTIONS , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.747	4.1816	0.16821	0.43624	0.43200
37	7.5906	2.3089	0.092874	0.24087	0.53000
47	8.9764	2.7000	0.10861	0.28167	0.62900
52	9.0615	2.7563	0.11087	0.28754	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.397	3.1625	0.12721	0.32992	0.42200
67	15.267	4.6439	0.18681	0.48467	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	31.822	9.6793	0.38936	1.0098	0.56400
82	9.9919	3.0393	0.12226	0.31707	0.63500
92	3.5113	1.0680	0.042963	0.11142	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	7.1503	2.1749	0.087489	0.22690	0.62400
112	4.7329	1.4396	0.057910	0.15019	0.83030
122	2.6900	0.81822	0.032914	0.085360	0.96000
127	3.4912	1.0619	0.042718	0.11079	1.0500
132	3.8768	1.1792	0.047435	0.12302	1.2200
142	3.4812	1.0589	0.042595	0.11047	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.1503	2.1749	0.087489	0.22690	-1.0000
-112	4.7329	1.4396	0.057910	0.15019	-1.0000
-122	2.6900	0.81822	0.032914	0.085360	-1.0000
-127	3.4912	1.0619	0.042718	0.11079	-1.0000
-132	3.8768	1.1792	0.047435	0.12302	-1.0000
-142	3.4812	1.0589	0.042595	0.11047	-1.0000
-152	3.4963	1.0635	0.042779	0.11094	-1.0000
-157	3.5013	1.0650	0.042840	0.11110	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4963	1.0635	0.042779	0.11094	-1.0000
-157	3.5013	1.0650	0.042840	0.11110	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5013	1.0650	0.042840	0.11110	-1.0000
-172	3.5013	1.0650	0.042840	0.11110	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.6365	1.1061	0.044494	0.11539	-1.0000
-187	3.4912	1.0619	0.042718	0.11079	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	16.980	5.1543	0.18756	0.43662	0.43230
37	9.341	2.8357	0.10319	0.24021	0.53000
47	10.943	3.3219	0.12098	0.28139	0.62000
52	11.169	3.3901	0.12336	0.28717	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.834	3.8958	0.14176	0.33001	0.42200
67	15.205	4.6154	0.16795	0.39097	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	34.904	10.595	0.38555	0.89752	0.56400
82	11.063	3.3582	0.12220	0.28447	0.63500
92	3.5144	1.0668	0.038820	0.090368	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	7.7954	2.3663	0.086109	0.20045	0.62400
112	5.1771	1.5715	0.057186	0.13312	0.83000
122	2.9834	0.90561	0.032954	0.076714	0.96000
127	3.5044	1.0638	0.038709	0.090111	1.0900
137	4.4961	1.3648	0.049663	0.11561	1.2200
142	4.2507	1.2903	0.046953	0.10930	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.7954	2.3663	0.086109	0.20045	-1.0000
-112	5.1771	1.5715	0.057186	0.13312	-1.0000
-122	2.9834	0.90561	0.032954	0.076714	-1.0000
-127	3.5044	1.0638	0.038709	0.090111	-1.0000
-137	4.4961	1.3648	0.049663	0.11561	-1.0000
-142	4.2507	1.2903	0.046953	0.10930	-1.0000
-152	3.5094	1.0653	0.038764	0.090240	-1.0000
-157	3.5144	1.0668	0.038820	0.090368	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5094	1.0653	0.038764	0.090240	-1.0000
-157	3.5144	1.0668	0.038820	0.090368	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5094	1.0653	0.038764	0.090240	-1.0000
-172	3.5044	1.0638	0.038709	0.090111	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.8500	1.1687	0.042527	0.098998	-1.0000
-187	3.7468	1.1383	0.041420	0.096422	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

120

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.344	4.6290	0.16772	0.43414	0.43200
37	8.4553	2.5512	0.092456	0.24033	0.53000
47	5.9102	2.9903	0.10837	0.28169	0.62900
52	10.133	3.0477	0.11045	0.28709	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.600	3.5003	0.12685	0.32973	0.42200
67	15.149	4.5711	0.16566	0.43060	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	35.260	10.646	0.38579	1.0028	0.56400
82	11.185	3.3751	0.12231	0.31793	0.63500
87	3.5417	1.0687	0.038729	0.10067	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	7.8398	2.3656	0.085729	0.22284	0.62400
112	5.1983	1.5686	0.056844	0.14776	0.83000
122	3.0211	0.91160	0.033036	0.085874	0.96000
127	3.5217	1.0627	0.038513	0.10015	1.0900
137	4.3376	1.3088	0.047432	0.12329	1.2200
142	3.8921	1.1744	0.042561	0.11063	1.3500

>ADDITIONAL PRESSURE RATIOS , PRIMARY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.8398	2.3656	0.085729	0.22284	-1.0000
-112	5.1983	1.5686	0.056844	0.14776	-1.0000
-122	3.0211	0.91160	0.033036	0.085874	-1.0000
-127	3.5217	1.0627	0.038513	0.10010	-1.0000
-137	4.3376	1.3088	0.047432	0.12329	-1.0000
-142	3.8921	1.1744	0.042561	0.11063	-1.0000
-152	3.5317	1.0657	0.038620	0.10039	-1.0000
-157	3.5317	1.0657	0.038620	0.10039	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5317	1.0657	0.038620	0.10039	-1.0000
-157	3.5317	1.0657	0.038620	0.10039	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5317	1.0657	0.038620	0.10039	-1.0000
-172	3.5317	1.0657	0.038620	0.10039	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.8471	1.1608	0.042068	0.10935	-1.0000
-187	3.7362	1.1276	0.040864	0.10622	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/11/79   CADDEII   REC 10/17/75 02:14:52.100   FAC 9X651   PGM C034   PPG 1167

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	18.627	5.6531	0.18897	0.43604	0.43200
37	10.257	3.1108	0.10359	0.23905	0.53000
47	12.025	3.6434	0.12179	0.28103	0.62900
52	12.265	3.7223	0.12443	0.28711	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.139	4.2912	0.14344	0.33009	0.42200
67	15.079	4.5763	0.15298	0.35299	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	37.653	11.427	0.38200	0.88144	0.56400
82	12.060	3.6601	0.12235	0.28231	0.63500
92	3.5165	1.0672	0.035675	0.082319	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	8.3798	2.5432	0.085014	0.19617	0.62400
112	5.6285	1.7082	0.057102	0.13176	0.83000
122	3.2512	0.98671	0.032984	0.076108	0.96000
127	3.5165	1.0672	0.035675	0.082319	1.0500
137	4.9329	1.4971	0.050045	0.11548	1.2200
142	4.6727	1.4181	0.047405	0.10938	1.3500

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	8.3798	2.5432	0.085014	0.19617	-1.0000
-112	5.6285	1.7082	0.057102	0.13176	-1.0000
-122	3.2512	0.98671	0.032984	0.076108	-1.0000
-127	3.5165	1.0672	0.035675	0.082319	-1.0000
-137	4.9329	1.4971	0.050045	0.11548	-1.0000
-142	4.6727	1.4181	0.047405	0.10938	-1.0000
-152	3.5065	1.0642	0.035574	0.082085	-1.0000
-157	3.5065	1.0642	0.035574	0.082085	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5065	1.0642	0.035574	0.082085	-1.0000
-157	3.5065	1.0642	0.035574	0.082085	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5065	1.0642	0.035574	0.082085	-1.0000
-172	3.5065	1.0642	0.035574	0.082085	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	4.0921	1.2389	0.041414	0.095560	-1.0000
-187	3.9970	1.2131	0.040553	0.093568	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/11/79   CADDFIT   PFC 10/17/79 02:15:51.951   FAC 9X6X1   PG° C034   RDG 1168

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	16.591	5.0294	0.16763	0.43565	0.43200
37	9.1396	2.7703	0.092333	0.24013	0.53000
47	10.699	3.2432	0.10800	0.28112	0.62900
52	10.928	3.3129	0.11042	0.28716	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.488	3.7957	0.12617	0.32814	0.42200
67	15.067	4.5674	0.15223	0.39590	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	37.669	11.419	0.38060	0.98980	0.56400
82	12.073	3.6599	0.12198	0.31724	0.63500
92	3.5147	1.0657	0.035521	0.092378	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	8.4135	2.5505	0.085007	0.22107	0.62400
112	5.6624	1.7165	0.057211	0.14879	0.83000
122	3.2604	0.98836	0.032942	0.085670	0.96000
127	3.5006	1.0612	0.035369	0.091983	1.0900
137	4.7019	1.4253	0.047505	0.12354	1.2200
142	4.2163	1.2781	0.042603	0.11079	1.3500

>ADDITIONAL PRESSURE RATIOS , SHROUD INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	8.4135	2.5505	0.085007	0.22107	-1.0000
-112	5.6624	1.7165	0.057211	0.14879	-1.0000
-122	3.2604	0.98836	0.032942	0.085670	-1.0000
-127	3.5006	1.0612	0.035369	0.091983	-1.0000
-137	4.7019	1.4253	0.047505	0.12354	-1.0000
-142	4.2163	1.2781	0.042603	0.11079	-1.0000
-152	3.5006	1.0612	0.035369	0.091983	-1.0000
-157	3.5056	1.0627	0.035420	0.092115	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5006	1.0612	0.035369	0.091983	-1.0000
-157	3.5056	1.0627	0.035420	0.092115	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5056	1.0627	0.035420	0.092115	-1.0000
-172	3.5056	1.0627	0.035420	0.092115	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	4.0762	1.2357	0.041185	0.10711	-1.0000
-187	3.9711	1.2038	0.040123	0.10435	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

123

>ADDITIONAL PRESSURE RATIOS . PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	16.517	5.0189	0.16751	0.43712	0.43200
37	9.3956	2.7607	0.092139	0.24345	0.53000
47	10.641	3.2335	0.10792	0.28162	3.62900
52	10.961	3.3304	0.11015	0.28745	0.72700

>ADDITIONAL PRESSURE RATIOS . FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.367	3.7578	0.12542	0.32729	0.42200
67	15.217	4.5632	0.15229	0.39743	0.69200

>ADDITIONAL PRESSURE RATIOS . FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	37.517	11.400	0.38047	0.95288	0.56400
82	12.037	3.6575	0.12207	0.31855	0.63500
92	3.5095	1.0664	0.035551	0.092877	0.69200

>ADDITIONAL PRESSURE RATIOS . EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	8.3651	2.5418	0.084833	0.22128	0.62400
112	5.6825	1.7267	0.057624	0.15039	0.83000
122	3.2491	0.98726	0.032951	0.085985	0.96000
127	3.5045	1.0649	0.035540	0.092745	1.0900
137	4.6712	1.4194	0.047372	0.12362	1.2200
142	4.1955	1.2718	0.042447	0.11077	1.3500

>ADDITIONAL PRESSURE RATIOS . COREFLOW INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	8.3651	2.5418	0.084833	0.22128	-1.0000
-112	5.6825	1.7267	0.057624	0.15039	-1.0000
-122	3.2491	0.98726	0.032950	0.085985	-1.0000
-127	3.5045	1.0649	0.035540	0.092745	-1.0000
-137	4.6712	1.4194	0.047372	0.12362	-1.0000
-142	4.1955	1.2718	0.042447	0.11077	-1.0000
-152	3.5045	1.0649	0.035540	0.092745	-1.0000
-157	3.4995	1.0633	0.035489	0.092612	-1.0000

>ADDITIONAL PRESSURE RATIOS . FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5045	1.0649	0.035540	0.092745	-1.0000
-157	3.4995	1.0633	0.035489	0.092612	-1.0000

>ADDITIONAL PRESSURE RATIOS . 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.4995	1.0633	0.035489	0.092612	-1.0000
-172	3.4995	1.0633	0.035489	0.092612	-1.0000

>ADDITIONAL PRESSURE RATIOS . 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	4.0954	1.2414	0.041631	0.10812	-1.0000
-187	3.9952	1.2109	0.040615	0.10547	-1.0000

>OPTION 5 . MEASURED THRUST PARAMETERS

124

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	19.535	5.6234	0.18760	0.43525	0.43200
37	19.174	3.9916	0.19315	0.23031	0.53000
47	11.918	3.6214	0.12082	0.28032	0.62500
52	12.188	3.7934	0.12356	0.28666	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.991	4.2513	0.14184	0.32507	0.42200
67	14.973	4.5687	0.15176	0.35210	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	37.402	11.392	0.39009	0.88184	0.56400
82	12.738	3.6578	0.12204	0.28314	0.63500
92	3.5156	1.0683	0.035642	0.082691	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	8.3903	2.5495	0.085061	0.19735	0.62400
112	5.7160	1.7369	0.057949	0.13445	0.83000
122	3.2605	0.99075	0.033055	0.076690	0.96000
127	3.5056	1.0652	0.035540	0.082455	1.0500
137	4.9210	1.4953	0.049889	0.11575	1.2200
142	4.6560	1.4148	0.047203	0.10951	1.3500

>ADDITIONAL PRESSURE RATIOS , CADDELL INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	8.3903	2.5495	0.085061	0.19735	-1.0000
-112	5.7160	1.7369	0.057949	0.13445	-1.0000
-122	3.2605	0.99075	0.033055	0.076690	-1.0000
-127	3.5056	1.0652	0.035540	0.082455	-1.0000
-137	4.9210	1.4953	0.049889	0.11575	-1.0000
-142	4.6560	1.4148	0.047203	0.10951	-1.0000
-152	3.4956	1.0622	0.035430	0.082220	-1.0000
-157	3.4956	1.0622	0.035430	0.082220	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4956	1.0622	0.035430	0.082220	-1.0000
-157	3.4956	1.0622	0.035430	0.082220	-1.0000

>ADDITIONAL PRESSURE RATIOS , 30 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5009	1.0637	0.035490	0.082338	-1.0000
-172	3.4956	1.0622	0.035430	0.082220	-1.0000

>ADDITIONAL PRESSURE RATIOS , 60 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	4.1128	1.2491	0.041676	0.096690	-1.0000
-187	4.0258	1.2233	0.040814	0.094690	-1.0000

>OPTIONS , MEASURED THRUST PARAMETERS

125

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	19.405	5.8544	0.21309	0.43734	0.43200
37	10.670	3.2191	0.11717	0.24047	3.53003
47	12.512	3.7746	0.13733	0.28198	0.62900
52	12.772	3.8531	0.14025	0.28784	3.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.703	4.4358	0.16145	0.33136	0.42200
67	14.978	4.5188	0.16449	0.33757	3.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	34.909	10.502	0.38224	0.78449	0.56400
82	11.151	3.3640	0.12244	0.25130	0.63500
92	3.5345	1.0663	0.038812	0.079656	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	7.8018	2.3537	0.085671	0.17583	0.62400
112	5.1927	1.5666	0.057021	0.11703	0.83000
122	3.0033	0.90604	0.032979	0.067685	0.96000
127	3.5294	1.0648	0.038757	0.079543	1.0900
137	4.8070	1.4502	0.052785	0.10834	1.2200
142	4.9471	1.4623	0.053226	0.10924	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.8018	2.3537	0.085671	0.17583	-1.0000
-112	5.1927	1.5666	0.057021	0.11703	-1.0000
-122	3.0033	0.90604	0.032979	0.067685	-1.0000
-127	3.5294	1.0648	0.038757	0.079543	-1.0000
-137	4.8070	1.4502	0.052785	0.10834	-1.0000
-142	4.9471	1.4623	0.053226	0.10924	-1.0000
-152	3.5194	1.0618	0.038646	0.079317	-1.0000
-157	3.5244	1.0633	0.038702	0.079430	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5194	1.0618	0.038646	0.079317	-1.0000
-157	3.5244	1.0633	0.038702	0.079430	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD ROTATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5244	1.0633	0.038702	0.079430	-1.0000
-172	3.5244	1.0633	0.038702	0.079430	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD ROTATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.8952	1.1751	0.042773	0.087786	-1.0000
-192	3.7652	1.1358	0.041341	0.084950	-1.0030

>OPTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	17.195	5.1762	0.18770	0.43650	0.43200
37	9.4541	2.8476	0.10326	0.24013	0.53000
47	11.064	3.3324	0.12084	0.28102	0.62900
52	11.309	3.4062	0.12352	0.28724	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.698	3.9150	0.14107	0.33015	0.42200
67	14.942	4.5005	0.16320	0.37952	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	34.898	10.511	0.38117	0.88642	0.56400
82	11.174	3.3656	0.12704	0.28381	0.63500
92	3.5419	1.0668	0.038686	0.080966	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	7.8591	2.3672	0.085839	0.19962	0.62400
117	5.2182	1.5717	0.056994	0.13254	0.83000
122	3.0164	0.90856	0.032946	0.076618	0.96000
127	3.5269	1.0623	0.038522	0.089585	1.0400
137	4.5578	1.3728	0.049781	0.11577	1.2200
142	4.3026	1.2960	0.046994	0.10929	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.8591	2.3672	0.085839	0.19962	-1.0000
-117	5.2182	1.5717	0.056994	0.13254	-1.0000
-122	3.0164	0.90856	0.032946	0.076618	-1.0000
-127	3.5269	1.0623	0.038522	0.089585	-1.0000
-137	4.5578	1.3728	0.049781	0.11577	-1.0000
-142	4.3026	1.2960	0.046994	0.10929	-1.0000
-152	3.5269	1.0623	0.038522	0.089585	-1.0000
-157	3.5269	1.0623	0.038522	0.089585	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5269	1.0623	0.038522	0.089585	-1.0000
-157	3.5269	1.0623	0.038522	0.089585	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5269	1.0623	0.038522	0.089585	-1.0000
-172	3.5269	1.0623	0.038522	0.089585	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
-197	3.9623	1.1974	0.043059	0.10013	-1.0000
-192	3.8335	1.1513	0.041747	0.097083	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

127

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.171	4.6080	1.16747	0.43606	0.43200
37	8.3771	2.5430	0.092390	0.24065	0.53000
47	9.7823	2.9713	0.11794	0.28118	0.62900
52	9.3923	3.0351	.11026	0.28721	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.482	3.4876	0.12470	0.33004	0.42200
67	14.981	4.5200	0.16420	0.42773	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	34.540	10.491	0.38113	0.99281	0.56400
82	11.067	3.3616	0.12212	0.31811	0.63500
92	3.5141	1.0674	0.038776	0.10101	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	7.7670	2.3592	0.085703	0.22325	0.62400
112	5.1656	1.5690	0.056999	0.14848	0.83000
122	2.9985	0.90775	0.032976	0.085501	0.96000
127	3.4991	1.0628	0.038610	0.10058	1.0900
137	4.2949	1.3046	0.047391	0.12345	1.2200
142	3.9495	1.1693	0.042476	0.11065	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.7670	2.3592	0.085703	0.22325	-1.0000
-112	5.1656	1.5690	0.056599	0.14848	-1.0000
-122	2.9985	0.90775	0.032976	0.085901	-1.0000
-127	3.4991	1.0628	0.038610	0.10058	-1.0000
-137	4.2949	1.3046	0.047391	0.12345	-1.0000
-142	3.8495	1.1693	0.042476	0.11065	-1.0000
-152	3.5041	1.0644	0.038665	0.10072	-1.0000
-157	3.5041	1.0644	0.038665	0.10072	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5041	1.0644	0.038665	0.10072	-1.0000
-157	3.5041	1.0644	0.038665	0.10072	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5041	1.0644	0.038665	0.10072	-1.0000
-172	3.5041	1.0644	0.038665	0.10072	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.8845	1.1799	0.042863	0.11166	-1.0000
-187	3.7536	1.1404	0.041427	0.10791	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

128

NASA-LEWIS   PRELIMINARY DATA   06/11/79   CADDF11   PEC 10/17/79 02:24:48.260   FAC 9X6E1   PGM C034   PRG 1175

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
37	15.416	4.6832	0.18709	0.43526	0.43200
37	8.4840	2.5788	0.10302	0.23968	0.53000
47	9.9399	3.0197	0.12062	0.28061	0.62900
52	10.149	3.0830	0.12317	0.28654	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.653	3.5401	0.14143	0.32902	0.42200
67	14.752	4.4813	0.17903	0.41650	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	31.652	9.6152	0.38413	0.89366	0.56400
82	10.059	3.0557	0.12208	0.28400	0.63500
92	3.5117	1.0668	0.042619	0.099150	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	7.1988	2.1838	0.087244	0.20297	0.62400
112	4.6977	1.4240	0.056890	0.13235	0.83000
122	2.7109	0.82352	0.032900	0.076540	0.96000
127	3.4967	1.0622	0.042437	0.098726	1.0900
137	4.0822	1.2401	0.049543	0.11526	1.2200
142	3.8620	1.1732	0.046870	0.10904	1.3500

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.1988	2.1838	0.087244	0.20297	-1.0000
-112	4.6877	1.4240	0.056890	0.13235	-1.0000
-122	2.7109	0.82352	0.032900	0.076540	-1.0000
-127	3.4967	1.0622	0.042437	0.098726	-1.0000
-137	4.0822	1.2401	0.049543	0.11526	-1.0000
-142	3.8620	1.1732	0.046870	0.10904	-1.0000
-152	3.5017	1.0638	0.042497	0.098867	-1.0000
-157	3.5017	1.0638	0.042497	0.098867	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5017	1.0638	0.042497	0.098867	-1.0000
-157	3.5017	1.0638	0.042497	0.098867	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5017	1.0638	0.042497	0.098867	-1.0000
-172	3.5017	1.0638	0.042497	0.098867	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.7269	1.1322	0.045231	0.10523	-1.0000
-187	3.5218	1.0011	0.042591	0.10141	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

130

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVG WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.300	4.1265	0.16781	0.43514	0.43200
37	7.4651	2.3147	0.092559	0.23596	0.53000
47	8.9739	2.7090	0.13823	0.28082	0.62400
52	9.1671	2.7679	0.11069	0.28654	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVG WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.523	3.1772	0.12705	0.32938	0.42200
67	14.744	4.4516	0.17801	0.46149	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVG WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	31.770	9.5925	0.38350	0.99444	0.56400
82	10.099	3.0488	0.12192	0.31607	0.63500
82	3.5262	1.0647	0.042575	0.11037	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	7.2457	2.1877	0.087484	0.22680	0.62400
112	4.7079	1.4215	0.056843	0.14736	0.83000
122	2.7199	0.92123	0.032839	0.085135	0.96000
127	3.5012	1.0571	0.042272	0.10959	1.0900
137	3.9168	1.1826	0.047291	0.12260	1.2200
142	3.5162	1.0617	0.042454	0.11006	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVG WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.2457	2.1877	0.087484	0.22680	-1.0000
-112	4.7079	1.4215	0.056843	0.14736	-1.0000
-122	2.7199	0.92123	0.032839	0.085135	-1.0000
-127	3.5012	1.0571	0.042272	0.10959	-1.0000
-137	3.9168	1.1826	0.047291	0.12240	-1.0000
-142	3.5162	1.0617	0.042454	0.11006	-1.0000
-152	3.5112	1.0602	0.042393	0.10990	-1.0000
-157	3.5162	1.0617	0.042454	0.11006	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVG WORD	PI	PI/PO	PI/PTF	PL/PTP	X/DMAX
-152	3.5112	1.0602	0.042393	0.10990	-1.0000
-157	3.5162	1.0617	0.042454	0.11006	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVG WORD	PI	PL/PO	PI/PTF	PL/PTP	X/DMAX
-167	3.5162	1.0617	0.042454	0.11006	-1.0000
-172	3.5212	1.0632	0.042514	0.11022	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVG WORD	PI	PL/PO	PI/PTF	PL/PTP	X/DMAX
-192	3.7315	1.1267	0.045054	0.11680	-1.0000
-197	3.6065	1.0889	0.043542	0.11288	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

131

NASA-LEWIS   PRELIMINARY DATA   06/11/79   CADDEII   REC 10/17/79 02:26:04.413   FAC 9X6X1   PGM C034   PDG 1177

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	16.331	4.8860	0.21692	0.43718	0.43200
37	8.9220	2.6908	0.11946	0.24076	0.53000
47	10.442	3.1492	0.13981	0.28178	0.62900
52	10.657	3.2141	0.14269	0.28759	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.267	3.6996	0.16425	0.33103	0.42200
67	14.736	4.4443	0.19731	0.35766	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	28.776	8.6784	0.38578	0.77652	0.56400
82	9.1220	2.7511	0.12221	0.24616	0.63500
92	3.5433	1.0686	0.047441	0.095615	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.6160	1.9953	0.088583	0.17853	0.62400
112	4.2441	1.2800	0.056825	0.11453	0.83000
122	2.4618	0.74246	0.032962	0.066433	0.96000
127	3.5293	1.0641	0.047240	0.095210	1.0900
137	3.9988	1.2060	0.053541	0.10791	1.2200
142	4.0489	1.2211	0.054211	0.10926	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.6160	1.9953	0.088583	0.17853	-1.0000
-112	4.2441	1.2800	0.056825	0.11453	-1.0000
-122	2.4618	0.74246	0.032962	0.066433	-1.0000
-127	3.5293	1.0641	0.047240	0.095210	-1.0000
-137	3.9988	1.2060	0.053541	0.10791	-1.0000
-142	4.0489	1.2211	0.054211	0.10926	-1.0000
-152	3.5293	1.0641	0.047240	0.095210	-1.0000
-157	3.5293	1.0641	0.047240	0.095210	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5293	1.0641	0.047240	0.095210	-1.0000
-157	3.5293	1.0641	0.047240	0.095210	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5293	1.0641	0.047240	0.095210	-1.0000
-172	3.5293	1.0641	0.047240	0.095210	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.5733	1.0777	0.047844	0.096426	-1.0000
-187	3.4181	1.0309	0.045766	0.092238	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

132

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.119	4.2430	0.18891	0.43617	0.43200
37	7.7956	2.3428	0.10430	0.24083	0.53000
47	9.1267	2.7428	0.12211	0.28195	0.62900
52	9.3018	2.7954	0.12446	0.28736	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.708	3.2179	0.14327	0.33079	0.42200
67	14.684	4.4129	0.19647	0.45363	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	28.905	8.6868	0.38675	0.89298	0.56400
82	9.1567	2.7518	0.12252	0.28298	0.63500
92	3.5401	1.0639	0.047367	0.10937	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.5944	1.9818	0.098232	0.20372	0.62400
112	4.2563	1.2791	0.056949	0.13149	0.83300
122	2.4692	0.74175	0.033024	0.076250	0.96000
127	3.5251	1.0594	0.047165	0.10890	1.0900
137	3.7204	1.1181	0.049779	0.11494	1.2200
142	3.5301	1.0609	0.047232	0.10906	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.5944	1.9818	0.098232	0.20372	-1.0000
-112	4.2563	1.2791	0.056949	0.13149	-1.0000
-122	2.4682	0.74175	0.033024	0.076250	-1.0000
-127	3.5251	1.0594	0.047165	0.10890	-1.0000
-137	3.7204	1.1181	0.049779	0.11494	-1.0000
-142	3.5301	1.0609	0.047232	0.10906	-1.0000
-152	3.5301	1.0609	0.047232	0.10906	-1.0000
-157	3.5401	1.0639	0.047367	0.10937	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5301	1.0609	0.047232	0.10906	-1.0000
-157	3.5401	1.0639	0.047367	0.10937	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5351	1.0624	0.047303	0.10921	-1.0000
-172	3.5301	1.0609	0.047232	0.10906	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.5602	1.3699	0.047635	0.10998	-1.0000
-187	3.3598	1.3397	0.044954	0.10380	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD HORD	PI	PI /PO	PI /PTF	PI /PTP	X/DMAX
32	12.572	3.7890	0.16822	0.43525	0.43209
37	6.3467	2.0936	0.092949	0.24049	0.53000
47	8.1423	2.4539	0.13895	0.29188	0.62900
52	8.3023	2.5321	0.11109	0.28742	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD HORD	PI	PI /PO	PI /PTF	PI /PTP	X/DMAX
62	9.5226	2.8699	0.12741	0.32966	0.42200
67	14.612	4.4036	0.19551	0.50585	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD HORD	PI	PI /PO	PI /PTF	PI /PTP	X/DMAX
77	28.911	8.7130	0.38684	1.0009	0.56400
82	9.1575	2.7598	0.12253	0.31703	0.63500
92	3.5438	1.0680	0.047417	0.12268	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD HORD	PI	PI /PO	PI /PTF	PI /PTP	X/DMAX
107	6.6065	1.9910	0.088397	0.22871	0.62400
112	4.2546	1.2822	0.056928	0.14729	0.83000
122	2.4674	0.74362	0.033015	0.085420	0.96000
127	3.5198	1.0605	0.047082	0.12182	1.0900
137	3.5638	1.0680	0.047417	0.12268	1.2200
142	3.1884	0.96090	0.042662	0.11038	1.3500

>ADDITIONAL PRESSURE RATIOS , COREBOX INLET

AVD HORD	PI	PI /PO	PI /PTF	PI /PTP	X/DMAX
-107	6.6065	1.9910	0.088397	0.22871	-1.0000
-112	4.2546	1.2822	0.056928	0.14729	-1.0000
-122	2.4674	0.74362	0.033015	0.085420	-1.0000
-127	3.5198	1.0605	0.047082	0.12182	-1.0000
-137	3.5638	1.0680	0.047417	0.12268	-1.0000
-142	3.1884	0.96390	0.042662	0.11038	-1.0000
-152	3.5298	1.0635	0.047216	0.12216	-1.0000
-157	3.5298	1.0635	0.047216	0.12216	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD HORD	PI	PI /PO	PI /PTF	PI /PTP	X/DMAX
-152	3.5298	1.0635	0.047216	0.12216	-1.0000
-157	3.5298	1.0635	0.047216	0.12216	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD HORD	PI	PI /PO	PI /PTF	PI /PTP	X/DMAX
-167	3.5298	1.0635	0.047216	0.12216	-1.0000
-172	3.5298	1.0635	0.047216	0.12216	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD HORD	PI	PI /PO	PI /PTF	PI /PTP	X/DMAX
-182	3.5639	1.0741	0.047685	0.12338	-1.0000
-187	3.3686	1.0152	0.045073	0.11662	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	11.044	3.3508	0.16797	0.43557	0.43200
37	6.1389	1.8535	0.092913	0.24094	0.53030
47	7.1503	2.1694	0.10875	0.28201	0.62900
52	7.3005	2.2150	0.11104	0.28793	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	8.4368	2.5597	0.12832	0.33274	0.42200
67	14.526	4.4071	0.22093	0.57289	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	25.678	7.7904	0.39055	1.0128	0.56400
82	8.0563	2.4443	0.12253	0.31774	0.63500
92	3.5198	1.0679	0.053531	0.13881	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	5.9237	1.7972	0.090095	0.23363	0.62400
112	3.7350	1.1332	0.056808	0.14731	0.83000
122	2.1718	0.65894	0.033032	0.085657	0.56900
127	3.4466	1.0577	0.05299A	0.13741	1.0900
137	3.1098	0.94322	0.047283	0.12261	1.2200
142	2.7932	0.84745	0.042482	0.11016	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	5.9237	1.7972	0.090095	0.23363	-1.0000
-112	3.7350	1.1332	0.056808	0.14731	-1.0000
-122	2.1718	0.65894	0.033032	0.085657	-1.0000
-127	3.4466	1.0577	0.05296A	0.13741	-1.0000
-137	3.1098	0.94322	0.047283	0.12261	-1.0000
-142	2.7932	0.84745	0.042482	0.11016	-1.0000
-152	3.5046	1.0633	0.052303	0.13822	-1.0000
-157	3.5046	1.0633	0.053303	0.13822	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	3.5046	1.0633	0.053303	0.13822	-1.0000
-157	3.5046	1.0633	0.053303	0.13822	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-147	3.5096	1.0648	0.053379	0.13842	-1.0000
-172	3.5046	1.0633	0.053303	0.13822	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-182	3.4345	1.0420	0.052236	0.13545	-1.0000
-187	3.2240	0.97818	0.049026	0.12716	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
22	12.442	3.7747	0.19028	0.43847	0.43200
27	6.8702	2.0843	0.10450	0.24101	0.53000
47	8.0459	2.4410	0.12239	0.28225	0.62900
52	8.2359	2.4896	0.12482	0.28787	0.72740

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	9.4564	2.8690	0.14385	0.33174	0.42200
67	14.462	4.3874	0.21598	0.50732	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	25.673	7.7888	0.39052	0.90062	0.56400
82	8.0509	2.4425	0.12247	0.28243	0.63500
92	3.5218	1.0685	0.053571	0.12355	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.9144	1.7944	0.089967	0.20748	0.62400
112	3.7321	1.1323	0.056770	0.13092	0.83000
122	2.1749	0.65980	0.033081	0.076292	0.96000
127	3.4967	1.0609	0.053190	0.12267	1.0900
132	3.2614	0.98947	0.049611	0.11441	1.2200
142	3.1062	0.94239	0.047250	0.10897	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.9144	1.7944	0.089967	0.20748	-1.0000
-112	3.7321	1.1323	0.056770	0.13092	-1.0000
-122	2.1749	0.65980	0.033081	0.076292	-1.0000
-127	3.4967	1.0609	0.053190	0.12267	-1.0000
-132	3.2614	0.98947	0.049611	0.11441	-1.0000
-142	3.1062	0.94238	0.047250	0.10897	-1.0000
-152	3.5018	1.0624	0.053267	0.12284	-1.0000
-157	3.5118	1.0654	0.053419	0.12319	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5018	1.0624	0.053267	0.12284	-1.0000
-157	3.5118	1.0654	0.053419	0.12319	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5018	1.0639	0.053343	0.12302	-1.0000
-172	3.5118	1.0654	0.053419	0.12319	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.4417	1.0442	0.052353	0.12074	-1.0000
-187	3.2314	0.99036	0.049154	0.11336	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.317	4.3470	0.21869	0.43536	0.43200
37	7.9909	2.3963	0.12040	0.23991	0.53000
47	9.2496	2.9390	0.14115	0.28127	0.62900
52	9.4346	2.9452	0.14297	0.28685	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.909	3.3130	0.16647	0.33173	0.42200
67	14.432	4.3737	0.21977	0.43794	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	25.627	7.7827	0.39107	0.77927	0.56400
82	8.0248	2.4370	0.12246	0.24402	0.63500
92	3.5132	1.0569	0.053611	0.10683	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	5.8945	1.7901	0.089950	0.17924	0.62400
112	3.7133	1.1277	0.056666	0.11292	0.83000
122	2.1619	0.65655	0.032991	0.065740	0.96000
127	3.4892	1.0593	0.053230	0.10607	1.0000
137	3.5432	1.0760	0.054069	0.10774	1.2200
142	3.5832	1.0882	0.054680	0.10896	1.3500

>ADDITIONAL PRESSURE RATIOS , FORFARING INLFT

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	5.8945	1.7901	0.089950	0.17924	-1.0000
-112	3.7133	1.1277	0.056666	0.11292	-1.0000
-122	2.1619	0.65655	0.032991	0.065740	-1.0000
-127	3.4892	1.0593	0.053230	0.10607	-1.0000
-137	3.5432	1.0760	0.054069	0.10774	-1.0000
-142	3.5832	1.0882	0.054680	0.10896	-1.0000
-152	3.4932	1.0608	0.053396	0.10622	-1.0000
-157	3.4992	1.0624	0.053382	0.10637	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.4932	1.0608	0.053396	0.10622	-1.0000
-157	3.4992	1.0624	0.053382	0.10637	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD ROTATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5032	1.0639	0.053459	0.10653	-1.0000
-172	3.4992	1.0624	0.053382	0.10637	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD ROTATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-192	3.4371	1.0424	0.052390	0.10440	-1.0000
-197	3.2179	0.97725	0.049134	0.097852	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

Run 19

NASA-LEWIS PRELIMINARY DATA CADDE-II FACILITY   8X6X1   PROGRAM C034 RDGS   1185 TO 1235
TIME AND DATE PROCESSED 19:57:50 JUN 28 1974

NOZZLE TYPE	P+W EJECTOR NOZZLE (MODEL A)
FLIGHT CONDITIONS	SUPER SONIC CRUISE (MS=.04 W?)
NOZZLE CONFIGURATION	A1
PRIMARY-NOZZLE PLUG	SPLIT PLUG (RETRACTED)
FLOW SPLITTER	CONICAL SPLITTER
FAN NOZZLE	THIS
CLAMSHELL POSITION	
EJECTOR INLET OPENING	

RDG	ND	PTF/PTP	PTF/PO	PTP/PO	OMEGA	PTS/PTF	CDF	CDP	CF1	ETA1	ETA1.INT	CFP1	CFP2	F9
1185	1.957	2.30	20.26	0.00	0.000	0.120	1.024	0.987	0.9702	0.9702	0.9733	0.9733	0.9730	1.5004
1186	1.957	2.31	22.31	9.65	0.000	0.120	1.027	0.987	0.9715	0.9715	0.9742	0.9742	0.9747	1.5005
1187	1.956	2.32	24.79	10.67	0.000	0.119	1.030	0.992	0.9697	0.9697	0.9721	0.9721	0.9728	1.5072
1188	1.948	2.33	27.38	11.72	0.000	0.119	1.029	0.990	0.9784	0.9784	0.9786	0.9786	0.9790	1.5101
1189	1.955	2.32	29.15	12.58	0.000	0.118	1.026	0.989	0.9771	0.9771	0.9792	0.9792	0.9796	1.5103
1190	1.956	2.32	28.97	12.51	0.000	0.119	1.031	0.991	0.9732	0.9732	0.9752	0.9752	0.9757	1.5096
1191	1.956	2.33	27.53	11.84	0.000	0.119	1.025	0.990	0.9760	0.9760	0.9782	0.9782	0.9786	1.5094
1192	1.958	2.33	29.02	10.74	0.000	0.120	1.028	0.990	0.9731	0.9731	0.9758	0.9758	0.9780	1.5096
1193	1.957	2.30	22.06	9.60	0.000	0.120	1.024	0.988	0.9730	0.9730	0.9758	0.9758	0.9763	1.5003
1194	1.950	2.30	19.50	8.50	0.000	0.121	1.039	0.988	0.9598	0.9598	0.9630	0.9630	0.9635	1.5093
1195	1.956	2.30	19.53	8.49	0.000	0.120	1.026	0.990	0.9696	0.9696	0.9728	0.9728	0.9733	1.5127
1196	1.958	2.31	22.20	9.63	0.000	0.120	1.026	0.990	0.9729	0.9729	0.9753	0.9753	0.9758	1.5193
1197	1.956	2.32	24.86	10.69	0.000	0.120	1.026	0.989	0.9792	0.9797	0.9821	0.9821	0.9826	1.5161
1198	1.958	2.32	27.89	11.80	0.000	0.120	1.023	0.989	0.9821	0.9821	0.9843	0.9843	0.9847	1.5175
1199	1.958	2.33	29.01	12.47	0.000	0.120	1.027	0.990	0.9796	0.9796	0.9817	0.9817	0.9821	1.5157
1200	1.958	2.31	29.28	12.66	0.000	0.120	1.028	0.991	0.9782	0.9782	0.9803	0.9803	0.9807	1.5130
1201	1.957	2.32	27.65	11.92	0.000	0.120	1.026	0.989	0.9800	0.9800	0.9829	0.9829	0.9834	1.5159
1202	1.958	2.32	24.97	10.77	0.000	0.120	1.028	0.989	0.9801	0.9801	0.9829	0.9829	0.9830	1.5166
1203	1.958	2.31	22.22	9.62	0.000	0.120	1.026	0.989	0.9749	0.9749	0.9777	0.9777	0.9782	1.5136
1204	1.956	2.30	19.30	8.36	0.000	0.121	1.028	0.990	0.9700	0.9706	0.9738	0.9738	0.9745	1.5158
1205	1.958	1.99	19.84	9.96	0.037	0.287	0.961	0.990	1.0114	0.9804	0.9835	1.0145	1.0150	1.5003
1206	1.958	2.29	19.76	8.61	0.039	0.287	0.961	0.992	1.0069	0.9736	0.9769	1.0098	1.0103	1.5001
1207	1.958	2.60	19.96	7.69	0.041	0.287	0.958	0.987	1.0147	0.9797	0.9831	1.0181	1.0186	1.5178
1208	1.957	2.00	22.34	11.15	0.037	0.287	0.961	0.989	1.0160	0.9849	0.9872	1.0187	1.0192	1.5110
1209	1.958	2.31	22.48	9.72	0.039	0.287	0.960	0.989	1.0156	0.9820	0.9848	1.0185	1.0190	1.5123
1210	1.958	2.59	22.51	8.62	0.041	0.287	0.961	0.989	1.0172	0.9818	0.9849	1.0201	1.0206	1.5109
1211	1.957	1.99	24.83	12.46	0.037	0.287	0.961	0.990	1.0157	0.9840	0.9864	1.0181	1.0185	1.5089
1212	1.958	2.32	24.98	10.72	0.039	0.287	0.962	0.989	1.0170	0.9835	0.9861	1.0201	1.0206	1.5130
1213	1.957	2.59	24.81	9.59	0.041	0.287	0.560	0.989	1.0205	0.9848	0.9875	1.0232	1.0236	1.5177
1214	1.955	2.00	27.45	13.20	0.037	0.287	0.962	0.993	1.0159	0.9834	0.9856	1.0181	1.0186	1.5102
1215	1.958	2.32	27.39	11.80	0.039	0.287	0.963	0.991	1.0179	0.9837	0.9860	1.0202	1.0207	1.5139
1216	1.957	2.60	27.41	10.59	0.041	0.287	0.962	0.990	1.0200	0.9841	0.9865	1.0224	1.0229	1.5173
1217	1.958	0.93	11.97	12.93	0.015	0.287	2.505	0.991	1.0501	1.0459	1.0401	1.0603	1.0607	2.3657
1218	1.958	0.78	9.02	11.51	0.012	0.287	3.350	0.991	1.0830	1.0739	1.0762	1.0893	1.0897	2.8999
1219	1.957	2.31	29.31	12.67	0.039	0.288	0.961	0.991	1.0233	0.9888	0.9909	1.0256	1.0250	1.5199
1220	1.958	2.60	29.23	11.29	0.041	0.287	0.963	0.991	1.0203	0.9842	0.9864	1.0229	1.0229	1.5181
1221	1.958	2.59	29.35	11.32	0.041	0.288	0.961	0.991	1.0206	0.9845	0.9867	1.0228	1.0232	1.5163
1222	1.959	2.31	29.35	12.71	0.039	0.288	0.962	0.993	1.0154	0.9812	0.9833	1.0178	1.0180	1.5102

140

ORIGINAL PAGE IS OF POOR QUALITY

NOZZLE TYPE	P&W EJECTOR NOZZLE (MODEL A)
FLIGHT CONDITIONS	SUPER SONIC CRUISE (MS=.04 BT)
NOZZLE CONFIGURATION	A1
PRIMARY-NOZZLE PLUG	SPLIT PLUG (RETRACTED)
FLOW SPLITTER	CONICAL SPLITTER
FAN NOZZLE	TRTS
CLAMSHELL POSITION	
EJECTOR INLET OPENING	

RDG	MN	PTF/PTP	PTF/PO	PTP/PO	OMEGA	PTS/PTF	CNF	CDP	CF1	ETA1	ETA1,INT	CFP1	CFP2	F9
1223	1.957	2.60	27.37	10.54	0.041	0.287	0.962	0.991	1.0134	0.9825	0.9849	1.0200	1.0212	1.5155
1224	1.957	2.33	27.54	11.84	0.039	0.287	0.961	0.990	1.0189	0.9825	0.9868	1.0212	1.0216	1.5120
1225	1.957	2.07	27.40	13.25	0.037	0.287	0.961	0.992	1.0149	0.9825	0.9847	1.0171	1.0176	1.5003
1226	1.957	2.59	24.79	9.58	0.041	0.287	0.961	0.990	1.0146	0.9791	0.9818	1.0172	1.0177	1.5114
1227	1.956	2.33	24.66	10.59	0.039	0.287	0.962	0.994	1.0117	0.9779	0.9805	1.0143	1.0148	1.5004
1228	1.958	2.00	24.84	12.40	0.037	0.287	0.961	0.993	1.0136	0.9820	0.9852	1.0167	1.0176	1.5007
1229	1.959	2.59	22.45	8.66	0.041	0.287	0.960	0.988	1.0181	0.9827	0.9857	1.0211	1.0216	1.5103
1230	1.958	2.31	22.38	9.69	0.039	0.287	0.960	0.990	1.0151	0.9815	0.9846	1.0180	1.0185	1.5122
1231	1.957	2.00	22.41	11.19	0.037	0.287	0.961	0.991	1.0149	0.9834	0.9861	1.0176	1.0181	1.5104
1232	1.957	2.60	19.87	7.65	0.041	0.287	0.960	0.988	1.0096	0.9748	0.9783	1.0131	1.0136	1.5131
1233	1.958	2.30	19.96	8.68	0.039	0.287	0.959	0.989	1.0077	0.9747	0.9779	1.0110	1.0115	1.5064
1234	1.958	2.00	19.99	10.00	0.037	0.287	0.961	0.990	1.0098	0.9788	0.9818	1.0128	1.0133	1.5073
1235	1.958	2.59	19.95	7.71	0.041	0.287	0.959	0.988	1.0121	0.9773	0.9807	1.0155	1.0160	1.5156

141

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.540	4.3561	0.21956	0.43746	0.43200
37	8.0287	2.4013	0.12123	0.24156	0.53000
47	9.3984	2.8157	0.14191	0.28276	0.62900
52	9.5783	2.8696	0.14463	0.28818	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.095	3.3232	0.16749	0.33376	0.42200
67	13.091	3.9220	0.19767	0.39387	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	28.223	7.8563	0.39596	0.78897	0.58400
82	8.1937	2.4548	0.12372	0.24652	0.63500
92	3.5827	1.0674	0.053793	0.10719	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	8.0737	2.4188	0.12191	0.24291	0.62400
112	3.9279	1.1768	0.059309	0.11818	0.83000
122	2.3518	0.70456	0.035510	0.070756	0.96000
127	3.5477	1.0629	0.053568	0.10674	1.0900
137	3.7328	1.1183	0.056363	0.11231	1.2200
142	3.6578	1.0998	0.055230	0.11005	1.3500

>ADDITIONAL PRESSURE RATIOS , AFTERBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	8.0737	2.4188	0.12191	0.24291	-1.0000
-112	3.9279	1.1768	0.059309	0.11818	-1.0000
-122	2.3518	0.70456	0.035510	0.070756	-1.0000
-127	3.5477	1.0629	0.053588	0.10674	-1.0000
-137	3.7328	1.1183	0.056363	0.11231	-1.0000
-142	3.6578	1.0998	0.055230	0.11005	-1.0000
-152	3.5527	1.0644	0.053644	0.10689	-1.0000
-157	3.5527	1.0644	0.053644	0.10689	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5527	1.0644	0.053644	0.10689	-1.0000
-157	3.5527	1.0644	0.053644	0.10689	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5527	1.0644	0.053644	0.10689	-1.0000
-172	3.5527	1.0644	0.053644	0.10689	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3476	1.0029	0.050546	0.10072	-1.0000
-187	3.2475	0.97292	0.049035	0.097705	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/28/79   CANNELL   REC 10/18/79 00:48:38.921   FAC RX4X1   PGM C034   RDG 1286

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.505	3.7774	0.19117	0.43869	0.43200
37	6.9107	2.0876	0.10565	0.24244	0.53000
47	8.0808	2.4411	0.12354	0.28349	0.62900
52	8.2458	2.4909	0.12606	0.28928	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	9.6407	2.9123	0.14738	0.33822	0.42200
67	12.974	3.9193	0.19835	0.45517	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	25.944	7.8373	0.39663	0.91018	0.56400
82	8.1058	2.4486	0.12392	0.28437	0.63500
92	3.5440	1.0706	0.054180	0.12433	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	7.9708	2.4079	0.12186	0.27964	0.62400
112	3.8792	1.1719	0.059305	0.13609	0.83000
122	2.3228	0.70167	0.035510	0.081488	0.96000
127	3.3190	1.0030	0.050797	0.12345	1.0900
137	3.2637	0.98592	0.049895	0.11450	1.2200
142	3.1686	0.95719	0.048442	0.11116	1.3500

>ADDITIONAL PRESSURE RATIOS , BORESCOPE INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.9708	2.4079	0.12186	0.27964	-1.0000
-112	3.8792	1.1719	0.059305	0.13609	-1.0000
-122	2.3228	0.70167	0.035510	0.081488	-1.0000
-127	3.3190	1.0030	0.050797	0.12345	-1.0000
-137	3.2637	0.98592	0.049895	0.11450	-1.0000
-142	3.1686	0.95719	0.048442	0.11116	-1.0000
-152	3.5290	1.0660	0.053950	0.12380	-1.0000
-197	3.5290	1.0660	0.053950	0.12380	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5290	1.0660	0.053950	0.12380	-1.0000
-197	3.5290	1.0660	0.053950	0.12380	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5290	1.0660	0.053950	0.12380	-1.0000
-172	3.5290	1.0660	0.053950	0.12380	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3238	1.0041	0.050813	0.11661	-1.0000
-187	3.2397	0.97885	0.049496	0.11349	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.139	3.3616	0.16839	0.43702	0.43200
37	6.1656	1.8613	0.093235	0.24197	0.53000
47	7.2058	2.1753	0.10897	0.28280	0.62900
52	7.3709	2.2251	0.11146	0.28928	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	8.6399	2.6070	0.13059	0.33893	0.42200
67	12.904	3.8956	0.19514	0.50645	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	26.154	7.8959	0.39590	1.0284	0.56400
82	8.1609	2.4636	0.12341	0.32028	0.63500
92	3.3390	1.0484	0.093318	0.13889	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTP	PL/PTP	X/DMAX
107	8.0759	2.4300	0.12212	0.31695	0.62400
112	3.9249	1.1847	0.059949	0.19401	0.83000
122	2.3428	0.70726	0.035428	0.091947	0.96000
127	3.5140	1.0608	0.053130	0.13791	1.0900
137	2.9435	0.88858	0.044511	0.11552	1.2200
142	2.8734	0.86743	0.043451	0.11277	1.3500

>ADDITIONAL PRESSURE RATIOS , SECONDARY INLET

AVD WORD	PL	PL/PO	PL/PTP	PL/PTP	X/DMAX
-107	8.0759	2.4300	0.12212	0.31695	-1.0000
-112	3.9249	1.1847	0.059949	0.19401	-1.0000
-122	2.3428	0.70726	0.035428	0.091947	-1.0000
-127	3.5140	1.0608	0.053130	0.13791	-1.0000
-137	2.9435	0.88858	0.044511	0.11552	-1.0000
-142	2.8734	0.86743	0.043451	0.11277	-1.0000
-152	3.5240	1.0638	0.053289	0.13830	-1.0000
-157	3.5240	1.0638	0.053289	0.13830	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5240	1.0638	0.053289	0.13830	-1.0000
-157	3.5240	1.0638	0.053289	0.13830	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5290	1.0653	0.053365	0.13850	-1.0000
-172	3.5290	1.0659	0.053365	0.13850	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3288	1.0049	0.050338	0.13064	-1.0000
-187	3.2437	0.97923	0.049052	0.12730	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/28/79   CADDETT   REC 10/18/79 00:51:53.159   FAC 8X6X1   PGR C034   RDG 120A

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	16.217	4.8828	0.21859	0.43778	0.43200
37	8.9335	2.6898	0.12041	0.24116	0.53000
47	10.459	3.1498	0.14097	0.28234	0.62900
52	10.684	3.2168	0.14400	0.28841	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.243	3.6864	0.16503	0.33052	0.42200
67	12.833	3.8640	0.17298	0.34644	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	29.306	8.8239	0.39502	0.79113	0.56400
82	9.1786	2.7636	0.12372	0.24778	0.63500
92	3.5451	1.0674	0.047785	0.095703	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	9.0735	2.7320	0.12230	0.24494	0.62400
112	4.4010	1.3251	0.059322	0.11881	0.83000
122	2.6290	0.79158	0.035436	0.070971	0.96000
127	3.5351	1.0644	0.047650	0.095432	1.0900
137	4.1758	1.2573	0.056286	0.11273	1.2200
142	4.0807	1.2287	0.055004	0.11016	1.3900

>ADDITIONAL PRESSURE RATIOS , BOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	9.0735	2.7320	0.12230	0.24494	-1.0000
-112	4.4010	1.3251	0.059322	0.11881	-1.0000
-122	2.6290	0.79158	0.035436	0.070971	-1.0000
-127	3.5351	1.0644	0.047650	0.095432	-1.0000
-137	4.1758	1.2573	0.056286	0.11273	-1.0000
-142	4.0807	1.2287	0.055004	0.11016	-1.0000
-152	3.5351	1.0644	0.047650	0.095432	-1.0000
-157	3.5401	1.0659	0.047717	0.095567	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5351	1.0644	0.047650	0.095432	-1.0000
-157	3.5401	1.0659	0.047717	0.095567	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5401	1.0659	0.047717	0.095567	-1.0000
-172	3.5401	1.0659	0.047717	0.095567	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3449	1.0071	0.045086	0.090297	-1.0000
-187	3.2549	0.98000	0.043871	0.087865	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

145

NASA-LEWIS   PRELIMINARY DATA   06/28/79   CADDEII   REC 10/18/79 00:52:38.836   FAC 9X6X1   PGM C034

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.199	4.2527	0.18920	0.43745	0.43200
37	7.8314	2.3463	0.10439	0.24135	0.53000
47	9.1704	2.7474	0.12224	0.28262	0.62900
52	9.3602	2.8043	0.12477	0.28847	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.089	3.2024	0.14248	0.32962	0.42200
67	12.756	3.8218	0.17003	0.39314	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	29.802	8.8688	0.39497	0.91229	0.56400
82	9.2803	2.7804	0.12370	0.28601	0.63500
92	3.5877	1.0689	0.047599	0.10995	0.89200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	9.1604	2.7445	0.12210	0.28231	0.62400
112	4.4428	1.3310	0.059219	0.13692	0.85000
122	2.6625	0.79770	0.035490	0.082056	0.96000
127	3.5477	1.0629	0.047289	0.10934	1.0900
137	3.7127	1.1123	0.049488	0.11442	1.2200
142	3.6077	1.0809	0.048089	0.11119	1.3500

>ADDITIONAL PRESSURE RATIOS , COREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	9.1604	2.7445	0.12210	0.28231	-1.0000
-112	4.4428	1.3310	0.059219	0.13692	-1.0000
-122	2.6625	0.79770	0.035490	0.082056	-1.0000
-127	3.5477	1.0629	0.047289	0.10934	-1.0000
-137	3.7127	1.1123	0.049488	0.11442	-1.0000
-142	3.6077	1.0809	0.048089	0.11119	-1.0000
-152	3.5577	1.0659	0.047422	0.10964	-1.0000
-157	3.5577	1.0659	0.047422	0.10964	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5577	1.0659	0.047422	0.10964	-1.0000
-157	3.5577	1.0659	0.047422	0.10964	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5577	1.0659	0.047422	0.10964	-1.0000
-172	3.5577	1.0659	0.047422	0.10964	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3527	1.0045	0.044689	0.10333	-1.0000
-187	3.2527	0.97450	0.043356	0.10024	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.613	3.7774	0.16928	0.43816	0.43200
37	6.9674	2.0865	0.093505	0.24203	0.53000
47	8.1469	2.4398	0.10933	0.28300	0.62400
52	8.3168	2.4907	0.11162	0.28891	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	9.5061	2.8468	0.12758	0.33022	0.42200
67	12.703	3.8043	0.17048	0.44128	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	29.368	8.7949	0.34613	1.0202	0.58400
82	9.2013	2.7555	0.12349	0.31963	0.63500
92	3.9873	1.0843	0.047875	0.12392	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	9.0514	2.7107	0.12147	0.31442	0.62400
112	4.4776	1.3409	0.060091	0.15554	0.83000
122	2.6369	0.78969	0.035389	0.091600	0.96000
127	3.5423	1.0608	0.047540	0.12305	1.0900
137	3.3222	0.99492	0.044586	0.11541	1.2200
142	3.2972	0.97545	0.04371	0.11319	1.3900

>ADDITIONAL PRESSURE RATIOS , SHROUD BASE

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	9.0514	2.7107	0.12147	0.31442	-1.0000
-112	4.4776	1.3409	0.060091	0.15554	-1.0000
-122	2.6369	0.78969	0.035389	0.091600	-1.0000
-127	3.5423	1.0608	0.047540	0.12305	-1.0000
-137	3.3222	0.99492	0.044586	0.11541	-1.0000
-142	3.2972	0.97545	0.043713	0.11315	-1.0000
-152	3.5523	1.0638	0.047674	0.12340	-1.0000
-157	3.5523	1.0638	0.047674	0.12340	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5523	1.0638	0.047674	0.12340	-1.0000
-157	3.5523	1.0638	0.047674	0.12340	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5573	1.0653	0.047741	0.12357	-1.0000
-172	3.5573	1.0653	0.047741	0.12357	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3573	1.0054	0.045056	0.11662	-1.0000
-187	3.2672	0.97845	0.043848	0.11390	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	18.090	5.4564	0.21975	0.43781	0.43200
37	9.9432	2.9992	0.12079	0.24065	0.53000
47	11.647	3.5131	0.14148	0.28188	0.62900
52	11.912	3.5930	0.14470	0.28829	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.639	4.1128	0.16563	0.33000	0.42200
67	12.656	3.8175	0.15374	0.30630	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.185	9.7082	0.39098	0.77898	0.56400
82	10.143	3.0595	0.12322	0.24549	0.63500
92	3.5393	1.0678	0.042995	0.085639	0.89200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	10.003	3.0173	0.12152	0.24210	0.62400
112	4.9097	1.4809	0.059642	0.11883	0.83000
122	2.9090	0.87745	0.035338	0.070404	0.96000
127	3.5293	1.0646	0.042873	0.085417	1.0900
137	4.6546	1.4040	0.056544	0.11265	1.2200
142	4.5496	1.3723	0.055268	0.11011	1.3900

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	10.003	3.0173	0.12152	0.24210	-1.0000
-112	4.9097	1.4809	0.059642	0.11889	-1.0000
-122	2.9090	0.87745	0.035338	0.070404	-1.0000
-127	3.5293	1.0646	0.042873	0.085417	-1.0000
-137	4.6546	1.4040	0.056544	0.11265	-1.0000
-142	4.5496	1.3723	0.055268	0.11011	-1.0000
-152	3.5243	1.0631	0.042812	0.085296	-1.0000
-157	3.5243	1.0631	0.042812	0.085296	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5243	1.0631	0.042812	0.085296	-1.0000
-157	3.5243	1.0631	0.042812	0.085296	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5293	1.0646	0.042873	0.085417	-1.0000
-172	3.5293	1.0646	0.042873	0.085417	-1.0000

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3442	1.0087	0.040625	0.080938	-1.0000
-187	3.2542	0.98157	0.039531	0.078759	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/28/79   CADDEII   REC 10/18/79 00:56:59.941   FAC 8X6X1   PGM C034   RDG 1212   *Run 19*

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
37	15.558	4.6918	0.18845	0.43782	0.43200
37	8.5835	2.5885	0.10397	0.24155	0.53000
47	10.036	3.0258	0.12156	0.28236	0.62900
52	10.249	3.0907	0.12414	0.28841	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.719	3.5360	0.14195	0.32978	0.42200
67	12.599	3.7994	0.15261	0.35454	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.390	9.7556	0.39185	0.91036	0.56400
82	10.189	3.0726	0.12341	0.28672	0.63500
92	3.5445	1.0689	0.042933	0.099744	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	10.054	3.0319	0.12178	0.28292	0.62400
112	4.9611	1.4961	0.060092	0.13961	0.83000
122	2.9186	0.88015	0.035353	0.082133	0.96000
127	3.5345	1.0659	0.042812	0.099462	1.0900
137	4.0551	1.2229	0.049118	0.11411	1.2200
142	3.9300	1.1912	0.047845	0.11116	1.3900

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	10.054	3.0319	0.12178	0.28292	-1.0000
-112	4.9611	1.4961	0.060092	0.13961	-1.0000
-122	2.9186	0.88015	0.035353	0.082133	-1.0000
-127	3.5345	1.0659	0.042812	0.099462	-1.0000
-137	4.0551	1.2229	0.049118	0.11411	-1.0000
-142	3.9300	1.1912	0.047845	0.11116	-1.0000
-152	3.5345	1.0659	0.042812	0.099462	-1.0000
-157	3.5299	1.0644	0.042751	0.099322	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5345	1.0659	0.042812	0.099462	-1.0000
-157	3.5299	1.0644	0.042751	0.099322	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5345	1.0659	0.042812	0.099462	-1.0000
-172	3.5345	1.0659	0.042812	0.099462	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3492	1.0100	0.040568	0.094250	-1.0000
-187	3.2591	0.99282	0.039477	0.091714	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/28/79   CADDETT   REC 10/18/79 00:57:52.451   FAC 8X6R1   PGM C034   PRG 1213

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.924	4.1961	0.16911	0.43770	0.43200
37	7.6832	2.3153	0.093309	0.24152	0.53000
47	8.9978	2.7115	0.10927	0.28284	0.62900
52	9.1627	2.7612	0.11129	0.28802	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.532	3.1732	0.12791	0.33107	0.42200
67	12.531	3.7761	0.15219	0.39389	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.323	9.7404	0.39255	1.0180	0.38400
82	10.157	3.0609	0.12336	0.31929	0.63500
92	3.9329	1.0849	0.042901	0.11104	0.89200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	10.027	3.0217	0.12178	0.31520	0.62400
112	4.9981	1.5062	0.060700	0.15711	0.83000
122	2.9021	0.87453	0.035245	0.091225	0.96000
127	3.5129	1.0585	0.042650	0.11041	1.0900
137	3.6726	1.1067	0.044602	0.11544	1.2200
142	3.5929	1.0828	0.043630	0.11293	1.3500

>ADDITIONAL PRESSURE RATIOS , SECONDARY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	10.027	3.0217	0.12178	0.31520	-1.0000
-112	4.9981	1.5062	0.060700	0.15711	-1.0000
-122	2.9021	0.87453	0.035245	0.091225	-1.0000
-127	3.5129	1.0585	0.042650	0.11041	-1.0000
-137	3.6726	1.1067	0.044602	0.11544	-1.0000
-142	3.5929	1.0828	0.043630	0.11293	-1.0000
-152	3.5225	1.0615	0.042779	0.11073	-1.0000
-157	3.5225	1.0615	0.042779	0.11073	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5225	1.0615	0.042779	0.11073	-1.0000
-157	3.5225	1.0615	0.042779	0.11073	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5225	1.0615	0.042779	0.11073	-1.0000
-172	3.5225	1.0615	0.042779	0.11073	-1.0000

>ADDITIONAL PRESSURE RATIOS , 60 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3224	1.0012	0.040349	0.10444	-1.0000
-187	3.2273	0.97254	0.039194	0.10145	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/28/79   CAMDEII   REC 10/18/79 01:00:26.289   FAC 84081   PGM C034   RDG 1214

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	19.246	5.740H	0.21067	0.43784	0.43200
37	10.596	3.1756	0.11571	0.24054	0.53900
47	12.402	3.7174	0.13544	0.28155	0.62900
52	12.672	3.7981	0.13838	0.28767	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.857	5.3903	0.15596	0.33252	0.42200
67	12.472	3.7383	0.13620	0.28314	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	35.596	10.657	0.50824	0.80718	0.56500
82	11.285	3.3824	0.12323	0.25618	0.63500
92	3.5802	1.0731	0.039099	0.081277	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	11.110	3.3300	0.12133	0.25221	0.62400
112	5.3185	1.6541	0.060285	0.12528	0.83900
122	3.2505	0.97427	0.035497	0.073791	0.94000
127	3.5092	1.0746	0.039155	0.081391	1.0900
137	4.9791	1.4924	0.054374	0.11303	1.2200
142	4.8942	1.4590	0.053010	0.11020	1.3900

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLOW

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	11.110	3.3300	0.12133	0.25221	-1.0000
-112	5.3185	1.6541	0.060285	0.12528	-1.0000
-122	3.2505	0.97427	0.035497	0.073791	-1.0000
-127	3.5092	1.0746	0.039155	0.081391	-1.0000
-137	4.0791	1.4924	0.044374	0.11763	-1.0000
-142	3.8500	1.4590	0.093010	0.11020	-1.0000
-152	3.5753	1.0716	0.039044	0.081164	-1.0000
-157	3.5753	1.0716	0.039044	0.081164	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5753	1.0716	0.039044	0.081164	-1.0000
-157	3.5753	1.0716	0.039044	0.081164	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5703	1.0701	0.038989	0.081051	-1.0000
-172	3.5743	1.0716	0.039044	0.081164	-1.0000

>ADDITIONAL PRESSURE RATIOS , MEASURED THRUST PARAMETERS

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3954	1.0177	0.037079	0.077001	-1.0000
-187	3.3096	0.99075	0.036097	0.075039	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

151

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	17.186	5.1757	0.18896	0.43858	0.43208
37	9.4510	2.8463	0.10392	0.24119	0.53000
47	11.090	3.3280	0.12150	0.28201	0.62900
52	11.290	3.4002	0.12414	0.28813	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.969	3.9059	0.14260	0.33098	0.42200
67	12.415	3.7388	0.13650	0.31682	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	35.471	10.683	0.39001	0.90523	0.56400
82	11.215	3.3776	0.12331	0.28622	0.63500
92	3.5449	1.0670	0.038977	0.090467	0.89200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTP	PL/PTP	X/DMAX
107	11.035	3.3235	0.12134	0.28163	0.62400
112	5.5610	1.6748	0.061144	0.14192	0.83000
122	3.2196	0.96965	0.035401	0.082167	0.96000
127	3.5349	1.0646	0.038867	0.090212	1.0900
137	4.4755	1.3479	0.049209	0.11422	1.2200
142	4.3454	1.3087	0.047779	0.11090	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTP	PL/PTP	X/DMAX
-107	11.035	3.3235	0.12134	0.28163	-1.0000
-112	5.5610	1.6748	0.061144	0.14192	-1.0000
-122	3.2196	0.96965	0.035401	0.082167	-1.0000
-127	3.5349	1.0646	0.038867	0.090212	-1.0000
-137	4.4755	1.3479	0.049209	0.11422	-1.0000
-142	4.3454	1.3087	0.047779	0.11090	-1.0000
-152	3.5349	1.0646	0.038867	0.090212	-1.0000
-157	3.5349	1.0646	0.038867	0.090212	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5349	1.0646	0.038867	0.090212	-1.0000
-157	3.5349	1.0646	0.038867	0.090212	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5349	1.0646	0.038867	0.090212	-1.0000
-172	3.5299	1.0631	0.038812	0.090084	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3697	1.0088	0.036831	0.085487	-1.0000
-187	3.2697	0.99472	0.035951	0.083444	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.347	4.6220	0.16864	0.43819	0.43200
37	8.4594	2.5476	0.092951	0.24153	0.53000
47	9.8845	2.9768	0.10861	0.28221	0.62900
52	10.104	3.0430	0.11103	0.28849	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.614	3.4977	0.12761	0.33160	0.42200
67	12.359	3.7219	0.13580	0.35286	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	35.467	10.681	0.38970	1.0126	0.56400
82	11.214	3.3772	0.12322	0.32018	0.63500
92	3.5468	1.0681	0.038972	0.10127	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	10.979	3.3065	0.12064	0.31347	0.62400
112	5.6134	1.6905	0.061680	0.16027	0.83000
122	3.2215	0.97016	0.035397	0.091977	0.96000
127	3.5318	1.0636	0.038807	0.10084	1.0900
137	3.9972	1.2038	0.043921	0.11413	1.2200
142	3.9872	1.2008	0.043811	0.11386	1.3500

>ADDITIONAL PRESSURE RATIOS , BOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	10.979	3.3065	0.12064	0.31347	-1.0000
-112	5.6134	1.6905	0.061680	0.16027	-1.0000
-122	3.2215	0.97016	0.035397	0.091977	-1.0000
-127	3.5318	1.0636	0.038807	0.10084	-1.0000
-137	3.9972	1.2038	0.043921	0.11413	-1.0000
-142	3.9872	1.2008	0.043811	0.11386	-1.0000
-152	3.5368	1.0651	0.038862	0.10098	-1.0000
-157	3.5368	1.0651	0.038862	0.10098	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5368	1.0651	0.038862	0.10098	-1.0000
-157	3.5368	1.0651	0.038862	0.10098	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5318	1.0636	0.038807	0.10084	-1.0000
-172	3.5368	1.0651	0.038862	0.10098	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3516	1.0093	0.036827	0.095692	-1.0000
-187	3.2469	0.98372	0.035892	0.093269	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   04/28/79   CADDE11   REC 10/18/79 01:05:26.620   FAC 8X6X1   PGM F034   ROG 1217

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	18.916	5.6633	0.47307	0.43805	0.43200
37	10.384	3.1091	0.25971	0.24049	0.53000
47	12.167	3.6431	0.30432	0.28179	0.62900
52	12.427	3.7209	0.31082	0.28781	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.280	4.2757	0.35717	0.33073	0.42200
67	12.312	3.6865	0.30794	0.28515	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	38.803	11.559	0.96592	0.89404	0.56400
82	12.297	3.6820	0.30757	0.28480	0.63500
92	3.5693	1.0675	0.089173	0.082572	0.89200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	12.047	3.6072	0.30132	0.27902	0.62400
112	6.0007	1.7967	0.15009	0.13898	0.85000
122	3.5353	1.0585	0.088422	0.081877	0.96000
127	3.5693	1.0675	0.089173	0.082572	1.0900
137	4.8756	1.4599	0.12195	0.11292	1.2200
142	4.8206	1.4434	0.12057	0.11165	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY SKIRT

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	12.047	3.6072	0.30132	0.27902	-1.0000
-112	6.0007	1.7967	0.15009	0.13898	-1.0000
-122	3.5353	1.0585	0.088422	0.081877	-1.0000
-127	3.5693	1.0675	0.089173	0.082572	-1.0000
-137	4.8756	1.4599	0.12195	0.11292	-1.0000
-142	4.8206	1.4434	0.12057	0.11165	-1.0000
-152	3.5453	1.0615	0.088672	0.082108	-1.0000
-157	3.5553	1.0645	0.088922	0.082340	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5453	1.0615	0.088672	0.082108	-1.0000
-157	3.5553	1.0645	0.088922	0.082340	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5553	1.0645	0.088922	0.082340	-1.0000
-172	3.5553	1.0645	0.088922	0.082340	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3702	1.0091	0.084293	0.078054	-1.0000
-187	3.2852	0.98364	0.082166	0.076084	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

154

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	16.846	5.0623	0.55878	0.43793	0.43200
37	9.2687	2.7743	0.30745	0.24095	0.53000
47	10.834	3.2627	0.35935	0.28163	0.62900
52	11.078	3.3160	0.36748	0.28800	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.638	3.7828	0.41921	0.32854	0.42200
67	12.283	3.6766	0.40744	0.31932	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	38.725	11.591	1.2845	1.0067	0.56400
82	12.333	3.6916	0.40910	0.32062	0.63500
92	3.5759	1.0703	0.11861	0.092959	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	12.073	3.6138	0.40048	0.31386	0.62400
112	6.0678	1.8162	0.20127	0.15774	0.83000
122	3.5508	1.0628	0.11778	0.092309	0.96000
127	3.5609	1.0658	0.11812	0.092569	1.0900
137	4.3866	1.3130	0.14551	0.11404	1.2200
142	4.3916	1.3145	0.14567	0.11417	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	12.073	3.6138	0.40048	0.31386	-1.0000
-112	6.0678	1.8162	0.20127	0.15774	-1.0000
-122	3.5508	1.0628	0.11778	0.092309	-1.0000
-127	3.5609	1.0658	0.11812	0.092569	-1.0000
-137	4.3866	1.3130	0.14551	0.11404	-1.0000
-142	4.3916	1.3145	0.14567	0.11417	-1.0000
-152	3.5659	1.0673	0.11828	0.092699	-1.0000
-157	3.5709	1.0688	0.11845	0.092829	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5659	1.0673	0.11828	0.092699	-1.0000
-157	3.5709	1.0688	0.11845	0.092829	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5659	1.0673	0.11828	0.092699	-1.0000
-172	3.5709	1.0688	0.11849	0.092829	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3857	1.0134	0.11230	0.088015	-1.0000
-187	3.3138	0.99093	0.10981	0.086063	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/28/79   CADDE11   REC 10/18/79 01:08:42.692   FAC 8X6X1   PGM CO34   RDG 1219

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	19.418	5.5523	0.18941	0.43839	0.43200
37	10.112	3.0484	0.10399	0.24069	0.53000
47	11.842	3.5698	0.12178	0.28186	0.62900
52	12.131	3.6482	0.12445	0.28805	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.911	4.1936	0.14306	0.33111	0.42200
67	12.216	3.6829	0.12563	0.29078	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	37.859	11.392	0.38729	0.89630	0.56400
82	11.982	3.6120	0.12322	0.28519	0.63500
92	3.5397	1.0671	0.038402	0.084294	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	11.737	3.5382	0.12070	0.27936	0.62400
112	5.9464	1.7926	0.061159	0.14154	0.83000
122	3.4396	1.0369	0.035373	0.081871	0.96000
127	3.5347	1.0656	0.036351	0.084195	1.0900
137	4.7557	1.4337	0.048908	0.11320	1.2200
142	4.7007	1.4171	0.048342	0.11189	1.3900

>ADDITIONAL PRESSURE RATIOS , COREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	11.737	3.5382	0.12070	0.27936	-1.0000
-112	5.9464	1.7926	0.061159	0.14154	-1.0000
-122	3.4396	1.0369	0.035373	0.081871	-1.0000
-127	3.5347	1.0656	0.036351	0.084195	-1.0000
-137	4.7557	1.4337	0.048908	0.11320	-1.0000
-142	4.7007	1.4171	0.048342	0.11189	-1.0000
-152	3.5297	1.0641	0.036299	0.084016	-1.0000
-157	3.5347	1.0656	0.036351	0.084135	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5297	1.0641	0.036299	0.084016	-1.0000
-157	3.5347	1.0656	0.036351	0.084135	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5297	1.0641	0.036299	0.084016	-1.0000
-172	3.5247	1.0626	0.036248	0.083896	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3445	1.0083	0.034395	0.079608	-1.0000
-187	3.2644	0.99411	0.033571	0.077702	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	16.389	4.9315	0.16870	0.43896	0.43200
37	9.0072	2.7103	0.092715	0.24125	0.53000
47	10.532	3.1691	0.10843	0.28209	0.62900
52	10.762	3.2393	0.11078	0.28824	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.326	3.7090	0.12688	0.33015	0.42200
67	12.187	3.6469	0.12544	0.32640	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	37.595	11.312	0.38698	1.0769	0.56400
82	11.967	3.6007	0.12318	0.32051	0.63500
92	3.5398	1.0651	0.036437	0.094810	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	11.727	3.5285	0.12071	0.31408	0.62400
112	5.8315	1.7547	0.060026	0.15619	0.83000
122	3.4297	1.0320	0.035304	0.091861	0.96000
127	3.5298	1.0621	0.036334	0.094942	1.0900
137	4.2605	1.2820	0.043855	0.11411	1.2200
142	4.2699	1.2920	0.043855	0.11411	1.3500

>ADDITIONAL PRESSURE RATIOS , SORESOOK INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	11.727	3.5285	0.12071	0.31408	-1.0000
-112	5.8315	1.7547	0.060028	0.15619	-1.0000
-122	3.4297	1.0320	0.035304	0.091861	-1.0000
-127	3.5298	1.0621	0.036334	0.094942	-1.0000
-137	4.2605	1.2820	0.043855	0.11411	-1.0000
-142	4.2699	1.2820	0.043855	0.11411	-1.0000
-152	3.5248	1.0606	0.036282	0.094408	-1.0000
-157	3.5298	1.0621	0.036334	0.094942	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5248	1.0606	0.036282	0.094408	-1.0000
-157	3.5298	1.0621	0.036334	0.094942	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5348	1.0636	0.036385	0.094676	-1.0000
-172	3.5298	1.0621	0.036334	0.094942	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3597	1.0109	0.034582	0.089984	-1.0000
-187	3.2796	0.98692	0.033759	0.087839	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

157

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	16.498	4.9610	0.16901	0.43829	0.43200
37	9.0564	2.7303	0.093005	0.24119	0.53000
47	10.591	3.1926	0.10P76	0.28206	0.62900
52	10.821	3.2619	0.11113	0.28818	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.270	3.8988	0.12601	0.32678	0.42200
67	12.155	3.6641	0.12483	0.32372	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	37.687	11.380	0.38702	1.0037	0.56400
82	11.986	3.6129	0.12308	0.31920	0.63500
92	3.5448	1.0689	0.036401	0.094399	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	11.761	3.5451	0.12078	0.31321	0.62490
112	5.8810	1.7728	0.060395	0.15662	0.85100
122	3.4395	1.0368	0.035322	0.091600	0.96300
127	3.5298	1.0640	0.036247	0.093999	1.0900
137	4.2752	1.2887	0.043904	0.11386	1.2200
142	4.2892	1.2917	0.044008	0.11412	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	11.761	3.5451	0.12078	0.31321	-1.0000
-112	5.8810	1.7728	0.060395	0.15662	-1.0000
-122	3.4395	1.0368	0.035322	0.091600	-1.0000
-127	3.5298	1.0640	0.036247	0.093999	-1.0000
-137	4.2752	1.2887	0.043904	0.11386	-1.0000
-142	4.2892	1.2917	0.044004	0.11412	-1.0000
-152	3.5346	1.0655	0.036298	0.094133	-1.0000
-157	3.5298	1.0640	0.036247	0.093999	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5346	1.0655	0.036298	0.094133	-1.0000
-157	3.5298	1.0640	0.036247	0.093999	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5346	1.0655	0.036298	0.094133	-1.0000
-172	3.5346	1.0655	0.036298	0.094133	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3444	1.0081	0.034345	0.089068	-1.0000
-187	3.2643	0.99401	0.033523	0.086936	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

158

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	18.606	5.5769	0.18999	0.43877	0.43200
37	10.216	3.0620	0.10431	0.24091	0.53000
47	11.969	3.5876	0.12222	0.28226	0.62900
52	12.204	3.6580	0.12462	0.28779	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.092	4.2239	0.14389	0.33232	0.42200
67	12.124	3.6340	0.12380	0.28591	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	37.908	11.362	0.38708	0.89394	0.56400
82	12.069	3.6176	0.12324	0.28461	0.63500
92	3.5675	1.0693	0.036428	0.084129	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	11.854	3.5532	0.12104	0.27955	0.62400
112	5.8528	1.7543	0.059763	0.13802	0.83000
122	3.4675	1.0393	0.035407	0.081770	0.96000
127	3.5575	1.0683	0.036326	0.083894	1.0900
137	4.8028	1.4396	0.049041	0.11326	1.2200
142	4.7373	1.4201	0.048378	0.11173	1.3900

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	11.854	3.5532	0.12104	0.27955	-1.0000
-112	5.8528	1.7543	0.059763	0.13802	-1.0000
-122	3.4675	1.0393	0.035407	0.081770	-1.0000
-127	3.5575	1.0683	0.036326	0.083894	-1.0000
-137	4.8028	1.4396	0.049041	0.11326	-1.0000
-142	4.7373	1.4201	0.048378	0.11173	-1.0000
-152	3.5525	1.0648	0.036275	0.083776	-1.0000
-157	3.5575	1.0683	0.036326	0.083894	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5525	1.0648	0.036275	0.083776	-1.0000
-157	3.5575	1.0683	0.036326	0.083894	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5575	1.0663	0.036326	0.083894	-1.0000
-172	3.5525	1.0648	0.036275	0.083776	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3575	1.0063	0.034283	0.079175	-1.0000
-187	3.2724	0.98086	0.033419	0.077170	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.467	4.6148	0.16861	0.43803	0.43200
37	8.5032	2.5402	0.092812	0.24112	0.53000
47	9.9485	2.9721	0.10859	0.28210	0.62700
52	10.163	3.0363	0.11093	0.28820	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.693	3.4814	0.12720	0.33045	0.42200
67	12.098	3.6144	0.13205	0.34307	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	35.979	10.828	0.39830	1.0088	0.58400
82	11.283	3.3709	0.12316	0.31996	0.63500
92	3.5548	1.0620	0.038801	0.10080	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	11.083	3.3112	0.12098	0.31429	0.62400
112	5.5017	1.6436	0.060051	0.15601	0.83000
122	3.2394	0.96777	0.035358	0.091858	0.96000
127	3.5548	1.0620	0.038801	0.10080	1.0900
137	4.0053	1.1966	0.043718	0.11358	1.2200
142	4.0159	1.1998	0.043827	0.11386	1.3500

>ADDITIONAL PRESSURE RATIOS , SHROUD INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	11.083	3.3112	0.12098	0.31429	-1.0000
-112	5.5017	1.6436	0.060051	0.15601	-1.0000
-122	3.2394	0.96777	0.035358	0.091858	-1.0000
-127	3.5548	1.0620	0.038801	0.10080	-1.0000
-137	4.0053	1.1966	0.043718	0.11358	-1.0000
-142	4.0159	1.1998	0.043827	0.11386	-1.0000
-152	3.5548	1.0620	0.038801	0.10080	-1.0000
-157	3.5548	1.0620	0.038801	0.10080	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5548	1.0620	0.038801	0.10080	-1.0000
-157	3.5549	1.0620	0.038801	0.10080	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5548	1.0620	0.038801	0.10080	-1.0000
-172	3.5498	1.0605	0.038746	0.10066	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3646	1.0052	0.036724	0.095407	-1.0000
-187	3.2945	0.98422	0.035959	0.093420	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

160

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	17.238	5.1852	0.18826	0.43791	0.43200
37	9.4944	2.8528	0.10358	0.24094	0.53000
47	11.104	3.3399	0.12126	0.28207	0.62900
52	11.333	3.4090	0.12377	0.28791	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.047	3.9245	0.14249	0.33144	0.42200
67	12.098	3.6390	0.13212	0.30733	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	35.547	10.692	0.38821	0.90302	0.56400
82	11.293	3.3970	0.12334	0.28689	0.63500
92	3.5539	1.0690	0.038812	0.090280	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	11.099	3.3384	0.12121	0.28194	0.62400
112	5.5097	1.6573	0.060172	0.13997	0.83000
122	3.2387	0.97416	0.035369	0.082273	0.96000
127	3.5489	1.0679	0.038757	0.090153	1.0900
137	4.4594	1.3413	0.048700	0.11328	1.2200
142	4.4143	1.3278	0.048209	0.11214	1.3500

>ADDITIONAL PRESSURE RATIOS , BOBBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	11.099	3.3384	0.12121	0.28194	-1.0000
-112	5.5097	1.6573	0.060172	0.13997	-1.0000
-122	3.2387	0.97416	0.035369	0.082273	-1.0000
-127	3.5489	1.0679	0.038757	0.090153	-1.0000
-137	4.4594	1.3413	0.048700	0.11328	-1.0000
-142	4.4143	1.3278	0.048209	0.11214	-1.0000
-152	3.5439	1.0660	0.038702	0.090026	-1.0000
-157	3.5389	1.0649	0.038648	0.089899	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5439	1.0660	0.038702	0.090026	-1.0000
-157	3.5389	1.0649	0.038648	0.089899	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5389	1.0645	0.038648	0.089899	-1.0000
-172	3.5439	1.0660	0.038702	0.090026	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3587	1.0103	0.036681	0.085323	-1.0000
-187	3.2637	0.98169	0.035642	0.082908	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PPELIMINARY DATA   06/28/79   CADDEII   REC 10/18/79 01:14:46.056   FAC 8X6XL   PGM C034

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	19.329	5.8190	0.21239	0.43906	0.43200
37	19.597	3.1901	0.11644	0.24070	0.53000
47	12.406	3.7348	0.13631	0.28179	0.62900
52	12.675	3.8159	0.13928	0.28791	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.634	4.4056	0.16080	0.33240	0.42200
67	12.086	3.6384	0.13280	0.27452	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	35.391	10.642	0.38884	0.80298	0.56400
82	11.226	3.3796	0.12335	0.25500	0.63500
92	3.5912	1.0891	0.039021	0.080684	0.89200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	11.021	3.3179	0.12110	0.25035	0.62400
112	5.4722	1.6474	0.060128	0.12430	0.83000
122	3.2310	0.97267	0.035502	0.073390	0.96000
127	3.5482	1.0676	0.038966	0.080550	1.0900
137	4.9620	1.4938	0.054522	0.11271	1.2200
142	4.8920	1.4697	0.053643	0.11089	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	11.021	3.3179	0.12110	0.25035	-1.0000
-112	5.4722	1.6474	0.060128	0.12490	-1.0000
-122	3.2310	0.97267	0.035502	0.073390	-1.0000
-127	3.5482	1.0676	0.038966	0.080550	-1.0000
-137	4.9620	1.4938	0.054522	0.11271	-1.0000
-142	4.8920	1.4697	0.053643	0.11089	-1.0000
-152	3.5362	1.0646	0.038856	0.080323	-1.0000
-157	3.5362	1.0646	0.038856	0.080323	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5362	1.0646	0.038856	0.080323	-1.0000
-157	3.5362	1.0646	0.038856	0.080323	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5412	1.0661	0.038911	0.080437	-1.0000
-172	3.5362	1.0646	0.038856	0.080323	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3611	1.0118	0.036931	0.076345	-1.0000
-187	3.2760	0.99622	0.035997	0.074413	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

162

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.894	4.1904	0.16901	0.43733	0.43200
37	7.6724	2.3140	0.093332	0.24151	0.53000
47	8.9721	2.7060	0.10914	0.28241	0.62900
52	9.1520	2.7603	0.11133	0.28808	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.736	3.2381	0.13060	0.33794	0.62200
67	12.015	3.6239	0.14616	0.37821	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.147	9.6958	0.39106	1.0119	0.56400
82	10.162	3.0648	0.12361	0.31985	0.63500
92	3.5467	1.0697	0.043144	0.11164	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	9.9616	3.0045	0.12118	0.31356	0.62400
112	4.9523	1.4936	0.060243	0.15588	0.83000
122	2.9113	0.87806	0.035414	0.091638	0.96000
127	3.5267	1.0637	0.042901	0.11161	1.0900
137	3.6217	1.0923	0.044057	0.11400	1.2200
142	3.6217	1.0923	0.044057	0.11400	1.3500

>ADDITIONAL PRESSURE RATIOS , POSERSON INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	9.9616	3.0045	0.12118	0.31356	-1.0000
-112	4.9523	1.4936	0.060243	0.15588	-1.0000
-122	2.9113	0.87806	0.035414	0.091638	-1.0000
-127	3.5267	1.0637	0.042901	0.11101	-1.0000
-137	3.6217	1.0923	0.044057	0.11400	-1.0000
-142	3.6217	1.0923	0.044057	0.11400	-1.0000
-152	3.5317	1.0652	0.042961	0.11117	-1.0000
-157	3.5267	1.0637	0.042901	0.11101	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5317	1.0652	0.042961	0.11117	-1.0000
-157	3.5267	1.0637	0.042901	0.11101	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5317	1.0652	0.042961	0.11117	-1.0000
-172	3.5267	1.0637	0.042901	0.11101	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3366	1.0063	0.040588	0.10503	-1.0000
-187	3.2465	0.97918	0.039492	0.10219	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVO WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.497	4.6481	0.18831	0.43879	0.43200
37	8.5197	2.5620	0.10379	0.24186	0.53000
47	9.9695	2.9980	0.12146	0.28302	0.62900
52	10.174	3.0596	0.12396	0.28884	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVO WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.779	3.5421	0.14350	0.33439	0.42200
67	11.964	3.5977	0.14576	0.33964	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVO WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.182	9.6718	0.39183	0.91303	0.56400
82	10.160	3.0551	0.12377	0.28841	0.63500
92	3.9477	1.0868	0.043221	0.10071	0.89200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVO WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	9.9346	2.9875	0.12103	0.28203	0.62400
112	4.9587	1.4912	0.060412	0.14077	0.85000
122	2.9071	0.87420	0.035417	0.082527	0.96000
127	3.5327	1.0629	0.043098	0.10029	1.0900
137	3.9930	1.2008	0.048647	0.11336	1.2200
142	3.9480	1.1872	0.048098	0.11208	1.3500

>ADDITIONAL PRESSURE RATIOS , SECONDARY INLET

AVO WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	9.9346	2.9875	0.12103	0.28203	-1.0000
-112	4.9587	1.4912	0.060412	0.14077	-1.0000
-122	2.9071	0.87420	0.035417	0.082527	-1.0000
-127	3.5327	1.0629	0.043098	0.10029	-1.0000
-137	3.9930	1.2008	0.048647	0.11336	-1.0000
-142	3.9480	1.1872	0.048098	0.11208	-1.0000
-152	3.5427	1.0653	0.043160	0.10057	-1.0000
-157	3.5377	1.0638	0.043099	0.10043	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVO WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5427	1.0653	0.043160	0.10057	-1.0000
-157	3.5377	1.0638	0.043099	0.10043	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVO WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5377	1.0638	0.043099	0.10043	-1.0000
-172	3.5427	1.0653	0.043160	0.10057	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVO WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3375	1.0036	0.040660	0.094746	-1.0000
-187	3.2474	0.97654	0.039563	0.092189	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/28/79   CADDELL   REC 10/18/79 01:17:57.533   FAC 9XAX1   PGM C034   RDG 122R

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	18.177	5.4439	0.21916	0.43916	0.43200
37	9.9857	2.9907	0.12039	0.24126	0.53000
47	11.665	3.4938	0.14066	0.28186	0.62900
52	11.935	3.5746	0.14389	0.28836	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.796	4.1314	0.16631	0.33328	0.42200
67	11.985	3.5896	0.14449	0.28957	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.380	9.6979	0.39038	0.78234	0.56400
82	10.221	3.0611	0.12322	0.24694	0.63500
92	3.5732	1.0702	0.043078	0.086330	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	10.046	3.0087	0.12111	0.24271	0.62400
112	4.9943	1.4958	0.060212	0.12067	0.83000
122	2.9325	0.87828	0.035354	0.070851	0.96000
127	3.5581	1.0657	0.042897	0.085967	1.0900
137	4.6491	1.3924	0.056050	0.11233	1.2200
142	4.5991	1.3774	0.055447	0.11112	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	10.046	3.0087	0.12111	0.24271	-1.0000
-112	4.9943	1.4958	0.060212	0.12067	-1.0000
-122	2.9325	0.87828	0.035354	0.070851	-1.0000
-127	3.5581	1.0657	0.042897	0.085967	-1.0000
-137	4.6491	1.3924	0.056050	0.11233	-1.0000
-142	4.5991	1.3774	0.055447	0.11112	-1.0000
-152	3.5581	1.0657	0.042897	0.085967	-1.0000
-157	3.5531	1.0642	0.042837	0.085847	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5581	1.0657	0.042897	0.085967	-1.0000
-157	3.5531	1.0642	0.042837	0.085847	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5581	1.0657	0.042897	0.085967	-1.0000
-172	3.5581	1.0657	0.042897	0.085967	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3780	1.0117	0.040725	0.081614	-1.0000
-187	3.2979	0.98772	0.039740	0.079679	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/28/79   CADDELL   REC 10/18/79 01:18:58.6AM   FAC 8X6X1   PGP C034   PRG 1229

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.657	3.7852	0.16859	0.43725	0.43200
37	6.9911	2.0908	0.093119	0.24152	0.53000
47	8.1816	2.4468	0.10898	0.28265	0.62900
52	8.3416	2.4947	0.11111	0.28817	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	9.6220	2.8776	0.12816	0.33240	0.42200
67	11.952	3.5744	0.15920	0.41290	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	29.521	8.8285	0.39321	1.0198	0.56400
82	9.2769	2.7744	0.12357	0.32048	0.63500
92	3.5651	1.0656	0.047480	0.12309	0.89200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	9.0969	2.7205	0.12117	0.31426	0.62400
112	4.5091	1.3489	0.060061	0.15577	0.83000
122	2.6569	0.79458	0.035389	0.091787	0.96000
127	3.5431	1.0596	0.047195	0.12240	1.0900
137	3.2928	0.98474	0.043859	0.11375	1.2200
142	3.2878	0.98924	0.043792	0.11358	1.3500

>ADDITIONAL PRESSURE RATIOS , SHROUD INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	9.0969	2.7205	0.12117	0.31426	-1.0000
-112	4.5091	1.3489	0.060061	0.15577	-1.0000
-122	2.6569	0.79458	0.035389	0.091787	-1.0000
-127	3.5431	1.0596	0.047195	0.12240	-1.0000
-137	3.2928	0.98474	0.043859	0.11375	-1.0000
-142	3.2878	0.98924	0.043792	0.11358	-1.0000
-152	3.5581	1.0641	0.047393	0.12292	-1.0000
-157	3.5581	1.0641	0.047393	0.12292	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5581	1.0641	0.047393	0.12292	-1.0000
-157	3.5581	1.0641	0.047393	0.12292	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5531	1.0626	0.047326	0.12275	-1.0000
-172	3.5531	1.0626	0.047326	0.12275	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3578	1.0042	0.044726	0.11600	-1.0000
-187	3.2677	0.97725	0.043525	0.11289	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.174	4.2412	0.18954	0.43748	0.43200
37	7.8202	2.3400	0.10458	0.24137	0.53000
47	9.1554	2.7395	0.12243	0.28258	0.62900
52	9.3404	2.7949	0.12491	0.28829	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.750	3.2167	0.14376	0.33180	0.42200
67	11.915	3.5652	0.15933	0.36775	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	29.435	8.8076	0.39363	0.90751	0.56400
82	9.2454	2.7664	0.12364	0.28536	0.63500
92	3.5878	1.0676	0.047711	0.11012	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	9.0554	2.7096	0.12110	0.27949	0.62400
112	4.4886	1.3431	0.060025	0.13854	0.83000
122	2.6468	0.79197	0.035394	0.081692	0.96000
127	3.5528	1.0631	0.047510	0.10966	1.0900
137	3.6629	1.0960	0.048983	0.11305	1.2200
142	3.6178	1.0825	0.048380	0.11166	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	9.0554	2.7096	0.12110	0.27949	-1.0000
-112	4.4886	1.3431	0.060025	0.13854	-1.0000
-122	2.6468	0.79197	0.035394	0.081692	-1.0000
-127	3.5528	1.0631	0.047510	0.10966	-1.0000
-137	3.6629	1.0960	0.048983	0.11305	-1.0000
-142	3.6178	1.0825	0.048380	0.11166	-1.0000
-152	3.5528	1.0631	0.047510	0.10966	-1.0000
-157	3.5578	1.0646	0.047577	0.10981	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5528	1.0631	0.047510	0.10966	-1.0000
-157	3.5578	1.0646	0.047577	0.10981	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5578	1.0646	0.047577	0.10981	-1.0000
-172	3.5578	1.0646	0.047577	0.10981	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3526	1.0032	0.044833	0.10348	-1.0000
-187	3.2679	0.97770	0.043699	0.10085	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	16.217	4.8882	0.21811	0.43690	0.43200
37	8.9265	2.6905	0.12005	0.24048	0.53000
47	10.449	3.1495	0.14053	0.28149	0.62900
52	10.674	3.2172	0.14355	0.28755	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.271	3.6986	0.16503	0.33057	0.42200
67	11.862	3.5752	0.15953	0.31955	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	29.206	8.8210	0.39359	0.78840	0.38400
82	9.1811	2.7673	0.12348	0.24733	0.63500
92	3.5470	1.0691	0.047703	0.095553	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	8.9964	2.7116	0.12099	0.24236	0.62400
112	4.4814	1.3447	0.060001	0.12019	0.83000
122	2.6373	0.79492	0.035469	0.071048	0.96000
127	3.5370	1.0661	0.047568	0.095284	1.0900
137	4.1666	1.2559	0.056036	0.11225	1.2200
142	4.1280	1.2438	0.055499	0.11117	1.3900

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	8.9964	2.7116	0.12099	0.24236	-1.0000
-112	4.4814	1.3447	0.060001	0.12019	-1.0000
-122	2.6373	0.79492	0.035469	0.071048	-1.0000
-127	3.5370	1.0661	0.047568	0.095284	-1.0000
-137	4.1666	1.2559	0.056036	0.11225	-1.0000
-142	4.1280	1.2438	0.055499	0.11117	-1.0000
-152	3.5320	1.0646	0.047501	0.095149	-1.0000
-157	3.5370	1.0661	0.047568	0.095284	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5320	1.0646	0.047501	0.095149	-1.0000
-157	3.5370	1.0661	0.047569	0.095284	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5320	1.0646	0.047501	0.095149	-1.0000
-172	3.5370	1.0661	0.047569	0.095284	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3421	1.0073	0.044947	0.090033	-1.0000
-187	3.2521	0.98021	0.043737	0.087610	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.131	3.3482	0.16849	0.43792	0.43200
37	6.1525	1.8507	0.093137	0.24207	0.53000
47	7.1935	2.1639	0.10889	0.28302	0.62900
52	7.3536	2.2120	0.11132	0.28932	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	8.4894	2.5537	0.12851	0.33401	0.42200
67	11.821	3.5558	0.17894	0.46508	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	26.439	7.9532	0.40024	1.0402	0.56400
82	8.1692	2.4574	0.12367	0.32141	0.63500
92	3.5493	1.0677	0.053729	0.13964	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	7.9991	2.4062	0.12109	0.31472	0.62400
112	3.9649	1.1927	0.060021	0.15600	0.83000
122	2.3473	0.70609	0.035534	0.092354	0.96000
127	3.5192	1.0586	0.053274	0.13846	1.0900
137	2.8983	0.87182	0.043874	0.11403	1.2200
142	2.8932	0.87032	0.043798	0.11383	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.9991	2.4062	0.12109	0.31472	-1.0000
-112	3.9649	1.1927	0.060021	0.15600	-1.0000
-122	2.3473	0.70609	0.035534	0.092354	-1.0000
-127	3.5192	1.0586	0.053274	0.13846	-1.0000
-137	2.8983	0.87182	0.043874	0.11403	-1.0000
-142	2.8932	0.87032	0.043798	0.11383	-1.0000
-152	3.5343	1.0631	0.053502	0.13905	-1.0000
-157	3.5393	1.0646	0.053578	0.13925	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5343	1.0631	0.053502	0.13905	-1.0000
-157	3.5393	1.0646	0.053578	0.13925	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5343	1.0631	0.053502	0.13905	-1.0000
-172	3.5393	1.0646	0.053578	0.13925	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3339	1.0029	0.050470	0.13117	-1.0000
-187	3.2488	0.97728	0.049181	0.12782	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.600	3.8012	0.19046	0.43798	0.43200
37	6.9564	2.0986	0.10515	0.24180	0.53000
47	8.1465	2.4576	0.12314	0.28317	0.62900
52	8.3065	2.5059	0.12556	0.28873	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	9.6763	2.9192	0.14628	0.33635	0.42200
67	11.781	3.5540	0.17807	0.40949	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	26.494	7.9808	0.39987	0.91955	0.56400
82	8.1715	2.4652	0.12352	0.28404	0.63500
92	3.5346	1.0663	0.053427	0.12286	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	8.0065	2.4154	0.12102	0.27830	0.62400
112	3.9700	1.1977	0.060008	0.13799	0.83000
122	2.3484	0.70849	0.035498	0.081631	0.96000
127	3.5146	1.0605	0.053124	0.12217	1.0900
137	3.2443	0.97876	0.049040	0.11277	1.2200
142	3.2143	0.96970	0.048586	0.11173	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	8.0065	2.4154	0.12102	0.27830	-1.0000
-112	3.9750	1.1977	0.060008	0.13799	-1.0000
-122	2.3484	0.70848	0.035498	0.081631	-1.0000
-127	3.5146	1.0605	0.053124	0.12217	-1.0000
-137	3.2443	0.97876	0.049040	0.11277	-1.0000
-142	3.2143	0.96970	0.048586	0.11173	-1.0000
-152	3.5296	1.0648	0.053351	0.12269	-1.0000
-157	3.5246	1.0633	0.053276	0.12251	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5296	1.0648	0.053351	0.12269	-1.0000
-157	3.5246	1.0633	0.053276	0.12251	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AV WOF	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5246	1.0633	0.053276	0.12251	-1.0000
-172	3.5246	1.0633	0.053276	0.12251	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3244	1.0029	0.050250	0.11556	-1.0000
-187	3.2343	0.97574	0.048888	0.11242	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

170

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.507	4.3736	0.21882	0.43755	0.43200
37	8.0015	2.4124	0.12070	0.24134	0.53000
47	9.3609	2.8222	0.14120	0.28234	0.62900
52	9.5508	2.8795	0.14407	0.28807	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.940	3.2983	0.16502	0.32997	0.42200
67	11.764	3.5468	0.17746	0.35483	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	26.488	7.9857	0.39955	0.79891	0.56400
82	8.1915	2.4666	0.12341	0.24677	0.63500
92	3.5413	1.0676	0.053418	0.10681	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	8.0265	2.4199	0.12107	0.24209	0.62400
112	3.9765	1.1989	0.059982	0.11994	0.83000
122	2.3555	0.71017	0.035532	0.071047	0.96000
127	3.5313	1.0646	0.053267	0.10651	1.0900
137	3.7214	1.1219	0.056134	0.11224	1.2200
142	3.6813	1.1099	0.055530	0.11104	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	8.0265	2.4199	0.12107	0.24209	-1.0000
-112	3.9763	1.1989	0.059982	0.11994	-1.0000
-122	2.3555	0.71017	0.035532	0.071047	-1.0000
-127	3.5313	1.0646	0.053267	0.10651	-1.0000
-137	3.7214	1.1219	0.056134	0.11224	-1.0000
-142	3.6813	1.1099	0.055530	0.11104	-1.0000
-152	3.5313	1.0646	0.053267	0.10651	-1.0000
-157	3.5313	1.0646	0.053267	0.10651	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5313	1.0646	0.053267	0.10651	-1.0000
-157	3.5313	1.0646	0.053267	0.10651	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5363	1.0661	0.053342	0.10666	-1.0000
-172	3.5313	1.0646	0.053267	0.10651	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3462	1.0088	0.050475	0.10093	-1.0000
-187	3.2611	0.99319	0.049192	0.098361	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

171

NASA-LEWIS   PRELIMINARY DATA   06/28/79   CADDFII   REC 10/18/79 01:24:38.484   FAC 8X6X1   PGM C034

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.257	3.3684	0.16882	0.43676	0.43200
37	6.2379	1.8663	0.093537	0.24199	0.53000
47	7.2874	2.1806	0.10929	0.28274	0.62900
52	7.4424	2.2269	0.11161	0.28876	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	8.5725	2.5651	0.12856	0.33260	0.42200
67	11.727	3.5090	0.17587	0.45499	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	26.677	7.9824	0.40008	1.0350	0.56400
82	8.2425	2.4664	0.12361	0.31980	0.63500
92	3.5892	1.0868	0.093468	0.23833	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	8.0825	2.4185	0.12121	0.31359	0.62400
112	3.9956	1.1956	0.059923	0.15503	0.83000
122	2.3690	0.70885	0.035528	0.091913	0.96000
127	3.5392	1.0578	0.053018	0.13716	1.0900
137	2.9446	0.88110	0.044161	0.11425	1.2200
142	2.9298	0.87661	0.043939	0.11367	1.3900

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	8.0825	2.4185	0.12121	0.31359	-1.0000
-112	3.9956	1.1956	0.059923	0.15503	-1.0000
-122	2.3690	0.70885	0.035528	0.091913	-1.0000
-127	3.5392	1.0578	0.053018	0.13716	-1.0000
-137	2.9446	0.88110	0.044161	0.11425	-1.0000
-142	2.9298	0.87661	0.043939	0.11367	-1.0000
-152	3.5602	1.0653	0.053393	0.13813	-1.0000
-157	3.5552	1.0638	0.053318	0.13794	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5602	1.0653	0.053393	0.13813	-1.0000
-157	3.5552	1.0638	0.053318	0.13794	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5552	1.0638	0.053318	0.13794	-1.0000
-172	3.5552	1.0638	0.053318	0.13794	-1.0000

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.3600	1.0054	0.050391	0.13037	-1.0000
-187	3.2600	0.97546	0.048890	0.12648	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS PRELIMINARY DATA CADDE-II FACILITY   BYEX1   PROGRAM C034 PDGS   1236 TO 1227
TIME AND DATE PROCESSED 04:08:35 JUN 11 1970

NOZZLE TYPE	P+W EJECTOR NOZZLE (MODEL A)
FLIGHT CONDITIONS	SUPER SONIC CRUISE (WS=.02 WT)
NOZZLE CONFIGURATION	A1
PRIMARY-NOZZLE PLUG	SPLIT PLUG (RETRACTED)
FLOW SPLITTER	CONICAL SPLITTER
FAN NOZZLE	IRIS
CLAMSHELL POSITION	
EJECTOR INLET OPENING	

PDC	MD	PTF/PTP	PTF/PO	PTP/PO	OMEGA	PTS/PTF	CDF	CDP	CF1	ETA1	ETA1,INT	CFP1	CFP2	F9
1236	0.938	2.30	18.85	8.21	0.000	0.150	0.992	0.985	0.9405	0.9405	0.9416	0.9416	0.9671	1.4795
1237	1.030	2.30	*****	*****	0.000	0.157	0.995	0.988	0.9125	0.9125	0.9125	0.9125	0.9126	1.4814
1238	1.953	7.34	19.84	8.60	0.000	0.158	0.991	0.987	0.9704	0.9704	0.9736	0.9736	0.9741	1.4842
1239	1.952	2.31	22.78	9.62	0.000	0.157	0.994	0.992	0.9756	0.9756	0.9784	0.9784	0.9789	1.4894
1240	1.954	2.32	25.15	10.84	0.000	0.155	0.993	0.990	0.9823	0.9823	0.9847	0.9847	0.9852	1.4928
1241	1.954	2.32	27.76	11.96	0.000	0.156	0.994	0.990	0.9841	0.9841	0.9863	0.9863	0.9867	1.4944
1242	1.954	2.31	29.18	12.66	0.000	0.158	0.994	0.995	0.9789	0.9789	0.9910	0.9810	0.9814	1.4989
1243	1.954	2.32	29.24	12.62	0.000	0.159	0.993	0.993	0.9838	0.9839	0.9860	0.9860	0.9864	1.4929
1244	1.952	2.33	27.65	11.89	0.000	0.159	0.995	0.990	0.9821	0.9821	0.9843	0.9843	0.9847	1.4922
1245	1.953	2.33	25.08	10.76	0.000	0.158	0.992	0.989	0.9800	0.9800	0.9824	0.9824	0.9829	1.4892
1246	1.954	2.30	22.35	9.71	0.000	0.159	0.993	0.989	0.9780	0.9780	0.9807	0.9807	0.9812	1.4905
1247	1.953	2.31	18.73	8.66	0.000	0.159	0.991	0.987	0.9731	0.9731	0.9803	0.9803	0.9838	1.4774
1248	1.954	1.99	19.88	9.08	0.018	0.159	0.962	0.989	0.9809	0.9839	0.9970	0.9975	1.4875
1249	1.953	2.30	19.84	8.69	0.019	0.159	0.961	0.988	0.9997	0.9856	0.9889	1.0029	1.0034	1.4949
1250	1.954	2.58	19.84	7.68	0.020	0.159	0.960	0.987	0.9971	0.9824	0.9859	1.0006	1.0011	1.4979
1251	1.955	2.01	22.44	11.15	0.018	0.159	0.963	0.991	0.9975	0.9840	0.9867	1.0002	1.0007	1.4897
1252	1.954	2.32	22.39	9.66	0.020	0.160	0.961	0.989	0.9988	0.9844	0.9872	1.0017	1.0022	1.4913
1253	1.953	2.59	22.43	8.69	0.020	0.160	0.960	0.989	0.9990	0.9839	0.9869	1.0020	1.0025	1.4936
1254	1.954	2.01	24.79	12.33	0.018	0.160	0.962	0.990	1.0015	0.9877	0.9900	1.0039	1.0044	1.4905
1255	1.955	2.34	24.86	10.64	0.020	0.159	0.962	0.991	1.0016	0.9868	0.9893	1.0041	1.0046	1.4942
1256	1.954	2.58	24.97	9.66	0.020	0.159	0.962	0.989	1.0023	0.9869	0.9895	1.0050	1.0054	1.4952
1257	1.954	2.07	27.19	13.15	0.019	0.159	0.964	0.994	1.0003	0.9862	0.9883	1.0025	1.0030	1.4915
1258	1.955	2.32	27.38	11.80	0.019	0.159	0.964	0.992	1.0015	0.9865	0.9888	1.0038	1.0043	1.4932
1259	1.954	2.59	27.52	10.61	0.020	0.159	0.963	0.991	1.0047	0.9889	0.9913	1.0071	1.0075	1.4983
1260	1.954	2.22	29.34	13.24	0.019	0.155	0.962	0.993	0.9997	0.9849	0.9869	1.0018	1.0022	1.4891
1261	1.954	2.33	29.27	12.62	0.020	0.155	0.963	0.990	1.0038	0.9885	0.9906	1.0058	1.0062	1.4941
1262	1.954	2.60	29.15	11.23	0.023	0.160	0.962	0.991	1.0060	0.9900	0.9922	1.0082	1.0086	1.4983
1263	1.953	2.60	29.25	11.24	0.020	0.159	0.964	0.991	1.0056	0.9896	0.9918	1.0078	1.0082	1.4995
1264	1.954	2.32	29.33	12.66	0.020	0.155	0.962	0.990	1.0049	0.9897	0.9918	1.0070	1.0074	1.4947
1265	1.954	2.60	27.51	13.55	0.025	0.156	0.961	0.988	1.0061	0.9903	0.9926	1.0085	1.0049	1.4975
1266	1.954	2.33	27.35	11.77	0.020	0.159	0.961	0.991	1.0020	0.9869	0.9892	1.0042	1.0047	1.4913
1267	1.954	2.09	27.38	13.16	0.019	0.155	0.961	0.991	1.0039	0.9896	0.9917	1.0061	1.0065	1.4924
1268	1.956	2.59	24.78	9.57	0.020	0.159	0.961	0.989	1.0044	0.9889	0.9916	1.0070	1.0075	1.4978
1269	1.954	2.33	24.80	10.65	0.023	0.159	0.962	0.990	1.0030	0.9882	0.9908	1.0056	1.0061	1.4947
1270	1.954	2.01	24.82	12.37	0.018	0.159	0.962	0.990	1.0022	0.9883	0.9907	1.0045	1.0050	1.4913
1271	1.953	2.59	22.38	9.64	0.020	0.155	0.960	0.989	0.9991	0.9839	0.9869	1.0021	1.0026	1.4931
1272	1.953	2.32	22.33	9.64	0.020	0.159	0.961	0.990	1.0014	0.9870	0.9899	1.0043	1.0048	1.4951
1273	1.954	2.01	22.43	11.14	0.018	0.160	0.960	0.989	1.0012	0.9876	0.9903	1.0039	1.0044	1.4911

NOZZLE TYPE	P+W EJECTOR NOZZLE (MODEL A)
FLIGHT CONDITIONS	SUPER SONIC CRUISE (WS=.02 WT)
NOZZLE CONFIGURATION	A1
PRIMARY-NOZZLE PLUG	SPLIT PLUG (RETRACTED)
FLOW SPLITTER	CONICAL SPLITTER
FAN NOZZLE	IRIS
CLAMSHELL POSITION	
EJECTOR INLET OPENING	

RDG	MD	PTF/PTP	PTF/PC	PTP/PO	OMEGA	PTS/PTF	CDF	CDP	CF1	ETA1	ETA1,INT	CFP1	CFP2	F9
1274	1.953	2.58	19.86	7.69	0.020	0.159	0.959	0.989	0.9943	0.9796	0.9830	0.9977	0.9982	1.4934
1275	1.954	2.33	19.93	4.65	0.020	0.159	0.960	0.989	1.0004	0.9863	0.9896	1.0036	1.0042	1.4974
1276	1.954	2.00	19.88	9.95	0.018	0.160	0.960	0.989	0.9990	0.9858	0.9889	1.0020	1.0026	1.4922
1277	1.954	2.59	37.48	10.61	0.020	0.160	0.963	0.990	1.0021	0.9863	0.9887	1.0045	1.0049	1.4942

174

NASA-LEWIS   PRELIMINARY DATA   04/11/79   CADDELL   PED 10/18/79 04:18:46.027   FAC 8X6X1   PGM C034   PDG 1248

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	14.526	4.3645	0.21959	0.43730	0.43200
37	8.0097	2.4362	0.12107	0.24139	0.53000
42	9.3636	2.8133	0.14155	0.28188	0.62900
52	9.5796	2.8779	0.14480	0.28835	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	10.993	3.3029	0.16619	0.33004	0.42200
67	11.348	3.4096	0.17155	0.34162	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	26.612	7.9956	0.40229	0.80113	0.56400
82	8.1537	2.4498	0.12326	0.24546	0.63500
92	3.5467	1.0656	0.053614	0.10677	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	6.8095	2.0456	0.10292	0.20494	0.62400
112	3.9170	1.1769	0.059212	0.11792	0.83000
122	2.2904	0.68815	0.034623	0.068950	0.96000
127	3.5266	1.0596	0.053311	0.10617	1.0900
137	3.6467	1.0957	0.055127	0.10978	1.2200
142	3.6067	1.0836	0.054522	0.10858	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	6.8085	2.0456	0.10292	0.20494	-1.0000
-112	3.9170	1.1769	0.059212	0.11792	-1.0000
-122	2.2904	0.68815	0.034623	0.068950	-1.0000
-127	3.5266	1.0596	0.053311	0.10617	-1.0000
-137	3.6467	1.0957	0.055127	0.10978	-1.0000
-142	3.6067	1.0836	0.054522	0.10858	-1.0000
-152	3.5316	1.0611	0.053387	0.10632	-1.0000
-157	3.5417	1.0641	0.053538	0.10662	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	3.5316	1.0611	0.053387	0.10632	-1.0000
-157	3.5417	1.0641	0.053538	0.10662	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-167	3.5417	1.0641	0.053538	0.10662	-1.0000
-172	3.5417	1.0641	0.053538	0.10662	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-182	3.2414	0.97388	0.048909	0.097579	-1.0000
-187	7.1943	3.56335	0.048938	0.096223	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/11/75   CADDELL   REC 10/18/75 04:19:19.785   FAC RX6X1   PGM C034   RDG 1249

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVO WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
32	12.675	3.7991	0.19011	0.43774	0.43200
37	6.9969	2.0973	0.10495	0.24143	0.53000
47	9.1968	2.4569	0.12254	0.28282	0.62900
52	8.3668	2.5079	0.12549	0.28870	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVO WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
62	9.6364	2.8894	0.14454	0.33251	0.42200
67	11.331	3.3962	0.16995	0.39096	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVO WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
77	26.791	5.0374	0.40169	0.92405	0.51400
82	8.2118	2.4614	0.12317	0.28335	0.63500
92	3.5507	1.0673	0.053408	0.12286	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVO WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
107	6.8669	2.0583	0.10300	0.23694	0.62400
112	3.9510	1.1843	0.059261	0.13633	0.83000
122	2.3147	0.69382	0.034719	0.079870	0.96000
127	3.5357	1.0598	0.053032	0.12200	1.0900
137	3.3106	0.99231	0.049655	0.11423	1.2200
142	3.1735	0.95032	0.047554	0.10940	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVO WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-107	6.8669	2.0583	0.10300	0.23694	-1.0000
-112	3.9510	1.1843	0.059261	0.13633	-1.0000
-122	2.3147	0.69382	0.034719	0.079870	-1.0000
-127	3.5357	1.0598	0.053032	0.12200	-1.0000
-137	3.3106	0.99231	0.049655	0.11423	-1.0000
-142	3.1735	0.95032	0.047554	0.10940	-1.0000
-152	3.5457	1.0628	0.053182	0.12235	-1.0000
-157	3.5507	1.0643	0.053257	0.12252	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVO WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-152	3.5457	1.0628	0.053182	0.12235	-1.0000
-157	3.5507	1.0643	0.053257	0.12252	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVO WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-167	3.5507	1.0643	0.053257	0.12252	-1.0000
-172	3.5507	1.0643	0.053257	0.12252	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVO WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-157	3.2505	0.97431	0.048755	0.11216	-1.0000
-162	3.2055	0.96082	0.048079	0.11061	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/11/79   CADDELL   REC 10/18/79 04:15:51.578   FAC 9X6X1   PGM C034   RDG 1250

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.241	3.3533	0.16536	0.43642	0.43200
37	6.5130	1.9549	0.09751A	0.24142	0.53000
47	7.2728	2.1604	0.10938	0.28237	0.62900
52	7.4328	2.2173	0.11179	0.28858	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	8.5573	2.5528	0.12870	0.33224	0.42200
67	11.276	3.3637	0.16958	0.43778	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	26.723	7.9719	0.40191	1.0375	0.56400
82	8.1775	2.4395	0.12259	0.31749	0.63500
52	3.5675	1.0643	0.053656	0.13851	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.8379	2.0399	0.10284	0.26548	0.62400
112	3.9327	1.1732	0.059148	0.15269	0.83000
122	2.2918	0.68369	0.034469	0.088980	0.96000
127	3.5375	1.0553	0.053204	0.13735	1.0900
137	3.0023	0.89563	0.045154	0.11656	1.2200
142	2.9672	0.85533	0.043122	0.11132	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.8379	2.0399	0.10284	0.26548	-1.0000
-112	3.9327	1.1732	0.059148	0.15269	-1.0000
-122	2.2918	0.68369	0.034469	0.088980	-1.0000
-127	3.5375	1.0553	0.053204	0.13735	-1.0000
-137	3.0023	0.89563	0.045154	0.11656	-1.0000
-142	2.8672	0.95533	0.043122	0.11132	-1.0000
-152	3.5575	1.0613	0.053505	0.13812	-1.0000
-157	3.5575	1.0613	0.053505	0.13812	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5575	1.0613	0.053505	0.13812	-1.0000
-157	3.5575	1.0613	0.053505	0.13812	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SIMPOD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-162	3.5525	1.0598	0.053432	0.13763	-1.0000
-172	3.5675	1.0613	0.053505	0.13812	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SIMPOD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.2474	0.96876	0.048841	0.12608	-1.0000
-187	3.2374	0.95682	0.048239	0.12453	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/11/79   CADDF11   REC 10/18/79 04:20:56.299   FAC 9X6X1   PGM C034   PPG 1251

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
33	16.293	4.8674	0.21693	0.43642	0.43200
37	9.0730	2.6922	0.11954	0.24060	0.53000
47	10.512	3.1405	0.13507	0.28171	0.62900
52	10.723	3.2047	0.14283	0.28747	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.336	3.6854	0.16425	0.33059	0.42200
67	11.252	3.3615	0.14981	0.33153	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	30.145	9.0058	0.40137	0.80786	0.56400
82	9.2779	2.7717	0.12353	0.24863	0.63500
92	3.5773	1.0697	0.047630	0.095865	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	7.7483	2.3148	0.10316	0.20764	0.62400
112	4.4728	1.3362	0.059553	0.11996	0.83000
122	2.6216	0.78319	0.034905	0.070254	0.96000
127	3.5673	1.0657	0.047497	0.095597	1.0900
137	4.1126	1.2286	0.054757	0.11021	1.2200
142	4.0626	1.2137	0.054091	0.10887	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.7483	2.3148	0.10316	0.20764	-1.0000
-112	4.4728	1.3362	0.059553	0.11996	-1.0000
-122	2.6216	0.78319	0.034905	0.070254	-1.0000
-127	3.5673	1.0657	0.047497	0.095597	-1.0000
-137	4.1126	1.2286	0.054757	0.11021	-1.0000
-142	4.0626	1.2137	0.054091	0.10887	-1.0000
-152	3.5723	1.0672	0.047563	0.095731	-1.0000
-157	3.5673	1.0657	0.047497	0.095597	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5723	1.0672	0.047563	0.095731	-1.0000
-157	3.5673	1.0657	0.047497	0.095597	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5723	1.0672	0.047563	0.095731	-1.0000
-172	3.5773	1.0687	0.047630	0.095865	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-177	3.2571	0.97155	0.043300	0.087150	-1.0000
-167	3.2123	0.95850	0.042767	0.086077	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.209	4.2283	0.18888	0.43779	0.43200
37	7.9378	2.3724	0.10413	0.24150	0.53000
47	9.1773	2.7211	0.12200	0.28277	0.62900
52	9.3632	2.7861	0.12445	0.28847	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.771	3.2056	0.14319	0.33189	0.42200
67	11.231	3.3422	0.14930	0.34605	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	30.152	8.9729	0.40082	0.92905	0.56400
82	9.2923	2.7653	0.12352	0.28632	0.63500
87	3.5874	1.0676	0.047688	0.11053	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	7.7678	2.3116	0.10326	0.23934	0.62400
112	4.4778	1.3325	0.059524	0.13797	0.83000
122	2.6169	0.77872	0.034785	0.080628	0.96000
127	3.5674	1.0616	0.047422	0.10992	1.0900
137	3.7274	1.1092	0.049550	0.11485	1.2200
142	3.5624	1.0601	0.047355	0.10976	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.7678	2.3116	0.10326	0.23934	-1.0000
-112	4.4778	1.3325	0.059524	0.13797	-1.0000
-122	2.6169	0.77872	0.034785	0.080628	-1.0000
-127	3.5674	1.0616	0.047422	0.10992	-1.0000
-137	3.7274	1.1092	0.049550	0.11485	-1.0000
-142	3.5624	1.0601	0.047355	0.10976	-1.0000
-152	3.5774	1.0646	0.047555	0.11023	-1.0000
-157	3.5774	1.0646	0.047555	0.11023	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5774	1.0646	0.047555	0.11023	-1.0000
-157	3.5774	1.0646	0.047555	0.11023	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5674	1.0616	0.047422	0.10992	-1.0000
-172	3.5774	1.0646	0.047555	0.11023	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.2672	0.97228	0.043431	0.10067	-1.0000
-187	3.2222	0.95888	0.042833	0.099282	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

PREPARATORY DATA   25/11/79   GARRETT   REC 10/16/79 04:22:18.47   FAC AV6PT   PGM C034   PDC 1253

>ADDITIONAL PRESSURE RATIOS, PRIMARY PLUG

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
22	12.464	7.9027	0.16944	0.43713	0.43200
32	7.6037	3.0082	0.69366	0.74172	0.53100
42	8.1232	2.4563	0.19971	0.39273	0.63900
52	8.3379	2.5274	0.11192	0.29939	0.72700

>ADDITIONAL PRESSURE RATIOS, FLOW SPLITTER I.D.

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
62	9.6719	2.9867	0.12885	3.33202	0.42200
67	11.165	3.3407	0.16951	0.39526	0.69200

>ADDITIONAL PRESSURE RATIOS, FLOW SPLITTER O.D.

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
77	70.019	8.2732	0.42052	1.0320	0.56400
82	9.2172	2.7653	0.12343	0.31804	0.63500
92	3.5503	1.0678	0.047662	0.12241	0.69200

>ADDITIONAL PRESSURE RATIOS, EJECTOR SHROUD

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
102	7.6913	2.3051	0.10289	0.26511	0.62500
112	4.4363	1.3303	0.059380	0.15301	0.83000
122	7.5840	0.77522	0.034602	0.089161	0.96009
132	3.5593	1.0568	0.047263	0.12178	1.0900
137	3.3742	1.0123	0.045184	0.11643	1.2200
142	3.7142	0.97029	0.043309	0.11169	1.3500

>ADDITIONAL PRESSURE RATIOS, FAN NOZZLE FLAP (COMMON FLANGE)

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
107	7.6913	2.3051	0.10289	0.26511	-1.0000
112	4.4363	1.3303	0.059380	0.15301	-1.0000
115	2.5840	0.77522	0.034602	0.089161	-1.0000
120	3.5593	1.0568	0.047260	0.12178	-1.0000
122	3.3742	1.0123	0.045184	0.11643	-1.0000
142	2.7042	0.97029	0.043300	0.11160	-1.0000
162	3.5643	1.0633	0.047461	0.12230	-1.0000
167	3.5643	1.0633	0.047461	0.12230	-1.0000

>ADDITIONAL PRESSURE RATIOS, 20 DEG SHROUD LOCATION

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
162	3.5643	1.0633	0.047461	0.12230	-1.0000
167	3.5643	1.0633	0.047461	0.12230	-1.0000

>ADDITIONAL PRESSURE RATIOS, 40 DEG SHROUD LOCATION

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
162	3.5643	1.0633	0.047461	0.12230	-1.0000
172	3.5593	1.0668	0.047528	0.12247	-1.0000

>SPATTER 5, MEASURED THRUST PARAMETERS

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
162	3.2202	2.96879	2.042242	2.11142	-1.0000
172	3.1342	2.95528	0.042630	0.12987	-1.0000

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	17.414	5.3944	0.21720	0.43470	0.43200
37	9.8446	2.9591	0.11937	0.23595	0.53000
47	11.538	3.4680	0.15993	0.28127	0.62900
52	11.782	3.5416	0.14286	0.28723	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	13.555	4.0744	0.16436	0.33045	0.42200
67	11.153	3.3524	0.13523	0.27189	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	32.439	9.8758	0.39819	0.80055	0.56400
82	10.179	3.0597	0.12343	0.24815	0.63500
92	3.5577	1.0694	0.043137	0.086729	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	8.4958	2.5537	0.10301	0.20711	0.62400
112	4.9176	1.4751	0.059506	0.11964	0.83000
122	2.8626	1.86043	0.034739	0.069784	0.96000
127	3.5427	1.0649	0.042955	0.086364	1.0900
137	4.5277	1.3609	0.054899	0.11038	1.2200
142	4.4677	1.3429	0.054171	0.10891	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	8.4958	2.5537	0.10301	0.20711	-1.0000
-112	4.9976	1.4751	0.059506	0.11964	-1.3000
-122	2.8626	0.86043	0.034709	0.069784	-1.0000
-127	3.5427	1.0649	0.042955	0.086364	-1.0000
-137	4.5277	1.3609	0.054899	0.11038	-1.0000
-142	4.4677	1.3429	0.054171	0.10891	-1.0000
-152	3.5427	1.0649	0.042955	0.086364	-1.0000
-157	3.5427	1.3649	0.042955	0.086364	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	3.5427	1.0649	0.042955	0.086364	-1.0000
-157	3.5427	1.0649	0.042955	0.086364	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-162	3.5427	1.0649	0.042955	0.086364	-1.0000
-172	3.5477	1.3466	0.043016	0.086485	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-192	3.2326	0.97166	0.039196	0.078805	-1.0000
-197	3.1936	0.95964	0.038711	0.077830	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/11/79   CADDELL   REC 10/18/79 04:24:07.449   FAC 9X6T1   PGM C034   RDG 1255

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.462	4.6569	0.18734	0.43777	0.43200
37	8.5367	2.5622	0.10307	0.24085	0.53000
47	9.9461	2.9957	0.12051	0.28161	0.62900
52	13.176	3.9659	0.12330	0.28812	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.465	3.5225	0.14170	0.33112	0.42230
67	11.130	3.3524	0.13486	0.31514	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.777	9.8721	0.39713	0.92831	0.56400
82	10.161	3.0604	0.12311	0.28769	0.63500
92	3.5413	1.0666	0.042907	0.10026	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	8.4918	2.5577	0.10289	0.24043	0.62400
112	4.9019	1.4764	0.059393	0.13879	0.83000
122	2.8458	0.85714	0.034481	0.080574	0.96000
127	3.5263	1.0621	0.042725	0.099840	1.0900
137	4.0415	1.2173	0.048969	0.11443	1.2200
142	3.8664	1.1645	0.046847	0.13947	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	8.4918	2.5577	0.10289	0.24043	-1.0000
-112	4.9019	1.4764	0.059393	0.13879	-1.0000
-122	2.8458	0.85714	0.034481	0.080574	-1.0000
-127	3.5263	1.0621	0.042725	0.059840	-1.0000
-137	4.0415	1.2173	0.048969	0.11443	-1.0000
-142	3.8664	1.1645	0.046847	0.10047	-1.0000
-152	3.5263	1.0621	0.042725	0.059840	-1.0000
-157	3.5363	1.0651	0.042847	0.10012	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5263	1.0621	0.042725	0.099840	-1.0000
-157	3.5363	1.0651	0.042847	0.10012	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5363	1.0651	0.042847	0.10012	-1.0000
-172	3.4313	1.0336	0.042786	0.096982	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-187	3.2461	0.97770	0.039331	0.091907	-1.0000
-197	3.2061	0.96565	0.038846	0.090774	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/11/79   CADDELL   PEC 10/18/79 04:24:37.625   FAC RX6X1   PGM C034   RDG 1256

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.014	4.2171	0.16891	0.43663	0.43200
37	7.7303	2.3261	0.093171	0.24084	0.53003
47	9.0342	2.7196	0.10989	0.28147	0.62900
52	9.2390	2.7892	0.11136	0.28786	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.623	3.1967	0.12804	0.33097	0.42200
67	11.137	3.3515	0.13424	0.34700	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.471	9.8917	0.39620	1.0242	0.56400
82	10.203	3.0704	0.12298	0.31790	0.63500
87	3.5537	1.0685	0.042797	0.11063	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	8.5595	2.5757	0.10317	0.26668	0.62400
112	4.9308	1.4838	0.059432	0.15363	0.83000
122	2.8704	0.86378	0.034598	0.089433	0.96000
127	3.5257	1.0609	0.042495	0.10985	1.0900
137	3.7357	1.1242	0.045027	0.11639	1.2200
142	3.5907	1.0835	0.043379	0.11187	1.3500

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	8.5595	2.5757	0.10317	0.26668	-1.0000
-112	4.9308	1.4838	0.059432	0.15363	-1.0000
-122	2.8704	0.86378	0.034598	0.089433	-1.0000
-127	3.5257	1.0609	0.042495	0.10985	-1.0000
-137	3.7357	1.1242	0.045027	0.11639	-1.0000
-142	3.5907	1.0835	0.043379	0.11187	-1.0000
-152	3.5357	1.0640	0.042616	0.11016	-1.0000
-157	3.5357	1.0640	0.042616	0.11016	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5357	1.0640	0.042616	0.11016	-1.0000
-157	3.5357	1.0640	0.042616	0.11016	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5407	1.0655	0.042676	0.11031	-1.0000
-172	3.5407	1.0655	0.042676	0.11031	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.2656	0.98262	0.039361	0.10174	-1.0000
-187	3.2236	0.96914	0.038818	0.10034	-1.0000

SECTION 5 , MEASURED TEST PARAMETERS

183

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	19.196	5.7550	0.21162	0.43753	0.43200
37	10.551	3.1648	0.11638	0.24061	0.53000
47	12.354	3.7057	0.13627	0.28173	0.62900
52	12.619	3.7851	0.13919	0.28777	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	14.517	4.3544	0.16012	0.33105	0.42200
67	11.145	3.3431	0.12293	0.25416	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	35.734	10.718	0.39414	0.81489	0.56400
82	11.180	3.3536	0.12332	0.25496	0.63500
92	3.5623	1.0685	0.039292	0.081237	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	9.3516	2.8050	0.10315	0.21326	0.62400
112	5.4027	1.6206	0.059592	0.12321	0.83000
122	3.1421	0.94249	0.034658	0.071654	0.96000
127	3.5573	1.0670	0.039237	0.081123	1.0900
137	4.8627	1.4586	0.053635	0.11089	1.2200
142	4.7827	1.4346	0.052753	0.10907	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	9.3516	2.8050	0.10315	0.21326	-1.0000
-112	5.4027	1.6206	0.059592	0.12321	-1.0000
-122	3.1421	0.94249	0.034658	0.071654	-1.0000
-127	3.5573	1.0670	0.039237	0.081123	-1.0000
-137	4.8627	1.4586	0.053635	0.11089	-1.0000
-142	4.7827	1.4346	0.052753	0.10907	-1.0000
-152	3.5623	1.0685	0.039292	0.081237	-1.0000
-157	3.5573	1.0670	0.039237	0.081123	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	3.5623	1.0685	0.039292	0.081237	-1.0000
-157	3.5573	1.0670	0.039237	0.081123	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-167	3.5525	1.0655	0.039182	0.081009	-1.0000
-172	3.5523	1.0655	0.039182	0.081009	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-182	3.2472	0.97400	0.035816	0.074050	-1.0000
-187	3.2372	0.96200	0.035275	0.073137	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	17.279	5.1539	0.18821	0.43602	0.43200
37	9.5038	2.8349	0.10357	0.24024	0.53000
47	11.132	3.3236	0.12126	0.28151	0.62500
52	11.362	3.3891	0.12376	0.28732	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	13.014	3.8921	0.14177	0.32912	0.47200
67	11.082	3.3057	0.12072	0.28025	0.65200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
72	36.065	10.758	0.39286	0.91204	0.56400
82	11.317	3.3757	0.12327	0.28619	0.63500
92	3.5821	1.0685	0.039020	0.090586	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	9.4538	2.8200	0.10298	0.23908	0.62400
112	5.4717	1.6322	0.059604	0.13837	0.83000
122	3.1820	0.94919	0.034662	0.080470	0.96000
127	3.5671	1.0640	0.038856	0.090206	1.0900
137	4.5320	1.3519	0.049367	0.11461	1.2200
142	4.3370	1.3037	0.047244	0.10968	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	9.4538	2.8200	0.10298	0.23908	-1.0000
-112	5.4717	1.6322	0.059604	0.13837	-1.0000
-122	3.1820	0.94919	0.034662	0.080470	-1.0000
-127	3.5671	1.0640	0.038856	0.090206	-1.0000
-137	4.5320	1.3519	0.049367	0.11461	-1.0000
-142	4.3370	1.3037	0.047244	0.10968	-1.0000
-152	3.5671	1.0640	0.038856	0.090206	-1.0000
-157	3.5771	1.0670	0.038965	0.090459	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	3.5671	1.0640	0.038856	0.090206	-1.0000
-157	3.5771	1.0670	0.038965	0.090459	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-167	3.5721	1.0655	0.038911	0.090333	-1.0000
-172	3.5771	1.0670	0.038965	0.090459	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-182	3.2670	0.97454	0.035599	0.082620	-1.0000
-187	3.2720	0.96117	0.035099	0.081491	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   26/11/79   CADDFII   REC 10/18/79 04:28:37.020   FAC RV6X1   PGM C034   ENG 1259

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.532	4.6352	0.16843	0.43696	0.43200
37	8.5595	2.5533	0.097779	0.24065	0.53030
47	10.324	2.9901	0.10965	0.28181	0.62900
52	10.229	3.0513	0.11087	0.28757	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.748	3.5043	0.12733	0.33027	0.62200
67	11.069	3.3016	0.11997	0.31117	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	36.233	10.808	0.39274	1.0187	0.56400
82	11.359	3.3880	0.12311	0.31932	0.63500
92	3.5745	1.0663	0.038745	0.10040	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	9.5191	2.8395	0.10318	0.26762	0.62400
112	5.4950	1.6392	0.059562	0.15440	0.83000
122	3.1943	0.95285	0.034624	0.089805	0.96000
127	3.5595	1.0618	0.038592	0.10007	1.0900
137	4.1397	1.2349	0.044872	0.11639	1.2200
142	3.9797	1.1871	0.043137	0.11189	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	9.5191	2.8395	0.10318	0.26762	-1.0000
-112	5.4950	1.6392	0.059562	0.15449	-1.0000
-122	3.1943	0.95285	0.034624	0.089805	-1.0000
-127	3.5595	1.0618	0.038592	0.10007	-1.0000
-137	4.1397	1.2349	0.044872	0.11639	-1.0000
-142	3.9797	1.1871	0.043137	0.11189	-1.0000
-152	3.5695	1.0648	0.038691	0.10035	-1.0000
-157	3.5645	1.0633	0.038636	0.10021	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5695	1.0648	0.038691	0.10035	-1.0000
-157	3.5645	1.0633	0.038636	0.10021	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5695	1.0648	0.038691	0.10035	-1.0000
-172	3.5695	1.0648	0.038691	0.10035	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.2693	0.97524	0.035437	0.091915	-1.0000
-187	3.2343	0.96475	0.035057	0.090930	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/11/79   CADDELL   REC 10/18/79 04:28:55.719   FAC 9X6X1   PGM C034   RDG 1268

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
32	19.225	5.7865	0.10724	0.43718	0.43200
37	10.563	3.1794	0.10837	0.24021	0.53000
47	12.391	3.7295	0.12712	0.28178	0.62900
52	12.655	3.8302	0.12984	0.28770	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
62	14.568	4.3847	0.14566	0.33128	0.42200
67	11.063	3.3297	0.11350	0.25157	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
77	38.130	11.477	0.39120	0.86711	0.56400
82	12.026	3.6198	0.12339	0.27349	0.63500
92	3.5528	1.0694	0.036450	0.080753	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
107	10.049	3.0246	0.10310	0.22852	0.62400
112	5.8122	1.7494	0.059631	0.13217	0.83000
122	3.3728	1.0152	0.034603	0.076699	0.96000
127	3.5528	1.0694	0.036450	0.080763	1.0900
137	4.9826	1.4997	0.051119	0.11331	1.2200
142	4.8176	1.4486	0.040375	0.10944	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-107	10.049	3.0246	0.10310	0.22852	-1.0000
-112	5.8122	1.7494	0.059631	0.13217	-1.0000
-122	3.3728	1.0152	0.034603	0.076699	-1.0000
-127	3.5528	1.0694	0.036450	0.080793	-1.0000
-137	4.9826	1.4997	0.051119	0.11331	-1.0000
-142	4.8176	1.4486	0.046375	0.10944	-1.0000
-152	3.5428	1.0663	0.036347	0.080565	-1.0000
-157	3.5428	1.0663	0.036347	0.080565	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-152	3.5428	1.0663	0.036347	0.080565	-1.0000
-157	3.5428	1.0663	0.036347	0.080565	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SIMPLON LOCATION

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-167	3.5428	1.0663	0.036347	0.080565	-1.0000
-172	3.5428	1.0663	0.036347	0.080565	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SIMPLON LOCATION

AVD WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-182	3.2278	0.97156	0.033114	0.073402	-1.0000
-187	3.1928	0.96100	0.032756	0.072606	-1.0000

>ADDITIONS , MEASURED THRUST PARAMETERS

187

NAS3-LEWIS   PRELIMINARY DATA   06/11/79   C/DDEJI   PEC 10/18/79 04:31:08,173   FAC BX6X1   PGM C034   PDG 1261

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	18.289	5.5074	0.18816	0.43638	0.43200
37	10.062	3.0300	0.10352	0.24008	0.53000
47	11.773	3.5455	0.12113	0.28052	0.62900
52	12.033	3.6236	0.12383	0.28712	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.889	4.1825	0.14289	0.33148	0.42200
67	11.000	3.3125	0.11317	0.26247	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	37.854	11.399	0.38945	0.90322	0.56400
82	11.968	3.6041	0.12313	0.28557	0.63500
92	3.5404	1.0662	0.036424	0.084477	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	10.017	3.0165	0.10306	0.23901	0.62400
112	5.7883	1.7431	0.059551	0.13811	0.83000
122	3.3605	1.0120	0.034574	0.080185	0.56000
127	3.5404	1.0662	0.036424	0.084477	1.0900
137	4.7943	1.4438	0.049325	0.11440	1.2200
142	4.5995	1.3851	0.047321	0.10975	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	10.017	3.0165	0.10306	0.23901	-1.0000
-112	5.7883	1.7431	0.059551	0.13811	-1.0000
-122	3.3605	1.0120	0.034574	0.080185	-1.0000
-127	3.5404	1.0662	0.036424	0.084477	-1.0000
-137	4.7943	1.4438	0.049325	0.11440	-1.0000
-142	4.5995	1.3851	0.047321	0.10975	-1.0000
-152	3.5304	1.0631	0.036322	0.084238	-1.0000
-157	3.5404	1.0662	0.036424	0.084477	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5304	1.0631	0.036322	0.084238	-1.0000
-157	3.5404	1.0662	0.036424	0.084477	-1.0000

>ADDITIONAL PRESSURE RATIOS , 70 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5404	1.0662	0.036424	0.084477	-1.0000
-172	3.5356	1.0647	0.036373	0.084357	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.2456	0.97738	0.033301	0.077443	-1.0000
-187	3.2355	0.96534	0.032500	0.076489	-1.0000

>SECTION 9 , MEASURED THRUST PARAMETERS

188

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	16.465	4.9330	0.16836	0.43464	0.47200
37	9.2684	2.7032	0.092729	0.24067	0.53039
47	10.626	3.1675	0.11866	0.29201	0.62500
52	10.946	3.2339	0.11050	0.28794	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	12.418	3.7016	0.12698	0.32956	0.42200
67	10.970	3.2702	0.11218	0.29115	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	38.111	11.360	0.38970	1.0114	0.56400
92	12.063	3.5960	0.12335	0.32016	0.63500
02	3.5438	1.0653	0.036646	0.095113	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTER SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	10.097	3.0098	0.10324	0.26796	0.62400
112	5.8372	1.7400	0.059688	0.15462	0.83000
122	3.3889	1.0102	0.034653	0.089940	0.96000
127	3.5688	1.0638	0.036493	0.094715	1.0900
137	4.3884	1.3081	0.044873	0.11646	1.2200
142	4.2285	1.2605	0.043238	0.11222	1.3500

>ADDITIONAL PRESSURE RATIOS , CONFARON INLEX

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	10.097	3.0098	0.10324	0.26796	-1.0000
-112	5.8372	1.7400	0.059688	0.15462	-1.0000
-122	3.3889	1.0102	0.034653	0.089940	-1.0000
-127	3.5688	1.0638	0.036493	0.094715	-1.0000
-137	4.3884	1.3081	0.044873	0.11646	-1.0000
-142	4.2285	1.2605	0.043238	0.11222	-1.0000
-152	3.5738	1.0653	0.036544	0.094847	-1.0000
-157	3.5738	1.0653	0.036544	0.094847	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	3.5738	1.0653	0.036544	0.094847	-1.0000
-157	3.5738	1.0653	0.036544	0.094847	-1.0050

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-167	3.5738	1.0653	0.036544	0.094847	-1.0000
-172	3.5738	1.0638	0.036595	0.094680	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-192	3.2590	0.97146	0.033324	0.086401	-1.0000
-197	3.7740	0.96104	0.032967	0.085563	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
22	16.413	4.8993	0.16749	0.43693	0.43200
37	9.0467	2.7004	0.092215	0.24033	0.53000
47	10.587	3.1602	0.10804	0.28126	0.62900
52	10.807	3.2257	0.11027	0.28708	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.437	3.7123	0.12691	0.33039	0.42200
67	10.951	3.2689	0.11175	0.29003	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	38.131	11.382	0.38910	1.0130	0.56400
82	12.083	3.6066	0.12330	0.32099	0.63500
92	3.5743	1.0669	0.036473	0.094953	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	10.114	3.0189	0.10320	0.26868	0.62400
112	5.8497	1.7461	0.059692	0.15540	0.83000
122	3.4046	1.0162	0.034741	0.090444	0.96000
127	3.5593	1.0624	0.036325	0.094555	1.0900
137	4.3928	1.3082	0.044723	0.11643	1.2200
142	4.2281	1.2620	0.043144	0.11232	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	10.114	3.0189	0.10320	0.26868	-1.0000
-112	5.8497	1.7461	0.059692	0.15540	-1.0000
-122	3.4046	1.0162	0.034741	0.090444	-1.0000
-127	3.5593	1.0624	0.036370	0.094555	-1.0000
-137	4.3928	1.3082	0.044723	0.11643	-1.0000
-142	4.2281	1.2620	0.043144	0.11232	-1.0000
-152	3.5693	1.0654	0.036422	0.094820	-1.0000
-157	3.5643	1.0639	0.036371	0.094687	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5693	1.0654	0.036422	0.094820	-1.0000
-157	3.5643	1.0639	0.036371	0.094687	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5743	1.0669	0.036473	0.094953	-1.0000
-172	3.5643	1.0639	0.036371	0.094687	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.2698	0.97601	0.033366	0.086864	-1.0000
-187	3.2399	0.96707	0.033060	0.086069	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	19.495	5.5244	0.18826	0.43641	0.43200
37	10.166	3.0360	0.10352	0.23583	0.53000
47	11.829	3.5544	0.12119	0.27078	0.62900
52	12.156	3.6303	0.12379	0.28478	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
42	13.978	4.1756	0.14237	0.32984	0.42200
47	10.947	3.2699	0.11149	0.25831	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	38.182	11.405	0.38887	0.90085	0.56400
82	12.089	3.6110	0.12312	0.28525	0.63500
52	3.5622	1.0640	0.036281	0.084056	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	10.114	3.0211	0.10301	0.23865	0.62400
112	5.8435	1.7455	0.059515	0.13748	0.83000
122	3.3975	1.0148	0.034602	0.080016	0.96000
127	3.5622	1.0640	0.036281	0.084056	1.0900
137	4.9502	1.4688	0.049399	0.11445	1.2200
142	4.6506	1.3891	0.047365	0.10974	1.3500

>ADDITIONAL PRESSURE RATIOS , EMERGON INLET

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	10.114	3.0211	0.10301	0.23865	-1.0000
-112	5.8435	1.7455	0.059515	0.13748	-1.0000
-122	3.3975	1.0148	0.034602	0.080016	-1.0000
-137	3.5622	1.0640	0.036281	0.084056	-1.0000
-137	4.9502	1.4688	0.049399	0.11445	-1.0000
-142	4.6506	1.3891	0.047365	0.10974	-1.0000
-152	3.5622	1.0640	0.036281	0.084056	-1.0000
-157	3.5622	1.0640	0.036281	0.084056	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5622	1.0640	0.036281	0.084056	-1.0000
-157	3.5622	1.0650	0.036281	0.084056	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD ROTATION

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
-147	3.5622	1.0640	0.036281	0.084056	-1.0000
-172	3.5572	1.0626	0.036230	0.083938	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD ROTATION

AVD WORD	PI	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.2576	0.97397	0.033179	0.076869	-1.0000
-187	3.2227	0.96263	0.032823	0.076044	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

191

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.352	4.6267	0.16817	0.43677	0.43200
37	8.4567	2.5486	0.092634	0.24059	0.53000
47	9.9363	2.9854	0.10851	0.29183	0.62900
52	10.116	3.0497	0.11081	0.28780	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER 1,D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.625	3.5335	0.12734	0.33074	0.42200
67	10.921	3.2912	0.11962	0.31069	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C,D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	35.610	10.732	0.39007	1.0131	0.56400
82	11.241	3.3875	0.12313	0.31979	0.63500
92	3.5407	1.0671	0.038785	0.10073	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	9.4165	2.8378	0.10315	0.26790	0.62400
112	5.4266	1.6354	0.059442	0.15439	0.83000
122	3.1505	0.94944	0.034510	0.089629	0.94000
127	3.5257	1.0625	0.038620	0.10031	1.0900
137	4.0911	1.2329	0.044813	0.11630	1.2200
142	3.9310	1.1847	0.043059	0.11184	1.3500

>ADDITIONAL PRESSURE RATIOS , SCREDODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	9.4165	2.8378	0.10315	0.26790	-1.0000
-112	5.4266	1.6354	0.059442	0.15439	-1.0000
-122	3.1505	0.94944	0.034510	0.089629	-1.0000
-127	3.5257	1.0625	0.038620	0.10031	-1.0000
-137	4.0911	1.2329	0.044813	0.11630	-1.0000
-142	3.9310	1.1847	0.043059	0.11184	-1.0000
-152	3.5307	1.0640	0.038675	0.10045	-1.0000
-157	3.5307	1.0640	0.038675	0.10045	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5307	1.0640	0.038675	0.10045	-1.0000
-157	3.5307	1.0640	0.038675	0.10045	-1.0000

>ADDITIONAL PRESSURE RATIOS , 30 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5407	1.0671	0.038785	0.10073	-1.0000
-172	3.5357	1.0655	0.038730	0.10055	-1.0000

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-132	3.2305	0.97354	0.035386	0.091907	-1.0000
-137	3.2355	0.96602	0.035112	0.091165	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS.

NASA-LEWIS   PRELIMINARY DATA   06/11/79   CANOELI   REC 10/18/79 04:35:55.341   FAC 9X6T1   PGM C034   RDG 1266

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
22	17.073	5.1468	0.18794	0.43744	0.43200
37	5.4015	2.9332	0.10346	0.24080	0.53000
47	11.030	3.3177	0.12115	0.28198	0.62500
52	11.239	3.3869	0.12369	0.28796	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.966	3.9078	0.14269	0.33210	0.42200
67	10.903	3.2846	0.11994	0.27917	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	35.522	10.705	0.39089	0.90981	0.56400
82	11.209	3.3779	0.12335	0.28709	0.63500
87	3.5409	1.0671	0.038965	0.090692	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	9.3666	2.8226	0.10307	0.23990	0.62400
112	5.4102	1.6304	0.059535	0.13857	0.83000
122	3.1460	0.94805	0.034619	0.080576	0.96300
127	3.5309	1.0641	0.038855	0.090436	1.0400
137	4.4706	1.3472	0.049196	0.11450	1.2200
142	4.2857	1.2915	0.047161	0.10977	1.3500

>ADDITIONAL PRESSURE RATIOS , PRIMARY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	9.3666	2.8226	0.10307	0.23990	-1.0000
-112	5.4102	1.6304	0.059535	0.13857	-1.0000
-122	3.1460	0.94805	0.034619	0.080576	-1.0000
-127	3.5309	1.0641	0.038855	0.090436	-1.0000
-137	4.4706	1.3472	0.049196	0.11450	-1.0000
-142	4.2857	1.2915	0.047161	0.10977	-1.0000
-152	3.5309	1.0641	0.038855	0.090436	-1.0000
-157	3.5359	1.0656	0.038910	0.090564	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5309	1.0641	0.038855	0.090436	-1.0000
-157	3.5359	1.0656	0.038910	0.090564	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5359	1.0656	0.038910	0.090564	-1.0000
-172	3.5309	1.0641	0.038855	0.090436	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-192	3.2160	0.96914	0.035399	0.082369	-1.0000
-197	3.1413	0.94671	0.034514	0.081729	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	19.172	5.7599	0.21031	0.43759	0.43200
37	10.521	3.1660	0.11566	0.24059	0.53000
47	12.313	3.7065	0.13537	0.24158	0.62900
52	12.573	3.7847	0.13822	0.28752	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.525	4.3722	0.15969	0.33215	0.42200
67	10.999	3.2812	0.11983	0.24926	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	35.556	10.703	0.39088	0.81308	0.56400
82	11.230	3.3804	0.12346	0.25682	0.63500
92	3.5508	1.0689	0.039036	0.081109	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	9.3821	2.8242	0.10314	0.21455	0.62400
112	5.4203	1.6316	0.059588	0.12395	0.83000
122	3.1558	0.94995	0.034693	0.072166	0.96000
127	3.5458	1.0673	0.038991	0.081085	1.0900
137	4.8655	1.4646	0.053480	0.11126	1.2200
142	4.7706	1.4360	0.052445	0.10909	1.3530

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	9.3821	2.8242	0.10314	0.21455	-1.0000
-112	5.4203	1.6316	0.059588	0.12395	-1.0000
-122	3.1558	0.94995	0.034693	0.072166	-1.0000
-127	3.5458	1.0673	0.038991	0.081085	-1.0000
-137	4.8655	1.4646	0.053480	0.11126	-1.0000
-142	4.7706	1.4360	0.052445	0.10909	-1.0000
-152	3.5358	1.0643	0.038871	0.080856	-1.0000
-157	3.5408	1.0658	0.038926	0.080970	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5358	1.0643	0.038871	0.080856	-1.0000
-157	3.5408	1.0658	0.038926	0.080970	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5408	1.0658	0.038926	0.080970	-1.0000
-172	3.5408	1.0658	0.038926	0.080970	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.2258	0.97103	0.035463	0.073767	-1.0000
-187	3.2303	0.96350	0.035189	0.073195	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

194

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.906	4.1817	0.16878	0.43710	0.43200
37	7.6721	2.3071	0.09311A	0.24115	0.53000
47	8.0712	2.6978	0.10986	0.28195	0.62900
52	9.1710	2.7579	0.11131	0.28827	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.550	3.1725	0.12805	0.33161	0.42200
57	10.845	3.2611	0.13162	0.34087	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.282	9.7078	0.39187	1.0147	0.56400
82	10.130	3.0463	0.12295	0.31862	0.63500
62	3.5479	1.0669	0.043062	0.11152	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	8.4916	2.5535	0.10306	0.26691	0.62400
112	4.8930	1.4714	0.059388	0.15366	0.83000
122	2.8477	0.85635	0.034564	0.089511	0.96000
127	3.5379	1.0669	0.042819	0.11089	1.0900
137	3.6929	1.1105	0.044822	0.11608	1.2200
142	3.5479	1.0669	0.043062	0.11152	1.3500

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	8.4916	2.5535	0.10306	0.26691	-1.0000
-112	4.8930	1.4714	0.059384	0.15385	-1.0000
-122	2.8477	0.85635	0.034564	0.089511	-1.0000
-127	3.5379	1.0669	0.042819	0.11089	-1.0000
-137	3.6929	1.1105	0.044822	0.11608	-1.0000
-142	3.5479	1.0669	0.043062	0.11152	-1.0000
-152	3.5479	1.0669	0.043062	0.11152	-1.0000
-157	3.5479	1.0669	0.043062	0.11152	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5479	1.0669	0.043062	0.11152	-1.0000
-157	3.5479	1.0669	0.043062	0.11152	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5429	1.0654	0.043001	0.11136	-1.0000
-172	3.5479	1.0669	0.043062	0.11152	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.2529	0.97818	0.039481	0.10224	-1.0000
-192	2.7224	0.96816	0.039117	0.10130	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

195

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
12	15.570	4.6452	0.19749	0.43661	0.43200
37	8.5454	2.5626	0.10330	0.24075	0.53000
47	10.053	3.00C9	0.12101	0.28181	0.62500
52	10.265	3.0653	0.12362	0.28784	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.780	3.5201	0.14195	0.33057	0.42200
67	10.824	3.2321	0.13034	0.30353	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.665	9.7538	0.39333	0.91599	0.56400
82	10.255	3.0620	0.12349	0.28756	0.63500
92	3.5799	1.3691	0.043137	0.10039	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	8.5604	2.5561	0.10308	0.24005	0.62400
112	4.9455	1.4767	0.059550	0.13868	0.83030
122	2.8795	0.85980	0.034672	0.080744	0.96000
127	3.5549	1.0615	0.042806	0.099685	1.0900
132	4.0852	1.2199	0.049191	0.11455	1.2200
142	3.9201	1.1705	0.047203	0.10993	1.3500

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	8.5604	2.5561	0.10308	0.24005	-1.0000
-112	4.9455	1.4767	0.059550	0.13868	-1.0000
-122	2.8795	0.85980	0.034672	0.080744	-1.0000
-127	3.5549	1.0615	0.042806	0.099685	-1.0000
-132	4.0852	1.2199	0.049191	0.11455	-1.0000
-142	3.9201	1.1705	0.047203	0.10993	-1.0000
-152	3.5649	1.0645	0.042926	0.099965	-1.0000
-157	3.5699	1.0660	0.042986	0.10011	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5649	1.0645	0.042926	0.099965	-1.0000
-157	3.5699	1.0660	0.042946	0.10011	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-162	3.5649	1.0645	0.042926	0.099965	-1.0000
-172	3.5649	1.0645	0.042926	0.099965	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.2307	0.96737	0.039010	0.090846	-1.0000
-187	3.2307	0.96840	0.039649	0.090065	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	18.164	5.4384	0.21791	0.43730	0.43200
37	9.8977	2.9739	0.11982	0.24051	0.53000
47	11.621	3.4912	0.14026	0.29153	0.62900
52	11.851	3.5596	0.14338	0.28778	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.749	4.0940	0.16495	0.33108	0.42200
67	10.707	3.2149	0.12953	0.26000	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	32.829	9.7752	0.39385	0.79053	0.56400
82	10.302	3.0677	0.12360	0.24809	0.63500
92	3.5790	1.0657	0.042937	0.086184	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	8.5835	2.5558	0.10298	0.20669	0.62400
112	4.9643	1.4782	0.059557	0.11954	0.83000
122	2.8887	0.86014	0.034656	0.069561	0.96000
127	3.5740	1.0642	0.042877	0.086063	1.0900
137	4.5893	1.3665	0.055058	0.11051	1.2200
142	4.5193	1.3457	0.054218	0.10883	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	8.5835	2.5558	0.10298	0.20669	-1.0000
-112	4.9643	1.4782	0.059557	0.11954	-1.0000
-122	2.8887	0.86014	0.034656	0.069561	-1.0000
-127	3.5740	1.0642	0.042877	0.086063	-1.0000
-137	4.5893	1.3665	0.055058	0.11051	-1.0000
-142	4.5193	1.3457	0.054218	0.10883	-1.0000
-152	3.5640	1.0612	0.042757	0.085822	-1.0000
-157	3.5740	1.0642	0.042877	0.086063	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5640	1.0612	0.042757	0.085822	-1.0000
-157	3.5740	1.0642	0.042877	0.086063	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5740	1.0642	0.042877	0.086063	-1.0000
-172	3.5690	1.0627	0.042817	0.085943	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.2539	0.96888	0.039037	0.078354	-1.0000
-187	3.2139	0.95696	0.038557	0.077391	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
52	12.577	3.7771	3.16875	0.43701	0.43203
57	6.9597	2.0875	0.093260	0.24152	0.53000
67	8.1353	2.4432	0.10915	0.28268	0.62503
57	8.3302	2.4928	0.11137	0.28941	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER T.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
57	9.5644	2.8724	0.12833	0.37234	0.42200
67	10.734	3.2235	0.14401	0.37296	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	29.571	8.8909	0.39676	1.0275	0.56400
82	9.2247	2.7704	0.12377	0.32053	0.63500
92	3.5507	1.0664	0.047641	0.12338	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	7.6655	2.3021	0.10285	0.26635	0.62400
112	4.4309	1.3307	0.059451	0.15396	0.83000
122	2.5803	0.77492	0.034629	0.089657	0.96000
127	3.5257	1.0589	0.047305	0.12251	1.0900
137	3.3556	1.0078	0.045023	0.11660	1.2200
142	3.2156	0.96572	0.043144	0.11173	1.3500

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	7.6655	2.3021	0.10285	0.26635	-1.0000
-112	4.4309	1.3307	0.059451	0.15396	-1.0000
-122	2.5803	0.77492	0.034629	0.089657	-1.0000
-127	3.5257	1.0589	0.047305	0.12251	-1.0000
-137	3.3556	1.0078	0.045023	0.11660	-1.0000
-142	3.2156	0.96572	0.043144	0.11173	-1.0000
-152	3.5407	1.0634	0.047504	0.12303	-1.0000
-157	3.5357	1.0619	0.047439	0.12286	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	3.5407	1.0634	0.047504	0.12303	-1.0000
-157	3.5357	1.0619	0.047439	0.12286	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-167	3.5357	1.0619	0.047439	0.12286	-1.0000
-172	3.5357	1.0619	0.047439	0.12286	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-187	3.2056	0.96271	0.043010	0.11138	-1.0000
-192	3.1908	0.95527	0.042674	0.11052	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

NASA-LEWIS   PRELIMINARY DATA   06/11/79   CADDELL   REC 10/18/79 04:42:12.407   FAC RX6X1   PGM C034   RDG 1272

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	M/PO	PL/PTF	PL/PTP	X/DMAX
32	14.038	4.2229	0.18508	1.43817	0.43200
37	7.7629	2.3292	0.10429	0.24168	0.53000
47	9.0573	2.7746	0.12200	0.28271	0.62900
52	9.2422	2.7902	0.12449	0.28848	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	10.646	3.2026	0.14340	0.33231	0.42200
67	10.711	3.2221	0.14427	0.33433	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	29.435	8.9546	0.39447	0.91877	0.56400
82	9.1722	2.7592	0.12356	0.28630	0.63500
92	3.5429	1.0658	0.047720	0.11059	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	M/PO	PL/PTF	PL/PTP	X/DMAX
107	7.6479	2.3006	0.10301	0.23872	0.62400
112	4.4131	1.3276	0.059442	0.13775	0.83000
122	2.5774	0.77532	0.034715	0.080448	0.96000
127	3.5229	1.0597	0.047455	0.10996	1.0400
137	3.6679	1.1034	0.049404	0.11449	1.2200
142	3.5129	1.0567	0.047316	0.10965	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.6479	2.3006	0.10301	0.23872	-1.0000
-112	4.4131	1.3276	0.059442	0.13775	-1.0000
-122	2.5774	0.77532	0.034715	0.080448	-1.0000
-127	3.5229	1.0597	0.047455	0.10996	-1.0000
-137	3.6679	1.1034	0.049404	0.11469	-1.0000
-142	3.5129	1.0567	0.047316	0.10965	-1.0000
-152	3.5379	1.0643	0.047653	0.11043	-1.0000
-157	3.5329	1.0628	0.047585	0.11027	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	M/PTF	PL/PTP	X/DMAX
-152	3.5379	1.0643	0.047653	0.11043	-1.0000
-157	3.5329	1.0528	0.047585	0.11027	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	M/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5329	1.0628	0.047585	0.11027	-1.0000
-172	3.5329	1.0628	0.047585	0.11027	-1.0000

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	M/PO	M/PTF	PL/PTP	X/DMAX
-182	3.2177	0.96795	0.043340	0.10044	-1.0000
-187	3.1827	0.95742	0.042869	0.099343	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

199

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	16.203	4.8756	0.21736	0.43768	0.43200
37	8.9250	2.6955	0.11973	0.24105	0.53000
47	10.435	3.1339	0.13909	0.28197	0.62900
52	10.660	3.2176	0.14301	0.29795	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	12.270	3.6919	0.16460	0.33143	0.42200
67	10.720	3.2256	0.14381	0.28957	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER D.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	29.596	8.9055	0.39704	0.79947	0.56400
82	9.2250	2.7758	0.12375	0.24919	0.63500
92	3.5570	1.0703	0.047717	0.096082	0.65200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	7.6947	2.3123	0.10309	0.20758	0.62400
112	4.4378	1.3353	0.059534	0.11988	0.83000
122	2.5958	0.77807	0.034689	0.069849	0.96000
127	3.5369	1.0643	0.047449	0.095541	1.0900
137	4.0925	1.2314	0.054901	0.11055	1.2200
142	4.0324	1.2134	0.054096	0.10893	1.3500

>ADDITIONAL PRESSURE RATIOS , FREEBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	7.6947	2.3123	0.10309	0.20758	-1.0000
-112	4.4378	1.3353	0.059534	0.11988	-1.0000
-122	2.5958	0.77807	0.034689	0.069849	-1.0000
-127	3.5369	1.0643	0.047449	0.095541	-1.0000
-137	4.0925	1.2314	0.054901	0.11055	-1.0000
-142	4.0324	1.2134	0.054096	0.10893	-1.0000
-152	3.5419	1.0658	0.047516	0.095676	-1.0000
-157	3.5369	1.0643	0.047449	0.095541	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5419	1.0658	0.047516	0.095676	-1.0000
-157	3.5369	1.0643	0.047449	0.095541	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5419	1.0658	0.047516	0.095676	-1.0000
-172	3.5369	1.0643	0.047449	0.095541	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.2166	0.96786	0.043151	0.086887	-1.0000
-187	3.1815	0.95732	0.042681	0.085941	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

Run 20

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.191	3.3620	0.16926	0.43728	0.43200
37	6.1856	1.8593	0.093553	0.24169	0.53000
47	7.2703	2.1690	0.10520	0.28211	0.62903
52	7.3899	2.2200	0.11177	0.28875	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	8.5109	2.5592	0.12884	0.33287	0.42200
67	10.682	3.2090	0.16155	0.41778	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	26.337	7.9121	0.39833	1.0291	0.56400
82	8.1393	2.4452	0.12319	0.31803	0.63500
92	3.5513	1.0669	0.053710	0.13876	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.8053	2.0444	0.10292	0.26591	0.62400
112	3.9213	1.1780	0.059306	0.15322	0.83000
122	2.2911	0.68827	0.034651	0.089521	0.96000
127	3.5263	1.0593	0.053332	0.13778	1.0900
137	2.9862	0.89711	0.045164	0.11668	1.2200
142	2.8562	0.85805	0.043198	0.11160	1.3500

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.8053	2.0444	0.10292	0.26591	-1.0000
-112	3.9213	1.1780	0.059306	0.15322	-1.0000
-122	2.2911	0.68827	0.034651	0.089521	-1.0000
-127	3.5263	1.0593	0.053332	0.13778	-1.0000
-137	2.9862	0.89711	0.045164	0.11668	-1.0000
-142	2.8562	0.85805	0.043158	0.11160	-1.0000
-152	3.5413	1.0639	0.053559	0.13837	-1.0000
-157	3.5413	1.0639	0.053559	0.13837	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5413	1.0639	0.053559	0.13837	-1.0000
-157	3.5413	1.0639	0.053559	0.13837	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5463	1.0654	0.053634	0.13857	-1.0000
-172	3.5413	1.0639	0.053559	0.13837	-1.0000

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-177	3.2513	0.97673	0.049173	0.12704	-1.0000
-182	3.2113	0.96471	0.048567	0.12548	-1.0000

SECTION 5 , MEASURED THRUST PARAMETERS

201

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.699	3.7825	0.18990	0.43715	0.43200
37	7.0179	2.0904	0.10489	0.24159	0.53000
47	8.2114	2.4457	0.12273	0.28267	0.62900
52	8.3912	2.4994	0.12542	0.28886	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	9.6543	2.8756	0.14439	0.33234	0.42200
67	10.668	3.1775	0.15944	0.36722	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	26.669	7.9436	0.33861	0.91805	0.56400
82	8.2514	2.4578	0.12333	0.28404	0.63500
92	3.5809	1.0666	0.053522	0.12327	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.8881	2.0517	0.10295	0.23712	0.62400
112	3.9707	1.1827	0.059348	0.13669	0.83000
122	2.3214	0.69145	0.034697	0.079911	0.96000
127	3.5609	1.0607	0.053223	0.12258	1.0900
137	3.3510	0.98920	0.049638	0.11432	1.2200
142	3.1811	0.94752	0.047546	0.10951	1.3500

>ADDITIONAL PRESSURE RATIOS , FORFBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.8881	2.0517	0.10295	0.23712	-1.0000
-112	3.9707	1.1827	0.059348	0.13669	-1.0000
-122	2.3214	0.69145	0.034697	0.079911	-1.0000
-127	3.5609	1.0607	0.053223	0.12258	-1.0000
-137	3.3510	0.98920	0.049638	0.11432	-1.0000
-142	3.1811	0.94752	0.047546	0.10951	-1.0000
-152	3.5709	1.0636	0.053373	0.12292	-1.0000
-157	3.5759	1.0651	0.053447	0.12310	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5709	1.0636	0.053373	0.12292	-1.0000
-157	3.5759	1.0651	0.053447	0.12310	-1.0000

>ADDITIONAL PRESSURE RATIOS , 30 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5759	1.0651	0.053447	0.12310	-1.0000
-172	3.5759	1.0651	0.053447	0.12310	-1.0000

>ADDITIONAL PRESSURE RATIOS , 60 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-182	3.2710	0.97491	0.048901	0.11260	-1.0000
-187	3.2361	0.96380	0.048368	0.11140	-1.0000

>OPTION 5 , MEASURED THRUST PARAMETERS

202

NASA-LEWIS   PRELIMINARY DATA   06/11/79   CADDEII   REC 10/18/79 04:45:22.290   FAC RKAX1   PG# C034   PDG 1276

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.586	4.3502	0.21881	0.43710	0.43200
37	8.0454	2.3994	0.12069	0.24109	0.53000
47	9.4189	2.8091	0.14129	0.28225	0.62900
52	9.6187	2.8687	0.14429	0.28824	0.72700

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	11.057	3.2976	0.16587	0.33123	0.47200
67	10.667	3.1814	0.16002	0.31966	0.69200

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	26.600	7.9332	0.39903	0.79711	0.56400
82	8.2202	2.4516	0.12331	0.24633	0.63500
92	3.5779	1.0671	0.053673	0.10722	0.69200

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	6.8514	2.0434	0.10278	0.20531	0.62400
112	3.9528	1.1789	0.059297	0.11845	0.83000
122	2.3179	0.69129	0.034771	0.069459	0.96000
127	3.5579	1.0598	0.053298	0.10647	1.0400
137	3.6679	1.0939	0.055022	0.10991	1.2200
142	3.6579	1.0920	0.054423	0.10871	1.3500

>ADDITIONAL PRESSURE RATIOS , EDEFACON INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	6.8514	2.0434	0.10278	0.20531	-1.0000
-113	3.9528	1.1789	0.059297	0.11845	-1.0000
-122	2.3179	0.69129	0.034771	0.069459	-1.0000
-127	3.5529	1.0598	0.053298	0.10647	-1.0000
-137	3.6679	1.0939	0.055022	0.10991	-1.0000
-142	3.6279	1.0820	0.054423	0.10871	-1.0000
-152	3.5679	1.0641	0.053523	0.10692	-1.0000
-157	3.5675	1.0641	0.053523	0.10692	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	3.5679	1.0641	0.053573	0.10692	-1.0000
-157	3.5679	1.0641	0.053523	0.10692	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-167	3.5629	1.0626	0.053448	0.10677	-1.0000
-172	3.5679	1.0641	0.053523	0.10692	-1.0000

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-18?	3.2579	0.97164	0.048873	0.097628	-1.0000
-187	3.2379	0.96575	0.048423	0.096729	-1.0000

>SECTION 5 , MEASURED THRUST PARAMETERS

TEST POINTS   PRELIMINARY DATA   04/11/79   CADRE11   REC 10/18/79 34:47:22.111   FM. REVI   PGM C036   RDG 1777

>ADDITIONAL PRESSURE RATIOS, PRIMARY PLUG

AVG HDRD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
22	15.602	6.6259	0.16423	0.43607	0.43200
32	8.5117	2.5497	0.09784	0.24076	0.53003
42	10.713	3.2017	0.12887	0.29400	0.62400
52	10.159	3.0469	0.12109	0.29723	0.72700

>ADDITIONAL PRESSURE RATIOS, FLOW SPLITTER I.D.

AVG HDRD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
62	11.721	3.5022	0.17764	0.33016	0.42700
67	10.597	3.1663	0.11522	0.29940	0.69200

>ADDITIONAL PRESSURE RATIOS, FLOW SPLITTER O.D.

AVG HDRD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
77	36.129	10.795	0.39287	1.0176	0.56400
82	11.357	3.3932	0.12358	0.21987	0.63500
92	3.5792	1.0494	0.038015	0.10081	0.69200

>ADDITIONAL PRESSURE RATIOS, EJECTOR SHROUD

AVG HDRD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
107	9.4582	2.8260	0.10284	0.26640	0.62400
117	5.4796	1.6372	0.059577	0.15434	0.83000
127	3.1891	0.95284	0.034673	0.089923	0.96000
127	3.5642	1.0619	0.038644	0.10011	1.0900
137	4.1294	1.2338	0.044897	0.11931	1.2200
142	3.9604	1.1860	0.043157	0.11140	1.3500

>ADDITIONAL PRESSURE RATIOS, FAN NOZZLE FLAP

AVG HDRD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-107	9.4582	2.8260	0.10284	0.26640	-1.0000
-117	5.4796	1.6372	0.059577	0.15434	-1.0000
-122	3.1891	0.95284	0.034673	0.089923	-1.0000
-127	3.5642	1.0619	0.038644	0.10011	-1.0000
-137	4.1294	1.2338	0.064897	0.11831	-1.0000
-142	3.9604	1.1860	0.043157	0.11140	-1.0000
-152	3.5642	1.0649	0.038752	0.10034	-1.0000
-157	3.5642	1.0649	0.038752	0.10039	-1.0000

>ADDITIONAL PRESSURE RATIOS, FAN NOZZLE FLAP

AVG HDRD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-152	3.5642	1.0649	0.038752	0.10039	-1.0000
-157	3.5642	1.0649	0.038755	0.10030	-1.0000

>ADDITIONAL PRESSURE RATIOS, 30 DEG SUPPORT LOCATION

AVG HDRD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-167	3.5592	1.0634	0.038698	0.10025	-1.0000
-172	3.5592	1.0634	0.038663	0.10025	-1.0000

>ADDITIONAL PRESSURE RATIOS, 90 DEG SUPPORT LOCATION

AVG HDRD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-177	3.2341	3.5629	0.035163	0.091091	-1.0000
-182	3.2341	0.95733	0.336917	0.090245	-1.0000

>SECTION 5, MEASURED THRUST PARAMETERS

NASA-LEWIS PRELIMINARY DATA CADDF-II FACILITY   9X6X1   PROGRAM CD34 PDGS   1349 TO 1407
TIME AND DATE PROCESSED 02:59:14 JUN 13 1979

NOZZLE TYPE	POW BASE EJECTOR NOZZLE (MODEL C)
FLIGHT CONDITIONS	TAKEOFF
NOZZLE CONFIGURATION	C3
PRIMARY-NOZZLE PLUG	SPLIT PLUG (EXTENDED)
FLOW SPLITTER	ISENTROPIC SPLITTER
FAN NOZZLE	SHORT FLAP
CLAMSHELL POSITION	17 DEG
EJECTOR INLET OPENING	MIDWAY

RDG	WD	PTF/PTP	PTF/P0	PTP/P0	OMEGA	PTS/PTF	CDF	CDP	CFI	ETAI	ETAI,INT	CFP1	CFP2	F0
1348	0.029	1.69	1.81	1.07	0.000	0.549	0.966	1.028	0.9512	0.9512	0.9512	0.9512	0.9524	••••••
1349	0.021	1.67	2.11	1.26	0.000	0.471	0.965	0.952	0.9512	0.9512	0.9512	0.9512	0.9539	••••••
1350	0.015	1.68	2.49	1.48	0.000	0.400	0.967	1.016	0.9295	0.9295	0.9295	0.9295	0.9327	••••••
1351	0.053	1.69	3.11	1.83	0.000	0.321	0.968	0.968	0.9185	0.9185	0.9185	0.9185	0.9212	••••••
1352	0.053	1.70	3.59	2.12	0.000	0.275	0.970	0.959	0.9461	0.9461	0.9461	0.9461	0.9483	••••••
1353	0.057	1.69	3.97	2.34	0.000	0.251	0.971	0.982	0.9438	0.9438	0.9438	0.9438	0.9458	••••••
1354	0.059	1.69	3.99	2.36	0.000	0.249	0.971	0.981	0.9445	0.9445	0.9445	0.9445	0.9445	••••••
1355	0.052	1.70	3.60	2.12	0.000	0.275	0.968	0.959	0.9448	0.9448	0.9448	0.9448	0.9478	••••••
1356	0.056	1.70	3.09	1.82	0.000	0.323	0.969	0.969	0.9140	0.9140	0.9141	0.9141	0.9168	••••••
1357	0.033	1.69	2.50	1.48	0.000	0.398	0.967	1.013	0.9224	0.9224	0.9224	0.9224	0.9256	••••••
1358	0.029	1.69	2.09	1.25	0.000	0.475	0.966	0.992	0.9428	0.9428	0.9428	0.9428	0.9454	••••••
1359	0.019	1.69	1.80	1.07	0.000	0.553	0.958	1.026	0.9313	0.9313	0.9313	0.9313	0.9324	••••••
1360	0.044	1.69	1.80	1.07	0.000	0.555	0.964	1.010	0.9366	0.9366	0.9366	0.9366	0.9378	••••••
1361	0.023	1.69	2.74	1.62	0.000	0.353	0.966	0.991	0.9134	0.9134	0.9134	0.9134	0.9165	••••••
1362	0.053	1.70	3.31	1.95	0.000	0.301	0.969	0.962	0.9229	0.9229	0.9229	0.9229	0.9254	••••••
1363	0.031	1.69	3.31	1.95	0.000	0.301	0.968	0.963	0.9239	0.9239	0.9239	0.9239	0.9263	••••••
1364	0.046	1.69	2.74	1.62	0.000	0.363	0.965	0.990	0.9164	0.9164	0.9165	0.9165	0.9196	••••••
1365	0.015	1.68	2.50	1.49	0.000	0.397	0.970	1.013	0.9231	0.9231	0.9231	0.9231	0.9263	••••••
1366	0.031	1.45	1.83	1.24	0.000	0.552	0.963	0.987	0.9450	0.9450	0.9450	0.9450	0.9482	••••••
1367	0.027	1.43	2.09	1.46	0.000	0.475	0.964	0.998	0.9561	0.9561	0.9561	0.9561	0.9508	••••••
1368	0.049	1.45	2.50	1.73	0.000	0.398	0.966	0.986	0.9264	0.9264	0.9264	0.9264	0.9299	••••••
1369	0.053	1.47	3.11	2.12	0.000	0.320	0.968	0.976	0.9194	0.9194	0.9194	0.9194	0.9220	••••••
1370	0.053	1.45	3.60	2.48	0.000	0.276	0.969	0.973	0.9412	0.9412	0.9413	0.9413	0.9434	••••••
1371	0.051	1.45	3.97	2.73	0.000	0.251	0.967	0.982	0.9422	0.9422	0.9422	0.9422	0.9441	••••••
1372	0.048	1.45	3.98	2.73	0.000	0.250	0.968	0.983	0.9427	0.9427	0.9427	0.9427	0.9446	••••••
1373	0.039	1.45	3.59	2.49	0.000	0.276	0.968	0.973	0.9511	0.9511	0.9511	0.9511	0.9532	••••••
1374	0.052	1.47	3.10	2.11	0.000	0.321	0.967	0.977	0.9214	0.9214	0.9215	0.9215	0.9240	••••••
1375	0.027	1.46	2.76	1.88	0.000	0.361	0.966	0.979	0.9210	0.9210	0.9211	0.9211	0.9241	••••••
1376	0.019	1.45	2.49	1.72	0.000	0.398	0.966	0.985	0.9279	0.9279	0.9279	0.9279	0.9314	••••••
1377	0.015	1.43	2.11	1.47	0.000	0.471	0.965	0.997	0.9483	0.9483	0.9483	0.9483	0.9522	••••••
1378	0.031	1.45	1.80	1.24	0.000	0.553	0.963	0.987	0.9461	0.9461	0.9461	0.9461	0.9494	••••••
1379	0.052	1.46	3.32	2.27	0.000	0.298	0.969	0.974	0.9332	0.9332	0.9332	0.9332	0.9356	••••••
1380	0.364	1.69	1.81	1.07	0.000	0.554	0.966	0.886	0.9012	0.9012	0.9036	0.9036	0.9067	••••••
1381	0.365	1.69	2.11	1.26	0.000	0.476	0.966	0.940	0.9154	0.9154	0.9171	0.9171	0.9196	••••••
1382	0.363	1.68	2.51	1.49	0.000	0.400	0.967	1.006	0.9074	0.9074	0.9086	0.9086	0.9117	••••••
1383	0.359	1.69	3.13	1.85	0.000	0.322	0.968	0.972	0.9016	0.9016	0.9024	0.9074	0.9051	••••••
1384	0.363	1.69	3.61	2.13	0.000	0.277	0.969	0.959	0.9298	0.9298	0.9305	0.9305	0.9327	••••••
1385	0.362	1.70	3.81	2.26	0.000	0.263	0.968	0.964	0.9346	0.9346	0.9352	0.9352	0.9373	••••••

NOZZLE TYPE   P&W BASE EJECTOR NOZZLE (MODEL C)
FLIGHT CONDITIONS   TAKEOFF
NOZZLE CONFIGURATION   C3
PRIMARY-NOZZLE PLUG   SPLIT PLUG (EXTENDED)
FLOW SPLITTER   ISENTROPIC SPLITTER
FAN NOZZLE   SHORT FLAP
CLAMSHELL POSITION   17 DEG
EJECTOR INLET OPENING   MIDWAY

PDG	MD	PTF/PTP	PTF/PO	PTP/PO	OMEGA	PTS/PTF	CDF	CDP	CFI	ETA1	ETA1,INT	CFP1	CFP2	FG
1386	0.360	1.69	3.81	2.25	0.000	0.262	0.969	0.964	0.9376	0.9376	0.9382	0.9382	0.9403	******
1387	0.363	1.70	3.61	2.13	0.000	0.277	0.969	0.959	0.9306	0.9306	0.9313	0.9313	0.9336	******
1388	0.364	1.69	3.11	1.84	0.000	0.325	0.968	0.973	0.9005	0.9005	0.9014	0.9014	0.9041	******
1389	0.358	1.68	2.50	1.49	0.000	0.431	0.967	1.004	0.9083	0.9083	0.9094	0.9094	0.9126	******
1390	0.359	1.69	2.12	1.26	0.000	0.472	0.965	0.945	0.9163	0.9163	0.9179	0.9179	0.9205	******
1391	0.362	1.69	1.81	1.07	0.000	0.552	0.965	0.988	0.8997	0.8997	0.9021	0.9021	0.9032	******
1392	0.362	1.69	2.74	1.62	0.000	0.367	0.967	0.969	0.9060	0.9060	0.9070	0.9070	0.9101	******
1393	0.356	1.66	1.91	1.25	0.000	0.555	0.965	0.960	0.9135	0.9135	0.9155	0.9155	0.9186	******
1394	0.361	1.44	2.11	1.47	0.000	0.476	0.967	0.990	0.9238	0.9238	0.9253	0.9253	0.9290	******
1395	0.362	1.45	2.51	1.73	0.000	0.399	0.968	0.984	0.9126	0.9126	0.9137	0.9137	0.9171	******
1396	0.358	1.47	2.75	1.88	0.000	0.365	0.968	0.981	0.9005	0.9005	0.9095	0.9095	0.9126	******
1397	0.358	1.47	3.12	2.13	0.000	0.323	0.967	0.979	0.9060	0.9060	0.9068	0.9068	0.9094	******
1398	0.363	1.45	3.62	2.50	0.000	0.277	0.966	0.973	0.9327	0.9327	0.9333	0.9333	0.9355	******
1399	0.359	1.45	3.79	2.61	0.000	0.264	0.969	0.975	0.9363	0.9363	0.9369	0.9369	0.9389	******
1400	0.361	1.45	3.79	2.61	0.000	0.265	0.969	0.974	0.9362	0.9362	0.9368	0.9368	0.9388	******
1401	0.365	1.45	3.62	2.50	0.000	0.277	0.970	0.972	0.9331	0.9331	0.9338	0.9338	0.9359	******
1402	0.359	1.46	3.12	2.13	0.000	0.323	0.968	0.979	0.9089	0.9089	0.9097	0.9097	0.9123	******
1403	0.359	1.47	2.76	1.88	0.000	0.364	0.967	0.980	0.9094	0.9094	0.9103	0.9103	0.9134	******
1404	0.362	1.43	2.11	1.47	0.000	0.476	0.967	0.979	0.9301	0.9301	0.9316	0.9316	0.9353	******
1405	0.359	1.44	1.92	1.26	0.000	0.551	0.965	0.960	0.9192	0.9192	0.9212	0.9212	0.9246	******
1406	0.363	1.69	3.42	2.02	0.000	0.295	0.970	0.963	0.9176	0.9176	0.9184	0.9184	0.9207	******
1407	0.360	1.44	3.43	2.37	0.000	0.291	0.970	0.975	0.9265	0.9265	0.9272	0.9272	0.9296	******

206

NASA-LEWIS   PRELIMINARY DATA   06/13/79   GARRETT   PEC 10/24/79 03:27:43.456   FAC 8X6X1   PGM C034   PRG 1348

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.211	0.98248	0.54316	0.91919	0.72200
37	14.470	1.0004	0.55337	0.93597	0.82000
47	14.565	1.0070	0.55670	0.94210	0.91900
52	14.605	1.0097	0.55822	0.94468	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.331	0.99076	0.54773	0.92693	0.42200
67	14.236	0.98421	0.54411	0.92080	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.529	0.86622	0.47888	0.81041	0.50800
82	16.022	1.1077	0.61238	1.0363	0.58300
92	14.415	0.99663	0.55098	0.93242	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.386	0.99456	0.54983	0.93048	-1.0000
-112	14.381	0.99421	0.54964	0.93016	-1.0000
-122	14.376	0.99387	0.54945	0.92984	-1.0000
-127	14.386	0.99456	0.54983	0.93048	-1.0000
-137	14.356	0.99249	0.54869	0.92855	-1.0000
-142	14.271	0.98662	0.54545	0.92306	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.386	0.99456	0.54983	0.93048	0.39800
112	14.381	0.99421	0.54964	0.93016	0.43100
122	14.376	0.99387	0.54945	0.92984	0.44900
127	14.386	0.99456	0.54983	0.93048	0.48600
137	14.356	0.99249	0.54869	0.92855	0.52200
142	14.271	0.98662	0.54545	0.92306	0.58800
-152	14.425	0.99732	0.55136	0.93307	-1.0000
-157	14.425	0.99732	0.55136	0.93307	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.425	0.99732	0.55136	0.93307	-1.0000
-157	14.425	0.99732	0.55136	0.93307	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.425	0.99732	0.55136	0.93307	0.79300
172	14.425	0.99732	0.55136	0.93307	0.84400

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.822	0.95557	0.52828	0.89401	0.79300
187	13.717	0.94833	0.52428	0.88723	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 297.31   FLC 296.33   SIGMA LC 2.7491   FTAPF-0.03945B   DSF 0.321821   CFM 2.9932123

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CARDFIT   REC 10/24/79 03:25:09.093   FAC 9X6X1   PGM C034   RPG 1349

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
22	13.922	0.96250	0.45664	0.76444	0.72200
27	14.821	1.0246	0.48609	0.81375	0.82000
47	15.085	1.0429	0.49477	0.82827	0.91900
52	15.185	1.0499	0.49804	0.83375	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.571	1.0073	0.47791	0.80005	0.42200
67	14.107	0.97526	0.46269	0.77458	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.311	0.85107	0.40377	0.67594	0.50000
82	16.826	1.1632	0.55188	0.92398	0.58300
92	14.402	0.99562	0.47235	0.79074	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.377	0.99389	0.47153	0.78937	-1.0000
-112	14.367	0.99320	0.47120	0.78882	-1.0000
-122	14.352	0.99217	0.47071	0.78800	-1.0000
-127	14.372	0.99355	0.47137	0.78910	-1.0000
-137	14.332	0.99079	0.47006	0.78690	-1.0000
-142	14.262	0.98596	0.46777	0.78307	-1.0000

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.377	0.99389	0.47153	0.78937	0.39000
112	14.367	0.99320	0.47120	0.78882	0.43100
122	14.352	0.99217	0.47071	0.78800	0.44900
127	14.372	0.99355	0.47137	0.78910	0.49600
137	14.332	0.99079	0.47006	0.78690	0.52200
142	14.262	0.98596	0.46777	0.78307	0.58000
152	14.416	0.99665	0.47284	0.79156	-1.0000
157	14.416	0.99665	0.47284	0.79156	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.416	0.99665	0.47284	0.79156	-1.0000
-157	14.416	0.99665	0.47284	0.79156	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.421	0.99700	0.47300	0.79184	0.79300
172	14.421	0.99700	0.47300	0.79184	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.719	0.94836	0.44993	0.75321	0.79300
187	13.578	0.93870	0.44534	0.74553	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FF-DI 428.37   FIC 427.62   SIGMA IC 1.4762   FTAPF-0.26267   DSW 0.012371   CFW 0.0033070

NASA-LEWIS   PRELIMINARY DATA   04/13/79   CARPETT   REC 10/24/79 03:30:39.626   FAC RX6X1   PG= C036   PRG 1350

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.259	0.83445	0.33565	0.56497	0.72200
37	14.929	1.0316	0.41496	0.69P43	0.82000
47	15.711	1.0871	0.43730	0.73606	0.91900
52	15.911	1.1009	0.44285	0.74560	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.713	1.0181	0.40953	0.68932	0.42200
67	12.518	0.96621	0.34843	0.58648	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	8.2714	0.57234	0.23022	0.38751	0.50800
82	20.659	1.4295	0.57501	0.96786	0.58700
92	14.384	0.99532	0.40036	0.67389	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.334	0.99187	0.39897	0.67156	-1.0000
-112	14.329	0.99152	0.39884	0.67132	-1.0000
-122	14.329	0.99152	0.39884	0.67132	-1.0000
-127	14.349	0.99290	0.39939	0.67226	-1.0000
-137	14.314	0.99048	0.39842	0.67062	-1.0000
-142	14.265	0.98703	0.39703	0.66829	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.334	0.99187	0.39897	0.67156	0.39800
112	14.329	0.99152	0.39884	0.67132	0.43100
122	14.329	0.99152	0.39884	0.67132	0.44960
127	14.349	0.99290	0.39939	0.67226	0.48600
137	14.314	0.99048	0.39842	0.67062	0.52200
142	14.265	0.98703	0.39703	0.66828	0.58800
152	14.399	0.99635	0.40078	0.67459	1.0000
157	14.399	0.99635	0.40078	0.67459	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.399	0.99635	0.40078	0.67459	-1.0000
-157	14.399	0.99635	0.40078	0.67459	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.399	0.99635	0.40078	0.67459	0.79300
172	14.399	0.99635	0.40078	0.67459	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.601	0.94112	0.37856	0.63720	0.79300
187	13.421	0.92869	0.37356	0.62878	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
(F-D) 573.92   FIC 571.32   SIGMA IC 1.3847   FTARF 0.10131   DSM 0.3369053   CFA 0.9035970

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CARDELL   REC 10/24/79 03:31:24.556   FAC 9X6FI   PGM C036   PRG 1351

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	8.1484	0.56431	0.19172	0.30773	0.72200
37	16.458	1.1398	0.38702	0.62155	0.82000
47	17.675	1.2241	0.39417	0.66752	0.91500
52	17.630	1.2209	0.39317	0.66582	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	18.244	1.2634	0.40685	0.68899	0.42200
67	15.749	1.0907	0.35122	0.59479	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	10.560	0.73129	0.23549	0.39880	0.50800
82	14.976	1.0371	0.33398	0.56559	0.58300
92	14.362	0.99466	0.32029	0.54241	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.302	0.99049	0.31896	0.54015	-1.0000
-112	14.297	0.99014	0.31885	0.53996	-1.0000
-122	14.297	0.99014	0.31885	0.53996	-1.0000
-127	14.322	0.99187	0.31940	0.54090	-1.0000
-137	14.287	0.98945	0.31862	0.53958	-1.0000
-142	14.258	0.98739	0.31796	0.53845	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.302	0.99049	0.31896	0.54015	0.39800
112	14.297	0.99014	0.31885	0.53996	0.43100
122	14.297	0.99014	0.31885	0.53996	0.44900
127	14.322	0.99187	0.31940	0.54090	0.48600
137	14.297	0.98945	0.31862	0.53958	0.52200
142	14.258	0.98738	0.31796	0.53845	0.58800
152	14.307	0.99636	0.32085	0.54335	-1.0000
157	14.307	0.99636	0.32085	0.54335	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.387	0.99636	0.32085	0.54335	-1.0000
-157	14.397	0.99636	0.32085	0.54335	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.392	0.99671	0.32096	0.54354	0.79300
172	14.392	0.99671	0.32096	0.54354	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/IMAX
182	13.474	0.93313	0.30049	0.50887	0.79300
187	13.290	0.91965	0.29615	0.50152	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-0) 795.69   FIC 754.20   SIGMA/C 1.2936   FTAPE 0.71493   DSP 0.066990   CFB 0.0029066

NASA-LEWIS   PRELIMINARY DATA   06/12/79   CADDET   REC 16/24/79 07:32:35.823   FAC RX6X1   PGM C036   RDG 1352

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.837	0.95886	0.26680	0.45291	0.72200
37	16.101	1.1158	0.31047	0.52703	0.82000
47	12.794	0.88661	0.24669	0.41878	0.91900
52	18.790	1.3021	0.36239	0.61503	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	21.428	1.4849	0.41318	0.70139	0.42200
67	18.455	1.2789	0.35586	0.60409	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.220	0.84694	0.23563	0.40000	0.50900
82	17.373	1.2039	0.33499	0.56866	0.58300
92	14.360	0.99516	0.27690	0.47005	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.290	0.99963	0.27536	0.46744	-1.0000
-112	14.271	0.98894	0.27517	0.46711	-1.0000
-122	14.261	0.98825	0.27497	0.46678	-1.0000
-127	14.295	0.99067	0.27565	0.46793	-1.0000
-137	14.251	0.98755	0.27478	0.46646	-1.0000
-142	14.211	0.98479	0.27401	0.46515	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.290	0.99963	0.27536	0.46744	0.39800
112	14.271	0.98894	0.27517	0.46711	0.43100
122	14.261	0.98825	0.27497	0.46678	0.44900
127	14.295	0.99067	0.27565	0.46793	0.48600
137	14.251	0.98755	0.27478	0.46646	0.52200
142	14.211	0.98479	0.27401	0.46515	0.58800
152	14.390	0.99723	0.27748	0.47103	-1.0000
157	14.395	0.99758	0.27757	0.47119	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.390	0.99723	0.27748	0.47103	-1.0000
-157	14.395	0.99758	0.27757	0.47119	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.390	0.99723	0.27748	0.47103	0.79300
172	14.395	0.99758	0.27757	0.47119	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.398	0.92844	0.25833	0.43875	0.79300
187	13.178	0.91323	0.25410	0.43135	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 1037.8   FLC 1006.3   SIGMA IC 2.8622   FTAPF 0.35028   DSM 0.066067   CFM 0.0029019

NASA-LEWIS   PRELIMINARY DATA   06/12/79   CADDET1   REC 10/24/79 03:33:53.373   F&C RKAY1   PGM CO36   PDG 1359

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	9.3540	0.64850	0.16343	0.27663	0.72200
37	18.113	1.2559	0.31646	0.53566	0.82000
47	14.221	0.99592	0.24846	0.42056	0.91900
52	20.396	1.3924	0.35089	0.59396	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	23.039	1.5972	0.40250	0.68130	0.42200
67	18.427	1.2775	0.32195	0.54495	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	13.432	0.93125	0.23469	0.39724	0.50800
82	19.171	1.3291	0.33494	0.56696	0.58300
92	14.356	0.99526	0.25081	0.42454	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	14.266	0.99903	0.24924	0.42188	-1.0000
-112	14.261	0.99868	0.24915	0.42174	-1.0000
-122	14.241	0.98730	0.24881	0.42115	-1.0000
-127	14.296	0.99041	0.24959	0.42247	-1.0000
-137	14.251	0.98799	0.24898	0.42144	-1.0000
-142	14.216	0.98557	0.24837	0.42041	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	14.266	0.99903	0.24924	0.42188	0.39800
112	14.261	0.99868	0.24915	0.42174	0.43100
122	14.241	0.98730	0.24881	0.42115	0.44900
127	14.296	0.99041	0.24959	0.42247	0.48600
137	14.251	0.98799	0.24898	0.42144	0.52200
142	14.216	0.98557	0.24837	0.42041	0.58800
-152	14.381	0.99699	0.25125	0.42528	-1.0000
-157	14.396	0.99733	0.25133	0.42543	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	14.381	0.99699	0.25125	0.42528	-1.0000
-157	14.396	0.99733	0.25133	0.42543	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
167	14.381	0.99699	0.25125	0.42528	0.79300
172	14.396	0.99733	0.25133	0.42543	0.84600

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
182	13.487	0.93505	0.23564	0.39886	0.79300
187	13.298	0.92191	0.23233	0.39325	0.84600

>SECTION 5 , MEASURED THRUST PARAMETERS

(F-D) 1159.8   FIC 1157.3   SIGMA IC 2.6336   FTARF 0.42937   DCW 0.075433   CEW 0.0028675

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   REC 10/24/79 03:34:46.902   FAC 9X6X1   PGM C034   PDG 1354

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	9.3447	0.64762	0.27445	0.27445	0.72200
37	18.298	1.2619	0.31607	0.53478	0.82000
47	14.321	0.99252	0.24859	0.42062	0.91900
52	20.164	1.3975	0.35002	0.59223	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	23.158	1.6049	0.40199	0.68015	0.42200
67	14.423	1.2768	0.31979	0.54108	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.558	0.93961	0.23534	0.39819	0.50800
82	19.316	1.3387	0.33530	0.56731	0.58300
92	14.356	0.99494	0.24920	0.42164	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.271	0.98906	0.24773	0.41915	-1.0000
-112	14.261	0.98837	0.24756	0.41886	-1.0000
-122	14.256	0.98803	0.24747	0.41871	-1.0000
-127	14.291	0.99045	0.24808	0.41974	-1.0000
-137	14.256	0.98803	0.24747	0.41871	-1.0000
-142	14.221	0.98561	0.24686	0.41769	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.271	0.98906	0.24773	0.41915	0.39800
112	14.261	0.98837	0.24756	0.41886	0.43100
122	14.256	0.98803	0.24747	0.41871	0.44900
127	14.291	0.99045	0.24808	0.41974	0.48600
137	14.256	0.98803	0.24747	0.41871	0.52200
142	14.221	0.98561	0.24686	0.41769	0.58800
-152	14.391	0.99737	0.24981	0.42267	-1.0000
-157	14.391	0.99737	0.24981	0.42267	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.391	0.99737	0.24981	0.42267	-1.0000
-157	14.391	0.99737	0.24981	0.42267	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.391	0.99737	0.24981	0.42267	0.79300
172	14.386	0.99702	0.24972	0.42252	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.503	0.93580	0.23439	0.39658	0.79300
187	13.313	0.92266	0.23110	0.39101	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FE-DI 1163.6   FLC 1167.9   SIGMA IC 2.5319   FTARE 2.65265   DSM 0.076646   CFM 0.0028631

NASA-LEWIS   PRELIMINARY DATA   06/13/79   GEOPGEI   REC 10/24/79 03:26:34.219   FAC RX6X1   PGM C034   PNG 1355

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.235	0.91648	0.25472	0.43247	0.72200
37	16.118	1.1161	0.31022	0.52669	0.82000
47	12.781	0.88504	0.24598	0.41764	0.91900
52	18.807	1.3023	0.36196	0.61455	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	21.415	1.4830	0.41217	0.69979	0.42200
67	18.413	1.2750	0.35434	0.60167	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.302	0.85187	0.23676	0.40198	0.50800
82	17.465	1.2094	0.33614	0.57070	0.58300
92	14.372	0.99525	0.27661	0.46964	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.287	0.98937	0.27498	0.46687	-1.0000
-112	14.273	0.98834	0.27469	0.46638	-1.0000
-122	14.273	0.98834	0.27465	0.46638	-1.0000
-127	14.307	0.99075	0.27537	0.46752	-1.0000
-137	14.263	0.98765	0.27450	0.46606	-1.0000
-142	14.218	0.98454	0.27364	0.46459	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.287	0.98937	0.27498	0.46687	0.39800
112	14.273	0.98834	0.27469	0.46638	0.43100
122	14.273	0.98834	0.27469	0.46638	0.44900
127	14.307	0.99075	0.27537	0.46752	0.48600
137	14.263	0.98765	0.27450	0.46606	0.52200
142	14.218	0.98454	0.27364	0.46459	0.58800
-152	14.397	0.99697	0.27719	0.47046	-1.0000
-157	14.407	0.99766	0.27729	0.47070	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.397	0.99697	0.27719	0.47046	-1.0000
-157	14.407	0.99766	0.27729	0.47070	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.402	0.99732	0.27719	0.47062	0.79300
172	14.402	0.99732	0.27719	0.47062	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.409	0.92857	0.25808	0.43818	0.79300
187	13.205	0.91440	0.25415	0.43149	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FE-21 1007.0   FIC 1006.0   SIGMA IC 1.650P   FTARF-0.063229   DSM 0.063969   CEM 0.0030387

NASA-LEWIS   PRELIMINARY DATA   06/12/79   CADDELL   REC 10/24/79 03:3P:27.84R   FAC RY6X1   PGM C934   PDG 1356

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	8.1036	0.56146	0.18183	0.30832	0.72200
37	16.486	1.1427	0.36991	0.62724	0.92000
47	17.619	1.2207	0.39533	0.67034	0.91900
52	17.594	1.2183	0.39454	0.66901	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	18.138	1.2567	0.40697	0.69009	0.42200
67	15.647	1.0841	0.35109	0.59534	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	10.556	0.73135	0.23685	0.40161	0.50800
82	14.944	1.0354	0.33530	0.56856	0.58300
92	14.370	0.99560	0.32242	0.56673	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.310	0.99145	0.32108	0.54445	-1.0000
-112	14.310	0.99145	0.32108	0.54445	-1.0000
-122	14.300	0.99077	0.32086	0.54407	-1.0000
-127	14.330	0.99283	0.32153	0.54521	-1.0000
-137	14.295	0.99041	0.32074	0.54388	-1.0000
-162	14.260	0.98799	0.31996	0.54255	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.310	0.99145	0.32108	0.54445	0.39800
112	14.310	0.99145	0.32108	0.54445	0.43100
122	14.300	0.99076	0.32086	0.54407	0.44900
127	14.330	0.99283	0.32153	0.54521	0.48600
137	14.295	0.99041	0.32074	0.54388	0.52200
142	14.260	0.98799	0.31996	0.54255	0.58800
-152	14.395	0.99733	0.32299	0.54767	-1.0000
-157	14.395	0.99733	0.32299	0.54767	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.395	0.99733	0.32299	0.54767	-1.0000
-157	14.395	0.99733	0.32299	0.54767	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.395	0.99733	0.32299	0.54767	0.79300
172	14.390	0.99698	0.32287	0.54748	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.476	0.93370	0.30238	0.51273	0.79300
187	13.271	0.91952	0.29778	0.50494	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

(F-D) 785.64   FIS 792.89   SIGMA LC 1.7352   FTAPE 0.69724   DSM 0.067186   CFM 0.0028963

215

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.054	0.83465	0.33415	0.56219	0.72200
37	14.934	1.0341	0.41398	0.69652	0.82000
47	15.743	1.0901	0.43640	0.73423	0.91900
52	15.937	1.1035	0.44179	0.74331	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.784	1.0237	0.40983	0.68954	0.42200
67	12.569	0.87025	0.34840	0.59618	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	8.2342	0.57015	0.22826	0.38404	0.50800
82	20.763	1.4377	0.57556	0.96837	0.58360
92	14.400	0.99709	0.39919	0.67161	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.350	0.99363	0.39789	0.66929	-1.0000
-112	14.340	0.99294	0.39752	0.66892	-1.0000
-122	14.335	0.99260	0.39738	0.66859	-1.0000
-127	14.355	0.99398	0.39794	0.66952	-1.0000
-137	14.320	0.99156	0.39697	0.66789	-1.0000
-142	14.270	0.98811	0.39558	0.66556	-1.0000

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.350	0.99363	0.39780	0.66929	0.30800
112	14.340	0.99294	0.39752	0.66882	0.43100
122	14.335	0.99260	0.39738	0.66859	0.44900
127	14.355	0.99398	0.39794	0.66952	0.48600
137	14.320	0.99156	0.39697	0.66789	0.52200
142	14.270	0.98811	0.39558	0.66556	0.58800
-152	14.410	0.99770	0.39946	0.67209	-1.0000
-157	14.415	0.99813	0.39960	0.67231	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE PTAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.410	0.59770	0.39946	0.67209	-1.0000
-157	14.415	0.99813	0.39960	0.67231	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.415	0.99813	0.39960	0.67231	0.79300
172	14.415	0.99813	0.39960	0.67231	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.607	0.94214	0.37718	0.63460	0.79300
187	13.427	0.92970	0.37220	0.62622	0.84400

>PORTION 5 , MEASURED THRUST PARAMETERS

TF-71 572.73   FI0 571.62   SIGMA IC 1.7718   FTAPE 0.090650   DSM 0.027370   CFM 0.0331615

RUN 22

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   REC 10/26/79 03:42:06.953   FAC 9X6X1   PGM C036   RDG 1358

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.961	0.96566	0.46230	0.77561	0.72200
37	14.799	1.0236	0.49006	0.82218	0.82000
47	15.048	1.0409	0.49832	0.83604	0.91900
52	15.148	1.0478	0.50162	0.84158	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.569	1.0078	0.48246	0.80943	0.42200
67	14.135	0.97773	0.46808	0.78531	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.369	0.85556	0.40959	0.68718	0.50900
82	16.660	1.1523	0.55167	0.92556	0.58300
92	14.410	0.99672	0.47717	0.80056	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.375	0.99430	0.47601	0.79862	-1.0000
-112	14.365	0.99361	0.47568	0.79806	-1.0000
-122	14.355	0.99292	0.47535	0.79751	-1.0000
-127	14.375	0.99430	0.47601	0.79862	-1.0000
-137	14.335	0.99154	0.47460	0.79640	-1.0000
-142	14.260	0.98636	0.47221	0.79224	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.375	0.99430	0.47601	0.79862	0.39800
112	14.365	0.99361	0.47568	0.79806	0.43100
122	14.355	0.99292	0.47535	0.79751	0.44900
127	14.375	0.99430	0.47601	0.79862	0.48600
137	14.335	0.99154	0.47460	0.79640	0.52200
142	14.260	0.98636	0.47221	0.79224	0.58800
-152	14.425	0.99775	0.47766	0.80139	-1.0000
-157	14.425	0.99361	0.47750	0.80111	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.425	0.99775	0.47766	0.80139	-1.0000
-157	14.425	0.99741	0.47750	0.80111	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.425	0.99775	0.47766	0.80139	0.79300
172	14.425	0.99775	0.47766	0.80139	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.721	0.94909	0.45437	0.76231	0.79300
187	13.571	0.94012	0.45007	0.75510	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 415.05   FIC 414.34   SIGMA IC 1.2498   FTAPE-0.015220   DSK 0.021766   CFN 0.0032089

217

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDE11   REC 13/24/79 02:44:21.133   FSC 8X6X1   PGM C034   PDG 1359

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.210	0.99237	0.54614	0.92188	0.72200
37	14.440	0.99961	0.55573	0.93808	0.82000
47	14.554	1.0062	0.55937	0.94421	0.91000
52	14.594	1.0089	0.56090	0.94680	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.340	0.99134	0.55113	0.93029	0.42200
67	14.230	0.99375	0.55691	0.92317	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.544	0.86716	0.49209	0.81376	0.50800
82	15.966	1.1038	0.61363	1.0358	0.58300
92	14.415	0.99651	0.55400	0.93515	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.390	0.99478	0.55306	0.93353	-1.0000
-112	14.380	0.99409	0.55266	0.93288	-1.0000
-122	14.375	0.99375	0.55247	0.93256	-1.0000
-127	14.390	0.99478	0.55306	0.93353	-1.0000
-137	14.355	0.99237	0.55170	0.93126	-1.0000
-142	14.275	0.98685	0.54863	0.92608	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.390	0.99478	0.55304	0.93353	0.39800
112	14.380	0.99409	0.55266	0.93288	0.43100
122	14.375	0.99375	0.55247	0.93256	0.44900
127	14.390	0.99478	0.55304	0.93353	0.48600
137	14.355	0.99237	0.55170	0.93126	0.52200
142	14.275	0.98685	0.54863	0.92608	0.58800
-152	14.435	0.99789	0.55477	0.93644	-1.0000
-157	14.430	0.99754	0.55459	0.93612	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.435	0.99789	0.55477	0.93644	-1.0000
-157	14.430	0.99754	0.55459	0.93612	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.430	0.99754	0.55458	0.93612	0.79300
172	14.425	0.99720	0.55439	0.93579	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.836	0.95650	0.53176	0.89760	0.79300
187	13.746	0.95029	0.52831	0.89178	0.84400

>>OPTION 5 , MEASURED THRUST PARAMETERS

TF-2) 295.16   FIC 284.67   SIGMA IC 1.0339   FTAPE-0.52279   DSM 0.010372   CFM 0.0336611

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CAODFII   REC 10/24/79 03:45:32.546   FAC 9X6X1   PGM C034   PDG 1360

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.210	0.98328	0.54757	0.92124	0.72200
37	14.459	1.0005	0.55718	0.93741	0.82000
47	14.544	1.0064	0.56045	0.94290	0.91900
52	14.586	1.0092	0.56198	0.94549	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.319	0.99088	0.55180	0.92835	0.42200
67	14.225	0.98432	0.54814	0.92221	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.518	0.86625	0.48240	0.81159	0.50800
82	15.976	1.1055	0.61561	1.0357	0.58300
92	14.409	0.99709	0.55526	0.93417	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTER SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.384	0.99536	0.55429	0.93256	-1.0000
-112	14.379	0.99502	0.55410	0.93223	-1.0000
-122	14.374	0.99467	0.55391	0.93191	-1.0000
-127	14.379	0.99502	0.55410	0.93223	-1.0000
-137	14.354	0.99329	0.55314	0.93062	-1.0000
-142	14.275	0.98777	0.55007	0.92544	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.384	0.99536	0.55429	0.93256	0.39800
112	14.379	0.99502	0.55410	0.93223	0.43100
122	14.374	0.99467	0.55391	0.93191	0.44900
127	14.379	0.99502	0.55410	0.93223	0.48600
137	14.354	0.99329	0.55314	0.93062	0.52200
142	14.275	0.98777	0.55007	0.92544	0.58800
-152	14.424	0.99813	0.55583	0.93514	-1.0000
-157	14.419	0.99778	0.55564	0.93482	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.424	0.99813	0.55583	0.93514	-1.0000
-157	14.419	0.99778	0.55564	0.93482	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.419	0.99778	0.55564	0.93482	0.79300
172	14.419	0.99778	0.55564	0.93482	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.821	0.95636	0.53257	0.89601	0.79300
187	13.731	0.95014	0.52911	0.89019	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
(F-D) 287.25   FIS 295.92   SIGMA LC 1.7510   FTAPF 0.49511   DSW 0.047554   CFW 0.0029979

<caption></caption>

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDE11   REC 10/24/79 02:48:18.693   FAC RX6V1   PGM C034   ORG 1361

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.824	0.81820	0.29836	0.50399	0.72200
37	14.958	1.0351	0.37746	0.63758	0.82000
47	16.205	1.1214	0.40892	0.69075	0.91900
52	16.454	1.1386	0.41522	0.70139	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER T.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	16.015	1.1083	0.40414	0.68267	0.42200
57	13.186	0.91248	0.33274	0.56207	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER D.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	9.1680	0.63442	0.23135	0.39079	0.50800
82	18.999	1.3147	0.47942	0.80986	0.58300
92	14.384	0.99536	0.36296	0.61312	0.67002

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.339	0.99225	0.36183	0.61121	-1.0000
-112	14.329	0.99156	0.36158	0.61078	-1.0000
-122	14.329	0.99156	0.36158	0.61078	-1.0000
-127	14.349	0.99294	0.36208	0.61163	-1.0000
-137	14.319	0.99087	0.36133	0.61036	-1.0000
-142	14.274	0.98776	0.36019	0.60844	-1.0000

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.339	0.99225	0.36183	0.61121	0.39800
112	14.329	0.99156	0.36158	0.61078	0.43100
122	14.329	0.99156	0.36158	0.61078	0.46900
127	14.349	0.99294	0.36208	0.61163	0.49600
137	14.319	0.99087	0.36133	0.61036	0.52200
142	14.274	0.98776	0.36019	0.60844	0.58800
-152	14.409	0.99708	0.36359	0.61418	-1.0000
-157	14.409	0.99708	0.36359	0.61418	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.409	0.99708	0.36359	0.61418	-1.0000
-157	14.439	0.99708	0.36359	0.61418	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.434	0.99674	0.36347	0.61397	0.79300
172	14.409	0.99708	0.36359	0.61418	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.590	0.93976	0.34269	0.57887	0.79300
187	13.391	0.92664	0.33791	0.57079	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

IF-11 657.83   FIC 657.28   SIGMA IC 1.0732   FTAPE-0.27270   DSM 0.014470   CFM 0.2033342

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFII   REC 10/24/79 03:50:14.996   FAC RVAVI   PGM C034   RPG 1362

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	9.4725	0.65628	0.19807	0.33645	0.72200
37	14.293	0.99028	0.25887	0.50768	0.82000
47	18.075	1.2523	0.37795	0.64199	0.91900
52	18.175	1.2592	0.38003	0.64553	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	19.586	1.3570	0.40955	0.69568	0.42200
67	16.918	1.1721	0.35375	0.60088	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	11.294	0.78250	0.23617	0.40116	0.50800
82	16.000	1.1085	0.33455	0.56828	0.58300
92	14.368	0.99547	0.30044	0.51033	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.293	0.99028	0.29887	0.50768	-1.0000
-112	14.278	0.98925	0.29856	0.50714	-1.0000
-122	14.293	0.98959	0.29867	0.50732	-1.0000
-127	14.308	0.99132	0.29919	0.50821	-1.0000
-137	14.273	0.98890	0.29846	0.50697	-1.0000
-142	14.238	0.98648	0.29773	0.50573	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.293	0.99028	0.29887	0.50768	0.39800
112	14.278	0.98925	0.29856	0.50714	0.43100
122	14.293	0.98959	0.29867	0.50732	0.44900
127	14.308	0.99132	0.29919	0.50821	0.48600
137	14.273	0.98890	0.29846	0.50697	0.52200
142	14.238	0.99648	0.29773	0.50573	0.58800
-152	14.393	0.99720	0.30096	0.51122	-1.0000
-157	14.398	0.99754	0.30107	0.51140	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.393	0.99720	0.30096	0.51122	-1.0000
-157	14.398	0.99754	0.30107	0.51140	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.393	0.99720	0.30096	0.51122	0.79300
172	14.393	0.99720	0.30096	0.51122	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.465	0.93290	0.28156	0.47824	0.79300
187	13.260	0.91872	0.27729	0.47000	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 876.52   FIC 875.29   SIGMA IC 2.4867   FTAPE 0.16194   DSM 0.064801   CFH 0.0029051

221

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CARDELL   PFC 10/24/79 03:52:52.151   FAC 9V6%I   PGM C034   RDS 1363

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	9.3299	0.64631	0.19543	0.33101	0.72200
37	14.257	0.98759	0.29864	0.50580	0.82000
47	19.379	1.2524	0.37870	0.64140	0.91900
52	18.193	1.2633	0.38110	0.64547	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	19.620	1.3592	0.41100	0.69610	0.42200
67	16.926	1.1725	0.35456	0.60051	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	11.262	0.78015	0.23591	0.39955	0.50800
82	15.969	1.1062	0.33449	0.56652	0.58300
92	14.366	0.99520	0.30093	0.50969	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.291	0.99001	0.29937	0.50704	-1.0000
-112	14.291	0.98932	0.29916	0.50668	-1.0000
-122	14.291	0.98932	0.29916	0.50668	-1.0000
-127	14.306	0.99105	0.29968	0.50757	-1.0000
-137	14.266	0.98828	0.29884	0.50615	-1.0000
-142	14.232	0.98587	0.29811	0.50491	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.291	0.99001	0.29937	0.50704	0.39800
112	14.291	0.98932	0.29916	0.50668	0.43100
122	14.291	0.98932	0.29916	0.50668	0.44900
127	14.306	0.99105	0.29968	0.50757	0.48600
137	14.266	0.98828	0.29884	0.50615	0.52200
142	14.232	0.98587	0.29811	0.50491	0.58800
-152	14.391	0.99693	0.30146	0.51058	-1.0000
-157	14.391	0.99693	0.30146	0.51058	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.391	0.99693	0.30146	0.51058	-1.0000
-157	14.391	0.99693	0.30146	0.51058	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.391	0.99693	0.30146	0.51058	0.79300
172	14.391	0.99693	0.30146	0.51058	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.463	0.93263	0.28201	0.47764	0.79300
187	13.249	0.91776	0.27752	0.47003	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FS-D] 875.78   FIC 876.86   SIGMA IC 1.5332   FTAPF-0.097231   DSW 0.024511   CEW 0.003177A

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   PFC 10/24/79 03:55:18.699   FRC RX6YI   PGM C036   PPG 1366

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.823	0.81924	0.29855	0.50538	0.72200
37	14.941	1.0353	0.37729	0.63866	0.82000
47	16.174	1.1207	0.40840	0.69133	0.91900
52	16.439	1.1390	0.41509	0.70263	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	15.969	1.1065	0.40324	0.68258	0.42200
67	13.160	0.91190	0.33232	0.56253	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	9.1334	0.63286	0.23063	0.39040	0.50800
82	18.957	1.3135	0.47868	0.81029	0.58300
92	14.383	0.99659	0.36318	0.61478	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.333	0.99313	0.36192	0.61265	-1.0000
-112	14.323	0.99244	0.36167	0.61222	-1.0000
-122	14.323	0.99244	0.36167	0.61222	-1.0000
-127	14.343	0.99382	0.36217	0.61307	-1.0000
-137	14.319	0.99219	0.36154	0.61201	-1.0000
-142	14.269	0.98864	0.36028	0.60987	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.333	0.99313	0.36192	0.61265	0.39800
112	14.323	0.99244	0.36167	0.61222	0.43100
122	14.323	0.99244	0.36167	0.61222	0.44900
127	14.343	0.99382	0.36217	0.61307	0.48600
137	14.319	0.99219	0.36154	0.61201	0.52200
142	14.269	0.98864	0.36028	0.60987	0.58800
152	14.438	0.99832	0.36381	0.61585	-1.0000
157	14.493	0.99797	0.36369	0.61563	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.438	0.99832	0.36381	0.61585	-1.0000
-157	14.493	0.99797	0.36369	0.61563	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.438	0.99832	0.36381	0.61585	0.79360
172	14.438	0.99832	0.36381	0.61585	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.589	0.94094	0.34290	0.58045	0.79300
187	13.395	0.92814	0.33824	0.57256	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FF=91 658.47   FIC 657.19   SIGMA LC 1.7248   FTPPF 0.22954   DS9 0.051415   CF9 1.0029656

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDEII   REC 10/24/79 03:56:27.786   FOR 9X6X1   PGM C034   PDG 1365

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.995	0.82982	0.33169	0.55652	0.72200
37	14.974	1.0290	0.41130	0.69061	0.82000
47	15.737	1.0887	0.43516	0.73069	0.91900
52	15.942	1.1029	0.44082	0.74019	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.804	1.0242	0.40936	0.69737	0.42200
67	12.524	0.86642	0.34631	0.58149	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	8.2011	0.56736	0.22677	0.38078	0.50800
82	20.921	1.4404	0.57573	0.96473	0.58300
92	14.390	0.99553	0.39791	0.66814	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.343	0.99208	0.39653	0.66583	-1.0000
-112	14.335	0.99173	0.39639	0.66559	-1.0000
-122	14.335	0.99173	0.39639	0.66559	-1.0000
-127	14.350	0.99277	0.39681	0.66629	-1.0000
-137	14.325	0.99104	0.39612	0.66513	-1.0000
-152	14.275	0.98759	0.39474	0.66281	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.340	0.99208	0.39653	0.66583	0.39800
112	14.335	0.99173	0.39639	0.66559	0.43100
122	14.335	0.99173	0.39639	0.66559	0.44900
127	14.350	0.99277	0.39681	0.66629	0.48600
137	14.325	0.99104	0.39612	0.66513	0.52200
142	14.275	0.98759	0.39474	0.66281	0.58800
-152	14.405	0.99656	0.39833	0.66884	-1.0000
-157	14.410	0.99691	0.39846	0.66907	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.405	0.99656	0.39833	0.66884	1.0000
-157	14.410	0.99691	0.39846	0.66907	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.400	0.99622	0.39819	0.66861	0.79300
172	14.400	0.99622	0.39819	0.66861	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.597	0.94064	0.37597	0.63131	0.79300
187	13.417	0.92821	0.37101	0.62297	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FG-PI 577.20   FIC 576.58   SIGMA-IC 2.5684   FTAPE-0.39308   DSP 0.0358995   CFM 0.3135778

224

VASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDETT   PFC 10/24/79 03:57:36.639   FAC 8X6X1   PGM C034   PDG 1366

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.932	0.96425	0.53445	0.77613	0.72200
37	14.716	1.0185	0.56453	0.81981	0.82000
47	14.940	1.0341	0.57315	0.83232	0.91900
52	15.030	1.0403	0.57660	0.83733	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
52	14.566	1.0081	0.55878	0.81146	0.42200
67	14.156	0.97960	0.54307	0.78865	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.568	0.86989	0.48215	0.70018	0.50800
82	16.024	1.1091	0.61471	0.89268	0.58300
92	14.406	0.99708	0.55265	0.80256	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.371	0.99466	0.55131	0.80061	-1.0000
-112	14.371	0.99466	0.55131	0.80061	-1.0000
-122	14.366	0.99432	0.55112	0.80033	-1.0000
-127	14.376	0.99501	0.55150	0.80089	-1.0000
-137	14.346	0.99294	0.55035	0.79922	-1.0000
-142	14.271	0.98775	0.54748	0.79505	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.371	0.99466	0.55131	0.80061	0.39800
112	14.371	0.99466	0.55131	0.80061	0.43100
122	14.366	0.99432	0.55112	0.80033	0.44900
127	14.376	0.99501	0.55150	0.80089	0.48600
137	14.346	0.99294	0.55035	0.79922	0.52200
142	14.271	0.98775	0.54749	0.79505	0.58800
152	14.416	0.99777	0.55303	0.80311	-1.0000
157	14.421	0.99812	0.55323	0.80339	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.416	0.99777	0.55303	0.80311	-1.0000
157	14.421	0.99812	0.55323	0.80339	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.416	0.99777	0.55303	0.80311	0.79300
172	14.416	0.99777	0.55303	0.80311	0.84400

>ADDITIONAL PRESSURE RATIOS , 50 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.817	0.95630	0.52005	0.76973	0.79300
187	13.712	0.94904	0.52602	0.76389	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 337.67   FI* 376.47   SIGMA IC 1.5366   FTAPF 0.18166   DSM 0.024485   CFN 0.0031730

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	12.651	0.87534	0.41858	0.59895	0.72200
37	14.939	1.0336	0.49426	0.70618	0.82000
47	15.433	1.0658	0.50963	0.72814	0.91900
52	15.573	1.0775	0.51525	0.73617	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	15.028	1.0398	0.49724	0.71043	0.42200
67	13.530	0.93617	0.44766	0.63960	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	12.331	0.85322	0.40800	0.58293	0.50800
82	16.596	1.1483	0.54912	0.78456	0.58300
92	14.399	0.99630	0.47642	0.68069	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	14.354	0.99319	0.47493	0.67856	-1.0000
-112	14.344	0.99250	0.47460	0.67809	-1.0000
-122	14.344	0.99250	0.47460	0.67809	-1.0000
-127	14.359	0.99354	0.47509	0.67880	-1.0000
-137	14.319	0.99077	0.47377	0.67691	-1.0000
-142	14.244	0.98559	0.47129	0.67337	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	14.354	0.99319	0.47493	0.67856	0.39800
112	14.344	0.99250	0.47460	0.67809	0.43100
122	14.344	0.99250	0.47460	0.67809	0.44900
127	14.359	0.99354	0.47509	0.67880	0.48600
137	14.319	0.99077	0.47377	0.67691	0.52200
142	14.244	0.98559	0.47129	0.67337	0.58800
-152	14.409	0.99699	0.47679	0.68116	-1.0000
-157	14.414	0.99734	0.47691	0.68140	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	14.409	0.99699	0.47675	0.68116	-1.0000
-157	14.414	0.99734	0.47691	0.68140	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
167	14.414	0.99734	0.47691	0.68140	0.79300
172	14.414	0.99734	0.47691	0.68140	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
182	13.715	0.94896	0.45378	0.64834	0.79300
187	13.500	0.94032	0.44964	0.64244	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

IF-DI 449.62   FIC 468.65   SIGMA IC 2.2679   FTAPF 0.0050704   DSM 0.019160   CFM 0.0032442

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.525	0.72889	3.39141	0.42168	0.72200
37	14.337	0.97005	0.38787	0.56120	0.82003
47	15.321	1.0956	0.43804	0.63785	0.91900
52	14.370	1.1337	0.45325	0.65586	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	16.865	1.1679	0.46694	0.67567	0.42200
67	13.133	0.90951	0.36763	0.52618	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	8.1811	0.56656	0.22651	0.32777	0.50900
82	20.775	1.4387	0.57521	0.83235	0.58300
92	14.397	0.99704	0.39862	0.57681	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.347	0.99358	0.39724	0.57481	-1.0000
-112	14.337	0.99288	0.39696	0.57441	-1.0000
-122	14.332	0.99254	0.39682	0.57421	-1.0000
-127	14.352	0.99392	0.39738	0.57501	-1.0000
-137	14.317	0.99150	0.39641	0.57361	-1.0000
-142	14.252	0.98700	0.39461	0.57101	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.347	0.99358	0.39724	0.57481	0.39900
112	14.337	0.99288	0.39696	0.57441	0.43100
122	14.332	0.99254	0.39682	0.57421	0.44900
127	14.352	0.99392	0.39728	0.57501	0.48600
137	14.317	0.99150	0.39641	0.57361	0.52200
142	14.252	0.98700	0.39461	0.57101	0.58800
152	14.412	0.99807	0.39904	0.57741	-1.0000
157	14.417	0.99842	0.39917	0.57761	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.412	0.99807	0.39904	0.57741	-1.0000
-157	14.417	0.99842	0.39917	0.57761	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.437	0.99773	0.39890	0.57721	0.79300
172	14.412	0.99807	0.39904	0.57741	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.623	0.94341	0.37718	0.54579	0.79300
187	13.448	0.93121	0.37234	0.53879	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

FG-21 621.98   FIG 620.37   SIGMA FG 1.6411   FTARF 0.54861   DFN 0.35528   CFN 0.3328453

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	8.7767	0.60873	0.19555	0.29753	0.72200
37	13.649	0.94646	0.33404	0.44705	0.82000
47	18.218	1.2633	0.40581	0.59669	0.91900
52	18.677	1.2951	0.41604	0.61174	1.0173

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER T.O.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	20.774	1.4405	0.46275	0.68042	0.42200
67	17.115	1.1868	0.38123	0.56055	1.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER B.O.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	10.512	0.72895	0.23417	0.34431	0.50900
82	14.977	1.0386	0.33363	0.49055	0.58330
92	14.353	0.99528	0.31972	0.47011	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.293	0.99113	0.31839	0.46815	-1.0000
-112	14.283	0.99044	0.31816	0.46782	-1.0000
-122	14.278	0.99009	0.31805	0.46766	-1.0000
-127	14.303	0.99182	0.31861	0.46847	-1.0000
-137	14.273	0.98974	0.31794	0.46749	-1.0000
-142	14.243	0.98766	0.31727	0.46651	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.293	0.99113	0.31839	0.46815	0.39800
112	14.283	0.99044	0.31816	0.46782	0.43100
122	14.278	0.99009	0.31805	0.46766	0.44900
127	14.303	0.99182	0.31861	0.46847	0.48600
137	14.273	0.98974	0.31794	0.46749	0.52200
142	14.243	0.98766	0.31727	0.46651	0.58800
-152	14.383	0.99736	0.32039	0.47109	-1.0000
-157	14.378	0.99701	0.32028	0.47093	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.383	0.99736	0.32039	0.47109	-1.0000
-157	14.378	0.99701	0.32028	0.47093	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.378	0.99701	0.32028	0.47093	0.79300
172	14.378	0.99701	0.32028	0.47093	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.499	0.93607	0.30070	0.44214	0.79300
187	13.305	0.92256	0.29636	0.43576	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

IF-DI 849.97   FIC 868.17   SIGMA IC 2.2283   FTAPF 0.63668   DSM 0.365962   CFM 0.0029337

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFIT   REC 10/24/79 04:02:13.114   FAC 9X6RI   PGM C036   PDG 1370

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	10.345	0.71709	0.19938	0.28874	0.72200
37	17.874	1.2386	0.34438	0.49874	0.82000
47	13.450	0.93203	0.25914	0.37530	0.91900
52	19.377	1.3428	0.37334	0.54068	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	24.619	1.7061	0.47435	0.68697	0.42200
67	20.355	1.4106	0.39219	0.56799	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.181	0.84413	0.23470	0.33990	0.50800
82	17.350	1.2023	0.33428	0.48412	0.58300
92	14.359	0.99502	0.27665	0.40066	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.274	0.98914	0.27502	0.39829	-1.0000
-112	14.269	0.98879	0.27492	0.39815	-1.0000
-122	14.274	0.98914	0.27502	0.39829	-1.0000
-127	14.299	0.99087	0.27550	0.39898	-1.0000
-137	14.259	0.98810	0.27473	0.39787	-1.0000
-142	14.229	0.98602	0.27415	0.39703	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.274	0.98914	0.27502	0.39829	0.39800
112	14.269	0.98879	0.27492	0.39815	0.43100
122	14.274	0.98914	0.27502	0.39829	0.44900
127	14.299	0.99087	0.27550	0.39898	0.48600
137	14.259	0.98810	0.27473	0.39787	0.52200
142	14.229	0.99602	0.27415	0.39703	0.58800
152	14.389	0.99710	0.27723	0.40149	1.0000
157	14.394	0.99675	0.27713	0.40135	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.389	0.99710	0.27723	0.40149	-1.0000
-157	14.394	0.99675	0.27713	0.40135	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.394	0.99675	0.27713	0.40135	0.79300
172	14.389	0.99710	0.27723	0.40149	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.495	0.93515	0.26001	0.37655	0.79300
187	13.310	0.92234	0.25644	0.37139	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 1072.6   FIC 1071.1   SIGMA IC 2.6742   FTAPE 0.46500   DSM 0.066865   CFM 0.0329061

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CARDETT   PFC 10/24/79 04:03:25.376   FAC 8X6X1   PGM C034   PDG 1371

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.447	0.72484	0.18265	0.26564	0.72200
37	23.180	1.4391	0.35282	0.51312	0.82000
47	15.292	1.0610	0.26736	0.38883	0.91900
52	20.560	1.4264	0.35945	0.52277	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	26.667	1.8501	0.46622	0.67805	0.42200
67	20.939	1.4458	0.36434	0.52987	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.374	0.92791	0.23383	0.34007	0.50800
82	19.127	1.3270	0.33440	0.48633	0.58300
92	14.343	0.99513	0.25077	0.36470	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.263	0.98958	0.24937	0.36267	-1.0000
-112	14.248	0.98855	0.24911	0.36229	-1.0000
-122	14.243	0.98820	0.24902	0.36216	-1.0000
-127	14.288	0.99132	0.24981	0.36331	-1.0000
-137	14.248	0.98855	0.24911	0.36229	-1.0000
-142	14.223	0.98681	0.24867	0.36166	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.263	0.98958	0.24937	0.36267	0.39800
112	14.248	0.98855	0.24911	0.36229	0.43100
122	14.243	0.98820	0.24902	0.36216	0.44900
127	14.288	0.99132	0.24981	0.36331	0.48600
137	14.248	0.98855	0.24911	0.36229	0.52200
142	14.223	0.98681	0.24867	0.36166	0.58800
-152	14.378	0.99755	0.25134	0.36559	-1.0000
-157	14.383	0.99790	0.25147	0.36572	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.378	0.99755	0.25134	0.36559	-1.0000
-157	14.383	0.99790	0.25147	0.36572	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.383	0.99790	0.25147	0.36572	0.79300
172	14.383	0.99790	0.25147	0.36572	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.589	0.94281	0.23759	0.34553	0.79300
187	13.424	0.93139	0.23470	0.34134	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

TF-01 1234.6   FLC 1223.1   SIGMA LC 2.8523   FTAPF 0.37954   DSW 0.060405   CFM 0.9329227

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CARDELL   REC 10/24/79 04:03:59.724   FAC RX6X1   PGM C034   PDG 1372

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	10.464	0.72528	0.18243	0.26520	0.72200
37	20.243	1.4030	0.35291	0.51303	0.82000
47	15.364	1.0649	0.26786	0.39939	0.91900
52	20.562	1.4252	0.35848	0.52113	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER T.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	26.720	1.8520	0.46583	0.67718	0.42200
67	20.882	1.4473	0.36405	0.52923	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.401	0.92886	0.23364	0.33965	0.50800
82	19.179	1.3293	0.33437	0.48608	0.58300
92	14.345	0.99429	0.25010	0.36357	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.256	0.98805	0.24853	0.36129	-1.0000
-112	14.251	0.98771	0.24844	0.36116	-1.0000
-122	14.246	0.98736	0.24835	0.36104	-1.0000
-127	14.285	0.99013	0.24905	0.36205	-1.0000
-137	14.246	0.98736	0.24835	0.36104	-1.0000
-142	14.216	0.98529	0.24783	0.36028	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.256	0.98805	0.24853	0.36129	0.39800
112	14.251	0.98771	0.24844	0.36116	0.43100
122	14.246	0.98736	0.24835	0.36104	0.44900
127	14.285	0.99013	0.24905	0.36205	0.48600
137	14.246	0.98736	0.24835	0.36104	0.52200
142	14.216	0.98529	0.24783	0.36028	0.58800
152	14.385	0.99705	0.25079	0.36458	-1.0000
157	14.385	0.99705	0.25079	0.36458	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.385	0.99705	0.25079	0.36458	-1.0000
-157	14.385	0.99705	0.25079	0.36458	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.380	0.99671	0.25071	0.36445	0.79300
172	14.385	0.99705	0.25079	0.36458	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.586	0.94167	0.23686	0.34433	0.79300
187	13.431	0.93094	0.23416	0.34040	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

IF-D) 1230.3   FIS 1229.0   SIGMA IC 2.6781   FTAPE 0.26570   DSM 0.055502   CFM 0.0029465

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	10.341	0.71621	0.19926	0.28819	0.72200
37	17.929	1.2349	0.34256	0.49690	0.82030
47	13.407	0.92856	0.25934	0.37364	0.91900
52	19.307	1.3372	0.37203	0.53838	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	24.633	1.7061	0.47466	0.68651	0.42200
67	20.350	1.4095	0.39213	0.56715	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.128	0.84003	0.23371	0.33802	0.50800
82	17.305	1.1986	0.33346	0.48229	0.58300
92	14.350	0.99391	0.27652	0.39994	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTER SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.270	0.98838	0.27498	0.39771	-1.0000
-112	14.269	0.98769	0.27479	0.39743	-1.0000
-122	14.255	0.98734	0.27469	0.39729	-1.0000
-127	14.290	0.98976	0.27537	0.39827	-1.0000
-137	14.245	0.98665	0.27450	0.39701	-1.0000
-142	14.215	0.98458	0.27392	0.39618	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.270	0.98838	0.27498	0.39771	0.39800
112	14.269	0.98769	0.27479	0.39743	0.43100
122	14.255	0.98734	0.27469	0.39729	0.44900
127	14.290	0.98976	0.27537	0.39827	0.48600
137	14.245	0.98665	0.27450	0.39701	0.52200
142	14.215	0.98458	0.27392	0.39618	0.58800
152	14.349	0.99599	0.27710	0.40077	-1.0000
157	14.349	0.99599	0.27710	0.40077	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.330	0.99599	0.27710	0.40077	-1.0000
-157	14.340	0.99599	0.27710	0.40077	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.380	0.99599	0.27710	0.40077	0.79300
172	14.375	0.99564	0.27700	0.40063	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.491	0.93375	0.25978	0.37573	0.79300
187	13.292	0.92061	0.25613	0.37044	0.84400

SECTION 5 , MEASURED THRUST PARAMETERS

FF-01 1072.2   FIC 1071.3   SIGMA IC 2.0438   FTABF-2.19680   DSM 0.036847   CFM 0.3030551

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDETT   PEC 10/24/79 04:06:51.543   FAC RX6X1   PG# C034   RDG 1374

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	8.7120	0.60357	0.19443	0.28672	3.72200
37	13.556	0.93915	0.30253	0.44614	0.82000
47	19.118	1.2552	0.40435	0.59629	3.91500
52	18.632	1.2909	0.41582	0.61321	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
52	20.679	1.4326	0.46149	0.68056	3.42200
67	16.980	1.1764	0.37895	0.55884	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	10.430	0.72260	0.23277	0.34327	0.50800
82	14.929	1.0343	0.33317	0.49132	0.58300
92	14.350	0.99414	0.32024	0.47226	3.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.285	0.98965	0.31880	0.47012	-1.0000
-112	14.280	0.98930	0.31868	0.46996	-1.0000
-122	14.280	0.98930	0.31868	0.46996	-1.0000
-127	14.305	0.99103	0.31924	0.47078	-1.0000
-137	14.280	0.98930	0.31868	0.46996	-1.0000
-142	14.245	0.98688	0.31790	0.46881	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.285	0.98965	0.31880	0.47012	0.39800
112	14.280	0.98930	0.31868	0.46996	0.43100
122	14.280	0.98930	0.31868	0.46996	0.44900
127	14.305	0.99103	0.31924	0.47078	0.48600
137	14.280	0.98930	0.31868	0.46996	0.52200
142	14.245	0.98688	0.31790	0.46881	0.58900
-152	14.390	0.99622	0.32091	0.47325	-1.0000
-157	14.390	0.99622	0.32091	0.47325	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.390	0.99622	0.32091	0.47325	-1.0000
-157	14.390	0.99622	0.32091	0.47325	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.390	0.99622	0.32091	0.47325	0.79300
172	14.390	0.99622	0.32091	0.47325	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.486	0.93431	0.30097	0.44384	0.79300
192	13.291	0.92082	0.29662	0.43743	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 848.06	FIC 846.45	SIGMA IC 2.0483	FTAPF 0.55416	CSF 0.059580	CFM 0.0079256

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	7.1693	0.49631	0.18002	0.26370	0.72200
37	14.535	1.0104	0.36640	0.53685	0.82000
47	16.791	1.1618	0.42139	0.61727	0.91900
52	17.265	1.1953	0.43355	0.63508	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	19.368	1.2716	0.46124	0.67566	0.42200
67	14.343	0.99278	0.36009	0.52749	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	9.0973	0.62981	0.22844	0.33463	0.50800
82	18.234	1.2623	0.45786	0.67070	0.58300
92	14.360	0.99416	0.36060	0.52822	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.305	0.99036	0.35922	0.52620	-1.0000
-112	14.295	0.98967	0.35897	0.52583	-1.0000
-122	14.290	0.98932	0.35884	0.52565	-1.0000
-127	14.315	0.99105	0.35947	0.52657	-1.0000
-137	14.285	0.98898	0.35872	0.52547	-1.0000
-142	14.225	0.98483	0.35721	0.52326	-1.0000

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.335	0.99036	0.35922	0.52620	0.39800
112	14.295	0.98967	0.35897	0.52583	0.43100
122	14.290	0.98932	0.35884	0.52565	0.44900
127	14.315	0.99105	0.35947	0.52657	0.48600
137	14.285	0.98898	0.35872	0.52547	0.52200
142	14.225	0.98483	0.35721	0.52326	0.58800
-152	14.385	0.99589	0.36122	0.52914	-1.0000
-157	14.380	0.99554	0.36110	0.52896	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.385	0.99589	0.36122	0.52914	-1.0000
-157	14.380	0.99554	0.36110	0.52896	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.380	0.99554	0.36110	0.52896	0.79300
172	14.385	0.99589	0.36122	0.52914	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.576	0.93990	0.34092	0.49930	0.79300
187	13.392	0.92711	0.33628	0.49260	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 714.14   FIC 713.43   SIGMA IC 1.3336   FTARF-0.31005   DSM 0.31010?   FFM 0.0035.1?

234

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDEII   PEC 10/24/79 04:08:41.952   FAC RX6XI   PGM C034   RDG 1376

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	9.8922	0.68392	0.27445	0.39667	0.72200
37	13.947	0.96521	0.38733	0.55981	0.82000
47	15.769	1.0913	C.43793	0.63295	0.91900
52	16.333	1.1293	0.45276	0.65439	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	16.947	1.1659	0.46787	0.67622	0.42200
67	13.118	0.90786	0.36431	0.52655	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	8.0940	0.56017	0.22479	0.32489	0.50800
82	20.830	1.4416	0.57869	0.83610	0.58300
92	14.371	0.99458	0.39911	0.57684	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.316	0.99078	0.39759	0.57464	-1.0000
-112	14.311	0.99043	0.39745	0.57444	-1.0000
-122	14.311	0.99043	0.39745	0.57444	-1.0000
-127	14.331	0.99181	C.39800	0.57524	-1.0000
-137	14.316	0.99009	0.39731	0.57424	-1.0000
-142	14.246	0.99594	0.39565	0.57184	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.316	0.99078	0.39759	0.57464	0.39800
112	14.311	0.99043	0.39745	0.57444	0.43100
122	14.311	0.99043	0.39745	0.57444	0.44900
127	14.331	0.99181	0.39800	0.57524	0.48600
137	14.336	0.99009	0.39731	0.57424	0.52200
142	14.246	0.98594	0.39565	0.57184	0.58900
152	14.396	0.99631	0.39989	0.57784	-1.0000
157	14.391	0.99596	0.39967	0.57769	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.396	0.99631	0.39989	0.57785	-1.0000
-157	14.391	0.99596	0.39967	0.57765	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.391	0.99596	0.39967	C.57765	0.79300
172	14.396	0.99562	0.39953	C.57745	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.592	0.94068	0.37768	C.54558	0.79300
187	13.427	0.92928	0.37291	0.53897	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

IF-21 620.06   FIC 619.28   SIGMA IC 1.2652   FTAPF-0.22389   DSM 0.010345   CFM 0.0034303

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADRELL   REC 10/24/79 04:09:28.809   FOC RXAE1   PGW C034   RDG 1377

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	12.557	0.96869	0.41174	0.54984	0.72200
37	14.928	1.0327	0.48945	0.70122	0.82000
47	15.403	1.0655	0.50503	0.72349	0.91900
52	15.577	1.0776	0.51076	0.73169	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	15.048	1.0410	0.49341	0.70884	0.42200
67	13.501	0.93396	0.44268	0.63416	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	12.293	0.84970	0.40274	0.57695	0.50800
82	16.675	1.1501	0.54513	0.78092	0.58380
92	14.399	0.99542	0.47181	0.67589	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	14.344	0.99232	0.47034	0.67378	-1.0000
-112	14.344	0.99232	0.47034	0.67378	-1.0000
-122	14.336	0.99162	0.47001	0.67332	-1.0000
-127	14.349	0.99266	0.47050	0.67402	-1.0000
-137	14.315	0.99024	0.46936	0.67238	-1.0000
-142	14.230	0.98437	0.46657	0.66839	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	14.344	0.99232	0.47034	0.67378	0.39800
112	14.344	0.99232	0.47034	0.67378	0.43100
122	14.336	0.99162	0.47001	0.67332	0.44900
127	14.349	0.99266	0.47050	0.67402	0.48600
137	14.315	0.99024	0.46936	0.67238	0.52200
142	14.230	0.98437	0.46657	0.66839	0.58800
-152	14.494	0.99646	0.47239	0.67660	-1.0000
-157	14.439	0.99680	0.47247	0.67683	-1.0000

>ADDITIONAL PRESSURE RATIOS , CAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	14.434	0.99666	0.47239	0.67660	-1.0000
-157	14.439	0.99680	0.47247	0.67683	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
167	14.494	0.99646	0.47239	0.67660	0.79300
172	14.494	0.99646	0.47239	0.67660	0.84400

>ADDITIONAL PRESSURE RATIOS , 60 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
182	13.706	0.94812	0.44939	0.64377	0.79300
187	13.556	0.93776	0.44449	0.63674	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
F-DI 478.07   FLC 477.63   SIGMA LC 1.2012   FTAPF-0.36226   DSW 0.00E8841   CFW 2.1935372

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.927	0.96371	0.53505	0.77640	0.72200
37	14.705	1.0176	0.56494	0.81979	0.82000
47	14.930	1.0331	0.57398	0.83231	0.91900
52	15.024	1.0397	0.57723	0.83760	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.555	1.0072	0.55921	0.81145	0.42200
67	14.166	0.98079	0.54425	0.78975	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.559	0.86909	0.48252	0.70017	0.50800
82	15.953	1.1039	0.61288	0.88933	0.50300
92	14.401	0.99651	0.55326	0.80282	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.371	0.99444	0.55211	0.80116	-1.0000
-112	14.366	0.99410	0.55192	0.80088	-1.0000
-122	14.366	0.99410	0.55192	0.80088	-1.0000
-127	14.376	0.99479	0.55231	0.80143	-1.0000
-137	14.341	0.99237	0.55096	0.79949	-1.0000
-142	14.281	0.98823	0.54866	0.79615	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.371	0.99444	0.55211	0.80116	0.39800
112	14.366	0.99410	0.55192	0.80088	0.43100
122	14.366	0.99410	0.55192	0.80088	0.44900
127	14.376	0.99479	0.55231	0.80143	0.48600
137	14.341	0.99237	0.55096	0.79949	0.52200
142	14.281	0.98823	0.54866	0.79615	0.58800
-152	14.411	0.99704	0.55361	0.80338	-1.0000
-152	14.411	0.99729	0.55389	0.80338	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.411	0.99720	0.55365	0.80338	-1.0000
-157	14.411	0.99720	0.55365	0.80338	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
157	14.411	0.99720	0.55365	0.80338	0.79300
172	14.411	0.99729	0.55365	0.80338	0.84400

>ADDITIONAL PRESSURE RATIOS , 50 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
192	13.812	0.95577	0.53064	0.77000	0.79300
197	13.607	0.94783	0.52623	0.76360	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

TF=0) 337.15   FTC 335.95   SIGMA TF 1.6835   FTAPF 0.17527   DSM 0.024460   CFM 0.0031733

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	9.7268	0.67469	0.20329	0.29715	0.72200
37	15.302	1.0543	0.31772	0.46641	0.82600
47	13.925	0.96573	0.29103	0.42539	0.91900
52	19.189	1.3239	0.39896	0.58315	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	22.377	1.5519	0.46768	0.68360	0.42200
67	18.440	1.2789	0.38541	0.56334	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	11.165	0.77431	0.23334	0.34197	0.50800
82	15.921	1.1042	0.33274	0.48636	0.58300
92	14.344	0.99480	0.29979	0.43819	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.274	0.98995	0.29833	0.43606	-1.0000
-112	14.264	0.98926	0.29812	0.43575	-1.0000
-122	14.264	0.98926	0.29812	0.43575	-1.0000
-127	14.296	0.99134	0.29874	0.43667	-1.0000
-137	14.259	0.98892	0.29801	0.43560	-1.0000
-142	14.224	0.98649	0.29728	0.43453	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.274	0.98995	0.29833	0.43606	0.39800
112	14.264	0.98926	0.29812	0.43575	0.43100
122	14.264	0.98926	0.29812	0.43575	0.44900
127	14.296	0.99134	0.29874	0.43667	0.48600
137	14.259	0.98892	0.29801	0.43560	0.52200
142	14.224	0.98649	0.29728	0.43453	0.58900
152	14.374	0.99688	0.30041	0.43911	-1.0000
-157	14.374	0.99688	0.30041	0.43911	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.374	0.99688	0.30041	0.43911	-1.0000
-157	14.374	0.99688	0.30041	0.43911	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.374	0.99688	0.30041	0.43911	0.79300
172	14.374	0.99688	0.30041	0.43911	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.341	0.92523	0.27882	0.40755	0.79300
187	13.116	0.90966	0.27413	0.40069	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

IF-DI 946.64   FI? 945.74   SIGMA IC 3.4205   FTAPE 0.33688   DSM 0.063817   CFM 0.0978081

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.295	1.0356	0.55651	0.93923	0.72200
37	15.510	1.0197	0.56473	0.95243	0.82000
47	15.590	1.0250	0.56124	0.95734	0.91900
52	15.625	1.0273	0.56851	0.95949	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	15.390	1.0112	0.55960	0.94445	0.42200
67	15.305	1.0062	0.55687	0.93984	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.495	0.88725	0.49102	0.82871	0.50800
82	17.239	1.1334	0.62726	1.0586	0.58300
92	15.230	1.0013	0.55414	0.93524	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.785	0.97205	0.53795	0.90792	-1.0000
-112	14.700	0.96644	0.53486	0.90270	-1.0000
-122	14.715	0.96745	0.53541	0.90362	-1.0000
-127	15.000	0.98618	0.54577	0.92112	-1.0000
-137	15.000	0.98618	0.54577	0.92112	-1.0000
-142	14.865	0.97731	0.54086	0.91283	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.785	0.97205	0.53795	0.90792	0.39800
112	14.700	0.96644	0.53486	0.90270	0.43100
122	14.715	0.96745	0.53541	0.90362	0.44900
127	15.000	0.98618	0.54577	0.92112	0.48600
137	15.000	0.98618	0.54577	0.92112	0.52200
142	14.865	0.97731	0.54086	0.91283	0.58800
152	15.235	1.0016	0.55437	0.93554	-1.0000
157	15.230	1.0013	0.55414	0.93524	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.235	1.0016	0.55437	0.93554	-1.0000
-157	15.230	1.0013	0.55414	0.93524	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.230	1.0013	0.55414	0.93524	0.79300
172	15.230	1.0013	0.55414	0.93524	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.565	0.95759	0.52995	0.89441	0.79300
187	14.155	0.93064	0.51503	0.86923	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

IF=DI 293.98   FIG 297.84   SIGMA FC 2.5435   FTARF 2.8430   DSM 2.3914   CFM 0.0071192

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CANAET   REF 10/24/79 04:47:09.879   ESE RESET   PGM C034   PDG 1391

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.294	1.0007	0.47498	0.79601	0.72200
37	16.074	1.0517	0.49020	0.83660	0.82000
47	16.332	1.0671	0.50650	0.84893	0.91900
52	16.304	1.0726	0.50914	0.85326	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	15.879	1.0390	0.48314	0.82646	0.62200
67	15.489	1.0134	0.48103	0.80616	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.389	0.87604	0.41581	0.69496	0.50800
82	18.164	1.1844	0.56410	0.94537	0.58300
92	15.319	1.0023	0.47575	0.79731	2.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.874	0.97321	0.46103	0.77415	-1.0000
-112	14.792	0.96830	0.45962	0.77025	-1.0000
-122	14.794		0.45945	0.76500	-1.0000
-127	15.079	0.98662	0.46820	0.78582	-1.0000
-137	15.094	0.98760	0.46877	0.78560	-1.0000
-142	14.954	0.97864	0.46442	0.77832	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.874	0.97321	0.46193	0.77415	0.39800
112	14.799	0.96830	0.45969	0.77025	0.43100
122	14.784	0.96797	0.45945	0.76999	0.44900
127	15.279	0.98662	0.46820	0.78442	0.58600
137	15.094	0.99760	0.46877	0.77822	0.52200
142	14.954	0.97864	0.46442	0.77822	0.58800
		1.0070			0.0000
		1.0017			-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.299	1.0010	0.47513	0.79627	-1.0000
-157	15.309	1.0017	0.47544	0.79479	

>ADDITIONAL PRESSURE RATIOS , 22 DEG SHROUD LOCATION

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.289	1.0004	0.47482	0.79575	3.79200
172	15.299	1.0010	0.47513	0.79677	0.44400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.639	0.96176	0.45650	0.76504	2.79300
187	14.329	0.93755	0.44501	0.74579	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FG-01 621.23   FIG 676.10   SIGMA IC 6.6700   FTABE 2.7266   DSM 2.4102   CFN 0.9928165

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL /PO	PL /PTF	PL /PTP	X/DMAX
32	13.443	0.89177	0.35140	0.59183	0.72200
37	16.347	1.0736	0.42784	0.72057	0.82000
47	17.032	1.1172	0.44522	0.74994	0.91900
52	17.217	1.1293	0.45005	0.75758	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL /PO	PL /PTF	PL /PTP	X/DMAX
62	15.842	1.0392	0.41412	0.69747	0.42200
67	13.792	0.90473	0.36055	0.60723	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL /PO	PL /PTF	PL /PTP	X/DMAX
77	8.7423	0.57364	0.22852	0.38468	0.50800
82	22.533	1.759	0.58816	0.99058	0.58800
92	15.252	1.0005	0.39873	0.67150	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL /PO	PL /PTF	PL /PTP	X/DMAX
-107	14.877	0.97589	0.38890	0.65499	-1.0000
-112	14.817	0.97195	0.38734	0.65235	-1.0000
-122	14.952	0.97425	0.38825	0.65389	-1.0000
-127	15.107	0.99097	0.39491	0.66512	-1.0000
-137	15.142	0.99327	0.39583	0.66668	-1.0000
-142	15.097	0.99031	0.39465	0.66468	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL /PO	PL /PTF	PL /PTP	X/DMAX
107	14.877	0.97589	0.38890	0.65499	0.39800
112	14.817	0.97195	0.38734	0.65235	0.43100
122	14.952	0.97425	0.38825	0.65389	0.44900
127	15.107	0.99097	0.39491	0.66512	0.48600
137	15.142	0.99327	0.39583	0.66666	0.52200
142	15.097	0.99031	0.39465	0.66468	0.58800
152	15.252	1.0005	0.39873	0.67150	-1.0000
157	15.252	1.0011	0.39897	0.67196	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL /PO	PL /PTF	PL /PTP	X/DMAX
-152	15.252	1.0005	0.39873	0.67150	-1.0000
-157	15.252	1.0011	0.39897	0.67196	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL /PO	PL /PTF	PL /PTP	X/DMAX
167	15.252	1.0005	0.39873	0.67150	0.79300
172	15.252	1.0005	0.39873	0.67150	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL /PO	PL /PTF	PL /PTP	X/DMAX
182	14.597	0.95752	0.38150	0.64267	0.79300
187	14.242	0.93424	0.37231	0.62704	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

IF-21 598.96   FLC 593.38   SIGMA IF 3.8154   FTAPE 2.6275   DSM 2.3696   CFM 2.7021216

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	9.3588	0.55946	0.17584	0.29767	0.72200
37	17.969	1.1833	0.37801	0.63991	0.82000
47	19.994	1.2442	0.39747	0.67284	0.91900
52	19.999	1.2439	0.39736	0.67266	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	19.249	1.2676	0.40493	0.68547	0.42200
67	16.329	1.0754	0.34352	0.58152	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	11.125	0.73261	0.23403	0.39617	0.50800
82	15.845	1.0434	0.33332	0.56425	0.58300
92	15.190	1.0003	0.31955	0.54093	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.835	0.97693	0.31208	0.52829	-1.0000
-112	14.900	0.97462	0.31134	0.52704	-1.0000
-122	14.930	0.97660	0.31197	0.52811	-1.0000
-127	15.095	0.99339	0.31734	0.53719	-1.0000
-137	15.140	0.99701	0.31849	0.53915	-1.0000
-142	15.195	1.0006	0.31965	0.54111	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.835	0.97693	0.31208	0.52829	0.39800
112	14.900	0.97462	0.31134	0.52704	0.43100
122	14.930	0.97660	0.31197	0.52811	0.44900
127	15.095	0.99339	0.31734	0.53719	0.48600
137	15.140	0.99701	0.31849	0.53915	0.52200
142	15.195	1.0006	0.31965	0.54111	0.58800
-152	15.200	1.0010	0.31976	0.54129	-1.0000
-157	15.200	1.0010	0.31976	0.54129	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.200	1.0010	0.31976	0.54129	-1.0000
-157	15.200	1.0010	0.31976	0.54129	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.205	1.0013	0.31986	0.54146	0.79300
172	15.200	1.0010	0.31976	0.54129	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.505	0.95520	0.30514	0.51654	0.79300
187	14.150	0.93182	0.29767	0.50393	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS
(F-D) 932.60   FIG 827.70   SIGMA IC 2.4453   FTAPE 2.5740   DSW 2.3259   CFW 0.0321239

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.481	0.95059	0.26347	0.44638	0.72200
37	16.756	1.5999	0.30486	0.51615	0.82000
47	15.611	1.0248	0.28433	0.49088	0.91900
52	20.383	1.3378	0.37080	0.62779	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	22.780	1.4953	0.41445	0.70171	0.42200
67	19.850	1.3030	0.36116	0.61147	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.836	0.84260	0.23354	0.39540	0.50800
82	18.366	1.2056	0.33414	0.56574	0.58300
92	15.266	1.0021	0.27775	0.47026	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.951	0.97488	0.27020	0.45748	-1.0000
-112	14.791	0.97094	0.26911	0.45563	-1.0000
-122	14.816	0.97258	0.26956	0.45640	-1.0000
-127	15.091	0.99063	0.27457	0.46487	-1.0000
-137	15.141	0.99391	0.27548	0.46641	-1.0000
-142	15.181	0.99654	0.27620	0.46764	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.951	0.97488	0.27020	0.45748	0.39800
112	14.791	0.97094	0.26911	0.45563	0.43100
122	14.816	0.97258	0.26956	0.45640	0.44900
127	15.091	0.99063	0.27457	0.46487	0.48600
137	15.141	0.99391	0.27548	0.46641	0.52200
142	15.191	0.99654	0.27620	0.46764	0.58800
-152	15.251	1.0011	0.27768	0.46980	-1.0000
-157	15.290	1.0015	0.27757	0.46995	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.251	1.0011	0.27768	0.46980	-1.0000
-157	15.256	1.0015	0.27757	0.46995	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.261	1.0018	0.27766	0.47010	0.79300
172	15.256	1.0015	0.27757	0.46995	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
192	14.496	0.95092	0.26356	0.44623	0.79300
197	14.076	0.92400	0.25610	0.43360	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

TF-DL 1051.1   FIC 1046.9   SIGMA IC 3.2857   FTARF 1.8249   DSM 2.3856   CFN 0.0021190

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	14.219	0.93541	0.24550	0.41728	0.72200
37	18.139	1.1867	0.31145	0.52928	0.82000
47	14.319	0.94198	0.24723	0.42022	0.91300
52	20.953	1.3719	0.36005	0.61158	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	23.748	1.5623	0.41003	0.69693	0.42200
67	20.188	1.3281	0.34857	0.59247	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	13.534	0.89034	0.23367	0.39718	0.50800
82	19.384	1.2752	0.33467	0.56885	0.58300
92	15.224	1.0015	0.26295	0.44678	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	14.929	0.97554	0.25603	0.43519	-1.0000
-112	14.769	0.97159	0.25500	0.43342	-1.0000
-122	14.784	0.97258	0.25526	0.43386	-1.0000
-127	15.054	0.98034	0.25692	0.44179	-1.0000
-137	15.099	0.99330	0.26069	0.44311	-1.0000
-142	15.144	0.99626	0.26147	0.44443	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	14.929	0.97554	0.25603	0.43519	0.39800
112	14.769	0.97159	0.25500	0.43342	0.43100
122	14.784	0.97258	0.25526	0.43386	0.44900
127	15.054	0.98034	0.25692	0.44179	0.48600
137	15.099	0.99330	0.26069	0.44311	0.52200
142	15.144	0.99626	0.26147	0.44443	0.58800
-152	15.219	1.0012	0.26277	0.44663	-1.0000
-157	15.219	1.0012	0.26277	0.44663	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	15.219	1.0012	0.26277	0.44663	-1.0000
-157	15.219	1.0012	0.26277	0.44663	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
167	15.219	1.0012	0.26277	0.44663	0.79300
172	15.219	1.0012	0.26277	0.44663	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
182	14.624	0.96205	0.25249	0.42917	0.79300
187	14.284	0.93968	0.24662	0.41919	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

IF-DI 1134.8   FIC 1130.1   SIGMA IC 3.1142   FTARF 2.3001   DSM 2.3651   CFM 0.9921208

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	13.857	0.91221	0.23960	0.40631	0.72200
37	19.046	1.1890	0.31263	0.52875	0.92000
47	14.307	0.94183	0.24738	0.41919	0.91900
52	20.855	1.3729	0.36060	0.61105	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	23.774	1.5651	0.41107	0.69658	0.42200
67	20.172	1.3278	0.34876	0.59000	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	13.527	0.89049	0.23389	0.39634	0.50800
82	19.350	1.2739	0.33459	0.56697	0.58300
92	15.201	1.0007	0.26285	0.44541	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	14.817	0.97540	0.25619	0.43413	-1.0000
-112	14.747	0.97079	0.25498	0.43208	-1.0000
-122	14.762	0.97178	0.25524	0.43252	-1.0000
-127	15.032	0.99955	0.25991	0.44043	-1.0000
-137	15.177	0.99251	0.26069	0.44175	-1.0000
-142	15.122	0.99548	0.26147	0.44397	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	14.817	0.97540	0.25619	0.43413	0.39800
112	14.747	0.97079	0.25498	0.43208	0.43100
122	14.762	0.97178	0.25524	0.43252	0.44900
127	15.032	0.99955	0.25991	0.44043	0.48600
137	15.177	0.99251	0.26069	0.44175	0.52200
142	15.122	0.99548	0.26147	0.44327	0.58500
152	15.191	1.0001	0.26269	0.44512	1.0000
157	15.191	1.0001	0.26269	0.44512	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	15.191	1.0001	0.26269	0.44512	-1.0000
-157	15.191	1.0001	0.26269	0.44512	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
167	15.206	1.0011	0.26294	0.44556	0.79300
172	15.196	1.0004	0.26276	0.44526	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
182	14.602	0.96125	0.25248	0.42783	0.79300
192	14.257	0.93854	0.24651	0.41773	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FG-PI 1130.1   FIG 1134.0   SIGMLIF 3.1001   FTARF 2.6992   DSM 2.3371   CFN 0.0021231

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.763	0.97186	0.26889	0.45597	0.72200
37	16.782	1.1049	0.30568	0.51837	0.82000
47	15.255	1.0044	0.27791	0.47126	0.91500
52	20.319	1.3379	0.37017	0.62772	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	22.759	1.4985	0.41462	0.70308	0.42200
67	19.839	1.3063	0.36143	0.61280	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.825	0.84444	0.23364	0.39619	0.50800
82	18.334	1.2072	0.33401	0.56640	0.58300
92	15.205	1.0012	0.27700	0.46972	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.830	0.97669	0.26962	0.45721	-1.0000
-112	14.735	0.97021	0.26844	0.45520	-1.0000
-122	14.765	0.97219	0.26898	0.45613	-1.0000
-127	15.035	0.98996	0.27390	0.46447	-1.0000
-137	15.090	0.99359	0.27490	0.46617	-1.0000
-142	15.140	0.99688	0.27581	0.46771	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.830	0.97669	0.26962	0.45721	0.39800
112	14.735	0.97021	0.26844	0.45520	0.43100
122	14.765	0.97219	0.26898	0.45613	0.44900
127	15.335	0.99996	0.27390	0.46447	0.49600
137	15.090	0.99359	0.27490	0.46617	0.52200
142	15.140	0.99688	0.27581	0.46771	0.58800
-147	15.220	1.0021	0.27727	0.47018	-1.0000
-152	15.215	1.0018	0.27718	0.47003	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLOW

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.220	1.0021	0.27727	0.47018	-1.0000
-157	15.215	1.0018	0.27718	0.47003	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.220	1.0021	0.27727	0.47018	0.79300
172	15.215	1.0018	0.27718	0.47003	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.452	0.95145	0.26324	0.44640	0.79300
187	14.055	0.92544	0.25605	0.43419	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

FG-21 1050.6   FIC 1045.7   SIGMA IC 3.1593   FTAPE 2.5839   DSK 2.3725   CFM 0.0021293

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	8.3209	0.54498	0.17539	0.29698	0.72200
37	18.929	1.1808	0.38002	0.64348	0.82000
47	18.936	1.2381	0.39846	0.67471	0.91900
52	18.924	1.2394	0.39888	0.67543	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	19.196	1.2571	0.40458	0.68506	0.42200
67	16.234	1.0633	0.34218	0.57942	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	11.093	0.72652	0.23381	0.39591	0.50800
82	15.809	1.0354	0.33322	0.56425	0.58300
92	15.264	0.99972	0.32173	0.54479	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.919	0.97712	0.31446	0.53248	-1.0000
-112	14.866	0.97352	0.31330	0.53051	-1.0000
-122	14.999	0.97516	0.31383	0.53141	-1.0000
-127	15.149	0.99219	0.31931	0.54069	-1.0000
-137	15.219	0.99677	0.32079	0.54319	-1.0000
-142	15.274	1.0004	0.32195	0.54515	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.919	0.97712	0.31446	0.53248	0.39800
112	14.964	0.97352	0.31330	0.53051	0.43190
122	14.889	0.97516	0.31383	0.53141	0.44900
127	15.149	0.99219	0.31931	0.54069	0.48600
137	15.219	0.99677	0.32079	0.54319	0.52200
142	15.274	1.0004	0.32195	0.54515	0.58800
-142	15.259	0.99939	0.32163	0.54461	-1.0000
-157	15.264	0.99972	0.32173	0.54479	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.259	0.99939	0.32163	0.54461	-1.0000
-157	15.264	0.99972	0.32173	0.54479	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.269	1.0000	0.32184	0.54497	0.79300
172	15.264	0.99972	0.32173	0.54479	0.94400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.584	0.95518	0.30740	0.52052	0.79300
187	14.214	0.93094	0.29960	0.50731	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

IF=0) 827.16   FIC 821.98   SIGMA IC 2.8726   FTAPF 2.8747   DS= 2.4047   CF= 0.0021170

Run 2J

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   REC 10/24/79 04:57:49.909   FAC RX6X1   PGM C036   PRG 1389

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.436	0.87960	0.35118	0.59156	0.72200
37	16.316	1.0705	0.42740	0.71956	0.82000
47	16.996	1.1151	0.44521	0.74995	0.91900
52	17.176	1.1269	0.44992	0.75790	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	15.801	1.0367	0.41391	0.69723	0.42200
67	13.751	0.99224	0.36021	0.60678	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	8.7050	0.57114	0.22802	0.38411	0.50800
82	22.523	1.4776	0.58991	0.99370	0.58300
92	15.241	1.0000	0.39924	0.67253	0.67900

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.866	0.97539	0.38942	0.65598	-1.0000
-112	14.906	0.97146	0.38785	0.65333	-1.0000
-122	14.926	0.97277	0.38837	0.65422	-1.0000
-127	15.086	0.98983	0.39518	0.66569	-1.0000
-137	15.126	0.99245	0.39623	0.66745	-1.0000
-142	15.096	0.98983	0.39518	0.66569	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.866	0.97539	0.38942	0.65598	0.39800
112	14.906	0.97146	0.38785	0.65333	0.43100
122	14.926	0.97277	0.38837	0.65422	0.44900
127	15.086	0.98983	0.39518	0.66569	0.49600
137	15.126	0.99245	0.39623	0.66745	0.52200
142	15.086	0.98983	0.39518	0.66569	0.58800
147	15.241	1.0000	0.39924	0.67253	-1.0000
147	15.246	1.0003	0.39937	0.67275	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.241	1.0000	0.39924	0.67253	-1.0000
-152	15.246	1.0003	0.39937	0.67275	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.236	0.99967	0.39911	0.67231	0.79300
172	15.241	1.0000	0.39924	0.67253	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.581	0.95670	0.38195	0.64341	0.79300
187	14.221	0.93308	0.37253	0.62752	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

IF-PL 596.52   FIC 581.74   SIGMA TC 2.5180   FTAPF 2.4274   DSM 2.3313   CFM 2.0021241

RUN N?..

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
37	15.213	0.99895	0.47067	0.79363	0.72200
27	16.318	1.0518	0.4955?	0.82564	0.82000
47	16.243	1.0666	0.50256	0.84738	0.91900
57	16.338	1.072?	0.5?56R	0.85233	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	15.838	1.0380	0.48908	0.82468	0.42200
67	15.408	1.0118	0.47670	0.80380	0.67900

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	13.262	0.87086	0.41031	0.69186	2.50900
87	18.096	1.1874	0.55948	0.94238	0.58300
92	15.243	1.0009	0.47160	0.79519	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	14.823	0.97333	0.45860	0.77328	-1.0000
-112	14.748	0.96860	0.45628	0.76936	-1.0000
-117	14.753	0.96872	0.45643	0.76962	-1.0000
-127	15.033	0.98712	0.46510	0.78424	-1.0000
-137	15.328	0.98680	0.46494	0.78397	-1.0000
-142	14.899	0.97826	0.46092	0.77719	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	14.823	0.97333	0.45860	0.77328	0.39800
112	14.748	0.96860	0.45628	0.76936	0.43100
117	14.753	0.96872	0.45643	0.76962	0.44900
127	15.033	0.98712	0.46510	0.78424	0.48600
137	15.328	0.98680	0.46494	0.78397	0.52200
147	14.898	0.97825	0.46092	0.77719	2.58800
15?	15.243	1.0009	0.47160	0.79519	-1.0000
15?	15.243	1.0009	0.47160	0.79519	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-157	15.243	1.0009	0.47160	0.79519	-1.0000
-157	15.243	1.0009	0.47160	0.79519	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
167	15.243	1.0009	0.47160	0.79519	0.79300
172	15.243	1.0009	0.47160	0.79519	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
18?	14.643	0.96151	0.45293	0.76388	0.79300
18?	14.273	0.93720	0.44158	0.74457	0.84400

>SECTION 5, MEASURED THRUST PARAMETERS

IF-11 635.00   EFF 429.75   SIGMA 1C 2.4093   FTARE 2.4250   DSW 2.3222   CFG 0.0021290

NASA-LEWIS   PRELIMINARY DATA   04/13/79   CADDFIT   REC 10/24/79 05:00:15.638   FAC 8X6V1   PGM C034   RDG 1301

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	15.353	1.0051	0.55486	0.93792	0.72200
37	15.563	1.0188	0.56245	0.95075	0.82000
47	15.638	1.0237	0.56516	0.95533	0.91900
52	15.673	1.0260	0.56643	0.95747	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	15.453	1.0116	0.55847	0.94403	0.42200
67	15.363	1.0057	0.55522	0.93853	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	13.528	0.88556	0.48688	0.82639	0.50800
82	17.309	1.1331	0.62553	1.0574	0.58300
92	15.293	1.0011	0.55269	0.93425	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTER SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	14.863	0.97298	0.53714	0.90797	-1.0000
-112	14.783	0.96774	0.53425	0.90309	-1.0000
-122	14.798	0.96873	0.53470	0.90400	-1.0000
-127	15.078	0.98706	0.54492	0.92111	-1.0000
-137	15.063	0.98608	0.54437	0.92020	-1.0000
-162	14.928	0.97724	0.53949	0.91195	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	14.863	0.97298	0.53714	0.90797	0.39800
112	14.783	0.96774	0.53425	0.90309	0.43100
122	14.798	0.96873	0.53470	0.90400	0.44900
127	15.078	0.98706	0.54492	0.92111	0.48600
137	15.063	0.98608	0.54437	0.92020	0.52200
142	14.928	0.97724	0.53949	0.91195	0.58800
-152	15.298	1.0015	0.55287	0.93456	-1.0000
-157	15.298	1.0015	0.55287	0.93456	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	15.298	1.0015	0.55287	0.93456	-1.0000
-157	15.298	1.0015	0.55287	0.93456	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
167	15.298	1.0015	0.55287	0.93456	0.79300
172	15.303	1.0018	0.55305	0.93486	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
182	14.639	0.95825	0.52901	0.89422	0.79300
187	14.233	0.93173	0.51437	0.86947	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 295.25   FLC 250.22   SIGMA LC 4.2860   FTAPE 2.6569   DSP 2.3764   CFM 0.0021205

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.342	0.84914	0.31002	0.52384	0.72200
37	16.341	1.0735	0.39192	0.66223	0.82007
47	17.485	1.1473	0.41887	0.70775	0.91900
52	17.735	1.1617	0.42413	0.71665	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	16.900	1.1089	0.40486	0.68408	0.42200
67	14.061	0.92261	0.33685	0.56916	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	9.6415	0.63261	0.23097	0.39026	0.50800
82	21.933	1.4306	0.52231	0.88253	0.58300
92	15.241	1.0000	0.36511	0.61691	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.891	0.97706	0.35673	0.60275	-1.0000
-112	14.831	0.97312	0.35529	0.60032	-1.0000
-122	14.856	0.97476	0.35589	0.60133	-1.0000
-127	15.116	0.99182	0.36211	0.61185	-1.0000
-137	15.166	0.99509	0.36331	0.61388	-1.0000
-142	15.171	0.99542	0.36343	0.61408	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.891	0.97706	0.35673	0.60275	0.34900
112	14.831	0.97312	0.35529	0.60032	0.43100
122	14.856	0.97476	0.35589	0.60133	0.44900
127	15.116	0.99182	0.36211	0.61185	0.48600
137	15.166	0.99509	0.36331	0.61388	0.52200
142	15.171	0.99542	0.36343	0.61408	0.58800
147	15.241	1.0000	0.36511	0.61691	-1.0000
157	15.246	1.0003	0.36523	0.61711	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.241	1.0000	0.36511	0.61691	-1.0000
-157	15.246	1.0003	0.36523	0.61711	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.251	1.0007	0.36535	0.61732	0.79300
172	15.241	1.0000	0.36511	0.61691	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.586	0.95705	0.34942	0.59041	0.79300
187	14.216	0.93278	0.34056	0.57543	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
(F-D) 697.11   FIC 691.68   SIGMA IC 3.0695   FTAPF 3.0591   DSP 2.3758   CFM 0.3321297

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.206	0.99869	0.55184	0.79668	0.72200
37	15.937	1.0466	0.57834	0.83494	0.82000
47	16.127	1.0591	0.58524	0.84490	0.91900
52	16.212	1.0647	0.58833	0.84935	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	15.812	1.0384	0.57381	0.82839	0.42200
67	15.441	1.0141	0.56037	0.80930	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.566	0.89093	0.49230	0.71072	0.50800
82	17.342	1.1389	0.62935	0.90857	0.58300
92	15.236	1.0007	0.55293	0.79825	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.836	0.97438	0.53841	0.77729	-1.0000
-112	14.781	0.97076	0.53641	0.77441	-1.0000
-122	14.786	0.97109	0.53659	0.77467	-1.0000
-127	15.061	0.98916	0.54658	0.78908	-1.0000
-137	15.071	0.98982	0.54694	0.78960	-1.0000
-142	14.976	0.98357	0.54349	0.78463	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.836	0.97438	0.53841	0.77729	0.39800
112	14.781	0.97076	0.53641	0.77441	0.43100
122	14.786	0.97109	0.53659	0.77467	0.44900
127	15.061	0.98916	0.54658	0.78908	0.48600
137	15.071	0.98982	0.54694	0.78960	0.52200
142	14.976	0.98357	0.54349	0.78463	0.58800
-152	15.236	1.0007	0.55293	0.79825	-1.0000
-157	15.236	1.0007	0.55293	0.79825	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.236	1.0007	0.55293	0.79825	-1.0000
-157	15.236	1.0007	0.55293	0.79825	-1.0000

>ADDITIONAL PRESSURE RATIOS , 30 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.231	1.0003	0.55275	0.79799	0.79300
172	15.231	1.0003	0.55275	0.79799	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.746	0.96846	0.53514	0.77257	0.79300
187	14.416	0.94678	0.52316	0.75527	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

| IF-D1 345.57 | FIC 341.12 | SIGMA LC 2.8468 | FTAPF 2.1433 | DSM 2.3942 | CFH 0.0021268 |

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDEII   REC 10/24/79 05:04:37.902   FAC RX6X1   PG" C034   PDG 1394

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.442	0.94691	0.44949	0.64569	0.72200
37	16.251	1.0655	0.50580	0.72658	0.82000
47	16.671	1.0931	0.51887	0.74535	0.91900
52	16.831	1.1036	0.52385	0.75250	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	16.246	1.0652	0.50565	0.72636	0.42200
67	14.972	0.98165	0.46599	0.66938	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.337	0.87448	0.41511	0.59630	0.50800
82	18.051	1.1835	0.56180	0.80732	0.58300
92	15.257	1.0003	0.47485	0.68211	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.837	0.97280	0.46178	0.66334	-1.0000
-112	14.762	0.96789	0.45945	0.65999	-1.0000
-122	14.802	0.97051	0.46069	0.66178	-1.0000
-127	15.072	0.98821	0.46909	0.67385	-1.0000
-137	15.067	0.98788	0.46894	0.67362	-1.0000
-142	14.942	0.97969	0.46505	0.66804	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.837	0.97280	0.46178	0.66334	0.39800
112	14.762	0.96789	0.45945	0.65999	0.43100
122	14.802	0.97051	0.46069	0.66178	0.44900
127	15.072	0.98821	0.46909	0.67385	0.48600
137	15.067	0.98788	0.46894	0.67362	0.52200
142	14.942	0.97969	0.46505	0.66804	0.58800
-152	15.267	1.0010	0.47516	0.68256	-1.0000
-157	15.267	1.0010	0.47516	0.68256	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.267	1.0010	0.47516	0.68256	-1.0000
-157	15.267	1.0010	0.47516	0.68256	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
157	15.267	1.0010	0.47516	0.68256	0.79300
172	15.267	1.0010	0.47516	0.68256	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.727	0.96559	0.45836	0.65843	0.79300
187	14.392	0.94364	0.44793	0.64345	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

IF-DI 497.99   FIC 483.32   SIGMA IC 3.2020   FTARE 2.6019   DSM 2.3677   CEM 0.0021215

253

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.354	0.83743	0.32183	C.46731	0.72200
37	15.265	0.93763	0.39764	0.57740	0.82000
47	17.125	1.1192	0.44609	0.64775	0.91900
52	17.679	1.1555	0.46055	0.66874	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	17.879	1.1685	0.46575	0.67631	0.42200
67	13.925	0.91005	0.36273	0.52671	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	8.7578	0.57237	0.22814	0.33127	0.50800
82	22.554	1.4740	0.58752	0.85312	0.58300
92	15.295	0.99959	0.39942	0.57853	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.890	0.97312	0.38787	0.56321	-1.0000
-112	14.840	0.96986	0.38657	0.56132	-1.0000
-122	14.860	0.97116	0.38709	0.56208	-1.0000
-127	15.130	0.98881	0.39412	0.57229	-1.0000
-137	15.145	0.98979	0.39451	0.57286	-1.0000
-142	15.095	0.98652	0.39321	0.57097	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.890	0.97312	0.38787	0.56321	0.39800
112	14.840	0.96986	0.38657	0.56132	0.43100
122	14.860	0.97116	0.38709	0.56208	0.44900
127	15.130	0.98881	0.39412	0.57229	0.48690
137	15.145	0.98979	0.39451	0.57286	0.52200
142	15.095	0.98652	0.39321	0.57097	0.58800
152	15.270	0.99805	0.39777	0.57759	-1.0000
157	15.275	0.99829	0.39790	0.57778	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.270	0.99805	0.39777	0.57759	-1.0000
-157	15.275	0.99829	0.39790	0.57778	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.275	0.99829	0.39790	0.57778	0.79300
172	15.275	0.99829	0.39790	0.57778	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.650	0.95744	0.38162	0.55413	0.79300
187	14.310	0.93522	0.37276	0.54127	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

IF=0I 652.21   FIG 647.13   SIGMA IG 3.6702   FTAPE 2.7017   DSM 2.3276   CFM 0.3021206

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	7.5367	0.49454	0.17977	0.26351	0.72200
37	15.366	1.0477	0.38084	0.55825	0.82000
47	18.152	1.1911	0.43296	0.63466	0.91900
52	18.437	1.2098	0.43976	0.64462	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	19.377	1.2715	0.46219	0.67749	0.42200
67	15.096	0.99059	0.36008	0.52783	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	9.6997	0.63641	0.23134	0.33910	0.50800
82	21.517	1.4119	0.51324	0.75233	0.58300
92	15.226	0.99912	0.36318	0.53237	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.846	0.97419	0.35412	0.51908	-1.0000
-112	14.786	0.97024	0.35269	0.51698	-1.0000
-122	14.806	0.97156	0.35316	0.51768	-1.0000
-127	15.071	0.98895	0.35949	0.52695	-1.0000
-137	15.101	0.99092	0.36020	0.52800	-1.0000
-142	15.196	0.99993	0.35984	0.52748	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.846	0.97419	0.35412	0.51908	0.39800
112	14.786	0.97024	0.35269	0.51698	0.43100
122	14.806	0.97156	0.35316	0.51768	0.44900
127	15.071	0.98895	0.35949	0.52695	0.48600
137	15.101	0.99092	0.36020	0.52800	0.52200
142	15.196	0.98993	0.35984	0.52748	0.58800
-152	15.221	0.99979	0.36306	0.53220	-1.0000
-157	15.221	0.99979	0.36306	0.53220	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAY NOZZLE PLAN

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.221	0.99979	0.36306	0.53220	-1.0000
-157	15.221	0.99979	0.36306	0.53220	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.236	0.99978	0.36342	0.53272	0.79300
172	15.236	0.99978	0.36342	0.53272	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.651	0.96138	0.34946	0.51226	0.79300
187	14.326	0.94005	0.34171	0.50090	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

| (F-D) 741.96 | FIC 737.58 | SIGMA IC 2.9599 | FTAPF 2.0590 | CSM 2.3204 | CEM 0.0021249 |

255

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDETI   REC 10/24/79 05:0R:30.761   FAC BKAX1   PGN C034   RDG 1397

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
33	8.9564	0.58950	0.18893	0.27718	0.72200
37	15.303	0.98759	0.31649	0.46432	0.82000
47	19.559	1.2873	0.41257	0.60527	0.91900
52	19.928	1.3116	0.42037	0.61672	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER T.O.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	21.928	1.4433	0.46255	0.67861	0.42200
67	17.469	1.1629	0.37270	0.54679	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.O.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	11.072	0.72878	0.23357	0.34267	0.50800
82	15.768	1.0379	0.33262	0.48799	0.58300
92	15.193	1.0009	0.32049	0.47020	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.938	0.97664	0.31391	0.45921	-1.0000
-112	14.803	0.97434	0.31227	0.45213	-1.0000
-122	14.818	0.97532	0.31258	0.45859	-1.0000
-127	15.078	0.99244	0.31807	0.46664	-1.0000
-137	15.133	0.99606	0.31923	0.46834	-1.0000
=142	15.188	0.99968	0.32039	0.47004	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.938	0.97664	0.31301	0.45921	0.39960
112	14.803	0.97434	0.31227	0.45813	0.43100
122	14.818	0.97532	0.31258	0.45859	0.44900
127	15.078	0.99244	0.31807	0.46664	0.48600
137	15.133	0.99606	0.31923	0.46834	0.52200
142	15.188	0.99968	0.32039	0.47004	0.58800
147	15.204	1.0010	0.32081	0.47066	-1.0000
132	15.204	1.0012	0.32081	0.47066	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.208	1.0010	0.32081	0.47066	-1.0000
-152	15.208	1.0012	0.32081	0.47066	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.208	1.0010	0.32081	0.47066	0.79300
172	15.208	1.0010	0.32081	0.47066	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.593	0.96051	0.30784	0.45163	0.79300
187	14.249	0.93780	0.30056	0.44095	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

TF-D) 296.66   FIT 891.38   SIGMA TC 4.0596   FTARF 2.7589   DSM 2.3221   CEM 0.0021256

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.291	0.74118	0.20488	0.29688	0.72200
37	18.439	1.2395	0.33432	0.48444	0.92000
47	14.153	0.92984	0.25702	0.37245	0.91900
52	21.225	1.3944	0.38545	0.55855	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
57	26.146	1.7178	0.47483	0.68807	0.42200
67	21.715	1.4266	0.39435	0.57145	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.872	0.84571	0.23377	0.33875	0.50800
82	18.384	1.2078	0.33386	0.48380	0.58300
92	15.228	1.0005	0.27655	0.40075	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.958	0.97617	0.26983	0.39101	-1.0000
-112	14.813	0.97322	0.26901	0.38983	-1.0000
-122	14.948	0.97552	0.26965	0.39075	-1.0000
-127	15.108	0.99269	0.27437	0.39759	-1.0000
-137	15.173	0.99688	0.27555	0.39930	-1.0000
-162	15.223	1.0002	0.27646	0.40062	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.858	0.97617	0.26983	0.39101	0.39800
112	14.813	0.97322	0.26901	0.38983	0.43100
122	14.948	0.97552	0.26965	0.39075	0.44900
127	15.108	0.99269	0.27437	0.39759	0.48600
137	15.173	0.99688	0.27555	0.39930	0.52200
142	15.223	1.0002	0.27646	0.40062	0.58800
-157	15.224	1.0005	0.27655	0.40075	-1.0000
-157	15.229	1.0002	0.27646	0.40062	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.228	1.0005	0.27655	0.40075	-1.0000
-157	15.223	1.0002	0.27646	0.40062	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.223	1.0002	0.27646	0.40062	0.79300
172	15.228	1.0005	0.27655	0.40075	0.94400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.633	0.96139	0.26574	0.38509	0.79300
187	14.313	0.94025	0.25993	0.37666	0.94400

>SECTION 5 , MEASURED THRUST PARAMETERS

(F-D) 1129.7   FIC 1124.8   SIGMA IC 4.1512   FTARE 2.5167   DCW 2.3829   CFW 0.0021206

257

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   PFC 10/24/79 05:13:10.C14   FAF 8X6X1   PGM C034   RDG 1399

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.357	0.74932	0.19732	0.28693	0.72200
37	19.918	1.3125	0.34609	0.50324	0.82000
47	14.953	0.99529	0.25981	0.37779	0.91900
52	21.273	1.4318	0.76963	0.53748	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	27.200	1.7923	0.47260	0.68721	0.42200
67	22.323	1.4710	0.38784	0.56401	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.427	0.88678	0.23330	0.33925	0.50800
82	19.208	1.2657	0.33375	0.48530	0.58300
92	15.163	0.99913	0.26346	0.38310	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.803	0.97540	0.25720	0.37400	-1.0000
-112	14.763	0.97277	0.25651	0.37299	-1.0000
-122	14.788	0.97442	0.25654	0.37362	-1.0000
-127	15.049	0.99155	0.26146	0.38019	-1.0000
-137	15.103	0.99518	0.26242	0.38159	-1.0000
-147	15.163	0.99913	0.26346	0.38310	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.803	0.97540	0.25720	0.37400	0.39800
112	14.763	0.97277	0.25651	0.37299	0.43100
122	14.788	0.97442	0.25654	0.37362	0.44900
127	15.049	0.99155	0.26146	0.38019	0.48600
137	15.103	0.99518	0.26242	0.38159	0.52200
147	15.163	0.99913	0.26346	0.38310	0.58800
	15.178	1.0001	0.26372	0.38347	-1.0000
	15.178	1.0001	0.26372	0.38347	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.178	1.0001	0.26372	0.38347	-1.0000
-163	15.178	1.0001	0.26372	0.38347	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.173	0.99979	0.26363	0.38335	0.79300
172	15.173	0.99979	0.26363	0.38335	0.94400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.698	0.96782	0.25520	0.37109	0.79300
187	14.393	0.94828	0.25008	0.36364	0.94400

>SECTION 5 , MEASURED THRUST PARAMETERS

FG-M 1234.2   FIC 1130.6   SIGMA IC 2.7673   FTAPE 2.3577   OSM 2.3342   CFN 0.0021246

NACA-LEWIS   PRELIMINARY DATA   06/13/79   CARPETT   REC 10/24/79 05:13:28.5PR   FAC RX6XI   PGM C036   RUN 11 / ROG 1400

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.349	0.74773	0.19716	0.28628	0.72200
37	19.931	1.3132	0.34626	0.50278	0.82900
47	14.995	0.98733	0.26033	0.37801	0.91900
52	21.301	1.4035	0.37004	0.53724	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
42	27.208	1.7927	0.47268	0.68634	0.42200
47	22.346	1.4723	0.38822	0.56371	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.435	0.88517	0.23340	0.33890	0.50800
82	19.231	1.2671	0.33409	0.48512	0.58300
92	15.195	1.0012	0.26398	0.38331	0.67003

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.825	0.97679	0.25755	0.37398	-1.0000
-112	14.775	0.97349	0.25668	0.37271	-1.0000
-122	14.805	0.97547	0.25720	0.37347	-1.0000
-127	15.065	0.99260	0.26172	0.38003	-1.0000
-137	15.120	0.99623	0.26268	0.38142	-1.0000
-142	15.180	1.0002	0.26372	0.38293	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.825	0.97679	0.25755	0.37398	0.39800
112	14.775	0.97349	0.25668	0.37271	0.43100
122	14.805	0.97547	0.25720	0.37347	0.44900
127	15.065	0.99260	0.26172	0.38003	0.48600
137	15.120	0.99623	0.26268	0.38142	0.52200
142	15.180	1.0002	0.26372	0.38293	0.58800
-152	15.190	1.0008	0.26389	0.38319	-1.0000
-157	15.195	1.0012	0.26398	0.38331	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.190	1.0008	0.26389	0.38319	-1.0000
-157	15.195	1.0012	0.26398	0.38331	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.195	1.0012	0.26398	0.38331	0.79300
172	15.200	1.0015	0.26407	0.38344	0.94400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.715	0.96954	0.25564	0.37120	0.79300
187	14.420	0.95009	0.25051	0.36376	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FG-D) 1204.9   FIC 1200.1   SIGMA IC 3.8358   FTARE 2.4995   DSM 2.3536   CFM 0.3021229

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDETT   REC 10/24/79 OF:15:03.359   FAC RX6X1   PGM C034   PDG 1491

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	11.316	0.74222	0.20515	0.29677	0.72200
37	18.451	1.2102	0.33450	0.48388	0.82000
47	14.186	0.93049	0.25719	0.37204	0.91900
52	21.260	1.3945	0.38544	0.55756	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	26.200	1.7185	0.47499	0.68711	0.42200
67	21.760	1.4273	0.39450	0.57067	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	12.876	0.84456	0.23344	0.33769	0.50800
82	18.431	1.2089	0.33414	0.48336	0.58300
92	15.241	0.99968	0.27632	0.39971	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	14.866	0.97509	0.26952	0.38988	1.0000
-112	14.821	0.97214	0.26870	0.38870	-1.0000
-122	14.851	0.97410	0.26925	0.38948	-1.0000
-127	15.126	0.99214	0.27423	0.39670	-1.0000
-137	15.181	0.99575	0.27523	0.39814	-1.0000
-142	15.231	0.99903	0.27613	0.39945	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	14.866	0.97509	0.26952	0.38988	0.39800
112	14.821	0.97214	0.26870	0.38870	0.43100
122	14.851	0.97410	0.26925	0.38948	0.44900
127	15.126	0.99214	0.27423	0.39670	0.48600
137	15.181	0.99575	0.27523	0.39814	0.52200
142	15.231	0.99903	0.27613	0.39945	0.58800
	15.241	0.99968	0.27632	0.39971	-1.0000
-147	15.241	0.99968	0.27632	0.39971	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	15.241	0.99968	0.27632	0.39971	-1.0000
-157	15.241	0.99968	0.27632	0.39971	1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
167	15.246	1.0000	0.27641	0.39984	0.79300
172	15.251	1.0003	0.27650	0.39997	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
182	14.666	0.96197	0.26589	0.38463	0.79300
187	14.331	0.94000	0.25982	0.37595	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

| FG-DJ 1133.4 | FIC 1129.7 | SIGMA IC 5.0836 | FTAPF 2.3429 | DSP 2.4126 | CFG 0.0021193 |

Run 22

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   REC 10/24/79 05:16:35.07?   FAC 8X6?1   PGM C034   RDG 1402

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	8.9843	0.59116	0.18966	0.27777	0.72200
37	14.920	0.98174	0.31497	0.46129	0.82000
47	19.564	1.2873	0.41300	0.60487	0.91900
52	19.949	1.3126	0.42113	0.61677	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	21.948	1.4442	0.46334	0.67858	0.42200
67	17.689	1.1640	0.37343	0.54691	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	11.060	0.72774	0.23348	0.34195	0.50800
82	15.765	1.0373	0.33281	0.48741	0.58300
92	15.210	1.0008	0.32109	0.47025	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.860	0.97779	0.31370	0.45944	-1.0000
-112	14.805	0.97417	0.31254	0.45774	-1.0000
-122	14.835	0.97614	0.31318	0.45866	-1.0000
-127	15.095	0.99325	0.31866	0.46670	-1.0000
-137	15.150	0.99687	0.31982	0.46840	-1.0000
-147	15.205	1.0005	0.32099	0.47010	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.860	0.97779	0.31370	0.45944	0.39800
112	14.805	0.97417	0.31254	0.45774	0.43100
122	14.835	0.97614	0.31318	0.45866	0.46900
127	15.095	0.99325	0.31866	0.46670	0.48600
137	15.150	0.99687	0.31982	0.46840	0.52200
142	15.205	1.0005	0.32099	0.47010	0.58900
-152	15.195	0.99983	0.32077	0.46979	-1.0000
-157	15.195	0.99983	0.32077	0.46979	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.195	0.99983	0.32077	0.46979	-1.0000
-157	15.195	0.99983	0.32077	0.46979	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.195	0.99983	0.32077	0.46979	0.79300
172	15.190	0.99950	0.32067	0.46964	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.595	0.95970	0.30790	0.45009	0.79300
187	14.250	0.93765	0.30083	0.44058	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 889.36   FLC 884.14   SIGMA LC 3.1538   FTAPE 2.8930   DSM 2.3363   CEM 0.0021244

Run 22

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDEII   REC 10/24/79 05:17:58.123   FAC RX6X1   PGM C034   PNG 1403

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	7.5367	0.49610	0.17951	0.26356	0.72200
37	15.861	1.0441	0.37779	0.55467	0.82000
47	18.112	1.1922	0.43139	0.63337	0.91900
52	18.497	1.2116	0.43841	0.64368	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
52	19.357	1.2742	0.46104	0.67691	0.42200
67	15.096	0.99370	0.35956	0.52792	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	9.6837	0.63742	0.23065	0.33864	0.50800
82	21.377	1.4071	0.50916	0.74756	0.58300
92	15.201	1.0006	0.36207	0.53159	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.836	0.97658	0.35337	0.51882	-1.0000
-112	14.776	0.97263	0.35194	0.51672	-1.0000
-122	14.906	0.97461	0.35265	0.51777	-1.0000
-127	15.051	0.99074	0.35849	0.52634	-1.0000
-137	15.086	0.99304	0.35933	0.52757	-1.0000
-142	15.071	0.99205	0.35897	0.52704	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.836	0.97658	0.35337	0.51882	0.39800
112	14.776	0.97263	0.35194	0.51672	0.43100
122	14.836	0.97461	0.35265	0.51777	0.44900
127	15.051	0.99074	0.35849	0.52634	0.48600
137	15.086	0.99304	0.35933	0.52757	0.52200
142	15.071	0.99205	0.35897	0.52704	0.58800
-152	15.201	1.0006	0.36207	0.53159	-1.0000
-157	15.201	1.0006	0.36207	0.53159	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.201	1.0006	0.36207	0.53159	-1.0000
-157	15.201	1.0006	0.36207	0.53159	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.196	1.0003	0.36195	0.53141	0.79300
172	15.196	1.0003	0.36195	0.53141	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.621	0.96243	0.34825	0.51130	0.79300
187	14.301	0.94136	0.34062	0.50011	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

IF=D) 744.23   FIC 735.45   SIGMA IC 3.4791   FTAPF 2.4587   DSM 2.3241   CFM 0.0921255

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	14.465	0.94635	0.44914	0.64326	0.72200
37	16.305	1.0667	0.50627	0.72509	0.82000
47	16.725	1.0942	0.51932	0.74377	0.91900
52	16.890	1.1050	0.52444	0.75111	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	16.310	1.0671	0.50643	0.72531	0.42200
67	15.010	0.98201	0.46606	0.66750	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	13.375	0.87502	0.41528	0.59477	0.50800
82	18.065	1.1819	0.56092	0.80336	0.58300
92	15.295	1.0007	0.47491	0.68017	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	14.860	0.97219	0.46140	0.66083	-1.0000
-112	14.795	0.96794	0.45938	0.65794	-1.0000
-122	14.805	0.96859	0.45970	0.65838	-1.0000
-127	15.080	0.98659	0.46824	0.67061	-1.0000
-137	15.095	0.98757	0.46870	0.67127	-1.0000
-142	14.965	0.97906	0.46466	0.66550	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	14.860	0.97219	0.46140	0.66083	0.39800
112	14.795	0.96794	0.45938	0.65794	0.43100
122	14.805	0.96859	0.45970	0.65838	0.44900
127	15.080	0.98659	0.46824	0.67061	0.48600
137	15.095	0.98757	0.46870	0.67128	0.52200
142	14.965	0.97906	0.46466	0.66550	0.58800
-152	15.295	1.0007	0.47491	0.68017	-1.0000
-157	15.290	1.0003	0.47476	0.67995	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	15.295	1.0007	0.47491	0.68017	-1.0000
-157	15.290	1.0003	0.47476	0.67995	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
167	15.295	1.0000	0.47460	0.67973	0.79300
172	15.290	0.99967	0.47445	0.67951	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
182	14.750	0.96499	0.45799	0.65593	0.79300
187	14.400	0.94209	0.44712	0.64037	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

IF-PI 493.30   FLC 488.35   SIGMA LC 2.8594   FTAPE 2.5735   DSM 2.3789   CFM 0.9021205

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFIT   REC 10/24/79 05:21:06.859   FAC RK6X1   PGM CO34   RDG 1405

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.195	0.99810	0.54919	0.79040	0.72200
37	15.950	1.0477	0.57542	0.82966	0.82000
47	16.145	1.0605	0.58245	0.83980	0.91900
52	16.235	1.0664	0.58570	0.84468	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	15.920	1.0391	0.57073	0.82290	0.42200
67	15.435	1.0139	0.55685	0.80288	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.551	0.89007	0.48886	0.70486	0.50800
82	17.334	1.1386	0.62537	0.90167	0.58300
92	15.250	1.0010	0.54982	0.79274	0.67000

>ADDITIONAL PRESSURE RATIOS , FORWARD SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.940	0.97478	0.53539	0.77194	-1.0000
-112	14.770	0.97019	0.53297	0.76830	-1.0000
-122	14.795	0.97183	0.53377	0.76960	-1.0000
-127	15.345	0.98825	0.54278	0.78260	-1.0000
-137	15.070	0.98989	0.54369	0.78390	-1.0000
-142	14.970	0.98332	0.54008	0.77870	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.940	0.97478	0.53539	0.77194	0.39800
112	14.770	0.97019	0.53287	0.76830	0.43100
122	14.795	0.97183	0.53377	0.76960	0.44900
127	15.345	0.98825	0.54278	0.78260	0.48600
137	15.070	0.98989	0.54369	0.78390	0.52200
142	14.970	0.98332	0.54008	0.77870	0.58800
-152	15.235	1.0007	0.54964	0.79248	-1.0000
-157	15.235	1.0007	0.54964	0.79248	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.235	1.0007	0.54964	0.79268	-1.0000
-157	15.235	1.0007	0.54964	0.79248	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.230	1.0004	0.54946	0.79222	0.79300
172	15.230	1.0004	0.54946	0.79222	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.740	0.96822	0.53178	0.76674	0.79300
187	14.413	0.94655	0.51988	0.74958	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FF=D) 353.11   FLC 349.30   SIGMA LC 3.6650   FTAPE 2.4908   DSM 2.3710   CFM 2.9921255

264

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDETT   PFC 10/24/79 05:24:12.916   FAC RX6X1   PGN C034   PPG 1406

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	10.063	0.65983	0.19296	0.32694	0.72200
37	15.723	1.0313	0.30151	0.51085	0.82000
47	19.812	1.2991	0.37993	0.64371	0.91900
52	19.942	1.3011	0.38050	0.64468	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	21.372	1.4014	0.40983	0.69438	0.42200
67	18.429	1.2083	0.35337	0.59872	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.183	0.79888	0.23363	0.39584	0.50800
82	17.379	1.1395	0.33324	0.56461	0.58300
92	15.263	1.0008	0.29269	0.49591	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.883	0.97593	0.28540	0.48356	-1.0000
-112	14.823	0.97199	0.28425	0.48161	-1.0000
-122	14.843	0.97330	0.28464	0.48226	-1.0000
-127	15.135	0.99068	0.28972	0.49087	-1.0000
-137	15.163	0.99428	0.29077	0.49266	-1.0000
-142	15.218	0.99789	0.29183	0.49445	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.883	0.97593	0.28540	0.48356	0.39800
112	14.823	0.97199	0.28425	0.48161	0.43100
122	14.843	0.97330	0.28464	0.48226	0.44900
127	15.135	0.99068	0.28972	0.49087	0.48600
137	15.163	0.99428	0.29077	0.49266	0.52200
142	15.219	0.99789	0.29183	0.49445	0.58600
147	15.253	1.0002	0.29250	0.49558	-1.0000
152	15.249	0.99986	0.29240	0.49542	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.253	1.0002	0.29250	0.49558	-1.0000
-157	15.248	0.99986	0.29240	0.49542	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.248	0.99986	0.29240	0.49542	0.79300
172	15.248	0.99986	0.29240	0.49542	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.573	0.95560	0.27946	0.47349	0.79300
187	14.138	0.93101	0.27227	0.46131	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
(F-D) 964.83   FIC 960.37   SIGMA IC 4.7906   FTARE 2.3743   DSM 2.3818   CF= 0.0021203

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	10.737	0.70621	0.20600	0.29749	0.72200
37	16.566	1.0883	0.31744	0.45842	0.82003
47	15.121	0.99457	0.29011	0.41896	0.91900
52	20.939	1.3752	0.40114	0.57930	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	24.657	1.6217	0.47306	0.68316	0.42200
67	20.294	1.3341	0.38916	0.56200	0.67003

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.177	0.80091	0.23362	0.33738	0.50800
82	17.369	1.1418	0.33307	0.48099	0.58360
92	15.206	1.0002	0.29174	0.42131	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.926	0.97517	0.28445	0.41079	-1.0000
-112	14.787	0.97254	0.28369	0.40968	-1.0000
-122	14.826	0.97385	0.28407	0.41023	-1.0000
-127	15.071	0.99128	0.28915	0.41757	-1.0000
-137	15.131	0.99522	0.29030	0.41924	-1.0000
-152	15.191	0.99917	0.29145	0.42090	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.926	0.97517	0.28445	0.41079	0.39800
112	14.787	0.97254	0.28369	0.40968	0.43190
122	14.826	0.97385	0.28407	0.41023	0.44900
127	15.071	0.99128	0.28915	0.41757	0.48600
137	15.131	0.99522	0.29030	0.41924	0.52200
142	15.191	0.99917	0.29145	0.42090	0.58800
-152	15.206	1.0002	0.29174	0.42131	-1.0000
-157	15.206	1.0002	0.29174	0.42131	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.206	1.0002	0.29174	0.42131	-1.0000
-157	15.206	1.0002	0.29174	0.42131	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.201	0.99983	0.29165	0.42117	0.79300
172	15.201	0.99983	0.29165	0.42117	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.402	0.94723	0.27630	0.39902	0.79300
187	16.012	0.92158	0.26882	0.38821	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
(F-D) 1043.6   FIG 1039.9   SIGMA IG 4.6247   FTAPF 2.4199   DFM 2.3445   CFM 0.0021232

NASA-LEWIS PRELIMINARY DATA CADDE-II FACILITY   RX/X1   PROGRAM C034   PDGS   1408 TO 1437
TIME AND DATE PROCESSED 03:51:25 JUN 13 1979

NOZZLE TYPE	P+W BASE EJECTOR NOZZLE (MODEL C)
FLIGHT CONDITIONS	TAKEOFF
NOZZLE CONFIGURATION	C3
PRIMARY-NOZZLE PLUG	SPLIT PLUG (EXTENDED)
FLOW SPLITTER	ISENTROPIC SPLITTER
FAN NOZZLE	SHORT FLAP
CLAMSHELL POSITION	21 DEG
EJECTOR INLET OPENING	MIDWAY

RDG	NO	PTF/PTP	PTF/PO	PTP/PO	OMEGA	PTS/PTF	COF	COP	CF1	ETA1	ETA1.INT	CFP1	CFP2	FG
1408	0.012	1.69	1.81	1.07	0.000	0.549	0.964	0.840	0.9390	0.9390	0.9390	0.9390	0.9430	******
1409	0.019	1.68	2.11	1.26	0.000	0.471	0.966	0.895	0.9285	0.9285	0.9285	0.9285	0.9310	******
1410	0.041	1.67	2.52	1.50	0.000	0.395	0.967	0.964	0.8928	0.8928	0.8928	0.8928	0.8959	******
1411	0.054	1.70	3.12	1.84	0.000	0.321	0.967	0.948	0.8764	0.8764	0.8764	0.8764	0.8791	******
1412	0.041	1.69	2.76	1.63	0.000	0.361	0.967	0.959	0.8824	0.8824	0.8824	0.8824	0.8854	******
1413	0.052	1.70	3.61	2.12	0.000	0.279	0.968	0.927	0.9083	0.9083	0.9083	0.9083	0.9105	******
1414	0.055	1.70	4.18	2.47	0.000	0.244	0.970	0.969	0.8995	0.8995	0.8995	0.8995	0.9014	******
1415	0.060	1.70	4.19	2.47	0.000	0.243	0.969	0.969	0.8998	0.8998	0.8998	0.8998	0.9016	******
1416	0.055	1.70	3.59	2.11	0.000	0.279	0.969	0.928	0.9083	0.9083	0.9084	0.9084	0.9105	******
1417	0.052	1.70	3.10	1.83	0.000	0.322	0.968	0.950	0.8764	0.8764	0.8764	0.8764	0.8791	******
1418	0.040	1.69	2.76	1.63	0.000	0.360	0.967	0.959	0.8819	0.8819	0.8819	0.8819	0.8849	******
1419	0.019	1.69	2.49	1.47	0.000	0.399	0.966	0.965	0.8916	0.8916	0.8916	0.8916	0.8947	******
1420	0.023	1.69	2.11	1.25	0.000	0.472	0.967	0.895	0.9220	0.9220	0.9220	0.9220	0.9245	******
1421	0.037	1.70	1.81	1.06	0.000	0.550	0.965	0.842	0.9247	0.9247	0.9248	0.9248	0.9256	******
1422	0.043	1.70	3.61	2.13	0.000	0.279	0.971	0.928	0.9075	0.9075	0.9075	0.9075	0.9096	******
1423	0.004	1.70	1.80	1.06	0.000	0.551	0.963	0.850	0.9300	0.9300	0.9300	0.9300	0.9309	******
1424	0.029	1.46	1.81	1.24	0.000	0.550	0.965	0.910	0.9212	0.9212	0.9213	0.9213	0.9242	******
1425	0.016	1.43	2.11	1.48	0.000	0.473	0.966	0.962	0.9196	0.9196	0.9196	0.9196	0.9233	******
1426	0.037	1.44	2.50	1.74	0.000	0.398	0.968	0.982	0.8944	0.8944	0.8944	0.8944	0.8979	******
1427	0.053	1.46	2.76	1.89	0.000	0.361	0.967	0.990	0.8874	0.8874	0.8874	0.8874	0.8904	******
1428	0.052	1.47	3.11	2.12	0.000	0.323	0.968	0.979	0.8783	0.8783	0.8783	0.8783	0.8809	******
1429	0.053	1.44	3.61	2.50	0.000	0.290	0.969	0.965	0.9050	0.9050	0.9050	0.9050	0.9071	******
1430	0.063	1.45	4.13	2.85	0.000	0.247	0.972	0.983	0.9004	0.9004	0.9004	0.9004	0.9023	******
1431	0.052	1.45	4.14	2.85	0.000	0.247	0.969	0.983	0.9004	0.9004	0.9004	0.9004	0.9023	******
1432	0.055	1.45	3.60	2.49	0.000	0.290	0.970	0.965	0.9048	0.9048	0.9048	0.9048	0.9069	******
1433	0.043	1.47	3.10	2.10	0.000	0.324	0.968	0.979	0.8787	0.8787	0.8787	0.8787	0.8813	******
1434	0.053	1.46	2.75	1.89	0.000	0.362	0.967	0.979	0.8860	0.8860	0.8861	0.8861	0.8891	******
1435	0.035	1.44	2.51	1.74	0.000	0.397	0.967	0.981	0.8963	0.8963	0.8963	0.8963	0.8998	******
1436	0.031	1.42	2.12	1.48	0.000	0.471	0.965	0.961	0.9226	0.9226	0.9226	0.9226	0.9263	******
1437	0.019	1.45	1.81	1.25	0.000	0.549	0.964	0.914	0.9243	0.9243	0.9243	0.9243	0.9273	******

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.509	1.0124	0.55976	0.94561	0.72200
37	14.689	1.0249	0.56670	0.95732	0.82000
47	14.738	1.0284	0.56862	0.96057	0.91900
52	14.748	1.0291	0.56901	0.96123	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.589	1.0180	0.56285	0.95081	0.42200
67	14.514	1.0127	0.55996	0.94593	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.567	0.87687	0.48483	0.81902	0.50800
82	16.016	1.1176	0.61793	1.0439	0.58300
92	14.299	0.99776	0.55167	0.93194	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.269	0.99567	0.55052	0.92999	-1.0000
-112	14.264	0.99533	0.55033	0.92966	-1.0000
-122	14.264	0.99533	0.55033	0.92966	-1.0000
-127	14.269	0.99567	0.55052	0.92999	-1.0000
-137	14.249	0.99428	0.54975	0.92869	-1.0000
-142	14.204	0.99114	0.54801	0.92576	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.269	0.99567	0.55052	0.92999	0.39800
112	14.264	0.99533	0.55033	0.92966	0.43100
122	14.264	0.99533	0.55033	0.92966	0.44900
127	14.269	0.99567	0.55052	0.92999	0.48600
137	14.249	0.99428	0.54975	0.92869	0.52200
142	14.204	0.99114	0.54801	0.92576	0.58800
-152	14.304	0.99811	0.55187	0.93227	-1.0000
-157	14.309	0.99846	0.55206	0.93259	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.304	0.99811	0.55187	0.93227	-1.0000
-157	14.309	0.99846	0.55206	0.93259	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
152	14.304	0.99811	0.55187	0.93227	0.79300
172	14.309	0.99846	0.55206	0.93259	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.615	0.95004	0.52528	0.88736	0.79300
187	13.520	0.94342	0.52162	0.88118	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-0) 286.82   FIC 285.94   SIGMA LC 2.7142   FTARF-0.13212   DSM 0.0041212   CFM 1.1137752

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
42	14.920	1.0342	0.49010	0.82372	0.72200
47	15.499	1.0916	0.51256	0.86146	0.82000
47	15.643	1.0917	0.51735	0.86951	0.91900
52	15.629	1.0907	0.51685	0.86867	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
42	15.239	1.0635	0.50397	0.84703	0.42200
57	14.934	1.0422	0.49390	0.83010	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.398	0.86522	0.41001	0.68911	0.50800
82	16.712	1.1663	0.55268	0.92889	0.58300
87	14.285	0.99694	0.47243	0.79402	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.250	0.99450	0.47128	0.79208	-1.0000
-112	14.250	0.99450	0.47128	0.79208	-1.0000
-122	14.255	0.99485	0.47144	0.79236	-1.0000
-127	14.270	0.99590	0.47194	0.79319	-1.0000
-137	14.245	0.99416	0.47111	0.79180	-1.0000
-142	14.205	0.99137	0.46979	0.78958	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY_INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.250	0.99450	0.47128	0.79208	0.39800
112	14.250	0.99450	0.47128	0.79208	0.43100
122	14.255	0.99485	0.47144	0.79236	0.44900
127	14.270	0.99590	0.47194	0.79319	0.48600
137	14.245	0.99415	0.47111	0.79180	0.52200
142	14.205	0.99137	0.46979	0.78958	0.58800
152	14.300	0.99799	0.47293	0.79485	-1.0000
157	14.305	0.99834	0.47309	0.79513	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.300	0.99799	0.47293	0.79485	-1.0000
-157	14.305	0.99834	0.47309	0.79513	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.300	0.99799	0.47293	0.79485	0.79300
172	14.310	0.99869	0.47326	0.79541	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.401	0.93526	0.44320	0.74490	0.79300
187	13.307	0.92864	0.44007	0.73962	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS
| IF-DI 407.69 | FL 406.76 | SIGMA IC 2.5298 | FTAPF-0.072544 | DSM 0.029607 | CFN 0.0039919 |

VARI-EMIC   PRELIMINARY DATA   06/17/79   CADDFI1   DEC 10/24/79 20:37:40.970   FAC SEAR1   PGM CO?6

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTF	X/DMAX
32	14.800	1.0347	0.41128	0.68858	0.72200
37	16.594	1.1596	0.46091	0.7716A	0.82000
47	16.946	1.1847	0.47089	0.78839	0.91900
5?	16.881	1.1801	0.46900	0.78537	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
57	15.659	1.0967	0.43512	0.72851	0.42200
67	14.301	0.99982	0.39741	0.66577	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	1/PO	PL/PTF	PL/PTP	X/DMAX
77	8.1426	2.56926	0.22627	0.37883	0.50800
8?	20.767	1.451A	0.57707	0.95617	0.58300
9?	14.267	0.99728	0.39654	0.66375	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.212	0.99355	0.39492	0.66119	-1.0000
-112	14.207	0.99320	0.39478	0.66096	-1.0000
-12?	14.202	0.99285	0.39464	0.66073	-1.0000
-12?	14.232	0.99494	0.39547	0.66212	-1.0000
-13?	14.732	0.99404	0.39547	0.66377	-1.0000
-142	14.222	0.99424	0.39519	0.66166	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.212	0.99355	0.39492	0.66119	0.39800
112	14.207	0.99320	0.39478	0.66096	0.42100
12?	14.202	0.99285	0.39464	0.66073	0.44900
127	14.232	0.99494	0.39547	0.66212	0.48600
13?	14.732	0.99494	0.39547	0.66212	0.52200
14?	14.222	0.99424	0.39519	0.66166	0.58800
-16?	14.298	0.99878	0.39878	0.66467	-1.0000
-17?	14.293	0.99843	0.39848	0.66228	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-16?	14.296	0.99878	0.39700	0.66467	-1.0000
-17?	14.291	0.99843	0.39686	0.66224	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.296	0.99878	0.39700	0.66467	0.79300
172	14.286	0.99878	0.39700	0.66467	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
18?	13.244	0.92587	0.36807	0.61616	0.79300
19?	13.779	0.96260	0.36760	0.61546	0.84400

>OPTIONS , MEASURED THRUST PARAMETERS

FELD 550.62   SIGMA 1C 2.3745   FTARF 0.20073   DSM C.040647   FEM 0.0030362

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFIT   REC 10/24/79 20:38:44.619   FAC 9X6X1   PGM C034   PDG 1411

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	16.010	1.1207	0.35914	0.60982	0.72200
37	19.089	1.3362	0.42819	0.72708	0.82000
47	19.468	1.3628	0.43670	0.74153	0.91900
52	19.094	1.3366	0.42931	0.72727	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	18.620	1.3034	0.41767	0.70922	0.42200
67	16.749	1.1724	0.37570	0.63795	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	10.431	0.73014	0.23397	0.39729	0.50800
82	14.898	1.0428	0.33417	0.56744	0.58300
92	14.249	0.99742	0.31962	0.54273	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.184	0.99288	0.31817	0.54025	-1.0000
-112	14.164	0.99148	0.31772	0.53949	-1.0000
-122	14.174	0.99219	0.31794	0.53987	-1.0000
-127	14.226	0.99567	0.31906	0.54178	-1.0000
-137	14.239	0.99672	0.31940	0.54235	-1.0000
-162	14.209	0.99463	0.31873	0.54121	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.184	0.99288	0.31917	0.54025	0.39800
112	14.164	0.99148	0.31772	0.53949	0.43100
122	14.174	0.99219	0.31794	0.53987	0.44900
127	14.224	0.99567	0.31906	0.54178	0.48600
137	14.239	0.99672	0.31940	0.54235	0.52200
142	14.209	0.99463	0.31873	0.54121	0.58800
-152	14.279	0.99952	0.32029	0.54387	-1.0000
-157	14.279	0.99952	0.32029	0.54387	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.279	0.99952	0.32029	0.54387	-1.0000
-157	14.279	0.99952	0.32029	0.54387	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.274	0.99917	0.32018	0.54368	0.79300
172	14.274	0.99917	0.32018	0.54368	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.221	0.92546	0.29656	0.50357	0.79300
187	13.196	0.92371	0.29600	0.50262	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS
IF-DI 752.38   FIC 750.51   SIGMA IC 2.5555   FTAPE 0.60297   DSM 0.966997   CFM 0.0929020

RUN23

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   PFC 10/24/79 20:40:33.331   FAC RK6X1   PGM C034   RDG 1412

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.993	1.0473	0.37995	0.64201	0.72200
37	17.433	1.2177	0.44178	0.74649	0.82000
47	17.837	1.2459	0.45202	0.76380	0.91900
52	17.668	1.2341	0.44772	0.75654	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	16.600	1.1595	0.42066	0.71081	0.42200
67	14.828	1.0358	0.37577	0.63496	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	9.0732	0.63376	0.22993	0.38852	0.50800
82	19.174	1.3393	0.48591	0.82106	0.58300
92	14.260	0.99603	0.36136	0.61060	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.195	0.99150	0.35971	0.60782	-1.0000
-112	14.190	0.99115	0.35959	0.60761	-1.0000
-122	14.210	0.99254	0.36009	0.60846	-1.0000
-127	14.245	0.99498	0.36098	0.60996	-1.0000
-137	14.245	0.99498	0.36098	0.60996	-1.0000
-142	14.220	0.99324	0.36034	0.60889	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.195	0.99150	0.35971	0.60782	0.39800
112	14.190	0.99115	0.35959	0.60761	0.43100
122	14.210	0.99254	0.36009	0.60846	0.44900
127	14.245	0.99498	0.36098	0.60996	0.48600
137	14.245	0.99498	0.36098	0.60996	0.52200
142	14.220	0.99324	0.36034	0.60889	0.58800
-152	14.284	0.99777	0.36199	0.61167	-1.0000
-157	14.284	0.99777	0.36199	0.61167	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.284	0.99777	0.36199	0.61167	-1.0000
-157	14.284	0.99777	0.36199	0.61167	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.279	0.99742	0.36186	0.61145	0.79300
172	14.279	0.99742	0.36186	0.61145	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.236	0.92457	0.33543	0.56679	0.79300
187	13.221	0.92352	0.33505	0.56615	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
(F-D) 431.64   FIC 420.58   SIGMA IC 1.0879   FTAPF 3.023912   DSM 0.040634   CFM 0.0030348

DATA-POINT   PRELIMINARY DATA   06/12/79   CERNELI   DFC 10/26/79 20:47:47.256   FAC AV481

>ADDITIONAL PRESSURE RATIOS , PRIMARY DUCT

AVD WORD	PT	PT/PD	PT/PTF	PL/PTP	X/DMAX
32	18.257	1.2770	0.35352	0.69103	0.72200
47	20.153	1.4097	0.39025	0.66347	0.82000
47	21.266	1.4875	0.41182	0.70011	0.91900
57	21.176	1.4778	0.40910	0.69451	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PT	PT/PD	PT/PTF	PL/PTP	X/DMAX
62	22.160	1.5503	0.42910	0.72952	0.42200
67	20.573	1.4367	0.39759	0.67695	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PT	PT/PD	PT/PTF	PL/PTP	X/DMAX
77	12.132	0.84861	0.23492	0.39940	0.50800
82	17.298	1.2100	0.34407	0.56968	0.58300
92	14.259	0.99737	0.27611	0.46941	0.67800

>ADDITIONAL PRESSURE RATIOS , F-OFFSIDE SHROUD

AVD WORD	PT	PT/PC	PL/PTF	PL/PTP	X/DMAX
-107	14.204	0.99353	0.27504	0.46760	-1.0000
-112	14.199	0.99318	0.27495	0.46744	-1.0000
-122	14.189	0.99248	0.27475	0.46711	-1.0000
-127	14.214	0.99423	0.27524	0.46793	0.0000
-137	14.184	0.99213	0.27466	0.46694	-1.0000
-152	14.169	0.99109	0.27437	0.46645	-1.0000

>ADDITIONAL PRESSURE RATIOS , FORWARDY INLET

AVD WORD	PT	PL/PC	PL/PTF	PL/PTP	X/DMAX
107	14.204	0.99353	0.27504	0.46760	0.39800
112	14.199	0.99318	0.27495	0.46744	0.43100
122	14.189	0.99248	0.27475	0.46711	0.44900
127	14.214	0.99423	0.27524	0.46793	0.48800
137	14.184	0.99213	0.27466	0.46694	0.52700
142	14.169	0.99109	0.27437	0.46645	0.59800
-157	14.209	0.99387	0.27513	0.47040	-1.0000
-157	14.208	0.99382	0.27510	0.47033	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PT	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	14.209	0.99447	0.27769	0.47040	-1.0000
-157	14.208	0.99412	0.27759	0.47073	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PT	PL/PD	PL/PTF	PL/PTP	X/DMAX
147	14.284	0.99912	0.27759	0.47023	0.79300
157	14.284	0.99912	0.27759	0.47023	0.84400

>ADDITIONAL PRESSURE RATIOS , 60 DEG SHROUD LOCATION

AVD WORD	PT	PL/PD	PL/PTF	PL/PTP	X/DMAX
162	13.300	0.93033	0.25755	0.43726	0.79300
167	13.265	0.92788	0.25687	0.43671	0.84400

>ADDITIONAL 5 , MEASURED THRUST PARAMETERS   SIGMA IC 2.7792   FTADF 0.61592   DSM C.062517   CFM C.0129192

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFII   REC 10/24/79 20:44:48.170   FAC RX6X1   PGM C034   PDG 1414

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	18.721	1.3106	0.31333	0.53159	0.72200
37	23.388	1.6372	0.39142	0.66438	0.82000
47	24.611	1.7228	0.41189	0.69880	0.91900
52	24.361	1.7054	0.40771	0.69171	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	24.331	1.7033	0.40721	0.69086	0.42200
67	20.623	1.4437	0.34515	0.58557	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.995	0.97968	0.23422	0.39737	0.50800
82	20.059	1.4042	0.33571	0.56956	0.58300
92	14.249	0.99750	0.23868	0.40459	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.139	0.98981	0.23664	0.40148	-1.0000
-112	14.114	0.98806	0.23622	0.40077	-1.0000
-122	14.119	0.98841	0.23631	0.40091	-1.0000
-127	14.189	0.99331	0.23748	0.40289	-1.0000
-137	14.204	0.99435	0.23773	0.40332	-1.0000
-142	14.219	0.99540	0.23798	0.40374	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.139	0.98981	0.23664	0.40148	0.39800
112	14.114	0.98806	0.23622	0.40077	0.43100
122	14.119	0.98841	0.23631	0.40091	0.44900
127	14.189	0.99331	0.23748	0.40289	0.48600
137	14.204	0.99435	0.23773	0.40332	0.52200
142	14.219	0.99540	0.23798	0.40374	0.58800
-152	14.279	0.99959	0.23898	0.40545	-1.0000
-157	14.279	0.99959	0.23898	0.40545	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN-NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.279	0.99959	0.23898	0.40545	-1.0000
-157	14.279	0.99959	0.23898	0.40545	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.279	0.99959	0.23898	0.40545	0.79300
172	14.279	0.99959	0.23898	0.40545	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.665	0.95661	0.22870	0.38801	0.79300
187	13.640	0.95487	0.22829	0.38730	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FF-11 1169.7   FLC 1167.5   SIGMA LC 2.7950   FTAPE 0.19291   DSM 0.2794.5   CFM 0.0728879

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CARDELL   REC 10/24/79 20:45:46.516   FAC RX6X1   PGM C034   RDG 1415

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	18.714	1.3099	0.31256	0.53121	0.72200
37	23.422	1.6394	0.39120	0.66497	0.82000
47	24.666	1.7265	0.41197	0.70016	0.91900
52	24.411	1.7086	0.40771	0.69292	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	24.356	1.7048	0.40680	0.69137	0.42200
67	20.601	1.4420	0.34408	0.58479	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	14.020	0.98133	0.23416	0.39798	0.50800
82	20.072	1.4049	0.33524	0.56976	0.58300
92	14.245	0.99705	0.23792	0.40435	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.140	0.98971	0.23617	0.40138	-1.0000
-112	14.110	0.98762	0.23567	0.40053	-1.0000
-122	14.135	0.98936	0.23608	0.40124	-1.0000
-127	14.195	0.99356	0.23708	0.40294	-1.0000
-137	14.190	0.99321	0.23700	0.40280	-1.0000
-142	14.215	0.99496	0.23742	0.40350	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.140	0.98971	0.23617	0.40138	0.39800
112	14.110	0.98762	0.23567	0.40053	0.43100
122	14.135	0.98936	0.23608	0.40124	0.44900
127	14.195	0.99356	0.23708	0.40294	0.48600
137	14.190	0.99321	0.23700	0.40280	0.52200
142	14.215	0.99496	0.23742	0.40350	0.58800
152	14.270	0.99880	0.23834	0.40506	-1.0000
157	14.280	0.99950	0.23850	0.40535	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.270	0.99880	0.23834	0.40506	-1.0000
-157	14.280	0.99950	0.23850	0.40535	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.275	0.99915	0.23842	0.40521	0.79300
172	14.280	0.99950	0.23850	0.40535	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.665	0.95651	0.22824	0.38791	0.79300
187	13.645	0.95511	0.22791	0.38734	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FG-01 1170.9   FIC 1169.2   SIGMA IC 3.8487   FTAPE 0.58905   DSM 0.092648   CFM 0.0029670

NASA-LEWIS   PRELIMINARY DATA   26/13/79   CADDELL   REC 10/24/79 20:50:06.446   FAC 9X6X1   PGM C034   RDG 1417

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.916	1.1129	0.35865	0.60911	0.72200
37	19.036	1.3288	0.42826	0.72774	0.82000
47	19.385	1.3553	0.43681	0.74185	0.91900
52	19.226	1.3302	0.42871	0.72810	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	18.526	1.2953	0.41747	0.70900	0.42200
67	16.669	1.1648	0.37541	0.63757	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	10.425	0.72885	0.23490	0.39894	0.50800
82	14.867	1.0392	0.33492	0.56890	0.58300
92	14.254	0.99659	0.32119	0.54550	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.189	0.99205	0.31973	0.54301	-1.0000
-112	14.174	0.99100	0.31939	0.54244	-1.0000
-122	14.186	0.99170	0.31962	0.54282	-1.0000
-127	14.239	0.99554	0.32086	0.54492	-1.0000
-137	14.239	0.99554	0.32086	0.54492	-1.0000
-142	14.224	0.99449	0.32052	0.54435	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.189	0.99205	0.31973	0.54301	0.39800
112	14.174	0.99100	0.31939	0.54244	0.43100
122	14.186	0.99170	0.31962	0.54282	0.44900
127	14.239	0.99554	0.32086	0.54492	0.48600
137	14.239	0.99554	0.32086	0.54492	0.52200
142	14.224	0.99449	0.32052	0.54435	0.58800
147	14.274	0.99794	0.32164	0.54626	-1.0000
-152	14.279	0.99833	0.32175	0.54645	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.274	0.99794	0.32164	0.54626	-1.0000
-157	14.279	0.99833	0.32175	0.54645	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.279	0.99833	0.32175	0.54645	0.79300
172	14.279	0.99833	0.32175	0.54645	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.221	0.92434	0.29791	0.50595	0.79300
187	13.201	0.92294	0.29746	0.50518	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

FGRN 747.43   FIC 745.36   SIGMA IC 3.3718   FTARF 3.42945   DSM 0.262505   CFM 0.3023181

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CARDEII   REC 10/24/79 20:51:04.796   EAC 9XAX1   PGM C034   RPG 141R

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.339	1.0487	0.37934	0.64167	0.72203
37	17.453	1.2201	0.44135	0.74656	0.82003
47	17.845	1.2477	0.45132	0.76344	0.91900
52	17.675	1.2358	0.44703	0.75617	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	16.636	1.1632	0.42076	0.71174	0.42200
67	14.864	1.0392	0.37593	0.63560	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	9.1245	0.63797	0.23078	0.39037	0.50800
82	18.743	1.3105	0.47405	0.80188	0.54303
92	14.276	0.99806	0.36103	0.61069	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.215	0.99385	0.35951	0.60913	-1.0000
-112	14.235	0.99318	0.35926	0.60770	-1.0000
-122	14.220	0.99420	0.35964	0.63834	-1.0000
-127	14.249	0.99630	0.31043	0.60963	-1.0000
-137	14.244	0.99595	0.36027	0.60941	-1.0000
-142	14.225	0.99455	0.35976	0.60856	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.215	0.99385	0.35951	0.60813	0.39800
112	14.235	0.99316	0.35926	0.60770	0.43100
122	14.220	0.99420	0.35964	0.60834	0.44900
127	14.249	0.99630	0.36040	0.60963	0.48600
137	14.244	0.99595	0.36027	0.60941	0.52700
142	14.225	0.99455	0.35976	0.60856	0.58800
-147	14.248	0.99874	0.36127	0.61112	-1.0000
-157	14.239	0.99909	0.36141	0.61133	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NEZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-147	16.284	0.99874	0.36128	0.61112	-1.0000
-157	14.299	0.99909	0.36141	0.61133	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.289	0.99909	0.36141	0.61133	0.79300
177	14.299	0.99909	0.36141	0.61133	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
187	13.266	0.92611	0.33503	0.56668	0.79300
197	13.236	0.92562	0.33475	0.56625	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
I=31 / 32.32   FIC /30.03   SIGMA IC 2.0868   ETARF 0.31158   DSM 0.055978   CFM 0.0029471

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDETT   PEC 13/24/79 20:52:36.369   FAC 8X6X1   PG= C034   RDG 1419

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
37	14.763	1.0334	0.41490	0.69926	0.72200
37	16.462	1.1492	0.46176	0.77991	0.82000
47	16.391	1.1729	0.47126	0.79559	0.91900
52	16.737	1.1694	0.46944	0.79291	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	15.524	1.0837	0.43542	0.73545	0.43200
67	14.286	0.99727	0.40069	0.67679	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	8.3633	0.58290	0.23617	0.38201	0.50800
82	20.895	1.4524	0.58354	0.98564	0.58300
92	14.271	0.99622	0.40027	0.67609	0.67900

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.221	0.99274	0.39887	0.67372	-1.0000
-112	14.216	0.99239	0.39873	0.67348	-1.0000
-122	14.211	0.99204	0.39859	0.67325	-1.0000
-127	14.241	0.99413	0.39943	0.67467	-1.0000
-137	14.246	0.99448	0.39957	0.67490	-1.0000
-142	14.221	0.99274	0.39887	0.67372	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.221	0.99274	0.39887	0.67372	0.39800
112	14.216	0.99239	0.39873	0.67348	0.43100
122	14.211	0.99204	0.39859	0.67325	0.44900
127	14.241	0.99413	0.39943	0.67467	0.48600
137	14.246	0.99448	0.39957	0.67490	0.52200
142	14.221	0.99274	0.39887	0.67372	0.58800
152	14.286	0.99727	0.40069	0.67679	1.0000
157	14.286	0.99727	0.40069	0.67679	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.286	0.99727	0.40069	0.67679	-1.0000
-157	14.286	0.99727	0.40069	0.67679	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.291	0.99762	0.40083	0.67703	0.79300
172	14.291	0.99762	0.40083	0.67703	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.237	0.92409	0.37129	0.62717	0.79300
187	13.202	0.92164	0.37031	0.62547	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

IF=01 539.71   FIC 538.22   SIGMA IC 2.3631   FTAPF=0.51581   DSM 0.010461   CFM 0.0034621

RUN 23

DATA-TAPE PRELIMINARY DATA 01/13/79 C2DDFII REC 10/24/75 20:54:32.775 FAC RKKK1 PGM C234 PPG 1420

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVG WORD	PT	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.799	1.0333	0.49360	0.82766	0.72200
37	15.453	1.0790	0.51207	0.84473	0.82000
57	15.598	1.0891	0.51687	0.87232	3.91900
62	15.598	1.0841	0.51654	0.87176	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVG WORD	PT	PL/PO	PL/PTF	PL/PTP	X/DMAX
42	15.203	1.0615	0.50380	0.85027	0.42200
47	14.909	1.0410	0.49404	0.83380	3.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVG WORD	PT	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.413	0.86670	0.41133	0.69421	0.50800
82	16.696	1.1657	0.55425	0.93373	0.58300
92	14.290	0.99712	0.47353	0.79919	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVG WORD	PT	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.755	0.99532	0.47237	0.79723	-1.0000
112	14.250	0.99497	0.47221	0.79695	-1.0000
122	14.255	0.99532	0.47237	0.79723	-1.0000
127	14.272	0.99636	0.47287	0.79807	-1.0000
137	14.244	0.99462	0.47204	0.79684	-1.0000
142	14.205	0.99183	0.47072	0.79444	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVG WORD	PT	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.255	0.99532	0.47237	0.79723	0.39800
117	14.250	0.99497	0.47221	0.74695	0.43100
122	14.255	0.99532	0.47237	0.79723	0.44900
127	14.270	0.99626	0.47287	0.79807	0.48600
137	14.745	0.99462	0.47204	0.79667	0.52200
142	14.205	0.99183	0.47072	0.79644	0.58800
	14.209	0.99880	0.47809	0.80007	-1.0000
	14.209	0.99880	0.47409	0.80002	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVG WORD	PT	PL/PO	PL/PTF	PL/PTP	X/DMAX
152	14.305	0.99880	0.47409	0.80002	-1.0000
152	14.305	0.99880	0.47403	0.80002	-1.0000

>ADDITIONAL PRESSURE RATIOS x 20 DEG SHROUD LOCATION

AVG WORD	PT	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.305	0.99880	0.47403	0.80007	0.79300
172	14.305	0.99880	0.47403	0.80002	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVG WORD	PT	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.307	0.93537	0.44202	0.74921	0.79300
187	13.292	0.92735	0.44012	0.74279	3.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FG 401.18   SIGMA FG 2.3685   FTARE 0.21781   DSM 0.016612   FEV 0.0033367

FG/FI 402.41

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDETT   REC 10/24/79 20:56:43.013   FAC 8X6X1   PGM C034   RPG 1421

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.451	1.0099	0.55884	0.95270	0.72200
37	14.610	1.0211	0.56502	0.96323	0.82000
47	14.640	1.0232	0.56618	0.96521	0.91900
52	14.655	1.0242	0.56675	0.96620	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.491	1.0127	0.56038	0.95534	0.42200
67	14.436	1.0089	0.55826	0.95172	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.539	0.87630	0.48490	0.82665	0.50800
82	15.948	1.1146	0.61675	1.0514	0.58300
92	14.286	0.99840	0.55247	0.94186	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.261	0.99666	0.55151	0.94020	-1.0000
-112	14.256	0.99631	0.55131	0.93987	-1.0000
-122	14.256	0.99631	0.55131	0.93987	-1.0000
-127	14.266	0.99701	0.55170	0.94053	-1.0000
-137	14.241	0.99526	0.55073	0.93888	-1.0000
-142	14.191	0.99108	0.54842	0.93493	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.261	0.99666	0.55151	0.94020	0.39800
112	14.256	0.99631	0.55131	0.93987	0.43100
122	14.256	0.99631	0.55131	0.93987	0.44900
127	14.266	0.99701	0.55179	0.94053	0.48600
137	14.241	0.99526	0.55073	0.93888	0.52200
142	14.191	0.99108	0.54842	0.93493	0.58800
-152	14.296	0.99910	0.55286	0.94250	-1.0000
-157	14.296	0.99910	0.55286	0.94250	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.296	0.99910	0.55286	0.94250	-1.0000
-157	14.296	0.99910	0.55286	0.94250	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.296	0.99910	0.55286	0.94250	0.79300
172	14.296	0.99910	0.55286	0.94250	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.612	0.95131	0.52641	0.89742	0.79300
187	13.507	0.94398	0.52236	0.89050	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

IF-D) 279.37   FIC 277.91   SIGMA IC 2.5914   FTARE 0.42772   DSP 0.033799   CFM 0.0030054

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFII   REC 10/24/79 21:02:58.096   FAC RK6X1   PGM C034   RDG 1422

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	18.242	1.2765	0.35344	0.59940	0.72200
37	20.129	1.4086	0.39001	0.66141	0.82000
47	21.262	1.4879	0.41196	0.69865	0.91900
52	21.127	1.4784	0.40935	0.69422	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	22.161	1.5508	0.42938	0.72812	0.42200
57	20.488	1.4337	0.39697	0.67322	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	12.160	0.85091	0.23560	0.39956	0.50800
82	17.323	1.2122	0.33564	0.56921	0.58300
92	16.247	0.99699	0.27605	0.46815	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	14.197	0.99350	0.27508	0.46651	-1.0000
-112	14.177	0.99210	0.27469	0.46585	-1.0000
-122	14.187	0.99280	0.27489	0.46618	-1.0000
-127	14.202	0.99384	0.27518	0.46667	-1.0000
-137	14.177	0.99210	0.27469	0.46585	-1.0000
-142	14.157	0.99070	0.27431	0.46519	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	14.197	0.99350	0.27508	0.46651	0.39800
112	14.177	0.99210	0.27469	0.46585	0.43100
122	14.187	0.99280	0.27489	0.46618	0.46900
127	14.202	0.99384	0.27518	0.46667	0.48600
137	14.177	0.99210	0.27469	0.46585	0.52200
142	14.157	0.99070	0.27431	0.46519	0.58800
-152	14.277	0.99909	0.27663	0.46913	-1.0000
-157	14.272	0.99874	0.27653	0.46897	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	14.277	0.99909	0.27663	0.46913	-1.0000
-157	14.272	0.99874	0.27653	0.46897	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
167	14.277	0.99909	0.27663	0.46913	0.79300
172	14.282	0.99944	0.27673	0.46930	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
182	13.309	0.93129	0.25786	0.43730	0.79300
187	13.253	0.92745	0.25679	0.43560	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 657.07   FIC 956.28   SIGMA IC 2.8837   FTAPF-0.047731   DSM 0.044320   CFM 0.0030097

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFII   REC 10/24/79 21:06:55.663   FAC RY6X1   PGM CO34   PDG 1423

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.459	1.0097	0.55975	0.94924	0.72200
37	14.629	1.0206	0.56632	0.96038	0.82000
47	14.676	1.0237	0.56806	0.96333	0.91900
52	14.684	1.0244	0.56845	0.96358	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.519	1.0129	0.56207	0.95317	0.42200
67	14.456	1.0084	0.55956	0.94891	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.548	0.87542	0.48576	0.82376	0.50800
82	15.956	1.1132	0.61771	1.0475	0.59300
92	14.285	0.99656	0.55299	0.93778	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.260	0.99482	0.55203	0.93614	-1.0000
-112	14.250	0.99413	0.55164	0.93548	-1.0000
-122	14.250	0.99413	0.55164	0.93548	-1.0000
-127	14.270	0.99552	0.55241	0.93679	-1.0000
-137	14.240	0.99363	0.55125	0.93483	-1.0000
-142	14.190	0.98995	0.54932	0.93155	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.260	0.99482	0.55203	0.93614	0.39800
112	14.250	0.99413	0.55164	0.93548	0.43100
122	14.250	0.99413	0.55164	0.93548	0.44900
127	14.270	0.99552	0.55241	0.93679	0.48600
137	14.240	0.99363	0.55125	0.93483	0.52200
142	14.190	0.98995	0.54932	0.93155	0.58800
-147	14.393	0.99761	0.55357	0.93876	-1.0000
-152	14.299	0.99726	0.55338	0.93863	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.393	0.99761	0.55357	0.93876	-1.0000
-157	14.295	0.99726	0.55338	0.93863	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.295	0.99726	0.55338	0.93863	0.79300
172	14.290	0.99691	0.55319	0.93810	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.606	0.94922	0.52672	0.89322	0.79300
187	13.497	0.94171	0.52228	0.88568	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
TF=21 280.67   FIC 279.35   SIGMA IF 3.8356   FTARF=2.67881   DSF 0.00056037   CFT 0.0266632

NASA-LEWIS   PRELIMINARY DATA   36/13/79   CORRELL   REC 10/24/79 21:10:48.122   FAC 8X6X1   PGM C034   PPG 1424

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.599	1.0198	0.56384	0.82405	0.72200
37	15.222	1.0633	0.58792	0.85926	0.82000
47	15.352	1.0724	0.59293	0.86659	0.91900
52	15.337	1.0713	0.59236	0.86574	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	15.048	1.0511	0.58115	0.84940	0.42200
67	14.758	1.0309	0.57000	0.83307	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.608	0.88062	0.48694	0.71167	0.50800
82	16.346	1.1208	0.61972	0.90573	0.56300
92	14.279	0.99745	0.55150	0.80602	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.254	0.99571	0.55054	0.80462	-1.0000
-112	14.254	0.99571	0.55054	0.80462	-1.0000
-122	14.254	0.99571	0.55054	0.80462	-1.0000
-127	14.264	0.99641	0.55092	0.80518	-1.0000
-137	14.244	0.99501	0.55015	0.80406	-1.0000
-142	14.209	0.99257	0.54880	0.80208	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.254	0.99571	0.55054	0.80462	0.39800
112	14.254	0.99571	0.55054	0.80462	0.43100
122	14.254	0.99571	0.55054	0.80462	0.44900
127	14.264	0.99641	0.55092	0.80518	0.48600
137	14.244	0.99501	0.55015	0.80406	0.52200
142	14.209	0.99257	0.54880	0.80208	0.58800
-152	14.299	0.99819	0.55189	0.80659	-1.0000
-157	14.299	0.99815	0.55189	0.80659	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.299	0.99815	0.55189	0.80659	-1.0000
-157	14.289	0.99815	0.55189	0.80659	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.294	0.99850	0.55208	0.80687	0.79300
172	14.289	0.99815	0.55189	0.80659	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.546	0.94622	0.52317	0.76462	0.79300
187	13.651	0.93950	0.51951	0.75927	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

IF-DJ 321.89   FLC 320.93   SIGMA IC 1.5924   FTAPF-0.079060   DSP 0.021968   CFM 0.0032097

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CANDELL   REC 10/26/79 21:12:31.873   FAC 8X6X1   PG9 C034   RDG 1425

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.310	0.99891	0.47287	0.67498	0.72200
37	15.900	1.1099	0.52543	0.75000	0.82000
47	16.254	1.1346	0.53712	0.76669	0.91900
52	16.254	1.1346	0.53712	0.76669	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	15.636	1.0994	0.51571	0.73612	0.42200
67	14.534	1.0146	0.48028	0.68556	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.395	0.86525	0.40960	0.58466	0.50800
82	16.693	1.1653	0.55162	0.78739	0.58300
92	14.275	0.99668	0.47172	0.67333	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.235	0.99369	0.47040	0.67145	-1.0000
-112	14.240	0.99404	0.47056	0.67169	-1.0000
-122	14.235	0.99369	0.47040	0.67145	-1.0000
-127	14.255	0.99508	0.47106	0.67239	-1.0000
-137	14.230	0.99334	0.47023	0.67122	-1.0000
-142	14.195	0.99091	0.46908	0.66957	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.235	0.99369	0.47040	0.67145	0.39800
112	14.240	0.99404	0.47056	0.67169	0.43100
122	14.235	0.99369	0.47040	0.67145	0.46900
127	14.255	0.99508	0.47106	0.67239	0.48600
137	14.230	0.99334	0.47023	0.67122	0.52200
142	14.195	0.99091	0.46908	0.66957	0.58800
147	14.285	0.99717	0.47205	0.67380	1.0000
157	14.290	0.99752	0.47221	0.67404	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.285	0.99717	0.47205	0.67380	-1.0000
-157	14.290	0.99752	0.47221	0.67404	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.290	0.99752	0.47221	0.67404	0.79300
172	14.290	0.99752	0.47221	0.67404	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.413	0.93626	0.44321	0.63265	0.79300
187	13.309	0.92895	0.43575	0.62771	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 458.13   FIC 457.44   SIGMA IC 1.5202   FTARE-0.31260   DSW 0.0965631   CFW 0.0935798

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CANDELL   REC 10/24/79 21:16:18.680   FOR 8V6X1   PGP C034   PAG 1426

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.249	0.92620	0.37089	0.53275	3.72200
37	15.373	1.1166	0.44713	0.64278	0.82000
47	17.359	1.2128	0.48567	0.69762	0.91900
52	17.459	1.2205	0.48874	0.70204	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	16.821	1.1759	0.47087	0.67637	0.42200
67	13.249	0.92620	0.37089	0.53275	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	8.0592	0.56338	0.22560	0.32406	0.50800
82	20.751	1.4506	0.58089	0.83441	0.58300
92	14.252	0.99630	0.39896	0.57307	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.197	0.99246	0.39742	0.57087	-1.0000
-112	14.177	0.99107	0.39686	0.57007	-1.0000
-122	14.192	0.99211	0.39728	0.57067	-1.0000
-127	14.217	0.99386	0.39798	0.57167	-1.0000
-137	14.202	0.99281	0.39756	0.57107	-1.0000
-142	14.192	0.99211	0.39728	0.57067	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.197	0.99246	0.39742	0.57087	0.39800
112	14.177	0.99107	0.39686	0.57007	0.43100
122	14.192	0.99211	0.39728	0.57067	0.44900
127	14.217	0.99386	0.39798	0.57167	0.48600
137	14.202	0.99281	0.39756	0.57107	0.52200
142	14.192	0.99211	0.39728	0.57067	0.58800
-152	14.277	0.99804	0.39969	0.57408	-1.0000
-157	14.272	0.99769	0.39951	0.57388	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.277	0.99804	0.39969	0.57408	-1.0000
-157	14.272	0.99769	0.39951	0.57388	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.267	0.99734	0.39937	0.57368	0.79300
172	14.277	0.99804	0.39965	0.57408	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.299	0.92969	0.37228	0.53476	0.79300
187	13.279	0.92829	0.37172	0.53396	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 596.11   FIC 595.95   SIGMA IC 2.6688   FTAPF 0.028381   DSM 0.032830   CFM 0.0030969

NASA-LEWIS   PRELIMINARY DATA   26/13/79   CADDELL   REC 10/24/79 21:19:56.097   F9C 9X9X1   PG9 C034   RDG 1427

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
22	13.765	0.96234	0.34073	0.50080	0.72200
37	16.697	1.1673	0.42301	0.61718	0.82000
47	18.333	1.2817	0.46444	0.67763	0.91900
52	19.417	1.2876	0.46659	0.68077	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	18.348	1.2827	0.46482	0.67819	0.42200
67	14.438	1.0073	0.36503	0.53258	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	9.0961	0.63522	0.23019	0.33585	0.50800
82	19.033	1.3305	0.48213	0.70343	0.58300
92	14.249	0.99615	0.36098	0.52665	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTO SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.199	0.99267	0.35972	0.52484	-1.0000
-112	14.194	0.99162	0.35924	0.52429	-1.0000
-122	14.194	0.99232	0.35959	0.52466	-1.0000
-127	14.234	0.99511	0.36060	0.52613	-1.0000
-137	14.239	0.99546	0.36073	0.52631	-1.0000
-142	14.224	0.99441	0.36035	0.52576	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.199	0.99267	0.35972	0.52484	0.39800
112	14.194	0.99162	0.35934	0.52429	0.43100
122	14.194	0.99232	0.35959	0.52466	0.44900
127	14.234	0.99511	0.36060	0.52613	0.48600
137	14.239	0.99546	0.36073	0.52631	0.52200
142	14.224	0.99441	0.36035	0.52576	0.58800
-152	14.269	0.99755	0.36149	0.52742	-1.0000
-157	14.269	0.99755	0.36149	0.52742	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.269	0.99755	0.36149	0.52742	-1.0000
-157	14.269	0.99755	0.36149	0.52742	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.274	0.99790	0.36161	0.52760	0.79300
172	14.269	0.99755	0.36149	0.52742	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.316	0.93096	0.33736	0.49221	0.79300
187	13.304	0.93026	0.33710	0.49184	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS
IF-01 684.30   FEC 682.59   SIGMA IF 2.0337   FTARE 0.66986   DSP 0.363608   FFW 0.0029120

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   PFD 10/24/79 21:20:23.837   FAC 9X4X1   PGM C034   RDG 1428

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.796	1.0341	0.33266	0.48805	0.72200
37	18.717	1.3090	0.42108	0.61778	0.82009
47	20.204	1.4133	0.45463	0.66703	0.91900
52	19.990	1.3976	0.44958	0.65959	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	20.563	1.4384	0.46271	0.67885	0.42200
67	16.614	1.1621	0.37384	0.54847	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	10.414	0.72846	0.23433	0.34380	0.50800
82	14.853	1.0390	0.33423	0.49036	0.58300
92	14.240	0.99610	0.32062	0.47010	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.170	0.99121	0.31885	0.46780	-1.0000
-112	14.145	0.98947	0.31829	0.46698	-1.0000
-122	14.160	0.99051	0.31863	0.46747	-1.0000
-127	14.225	0.99505	0.32009	0.46961	-1.0000
-137	14.250	0.99679	0.32065	0.47043	-1.0000
-142	14.225	0.99505	0.32009	0.46961	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.170	0.99121	0.31885	0.46780	0.39800
112	14.145	0.98947	0.31829	0.46698	0.43100
122	14.160	0.99051	0.31863	0.46747	0.44900
127	14.225	0.99505	0.32009	0.46961	0.48600
137	14.250	0.99679	0.32065	0.47043	0.52200
142	14.225	0.99505	0.32009	0.46961	0.58800
147	14.265	0.99784	0.32099	0.47093	-1.0000
152	14.270	0.99819	0.32110	0.47109	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.265	0.99784	0.32099	0.47093	-1.0000
-152	14.270	0.99819	0.32110	0.47109	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.270	0.99819	0.32110	0.47109	0.79300
172	14.265	0.99784	0.32099	0.47093	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.372	0.93539	0.30090	0.44145	0.79300
192	13.347	0.93364	0.30034	0.44063	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

[F-D] 804.00   FLC 803.26   SIGM LC 2.8004   STAPE 0.47382   DCM 0.262668   CFM 3.3320374

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFII   REC 10/24/79 21:22:39.720   FAC RY6X1   PGM C034   RDG 2429

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.413	0.79881	0.22138	0.31970	0.72200
37	20.200	1.4138	0.39184	0.56585	0.82000
47	22.987	1.6089	0.44551	0.64393	0.91900
52	22.798	1.5957	0.44223	0.63862	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	24.837	1.7384	0.48180	0.69576	0.42200
67	21.541	1.5077	0.41786	0.60342	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.126	0.84873	0.23522	0.33968	0.50000
82	17.263	1.2083	0.33486	0.48357	0.58300
92	14.231	0.99606	0.27605	0.39864	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.141	0.98978	0.27431	0.39613	-1.0000
-112	14.126	0.98873	0.27402	0.39571	-1.0000
-122	14.136	0.98943	0.27421	0.39599	-1.0000
-127	14.196	0.99292	0.27518	0.39738	-1.0000
-137	14.166	0.99152	0.27479	0.39682	-1.0000
-142	14.176	0.99222	0.27499	0.39710	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.141	0.98978	0.27431	0.39613	0.39200
112	14.126	0.98873	0.27402	0.39571	0.43160
122	14.136	0.98943	0.27421	0.39599	0.44900
127	14.196	0.99292	0.27518	0.39738	0.48600
137	14.166	0.99152	0.27479	0.39682	0.52200
142	14.176	0.99222	0.27499	0.39710	0.58800
147	14.296	0.99890	0.27673	0.39982	-1.0000
157	14.261	0.99817	0.27663	0.39940	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.266	0.99840	0.27673	0.39962	-1.0000
-157	14.261	0.99815	0.27663	0.39948	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.261	0.99915	0.27663	0.39948	0.79300
172	14.261	0.99815	0.27663	0.39948	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.519	0.94614	0.26221	0.37866	0.79300
187	13.488	0.94404	0.26163	0.37782	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

TF-DI 1924.7   FIC 1323.3   SIGMA IC 2.6737   FTAPE 0.31211   DSM 0.075219   CFM 0.0079684

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CARDETT   REC 10/24/79 21:24:41.642   FAC 9X6X1   PGM C034   RDG 1430

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.299	0.78351	0.18962	0.27497	0.72200
37	23.443	1.6416	0.39730	0.57612	0.82000
47	26.126	1.8295	0.44277	0.64206	0.91900
52	25.937	1.8162	0.43905	0.63667	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	27.568	1.9305	0.46720	0.67749	0.42200
67	21.489	1.5047	0.36417	0.52808	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.888	0.97250	0.23536	0.34130	0.50000
82	19.842	1.3895	0.33628	0.48763	0.58300
92	14.227	0.99625	0.24111	0.34963	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.112	0.98822	0.23916	0.34681	-1.0000
-112	14.077	0.98577	0.23857	0.34595	-1.0000
-122	14.107	0.98787	0.23908	0.34669	-1.0000
-127	14.202	0.99450	0.24069	0.34902	-1.0000
-137	14.227	0.99625	0.24111	0.34963	-1.0000
-142	14.277	0.99974	0.24195	0.35086	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.112	0.98822	0.23916	0.34681	0.39800
112	14.077	0.98577	0.23857	0.34595	0.43100
122	14.107	0.98787	0.23908	0.34669	0.44900
127	14.202	0.99650	0.24069	0.34902	0.48800
137	14.227	0.99625	0.24111	0.34963	0.52200
142	14.277	0.99974	0.24195	0.35086	0.58000
-152	14.262	0.99870	0.24170	0.35049	-1.0000
-157	14.257	0.99835	0.24162	0.35037	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.262	0.99870	0.24170	0.35049	-1.0000
-157	14.257	0.99835	0.24162	0.35037	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.257	0.99835	0.24162	0.35037	0.79300
172	14.262	0.99870	0.24170	0.35049	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
192	13.903	0.97285	0.23544	0.34142	0.79300
197	13.919	0.96765	0.23418	0.33958	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

IF-D) 1229.7   FLC 1227.0   SIGMA IC 3.0014   FTAPF 0.67523   DSM 0.300353   CFM 0.9328232

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFII   REC 10/24/79 21:25:20.345   FAC R46X1   PCM C034   PRG 1431

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.224	0.78551	0.18987	0.27601	0.72200
37	23.583	1.6504	0.39893	0.57992	0.82000
47	26.172	1.8316	0.44272	0.64358	0.91900
52	25.947	1.8159	0.43892	0.63806	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
52	27.558	1.9286	0.46618	0.67769	0.42200
67	21.488	1.5038	0.36350	0.52842	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.903	0.97298	0.23519	0.34189	0.50800
82	19.878	1.3911	0.33625	0.48881	0.58300
92	14.227	0.99567	0.24067	0.34986	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.133	0.98904	0.23907	0.34753	-1.0000
-112	14.088	0.98590	0.23831	0.34643	-1.0000
-122	14.109	0.98729	0.23865	0.34692	-1.0000
-127	14.202	0.99392	0.24025	0.34925	-1.0000
-137	14.242	0.99672	0.24092	0.35023	-1.0000
-142	14.287	0.99986	0.24168	0.35133	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.133	0.98904	0.23907	0.34753	0.39000
112	14.088	0.98590	0.23831	0.34643	0.43100
122	14.109	0.98729	0.23865	0.34692	0.44900
127	14.202	0.99392	0.24025	0.34925	0.48600
137	14.242	0.99672	0.24092	0.35023	0.52200
142	14.287	0.99986	0.24168	0.35133	0.58000
147	14.262	0.99811	0.24126	0.35072	1.0000
152	14.267	0.99846	0.24135	0.35084	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.262	0.99811	0.24126	0.35072	-1.0000
-157	14.267	0.99846	0.24135	0.35084	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.262	0.99811	0.24126	0.35072	0.79300
172	14.262	0.99811	0.24126	0.35072	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.898	0.97263	0.23519	0.34177	0.79300
187	13.828	0.96775	0.23392	0.34005	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
IF-01 1228.2   FIC 1226.5   SIGMA IC 3.2996   FTAPF 0.65532   DSM 0.962582   CFM 0.9929121

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFII   REC 10/24/79 21:27:17.913   FAC RX6X1   PGM C034   RDG 1492

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	11.298	3.79075	0.21948	0.31775	0.72200
37	20.330	1.4235	0.30512	0.57203	0.82000
47	22.952	1.6066	0.44588	0.64551	0.91900
52	22.768	1.5935	0.44230	0.64033	..0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	24.728	1.7307	0.48037	0.69544	0.42200
67	21.332	1.4930	0.41460	0.59994	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	12.191	0.85324	0.23683	0.34286	0.50000
82	17.313	1.2117	0.33633	0.48691	0.58300
92	14.236	0.99636	0.27655	0.40037	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	14.136	0.99938	0.27462	0.39757	-1.0000
-112	14.126	0.98868	0.27442	0.39729	-1.0000
-122	14.131	0.98903	0.27452	0.39743	-1.0000
-127	14.181	0.99252	0.27549	0.39883	-1.0000
-137	14.146	0.99148	0.27520	0.39841	-1.0000
-142	14.181	0.99252	0.27549	0.39883	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	14.136	0.98938	0.27462	0.39757	0.39400
112	14.126	0.98869	0.27442	0.39729	0.43100
122	14.131	0.98903	0.27452	0.39743	0.44900
127	14.181	0.99252	0.27549	0.39883	0.68600
137	14.146	0.99148	0.27520	0.39841	0.52200
142	14.181	0.99252	0.27549	0.39883	0.58000
147	14.261	0.99811	0.27704	0.40109	1.0000
157	14.261	0.99811	0.27704	0.40109	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	14.261	0.99811	0.27704	0.40108	-1.0000
-157	14.261	0.99811	0.27704	0.40108	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
167	14.266	0.99846	0.27714	0.40122	0.74300
172	14.261	0.99811	0.27704	0.40108	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
182	13.523	0.94665	0.26270	0.38032	0.74300
187	13.493	0.94435	0.26212	0.37947	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

IF-D1 1021.9   FIS 1020.3   SIGMA IC 3.7315   FTAPF 0.53354   DSM 0.069253   CFM 0.9928997

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CANOEII   REC 10/24/79 21:28:38.066   FAC RX6X1   PGM C034   RDG 1433

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.731	1.0302	0.33247	0.48959	0.72200
37	14.721	1.3092	0.42251	0.62219	0.82000
47	20.152	1.4093	0.45491	0.66975	0.91900
52	19.923	1.3932	0.44963	0.66213	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	20.456	1.4305	0.46167	0.67986	0.42200
67	16.602	1.1610	0.37468	0.55175	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	10.541	0.73715	0.23790	0.35033	0.50800
82	14.861	1.0392	0.33539	0.49390	0.58300
92	14.243	0.99600	0.32144	0.47335	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.173	0.99112	0.31986	0.47103	-1.0000
-112	14.148	0.98937	0.31930	0.47020	-1.0000
-122	14.173	0.99112	0.31986	0.47103	-1.0000
-127	14.228	0.99495	0.32110	0.47285	-1.0000
-137	14.243	0.99600	0.32144	0.47335	-1.0000
-142	14.223	0.99460	0.32099	0.47269	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.173	0.99112	0.31986	0.47103	0.39800
112	14.148	0.98937	0.31930	0.47020	0.43100
122	14.173	0.99112	0.31986	0.47103	0.44900
127	14.228	0.99495	0.32110	0.47285	0.48600
137	14.243	0.99600	0.32144	0.47335	0.52200
142	14.223	0.99460	0.32099	0.47269	0.58000
-152	14.273	0.99804	0.32211	0.47434	-1.0000
-157	14.268	0.99774	0.32200	0.47418	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.273	0.99804	0.32211	0.47434	-1.0000
-157	14.268	0.99774	0.32200	0.47418	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.268	0.99774	0.32200	0.47418	0.79300
172	14.268	0.99774	0.32200	0.47418	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
192	13.370	0.93496	0.39174	0.44434	0.79300
197	13.335	0.93252	0.30095	0.44318	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

SF-D) 820.30   FIC 795.38   SIGMA IC 3.2612   FTAPF 0.17425   DSW 0.044205   CFW 0.0038304

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDEII   REC 10/24/79 21:30:49.433   FAC 3X6X1   PGM C036   PDG 1434

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.714	0.95967	0.34886	0.50816	0.72200
37	16.571	1.1593	0.42153	0.61401	0.82000
47	18.241	1.2762	0.46401	0.67589	0.91900
52	18.350	1.2838	0.46680	0.67995	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	18.275	1.2786	0.46490	0.67718	0.42200
67	14.347	1.0038	0.36497	0.53163	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	9.1958	0.66337	0.23393	0.34074	0.50800
82	19.218	1.3445	0.48886	0.71209	0.58300
92	14.243	0.99665	0.36231	0.52775	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.183	0.99226	0.36079	0.52553	-1.0000
-112	14.178	0.99191	0.36066	0.52534	-1.0000
-122	14.183	0.99226	0.36079	0.52553	-1.0000
-127	14.223	0.99505	0.36180	0.52701	-1.0000
-137	14.223	0.99505	0.36180	0.52701	-1.0000
-142	14.203	0.99366	0.36129	0.52627	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.183	0.99226	0.36079	0.52553	0.39800
112	14.178	0.99191	0.36066	0.52534	0.43100
122	14.183	0.99226	0.36079	0.52553	0.44900
127	14.223	0.99505	0.36180	0.52701	0.48600
137	14.223	0.99505	0.36180	0.52701	0.52200
142	14.203	0.99366	0.36129	0.52627	0.58800
-152	14.262	0.99784	0.36281	0.52848	-1.0000
-157	14.267	0.99819	0.36294	0.52867	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.262	0.99784	0.36281	0.52848	-1.0000
-157	14.267	0.99819	0.36294	0.52867	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.262	0.99784	0.36281	0.52848	0.79300
172	14.267	0.99819	0.36294	0.52867	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.305	0.93087	0.33846	0.49301	0.79300
187	13.290	0.92982	0.33808	0.49246	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

IF-01 679.68   FIC 677.95   SIGMA IC 2.9664   FTAPE 0.76546   DSM 0.966667   CFM 0.3329976

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDETT   REC 10/24/79 21:31:31.026   FAC RX6E1   PGM C034   PPG 1435

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.255	0.92699	0.36992	0.53367	0.72200
37	15.944	1.1150	0.44454	0.64190	0.82000
47	17.333	1.2119	0.48363	0.69772	0.91900
52	17.455	1.2207	0.48711	0.70274	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	16.811	1.1757	0.46916	0.67684	0.42200
67	13.260	0.92734	0.37006	0.53387	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	8.1362	0.56900	0.22706	0.32757	0.50800
82	20.581	1.4393	0.57437	0.82862	0.58300
92	14.258	0.99711	0.39790	0.57403	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.198	0.99292	0.39623	0.57162	-1.0000
-112	14.183	0.99187	0.39581	0.57102	-1.0000
-122	14.183	0.99187	0.39581	0.57102	-1.0000
-127	14.219	0.99432	0.39679	0.57243	-1.0000
-137	15.198	0.99292	0.39623	0.57162	-1.0000
-162	14.199	0.99292	0.39623	0.57162	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.198	0.99292	0.39623	0.57162	0.39800
112	14.183	0.99187	0.39581	0.57102	0.43100
122	14.183	0.99187	0.39581	0.57102	0.44900
127	14.219	0.99432	0.39679	0.57243	0.48600
137	14.199	0.99292	0.39623	0.57162	0.52200
142	14.199	0.99292	0.39623	0.57162	0.58800
152	14.209	0.99300	0.39619	0.57149	-1.0000
157	14.273	0.99815	0.39832	0.5746	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.268	0.99780	0.39818	0.57444	-1.0000
-157	14.273	0.99815	0.39832	0.57464	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.273	0.99815	0.39832	0.57464	0.79300
172	14.273	0.99815	0.39832	0.57464	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.300	0.93013	0.37117	0.53548	0.79300
187	13.260	0.92734	0.37006	0.53387	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

TF-DI 568.45   FIC 597.18   SIGMA IC 1.8206   FTAPE 0.23769   CSP 0.030605   CF9 0.0031111

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDEIT   REC 10/24/79 21:33:06.577   FAC RXEX1   PGM F034   RDG 1436

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.276	0.99757	0.47156	0.67444	0.72200
37	15.876	1.1094	0.52440	0.75004	0.82000
47	16.275	1.1338	0.53592	0.76652	0.91900
52	16.239	1.1341	0.53608	0.76675	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	15.557	1.0871	0.51386	0.73496	0.42200
67	16.486	1.0122	0.47846	0.68433	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.407	0.86693	0.40979	0.58612	0.50800
82	16.799	1.1738	0.55485	0.79360	0.58300
92	16.271	0.99722	0.47138	0.67421	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.236	0.99478	0.47023	0.67256	-1.0000
-112	14.236	0.99478	0.47023	0.67256	-1.0000
-122	14.236	0.99478	0.47023	0.67256	-1.0000
-127	14.256	0.99617	0.47089	0.67350	-1.0000
-137	14.231	0.99443	0.47006	0.67232	-1.0000
-142	14.197	0.99199	0.46891	0.67068	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.236	0.99478	0.47023	0.67256	0.39800
112	14.236	0.99478	0.47023	0.67256	0.43100
122	14.236	0.99478	0.47023	0.67256	0.44900
127	14.256	0.99617	0.47089	0.67350	0.48600
137	14.231	0.99443	0.47006	0.67232	0.52200
142	14.197	0.99199	0.46891	0.67068	0.58800
-152	14.284	0.99824	0.47187	0.67491	-1.0000
-157	14.299	0.99820	0.47187	0.67491	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.296	0.99826	0.47187	0.67491	-1.0000
-157	14.296	0.99826	0.47187	0.67491	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.296	0.99826	0.47187	0.67491	0.79300
172	14.296	0.99826	0.47187	0.67491	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.404	0.93661	0.44273	0.63323	0.79300
187	13.300	0.92929	0.43927	0.62828	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
(F-DI 450.27   FIC 459.01   SIGMA IC 2.0139   FTARF 0.23970   DSM 0.024687   CFM 0.0031732

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CAOOFII   RFC 10/24/79 21:34:24.499   FAC RX6X1   PGM CO34   PRG 1497

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
22	14.557	1.0160	0.56023	0.81152	0.72200
37	15.225	1.0626	0.58594	0.84876	0.82000
47	15.365	1.0723	0.59131	0.85654	0.91900
52	15.360	1.0729	0.59112	0.85626	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	15.036	1.0494	0.57865	0.83820	0.42200
67	14.717	1.0271	0.56637	0.82041	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	12.613	0.88026	0.49540	0.70312	0.50800
82	16.083	1.1224	0.61894	0.89656	0.50300
92	14.273	0.99614	0.56930	0.79568	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	14.243	0.99405	0.56814	0.79401	-1.0000
-112	14.243	0.99405	0.56814	0.79401	-1.0000
-122	14.238	0.99370	0.56795	0.79373	-1.0000
-127	14.253	0.99474	0.56853	0.79457	-1.0000
-137	14.233	0.99335	0.56776	0.79346	-1.0000
-142	14.203	0.99127	0.56661	0.79179	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	14.243	0.99405	0.56814	0.79401	0.39800
112	14.243	0.99405	0.56814	0.79401	0.43100
122	14.238	0.99370	0.56795	0.79373	0.44900
127	14.253	0.99474	0.56853	0.79457	0.48600
137	14.233	0.99335	0.56776	0.79346	0.52200
142	14.203	0.99127	0.56661	0.79179	0.58800
152	14.288	0.99718	0.56987	0.79651	-1.0000
157	14.288	0.99718	0.56987	0.79651	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	14.288	0.99718	0.54987	0.79651	-1.0000
-157	14.288	0.99718	0.54987	0.79651	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
167	14.283	0.99683	0.54968	0.79623	0.79300
172	14.283	0.99683	0.54969	0.79623	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
182	13.520	0.94360	0.52032	0.75371	0.79300
187	13.416	0.93629	0.51629	0.74787	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 227.67   FLC 326.36   SIGMA LC 1.4373   FTAPE-0.30418   OSM 0.010462   CFM 0.0034696

297

NASA-LEWIS PRELIMINARY DATA CANOE-II FACILITY   9X6X1   PROGRAM C034 PDGS   1438 TO 1498
TIME AND DATE PROCESSED 05:27:48 JUN 13 1979

NOZZLE TYPE	P+W BASE EJECTOR NOZZLE (MODEL C)
FLIGHT CONDITIONS	TAKEOFF
NOZZLE CONFIGURATION	C3
PRIMARY-NOZZLE PLUG	SPLIT PLUG (EXTENDED)
FLOW SPLITTER	ISENTROPIC SPLITTER
FAN NOZZLE	SHORT FLAP
CLAMSHELL POSITION	12 DEG
EJECTOR INLET OPENING	MIDWAY

PDG	MD	PTF/PTP	PTF/PO	PTP/PO	OMEGA	PTS/PTF	CDF	CDP	CF1	ETA1	ETA1,INT	CFP1	CFP2	F9
1438	0.037	1.45	1.81	1.25	0.000	0.568	0.965	1.049	0.9630	0.9630	0.9631	0.9631	0.9665	######
1439	0.008	1.69	1.81	1.07	0.000	0.569	0.966	1.224	0.9622	0.9622	0.9622	0.9622	0.9636	######
1440	0.021	1.69	2.11	1.25	0.000	0.471	0.968	1.091	0.9556	0.9556	0.9556	0.9556	0.9594	######
1441	0.027	1.69	2.50	1.48	0.000	0.397	0.970	1.028	0.9321	0.9321	0.9322	0.9322	0.9354	######
1442	0.043	1.70	3.11	1.83	0.000	0.317	0.967	0.970	0.9332	0.9332	0.9332	0.9332	0.9390	######
1443	0.053	1.70	3.60	2.12	0.000	0.277	0.968	0.973	0.9435	0.9435	0.9436	0.9436	0.9458	######
1444	0.060	1.70	4.20	2.47	0.000	0.241	0.969	0.982	0.9452	0.9452	0.9452	0.9452	0.9471	######
1445	0.057	1.70	4.19	2.47	0.000	0.241	0.969	0.981	0.9456	0.9456	0.9456	0.9456	0.9475	######
1446	0.054	1.70	3.61	2.12	0.000	0.277	0.969	0.973	0.9431	0.9431	0.9431	0.9431	0.9453	######
1447	0.054	1.70	3.10	1.82	0.000	0.318	0.968	0.972	0.9290	0.9290	0.9291	0.9291	0.9318	######
1448	0.052	1.70	2.76	1.63	0.000	0.356	0.968	0.989	0.9287	0.9287	0.9288	0.9288	0.9318	######
1449	0.052	1.69	2.76	1.63	0.000	0.357	0.968	0.989	0.9290	0.9290	0.9291	0.9291	0.9321	######
1450	0.027	1.69	2.49	1.48	0.000	0.397	0.967	1.026	0.9327	0.9327	0.9327	0.9327	0.9360	######
1451	0.052	1.69	2.12	1.26	0.000	0.470	0.966	1.084	0.9558	0.9558	0.9558	0.9558	0.9587	######
1452	0.035	1.68	1.79	1.07	0.000	0.556	0.969	1.216	0.9582	0.9582	0.9582	0.9582	0.9595	######
1453	0.055	1.69	2.77	1.63	0.000	0.355	0.967	0.988	0.9301	0.9301	0.9301	0.9301	0.9332	######
1454	0.051	1.70	3.59	2.11	0.000	0.277	0.970	0.973	0.9435	0.9435	0.9435	0.9435	0.9458	######
1455	0.023	1.45	1.81	1.25	0.000	0.551	0.966	1.063	0.9557	0.9557	0.9557	0.9557	0.9592	######
1456	0.031	1.43	2.12	1.48	0.000	0.469	0.964	1.022	0.9536	0.9536	0.9536	0.9536	0.9575	######
1457	0.065	1.44	2.51	1.74	0.000	0.394	0.969	0.983	0.9358	0.9358	0.9358	0.9358	0.9393	######
1458	0.047	1.45	2.76	1.90	0.000	0.356	0.970	0.976	0.9323	0.9323	0.9323	0.9323	0.9353	######
1459	0.051	1.47	3.11	2.12	0.000	0.318	0.966	0.970	0.9360	0.9360	0.9361	0.9361	0.9386	######
1460	0.054	1.44	3.60	2.50	0.000	0.278	0.969	0.977	0.9439	0.9439	0.9439	0.9439	0.9461	######
1461	0.062	1.45	4.18	2.87	0.000	0.243	0.969	0.983	0.9459	0.9459	0.9459	0.9459	0.9477	######
1462	0.055	1.45	4.18	2.87	0.000	0.243	0.969	0.983	0.9457	0.9457	0.9458	0.9458	0.9476	######
1463	0.050	1.44	3.60	2.49	0.000	0.278	0.969	0.978	0.9435	0.9435	0.9435	0.9435	0.9457	######
1464	0.041	1.46	3.11	2.12	0.000	0.318	0.969	0.979	0.9328	0.9328	0.9328	0.9328	0.9354	######
1465	0.065	1.45	2.76	1.90	0.000	0.356	0.968	0.979	0.9327	0.9327	0.9328	0.9328	0.9358	######
1466	0.069	1.44	2.51	1.74	0.000	0.394	0.968	0.983	0.9378	0.9378	0.9378	0.9378	0.9413	######
1467	0.006	1.43	2.11	1.47	0.000	0.470	0.966	1.023	0.9571	0.9571	0.9571	0.9571	0.9610	######
1468	0.010	1.45	1.81	1.25	0.000	0.550	0.966	1.063	0.9573	0.9573	0.9573	0.9573	0.9607	######
1469	0.359	1.67	1.81	1.08	0.000	0.555	0.965	1.017	0.9097	0.9097	0.9120	0.9120	0.9133	######
1470	0.364	1.66	2.10	1.27	0.000	0.478	0.971	1.025	0.9249	0.9249	0.9265	0.9265	0.9293	######
1471	0.366	1.68	2.50	1.49	0.000	0.402	0.967	1.017	0.9146	0.9146	0.9158	0.9158	0.9190	######
1472	0.371	1.70	2.76	1.62	0.000	0.362	0.968	0.990	0.9106	0.9106	0.9117	0.9117	0.9147	######
1473	0.372	1.71	3.11	1.82	0.000	0.320	0.969	0.973	0.9113	0.9113	0.9122	0.9122	0.9150	######
1474	0.369	1.71	3.61	2.11	0.000	0.278	0.972	0.969	0.9313	0.9313	0.9320	0.9320	0.9342	######
1475	0.359	1.70	3.97	2.33	0.000	0.256	0.971	0.979	0.9342	0.9342	0.9348	0.9348	0.9368	######

NOZZLE TYPE   POW BASE EJECTOR NOZZLE (MODEL C)
FLIGHT CONDITIONS   TAKEOFF
NOZZLE CONFIGURATION   C3
PRIMARY-NOZZLE PLUG   SPLIT PLUG (EXTENDED)
FLOW SPLITTER   ISENTROPIC SPLITTER
FAN NOZZLE   SHORT FLAP
CLAMSHELL POSITION   13 DEG
EJECTOR INLET OPENING   MIDWAY

RDG	MD	PTF/PTP	PTF/PD	PTP/PD	OMEGA	PTS/PTF	CDF	CDP	CF1	ETA1	ETA1,INT	CFP1	CFP2	F9
1476	0.358	1.71	3.07	2.32	0.000	0.256	0.970	0.990	0.9350	0.9350	0.9356	0.9356	0.9375	000000
1477	0.365	1.71	3.61	2.11	0.000	0.278	0.963	0.966	0.9360	0.9360	0.9367	0.9367	0.9389	000000
1478	0.359	1.71	3.13	1.83	0.000	0.318	0.968	0.974	0.9133	0.9133	0.9142	0.9142	0.9169	000000
1479	0.357	1.70	2.76	1.62	0.000	0.361	0.968	0.990	0.9118	0.9118	0.9128	0.9128	0.9199	000000
1480	0.362	1.70	2.51	1.48	0.000	0.430	0.967	1.025	0.9139	0.9139	0.9151	0.9151	0.9183	000000
1481	0.363	1.69	2.11	1.25	0.000	0.476	0.966	1.029	0.9221	0.9221	0.9237	0.9237	0.9264	000000
1482	0.361	1.70	1.82	1.07	0.000	0.552	0.964	1.039	0.9080	0.9080	0.9103	0.9103	0.9115	000000
1483	0.358	1.44	1.81	1.26	0.000	0.555	0.964	1.011	0.9192	0.9192	0.9212	0.9212	0.9246	000000
1484	0.360	1.43	2.11	1.48	0.000	0.477	0.966	1.012	0.9268	0.9268	0.9283	0.9293	0.9321	000000
1485	0.365	1.47	2.52	1.72	0.000	0.397	0.966	0.986	0.9194	0.9194	0.9205	0.9205	0.9239	000000
1486	0.366	1.48	2.76	1.86	0.000	0.360	0.968	0.980	0.9196	0.9196	0.9206	0.9205	0.9237	000000
1487	0.360	1.48	3.12	2.11	0.000	0.310	0.968	0.979	0.9179	0.9179	0.9187	0.9187	0.9213	000000
1488	0.364	1.65	3.62	2.49	0.000	0.278	0.971	0.976	0.9359	0.9359	0.9366	0.9366	0.9387	000000
1489	0.366	1.46	3.92	2.67	0.000	0.259	0.970	0.981	0.9370	0.9370	0.9376	0.9376	0.9395	000000
1490	0.364	1.46	3.92	2.68	0.000	0.259	0.971	0.978	0.9406	0.9406	0.9412	0.9412	0.9432	000000
1491	0.363	1.45	3.62	2.49	0.000	0.277	0.967	0.971	0.9419	0.9419	0.9425	0.9425	0.9446	000000
1492	0.362	1.46	3.12	2.13	0.000	0.319	0.968	0.979	0.9196	0.9196	0.9204	0.9204	0.9229	000000
1493	0.357	1.48	2.76	1.87	0.000	0.360	0.968	0.980	0.9215	0.9215	0.9224	0.9224	0.9255	000000
1494	0.356	1.46	2.51	1.72	0.000	0.397	0.968	0.984	0.9182	0.9182	0.9193	0.9193	0.9227	000000
1495	0.358	1.43	2.10	1.46	0.000	0.478	0.966	1.014	0.9303	0.9303	0.9319	0.9319	0.9356	000000
1496	0.362	1.45	1.81	1.25	0.000	0.556	0.965	1.006	0.9295	0.9295	0.9315	0.9315	0.9348	000000
1497	0.359	1.45	1.81	1.25	0.000	0.555	0.964	1.004	0.9225	0.9225	0.9245	0.9245	0.9278	000000
1498	0.354	1.70	1.92	1.07	0.000	0.553	0.965	1.037	0.9115	0.9115	0.9138	0.9138	0.9150	000000

299

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.868	0.90008	0.49673	0.72254	0.72200
37	13.917	0.97345	0.53721	0.78144	0.82000
47	14.277	0.99860	0.55109	0.80163	0.91900
52	14.491	1.0136	0.55938	0.81369	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER T.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
52	13.687	0.95738	0.52834	0.76854	0.42200
67	13.093	0.91590	0.50540	0.73516	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.064	0.84383	0.46569	0.67739	0.50800
82	15.570	1.0891	0.60102	0.87425	0.58300
92	14.277	0.99860	0.55109	0.80163	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.232	0.99546	0.54936	0.79910	-1.0000
-112	14.222	0.99476	0.54897	0.79854	-1.0000
-122	14.222	0.99476	0.54897	0.79854	-1.0000
-127	14.227	0.99511	0.54917	0.79882	-1.0000
-137	14.182	0.99196	0.54743	0.79630	-1.0000
-142	14.057	0.98323	0.54261	0.78929	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.232	0.99546	0.54936	0.79910	0.39800
112	14.222	0.99476	0.54897	0.79854	0.43100
122	14.222	0.99476	0.54897	0.79854	0.44900
127	14.227	0.99511	0.54917	0.79882	0.48600
137	14.182	0.99196	0.54743	0.79630	0.52200
142	14.057	0.98323	0.54261	0.78929	0.58800
152	14.282	0.99895	0.55129	0.80191	-1.0000
157	14.282	0.99895	0.55129	0.80191	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.282	0.99895	0.55129	0.80191	-1.0000
-157	14.282	0.99895	0.55129	0.80191	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.282	0.99895	0.55129	0.80191	0.79300
172	14.282	0.99895	0.55129	0.80191	0.84600

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.697	0.95808	0.52873	0.76910	0.79300
187	13.612	0.95214	0.52545	0.76433	0.84600

>OPTION 5 , MEASURED THRUST PARAMETERS

IF-D) 340.62   FIC 340.17   SIGMA IC 1.3582   FTAFF 0.41639   DCM 0.033969   CFM 0.0038833

NASA-LEWIS PRELIMINARY DATA   06/13/79   CADDELL   REC 10/24/79 22:30:59.912   FAC RX6X1   PGM F034   DRG 1439

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.533	0.94588	0.52309	0.88505	0.72200
37	13.933	0.97392	0.53954	0.91119	0.82000
47	14.102	0.98569	0.54511	0.92230	0.91900
52	14.197	0.99232	0.54878	0.92851	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.718	0.95880	0.53024	0.89714	0.42200
67	13.578	0.94902	0.52482	0.88799	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.119	0.84704	0.46843	0.79257	0.50800
82	15.601	1.0904	0.60304	1.0203	0.58300
92	14.277	0.99791	0.55187	0.93374	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.252	0.99617	0.55090	0.93211	-1.0000
-112	14.237	0.99512	0.55032	0.93112	-1.0000
-122	14.232	0.99477	0.55013	0.93080	-1.0000
-127	14.242	0.99547	0.55051	0.93145	-1.0000
-137	14.197	0.99232	0.54878	0.92851	-1.0000
-142	14.062	0.98290	0.54356	0.91969	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.252	0.99617	0.55090	0.93211	0.39800
112	14.237	0.99512	0.55032	0.93112	0.43100
122	14.232	0.99477	0.55013	0.93080	0.44900
127	14.242	0.99547	0.55051	0.93145	0.48600
137	14.197	0.99232	0.54878	0.92851	0.52200
142	14.062	0.98290	0.54356	0.91969	0.58800
152	14.292	0.99896	0.55244	0.93472	-1.0000
157	14.287	0.99861	0.55225	0.93439	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.292	0.99896	0.55244	0.93472	-1.0000
-157	14.287	0.99861	0.55225	0.93439	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.292	0.99896	0.55244	0.93472	0.79300
172	14.292	0.99896	0.55244	0.93472	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.683	0.95635	0.52888	0.89485	0.79300
187	13.608	0.95112	0.52599	0.88995	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
(F-D) 301.13   FIG 302.38   SIGMA IF 1.4302   FTAPF-0.25562   PSW 0.3019724   CFW 3.0348615

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CARDELL   REC 10/24/79 22:32:34.700   FAC 9X6X1   PGM C034   PPG 1448

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.568	3.87833	0.41706	0.70303	0.72200
37	13.807	0.96492	0.45819	0.77234	0.82000
47	14.242	0.99530	0.47260	0.79665	0.91900
52	14.486	1.0124	0.49072	0.81035	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.452	0.94013	0.44641	0.75250	0.42200
67	12.708	0.88811	0.42170	0.71090	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	11.719	0.81897	0.38887	0.65552	0.50800
92	16.499	1.1531	0.54753	0.92295	0.58300
92	14.272	0.99739	0.47359	0.79833	0.67800

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.222	0.99390	0.47194	0.79554	-1.0000
-112	14.212	0.99320	0.47161	0.79598	-1.0000
-122	14.207	0.99285	0.47144	0.79470	-1.0000
-127	14.222	0.99390	0.47194	0.79554	-1.0000
-137	14.167	0.99006	0.47011	0.79246	-1.0000
-142	14.027	0.98029	0.46547	0.78664	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.222	0.99390	0.47194	0.79554	0.39800
112	14.212	0.99320	0.47161	0.79498	0.43100
122	14.207	0.99285	0.47144	0.79470	0.46900
127	14.222	0.99390	0.47194	0.79554	0.48600
137	14.167	0.99006	0.47011	0.79246	0.52200
142	14.027	0.98029	0.46547	0.78664	0.58900
152	14.242	0.99800	0.47393	0.79889	-1.0000
157	14.242	0.99800	0.47393	0.79889	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.282	0.99809	0.47393	0.79889	-1.0000
-157	14.292	0.99800	0.47393	0.79889	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.282	0.99809	0.47393	0.79889	0.79300
172	14.297	0.99844	0.47409	0.79017	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.602	0.95061	0.45139	0.76088	0.79300
187	13.507	0.94397	0.44823	0.75557	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
F5-71 433.44   FIC 629.67   SIGMA IC 1.2399   FTAPE-0.24626   DSM 0.312596   CFM 0.8033930

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFIT   REC 10/26/79 22:35:10.74A   FSC RX6%I   PGM C034   PPG 1441

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	5.9745	0.41782	0.16731	0.28284	0.72200
37	12.931	0.89522	0.35847	0.63691	1.82000
47	14.319	1.0014	0.40099	0.67790	3.91900
52	14.864	1.0395	0.41624	0.70367	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.324	1.0018	0.40113	0.67814	0.42200
67	11.492	0.80369	0.32182	0.54405	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	8.2090	0.57410	0.22988	0.38863	0.50800
82	19.967	1.3964	0.55916	0.94530	3.58300
92	14.244	0.99617	0.39889	0.67435	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.199	0.99303	0.39763	0.67222	-1.0000
-112	14.189	0.99233	0.39735	0.67175	-1.0000
-122	14.184	0.99199	0.39721	0.67151	-1.0000
-127	14.199	0.99303	0.39763	0.67222	-1.0000
-137	14.144	0.98919	0.39609	0.66962	-1.0000
-142	14.039	0.98185	0.39316	0.66466	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.199	0.99303	0.39763	0.67222	0.39800
112	14.189	0.99233	0.39735	0.67175	0.43100
122	14.184	0.99199	0.39721	0.67151	0.44900
127	14.199	0.99303	0.39763	0.67222	0.48600
137	14.144	0.98919	0.39609	0.66962	0.52200
142	14.039	0.98185	0.39316	0.66466	0.58800
152	14.259	0.99782	0.39959	0.67553	1.0000
157	14.259	0.99722	0.39931	0.67504	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.269	0.99782	0.39959	0.67553	-1.0000
-157	14.259	0.99722	0.39931	0.67504	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.264	0.99757	0.39945	0.67530	0.79300
172	14.264	0.99757	0.39945	0.67530	0.84600

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
192	13.550	0.94762	0.37945	0.64148	3.79300
197	13.395	0.93679	0.37511	0.63415	0.84600

>OPTION 5 , MEASURED THRUST PARAMETERS
(F-D) 574.67   FIC 574.12   SIGMA IC 1.9525   FTAPF=0.46654   PSW 0.919424   CFW 2.1932451

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFII   REC 10/24/79 22:36:59.999   FOR RX6VI   PGM C934   PRG 1442

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	7.7976	0.54554	0.17547	0.29755	0.72200
37	13.167	0.92116	0.29629	0.50242	0.82000
47	10.333	0.72299	0.23252	0.39428	0.91900
52	15.405	1.0778	0.34667	0.58785	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	17.993	1.2589	0.40491	0.68661	0.42200
67	14.981	1.0461	0.33711	0.57164	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	10.652	0.74527	0.23972	0.40648	0.50000
82	14.946	1.0456	0.33632	0.57030	0.58300
92	14.231	0.99563	0.32024	0.54304	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	14.171	0.99144	0.31890	0.54075	-1.0000
-112	14.156	0.99039	0.31856	0.54018	-1.0000
-122	14.151	0.99004	0.31845	0.53999	-1.0000
-127	14.176	0.99179	0.31901	0.54094	-1.0000
-137	14.136	0.98899	0.31811	0.53941	-1.0000
-142	14.091	0.98514	0.31687	0.53732	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	14.171	0.99144	0.31890	0.54075	0.39800
112	14.156	0.99039	0.31856	0.54018	0.43100
122	14.151	0.99004	0.31845	0.53999	0.44900
127	14.176	0.99179	0.31901	0.54094	0.48600
137	14.136	0.98899	0.31811	0.53941	0.52200
142	14.091	0.98514	0.31687	0.53732	0.58900
-152	14.256	0.99738	0.32081	0.54399	-1.0000
-157	14.261	0.99773	0.32092	0.54418	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	14.256	0.99738	0.32081	0.54399	-1.0000
-157	14.261	0.99773	0.32092	0.54418	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
167	14.256	0.99738	0.32081	0.54399	0.79300
172	14.256	0.99738	0.32081	0.54399	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
182	13.431	0.93960	0.30225	0.51253	0.79300
187	13.217	0.92466	0.29742	0.50433	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 801.25   FIC 759.95   SIGMA IC 2.1506   FTAPF 0.25945   DSM 0.044623   CFN 0.3839075

304

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFIT   PEC 10/26/79 22:39:52.117   FAC 974X1   PGM F096   RAG 1443

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	8.6613	0.63699	0.14869	0.28653	0.72200
37	14.368	1.0476	0.24077	0.49450	0.82000
47	12.364	0.90156	0.25024	0.42557	0.91500
52	15.447	1.0826	0.30049	0.51102	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	20.717	1.4519	0.40300	0.68537	0.42200
67	17.376	1.1967	0.33216	0.56490	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.274	0.86024	0.23877	0.40607	0.50800
82	17.255	1.2093	0.33566	0.57085	0.58300
92	14.223	0.99681	0.27667	0.47053	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.143	0.99120	0.27512	0.46780	-1.0000
-112	14.133	0.99050	0.27493	0.46756	-1.0000
-122	14.128	0.99015	0.27483	0.46739	-1.0000
-127	14.153	0.99191	0.27531	0.46822	-1.0000
-137	14.113	0.98910	0.27454	0.46690	-1.0000
-142	14.063	0.98560	0.27356	0.46524	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.143	0.99120	0.27512	0.46780	0.39800
112	14.133	0.99050	0.27493	0.46756	0.43100
122	14.128	0.99015	0.27483	0.46739	0.44900
127	14.153	0.99191	0.27531	0.46822	0.48600
137	14.113	0.98910	0.27454	0.46690	0.52200
142	14.063	0.98560	0.27356	0.46524	0.58800
152	14.243	0.99850	0.27716	0.47136	1.0000
157	14.249	0.99856	0.27716	0.47136	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.243	0.99856	0.27716	0.47136	-1.0000
-157	14.249	0.99856	0.27716	0.47136	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.243	0.99856	0.27716	0.47136	0.79300
172	14.249	0.99856	0.27716	0.47136	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.484	0.94498	0.26229	0.44607	0.79300
187	13.264	0.92958	0.25801	0.43880	0.94400

>SECTION 5 , MEASURED THRUST PARAMETERS
TF-71 S99.32   FLC 956.57   SIGMA IC 1.0305   FTAPF 0.68286   DSP 0.066565   CFM 0.9029390

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CANOFIT   REC 10/26/79 27:42:06.697   F. W. REST   PGR C036

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	9.4337	0.64114	0.15754	0.24728	0.72200
37	16.092	1.1278	0.26874	0.45580	0.82000
47	16.864	1.0417	0.24823	0.42100	0.91900
57	12.966	0.90928	0.21453	0.36285	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	23.867	1.6727	0.39859	0.67632	0.42200
67	18.629	1.3056	0.31111	0.52765	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	14.326	1.0039	0.23922	0.40573	0.59000
82	20.137	1.4113	0.33629	0.57096	0.58300
92	16.214	0.99619	0.23739	0.40281	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.115	0.98919	0.23532	0.39978	-1.0000
-112	14.120	0.98889	0.23563	0.39964	-1.0000
-122	14.100	0.98814	0.23547	0.39936	-1.0000
-127	14.135	0.99059	0.23605	0.40035	-1.0000
-137	14.105	0.98849	0.23555	0.39950	-1.0000
-142	14.072	0.98604	0.23497	0.39851	-1.0000

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.115	0.98919	0.23572	0.39978	0.39900
112	14.113	0.98886	0.23563	0.39964	0.43100
122	14.100	0.98814	0.23547	0.39936	0.44900
127	14.135	0.99059	0.23605	0.40035	0.46800
137	14.105	0.98849	0.23555	0.39950	0.52200
142	14.070	0.98604	0.23497	0.39851	0.58800

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-252	14.234	0.99789	0.23788	0.40344	-1.0000
-257	14.244	0.99829	0.23798	0.40368	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.249	0.99864	0.23797	0.40360	0.79300
172	14.248	0.99866	0.23787	0.40360	0.86400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.625	0.94089	0.22421	0.38026	0.79300
187	13.131	0.92024	0.21924	0.37101	0.86400

>ADDITIONAL S , MEASURED THRUST PARAMETERS

(F-3) 1735.5   FIG 1736.0   SIGF 16 7.5993   FTGF 3.41155   DCM 0.041355   FFM 0.002602

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   REC 10/24/79 22:43:05.013   FAC RX6X1   PGM C034   PRG 1445

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	9.4202	0.66013	0.15739	0.26697	0.72200
37	16.079	1.1268	0.26865	0.45570	0.82000
47	14.861	1.0614	0.24829	0.42116	0.91900
52	12.973	0.90906	0.21674	0.36765	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	23.880	1.6734	0.39898	0.67677	0.42200
67	18.621	1.3049	0.31112	0.52774	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	14.236	0.99762	0.23786	0.40347	0.50800
82	20.105	1.4088	0.33590	0.56977	0.58300
92	14.216	0.99622	0.23752	0.40299	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.117	0.99922	0.23585	0.40007	-1.0000
-112	14.112	0.98887	0.23577	0.39993	-1.0000
-122	14.112	0.98887	0.23577	0.39993	-1.0000
-127	14.146	0.99132	0.23635	0.40092	-1.0000
-137	14.097	0.98782	0.23552	0.39950	-1.0000
-142	14.072	0.98607	0.23510	0.39880	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.117	0.99922	0.23585	0.40007	0.39800
112	14.112	0.98887	0.23577	0.39993	0.43100
122	14.112	0.98887	0.23577	0.39993	0.44900
127	14.146	0.99132	0.23635	0.40092	0.48600
137	14.097	0.98782	0.23552	0.39950	0.52200
142	14.072	0.98607	0.23510	0.39980	0.58800
152	14.251	0.99867	0.23811	0.40389	1.0000
157	14.251	0.99867	0.23811	0.40389	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.251	0.99867	0.23811	0.40389	-1.0000
-157	14.251	0.99867	0.23811	0.40389	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.246	0.99832	0.23802	0.40375	0.79300
172	14.251	0.99867	0.23811	0.40389	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.427	0.94091	0.22634	0.38053	0.79300
187	13.137	0.92061	0.21950	0.37232	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

FG-PI 1236.8   FIC 1233.3   SIGMA IC 2.6458   FTARE 0.38722   DSW 0.975177   CFG 0.982868

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADOFII   REC 10/24/79 22:44:43.654   FAC 9Y6Y1   PGM C034   PAG 1446

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	8.6575	0.60649	0.16815	0.28644	0.72200
37	14.794	1.0364	0.29733	0.48947	0.82000
47	12.935	0.90408	0.25065	0.42699	0.91900
52	15.458	1.0829	0.30024	0.51145	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	20.708	1.4507	0.40220	0.68514	0.42200
67	17.132	1.2001	0.33274	0.56682	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.326	0.86347	0.23940	0.40781	0.50800
82	17.312	1.2127	0.33623	0.57277	0.58300
92	14.224	0.99648	0.27627	0.47062	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.144	0.99088	0.27472	0.46798	-1.0000
-112	14.129	0.98983	0.27443	0.46749	-1.0000
-122	14.129	0.98983	0.27443	0.46749	-1.0000
-127	14.154	0.99158	0.27491	0.46831	-1.0000
-137	14.114	0.98878	0.27414	0.46699	-1.0000
-142	14.070	0.98563	0.27326	0.46550	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.144	0.99088	0.27472	0.46798	0.39800
112	14.129	0.98983	0.27443	0.46749	0.43100
122	14.129	0.98983	0.27443	0.46749	0.44900
127	14.154	0.99158	0.27491	0.46831	0.48000
137	14.114	0.98878	0.27414	0.46699	0.52200
142	14.070	0.98563	0.27326	0.46550	0.58800
152	14.254	0.99858	0.27685	0.47162	-1.0000
157	14.249	0.99823	0.27676	0.47145	-1.0000

>ADDITIONAL PRESSURE RATIOS , PRI NOZZLE PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.254	0.99858	0.27685	0.47162	-1.0000
-157	14.249	0.99823	0.27676	0.47145	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.249	0.99823	0.27676	0.47145	0.79300
172	14.259	0.99893	0.27695	0.47178	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.495	0.94538	0.26210	0.44649	0.79300
187	13.265	0.92928	0.25764	0.43889	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
(F-D) 999.72   FL: 999.35   SIGMA IC 1.9961   FTARE 0.30159   DSW 0.268952   CFW 0.0028973

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFIT   REC 13/24/79 22:46:45.072   FAC 8x6X1   PGM F034   PRG 1447

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	7.6389	0.53495	0.17236	0.29239	0.72200
37	13.214	0.92535	0.29815	0.50752	0.87033
47	10.297	0.72039	0.23211	0.39509	0.91400
52	15.311	1.0722	0.34547	0.58805	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
52	17.872	1.2516	0.40327	0.68662	0.62280
57	14.856	1.0404	0.33522	0.57060	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.577	0.76068	0.23885	0.40622	0.50800
82	14.846	1.0397	0.33500	0.57021	0.58300
92	14.222	0.99599	0.32091	0.54624	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.157	0.99164	0.31565	0.54375	-1.0000
-112	14.152	0.99109	0.31934	0.54356	-1.0000
-122	14.147	0.99074	0.31922	0.54337	-1.0000
-127	14.167	0.99214	0.31967	0.54413	-1.0000
-137	14.122	0.99899	0.31866	0.54241	-1.0000
-142	14.068	0.98515	0.31742	0.54030	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.157	0.99164	0.31565	0.54375	0.39800
112	14.152	0.99109	0.31934	0.54356	0.43100
122	14.147	0.99074	0.31922	0.54337	0.44900
127	14.167	0.99214	0.31967	0.54413	0.48600
137	14.122	0.99899	0.31866	0.54241	0.52200
142	14.068	0.98515	0.31742	0.54030	0.55800
152	14.247	0.99773	0.32149	0.54730	-1.0000
157	14.247	0.99773	0.32149	0.54730	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.247	0.99773	0.32149	0.54720	-1.0000
-157	14.247	0.99773	0.32149	0.54720	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
162	14.247	0.99773	0.32149	0.54720	0.79300
172	14.252	0.99808	0.32159	0.54739	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.403	0.93866	0.30243	0.51476	0.79300
187	13.194	0.92375	0.29749	0.50625	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS
IF-31 724.63   FLC 793.67   SIGMA IC 1.8829   FTAFF 0.23463   DSW 0.366941   CFW 0.3028975

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADCELL   PEC 10/24/79 22:47:69.385   FAC 9T6T1   PGM C036   RPG 1469

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
22	6.9959	0.47659	0.17242	0.29226	0.72200
32	10.935	0.75639	0.27370	0.46303	0.82000
47	13.997	0.96656	0.34975	0.59284	0.91900
52	14.861	1.0403	0.37644	0.63810	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	15.990	1.1117	0.40225	0.68184	0.42200
47	13.183	0.92295	0.33393	0.56604	1.67300

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER D.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	9.3409	0.65389	0.23661	0.40107	0.50800
92	13.353	0.93474	0.33823	0.57333	0.58300
92	14.227	0.99593	0.36037	0.61086	0.67000

>ADDITIONAL PRESSURE RATIOS , FSECOND SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	14.167	0.99173	0.35886	0.60829	-1.0000
-112	14.157	0.99103	0.35860	0.60786	-1.0000
-122	14.152	0.99068	0.35848	0.60764	-1.0000
-127	14.172	0.99208	0.35898	0.60850	-1.0000
-137	14.132	0.98929	0.35797	0.60678	-1.0000
-142	14.047	0.98334	0.35582	0.60314	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	14.167	0.99173	0.35886	0.60829	0.39800
112	14.157	0.99103	0.35860	0.60786	0.43100
122	14.152	0.99068	0.35848	0.60764	0.44900
127	14.172	0.99208	0.35898	0.60850	0.48600
137	14.132	0.98929	0.35797	0.60678	0.52200
142	14.047	0.98334	0.35582	0.60314	0.58800
-142	14.242	0.99898	0.36079	0.61150	-1.0000
-152	14.242	0.99898	0.36079	0.61150	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	14.242	0.99898	0.36079	0.61150	-1.0000
-157	14.242	0.99898	0.36075	0.61150	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
167	14.242	0.99898	0.36075	0.61150	0.79300
172	14.242	0.99898	0.36075	0.61150	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
182	13.423	0.93963	0.34009	0.57623	0.79300
187	13.208	0.92460	0.33456	0.56711	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

F5-D1 669.92   F1C 667.21   SIGMA 1C 1.7324   FTAPF 0.62306   DSP 0.062441   CF5 0.0029155

NACA-LEWIS   PRELIMINARY DATA   08/13/79   CARDELL   REC 10/24/79 22:48:25.312   FAC RX4X1   PGM C034   PPG 1449

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	6.7862	0.47534	0.17244	0.29147	0.72200
37	10.769	0.75432	0.27365	0.46253	0.82000
47	13.831	0.96880	0.35145	0.59405	0.91900
52	14.972	1.0416	0.37785	0.63866	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	15.884	1.1126	0.40361	0.68220	0.42200
67	13.157	0.92157	0.33432	0.56509	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	9.3301	0.65143	0.23632	0.39944	0.50800
82	13.496	0.94466	0.34270	0.57924	0.58300
92	14.226	0.99643	0.36148	0.61099	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.176	0.99293	0.36021	0.60885	-1.0000
-112	14.161	0.99188	0.35983	0.60820	-1.0000
-122	14.156	0.99153	0.35970	0.60799	-1.0000
-127	14.176	0.99293	0.36021	0.60885	-1.0000
-137	14.136	0.99013	0.35919	0.60713	-1.0000
-142	14.346	0.98384	0.35691	0.60327	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.176	0.99293	0.36021	0.60885	0.39800
112	14.161	0.99188	0.35983	0.60820	0.43100
122	14.156	0.99153	0.35970	0.60799	0.44900
127	14.176	0.99293	0.36021	0.60885	0.48600
137	14.136	0.99013	0.35919	0.60713	0.52200
142	14.346	0.99384	0.35691	0.60327	0.58900

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.246	0.99793	0.36199	0.61185	-1.0000
-157	14.246	0.99793	0.36199	0.61185	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.251	0.99818	0.36211	0.61206	0.79300
172	14.251	0.99818	0.36211	0.61206	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.431	0.94081	0.34130	0.57688	0.79300
187	13.227	0.92646	0.33610	0.56809	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 667.27   FID 665.77   SIGMA LC 1.8966   FTAPF 2.63670   DCM 0.363527   CFM 0.3929113

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CARDELL   REC 10/24/79 22:49:43.166   FOR AK6E1   PGM C926   PBG 1459

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PI/PO	PL/PTF	PI/PTP	X/DMAX
32	6.7769	0.47762	0.18993	0.33082	0.72200
37	12.498	0.88743	0.35587	0.60111	0.82000
67	14.131	0.99761	0.39695	0.66897	0.91900
52	14.736	1.0298	0.41208	0.69758	1.0173

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PI/PO	PL/PTF	PI/PTP	X/DMAX
62	14.311	1.0002	0.40109	0.67748	0.42200
67	11.474	0.80190	0.32157	0.54318	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PI/PO	PL/PTF	PI/PTP	X/DMAX
77	8.2114	0.57388	0.23013	0.38872	0.50800
82	20.039	1.4005	0.56161	0.94862	0.58300
92	14.246	0.99563	0.39927	0.67461	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.191	0.99179	0.39773	0.67181	-1.0000
-112	16.191	0.99110	0.39745	0.67134	-1.0000
-122	14.176	0.99075	0.39731	0.67110	-1.0000
-127	14.191	0.99179	0.39773	0.67181	-1.0000
-137	14.146	0.98865	0.39647	0.66968	-1.0000
-142	14.021	0.97993	0.39297	0.66377	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.191	0.99179	0.39773	0.67181	0.39800
112	14.191	0.99110	0.39745	0.67134	0.43100
122	14.176	0.99075	0.39731	0.67110	0.46400
127	14.191	0.99179	0.39773	0.67181	0.49600
137	14.146	0.98865	0.39647	0.66968	0.52200
142	14.021	0.97993	0.39297	0.66377	0.58800
152	14.261	0.99668	0.39969	0.67512	-1.0000
157	14.261	0.99668	0.39969	0.67512	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PI/PTP	X/DMAX
-152	14.261	0.99668	0.39969	0.67512	-1.0000
-157	14.261	0.99668	0.39969	0.67512	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PI/PO	PI/PTF	PI/PTP	X/DMAX
167	14.266	0.99703	0.39983	0.67536	0.79300
172	14.261	0.99668	0.39969	0.67512	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PI/PO	PL/PTF	PI/PTP	X/DMAX
182	13.552	0.94712	0.37981	0.64155	0.79300
187	13.397	0.93569	0.37519	0.63374	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 572.39   FIC 571.39   SIGMA IC 1.4115   FTAPF-0.029929   DCF 0.019605   CFM 0.0032433

MESA-1 FMIS   PRELIMINARY DATA   X/13/79   CADDELL   PFC 10/24/79 22:52:00.122   FAT RX4XI   PGM CO24   PAG 1451

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WOPD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.557	0.87893	0.41547	0.70013	0.72200
37	13.795	0.96563	0.45645	0.76918	0.92000
47	14.230	0.99604	0.47083	0.79341	0.91900
52	14.482	1.0135	0.47909	0.80733	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WOPD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.476	0.94326	0.44588	0.75136	0.42200
67	12.717	0.89012	0.42076	0.73094	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WOPD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	11.653	0.81566	0.38556	0.64972	0.50800
82	16.402	1.1481	0.54270	0.91451	0.58300
92	14.260	0.99814	0.47182	0.79508	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WOPD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.215	0.99499	0.47033	0.79257	-1.0000
-112	14.200	0.99394	0.46984	0.79174	-1.0000
-122	14.200	0.99394	0.46984	0.79174	-1.0000
-127	14.215	0.99499	0.47033	0.79257	-1.0000
-137	14.155	0.99079	0.46835	0.78923	-1.0000
-142	14.019	0.98066	0.46356	0.78115	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WOPD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.215	0.99499	0.47033	0.79257	0.39800
112	14.200	0.99394	0.46984	0.79174	0.43100
122	14.200	0.99394	0.46984	0.79174	0.44900
127	14.215	0.99499	0.47033	0.79257	0.48600
137	14.155	0.99079	0.46835	0.78923	0.52200
142	14.019	0.98066	0.46356	0.78115	0.58600
152	14.275	0.99918	0.47231	0.79591	-1.0000
152	14.275	0.99918	0.47231	0.79591	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WOPD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.275	0.99918	0.47231	0.79591	-1.0000
-157	14.275	0.99918	0.47231	0.79591	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WOPD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.270	0.99883	0.47215	0.79563	0.79300
172	14.275	0.99918	0.47231	0.79591	0.84400

>ADDITIONAL PRESSURE RATIOS , 50 DEG SHROUD LOCATION

AVD WOPD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.591	0.95060	0.44935	0.75721	0.79300
187	13.471	0.94291	0.44571	0.75108	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FG-D) 422.24   FIF 431.17   SIGMA FG 0.96530   ETARF 0.60815   DSH 0.063551   CFH 0.0029112

313

PUN24

YE53-IFNIS   PRELIMINARY DATA   06/13/79   CANDFIT   PFF 10/24/79 22:57:08.202   FAF 84681   PGM C054   PDC 1452

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVR WORD	PL	PL/PD	PL/PTF	PL/PTF	X/DMAX
22	13.568	0.96737	0.52525	0.88900	2.72200
27	13.928	0.97301	0.54408	0.91290	0.82000
77	14.098	0.93578	0.55071	0.92504	0.91600
52	14.198	2.00171	0.55403	0.93062	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVR WORD	PL	PL/PD	PL/PTF	PL/PTF	X/DMAX
62	13.743	0.96098	0.53696	0.9317R	0.42200
67	13.598	0.95306	0.53120	0.8922R	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVR WORD	PL	PL/PD	PL/PTF	PL/PTF	X/DMAX
77	12.090	0.86539	0.47229	0.79330	0.50800
82	15.511	1.0046	0.60592	1.0178	0.58300
92	14.273	0.98800	0.55754	0.93651	0.67000

>ADDITIONAL PRESSURE RATIOS , SECONDARY SHROUD

AVR WORD	PL	PL/PD	PL/PTF	PL/PTF	X/DMAX
-107	14.743	0.99591	0.55533	0.93455	-1.0000
-112	14.233	0.99521	0.55598	0.93388	-1.0000
-122	14.229		0.55579	0.93356	-1.0000
-127	14.233	0.99521	0.55598	0.93389	-1.0000
-132	14.198	0.99206	0.55422	0.93204	-1.0000
-137	14.058	0.98298	0.54915	0.92747	-1.0000

>ADDITIONAL PRESSURE RATIOS , SECONDARY INLET

AVR WORD	PL	PL/PD	PL/PTF	PL/PTF	X/DMAX
107	14.243	0.99591	0.55637	0.93455	0.39800
112	14.233	0.99521	0.55598	0.93389	0.43100
122	14.228	0.99446	0.55579	0.93356	0.44900
127	14.233	0.99521	0.55598	0.93389	0.48600
137	14.188	0.99208	0.55427	0.93004	0.52200
142	14.058	0.98298	0.54915	0.92242	0.58000
-152					-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN DUCT SHROUD

AVR WORD	PL	PL/PD	PL/PTF	PL/PTF	X/DMAX
-152	14.283	0.99870	0.55703	0.93717	-1.0000
-157	14.288	0.99905	0.55813		-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVR WORD	PL	PL/PD	PL/PTF	PL/PTF	X/DMAX
167	14.288	0.99905	0.55813	0.93750	0.79300
172	14.283	0.99872	0.55793	0.93717	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVR WORD	PL	PL/PD	PL/PTF	PL/PTF	Y/DMAX
182	13.683	0.95679	0.53452	0.89785	0.79300
187	13.503	0.95351	0.53101	0.89105	0.84400

SWITCH 5 , MEASURED THRUST PARAMETERS

314

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFII   PEC 10/24/79 22:59:49.097   FAC RX6X1   PG= C034   PRG 1453

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	6.8170	0.47711	0.17230	0.29189	0.72200
37	10.809	0.75646	0.27319	0.46279	0.82000
47	13.729	0.96090	0.34702	0.58787	0.91900
52	14.813	1.0367	0.37440	0.63426	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	15.936	1.1153	0.40279	0.68235	0.42200
67	13.223	0.92526	0.33415	0.56606	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	9.2950	0.65055	0.23494	0.39800	0.50200
82	13.395	0.93749	0.33856	0.57355	0.58300
92	14.224	0.99550	0.35951	0.60903	0.67000

>ADDITIONAL PRESSURE RATIOS , FOREBODY SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.164	0.99130	0.35800	0.60647	-1.0000
-112	14.154	0.99060	0.35774	0.60604	-1.0000
-122	14.159	0.99095	0.35787	0.60625	-1.0000
-127	14.179	0.99235	0.35838	0.60711	-1.0000
-137	14.124	0.98851	0.35699	0.60476	-1.0000
-142	14.059	0.98397	0.35535	0.60198	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.164	0.99130	0.35800	0.60647	0.39800
112	14.154	0.99060	0.35774	0.60604	0.43100
122	14.159	0.99095	0.35787	0.60625	0.44900
127	14.179	0.99235	0.35838	0.60711	0.48600
137	14.124	0.98851	0.35699	0.60476	0.52200
142	14.059	0.99397	0.35535	0.60198	0.58800
152	14.244	0.99689	0.35992	0.60989	1.0000
157	14.244	0.99689	0.36002	0.60989	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.244	0.99689	0.35802	0.60989	-1.0000
-157	14.244	0.99689	0.36002	0.60989	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.244	0.99689	0.36002	0.60989	0.79300
172	14.244	0.99689	0.36002	0.60989	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.400	0.93794	0.33869	0.57376	0.79300
187	13.180	0.92247	0.33314	0.56435	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
(F-D) 671.69   TIC 669.57   SIGMA IC 1.5302   FTAPF 1.0567   DSM 0.061345   CFM 0.2029293

315

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFIT   REC 10/24/79 23:02:46.768   FAC RX6X1   PGM C034   PMG 1454

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	8.6184	0.60380	0.16829	0.28657	0.72200
37	15.212	1.0657	0.29704	0.50582	0.82000
47	12.767	0.89443	0.24929	0.42651	0.91900
52	15.417	1.0801	0.30104	0.51262	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	20.616	1.4443	0.40255	0.68549	0.42200
67	17.088	1.1972	0.33367	0.56820	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.173	0.85282	0.23769	0.40476	0.50800
82	17.143	1.2010	0.33475	0.57003	0.58300
92	14.209	0.99567	0.27746	0.47247	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.134	0.99023	0.27599	0.46998	-1.0000
-112	14.124	0.98953	0.27580	0.46965	-1.0000
-122	14.114	0.98883	0.27560	0.46932	-1.0000
-127	14.144	0.99093	0.27619	0.47031	-1.0000
-137	14.099	0.98778	0.27531	0.46882	-1.0000
-142	14.054	0.98463	0.27443	0.46732	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.134	0.99023	0.27599	0.46998	0.39800
112	14.124	0.98953	0.27580	0.46965	0.43100
122	14.114	0.98883	0.27560	0.46932	0.44900
127	14.144	0.99093	0.27619	0.47031	0.48600
137	14.099	0.98778	0.27531	0.46882	0.52200
142	14.054	0.98463	0.27443	0.46732	0.58800
152	14.239	0.99757	0.27804	0.47346	-1.0000
157	14.244	0.99792	0.27814	0.47363	-1.0000

>ADDITIONAL PRESSURE RATIOS , CAN WRPPER FLOP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.239	0.99757	0.27804	0.47346	-1.0000
-157	14.244	0.99792	0.27814	0.47363	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.239	0.99757	0.27804	0.47346	0.79300
172	14.239	0.99757	0.27804	0.47346	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.473	0.94373	0.26303	0.44791	0.79300
187	13.244	0.92799	0.25865	0.44044	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 993.63   FIC 292.13   SIGMA IC 2.5582   FTADE 0.43146   DSW C.061303   CFW 0.002918

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDEII   REC 10/24/79 23:05:24.396   FAC RNAX1   PGM C936   PAG 1455

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.898	0.90213	0.49967	0.72329	0.72200
37	13.521	0.97369	0.53931	0.78066	0.82003
47	14.270	0.99913	0.55284	0.80026	0.91300
52	14.490	1.0128	0.56096	0.81201	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.726	0.96008	0.53177	0.76975	0.42200
67	13.132	0.91854	0.50876	0.73644	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.034	0.84173	0.46622	0.67486	0.50800
82	15.483	1.0829	0.59582	0.86826	0.58300
92	14.265	0.99773	0.55265	0.79959	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.225	0.99499	0.55110	0.79774	-1.0000
-112	14.220	0.99464	0.55091	0.79746	-1.0000
-122	14.210	0.99394	0.55052	0.79690	-1.0000
-127	14.230	0.99534	0.55130	0.79802	-1.0000
-137	14.180	0.99184	0.54936	0.79522	-1.0000
-142	14.046	0.98242	0.54414	0.78766	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.225	0.99499	0.55110	0.79774	0.39800
112	14.220	0.99464	0.55091	0.79746	0.43100
122	14.210	0.99394	0.55052	0.79690	0.46900
127	14.230	0.99534	0.55130	0.79802	0.48600
137	14.180	0.99184	0.54936	0.79522	0.52200
142	14.046	0.98242	0.54414	0.78766	0.58800
-152	14.290	0.99983	0.55328	0.80092	-1.0000
-157	14.275	0.99848	0.55304	0.80044	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN SPLIT PERP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.290	0.99983	0.55328	0.80092	-1.0000
-157	14.275	0.99848	0.55304	0.80044	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.290	0.99983	0.55328	0.80092	0.79300
172	14.270	0.99913	0.55284	0.80026	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.686	0.95729	0.53022	0.76751	0.79300
187	13.607	0.95170	0.52713	0.76303	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
(F-D) 245.37   FIC 364.32   SIGMA IC 1.2552   FTARE 0.036024   DSW 0.014623   CFW 2.003328

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CANOEII   REC 10/24/79 23:38:59.586   FAC 9X6X1   PG# C036   RDG 1456

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	13.285	0.71890	0.33941	0.49607	0.72200
37	13.560	0.94783	0.46759	0.64086	0.82900
47	14.433	1.0089	0.47633	0.68215	0.91500
52	14.778	1.0330	0.48770	0.69842	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	14.448	1.0099	0.47683	0.68285	0.42200
67	11.977	0.83721	0.39528	0.56607	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	11.543	0.80685	0.38094	0.54554	0.58000
82	16.410	1.1470	0.54156	0.77556	0.58300
92	14.246	0.99563	0.47007	0.67312	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	14.194	0.99214	0.46842	0.67092	-1.0000
-112	14.184	0.99145	0.46809	0.67035	-1.0000
-122	14.174	0.99075	0.46777	0.66988	-1.0000
-127	14.199	0.99179	0.46826	0.67059	-1.0000
-137	14.134	0.98796	0.46645	0.66799	-1.0000
-142	13.974	0.97679	0.46118	0.66044	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	14.194	0.99214	0.46842	0.67092	0.39800
112	14.184	0.99145	0.46809	0.67035	0.43100
122	14.174	0.99075	0.46777	0.66988	0.44900
127	14.199	0.99179	0.46826	0.67059	0.48600
137	14.134	0.98796	0.46645	0.66799	0.52200
142	13.974	0.97679	0.46119	0.66044	0.58800
-147	14.259	0.99668	0.47057	0.67389	-1.0000
-157	14.259	0.99668	0.47057	0.67389	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	14.259	0.99668	0.47057	0.67389	-1.0000
-157	14.259	0.99668	0.47057	0.67389	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
167	14.259	0.99668	0.47057	0.67389	0.79300
172	14.264	0.99703	0.47073	0.67412	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
182	13.565	0.94818	0.44767	0.64110	0.79300
187	13.465	0.94120	0.44437	0.63638	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

FG-DI 482.18   FLC 480.95   SIGMA IC 1.8556   FTAPF 0.20612   DSW 0.024753   CFP 0.3031792

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFII   REC 10/24/79 23:10:35.614   FAC AX6X1   PGM C936   RDG 1457

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	6.5564	0.45015	0.18296	0.26389	0.72200
37	9.9717	0.69482	0.27686	0.39934	0.87000
47	14.179	0.99294	0.39565	0.57069	0.91900
52	15.231	1.0667	0.42503	0.61305	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	16.758	1.1736	0.46763	0.67459	0.42209
67	13.021	0.91187	0.36335	0.52409	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	8.2842	0.58015	0.23117	0.33343	0.50800
82	19.961	1.3979	0.55700	0.80340	0.58300
92	14.229	0.99643	0.39704	0.57269	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	14.176	0.99259	0.39551	0.57048	-1.0000
-112	14.166	0.99189	0.39523	0.57008	-1.0000
-122	14.156	0.99119	0.39495	0.56967	-1.0000
-127	14.174	0.99259	0.39551	0.57048	-1.0000
-137	14.124	0.98910	0.39412	0.56847	-1.0000
-142	14.019	0.98176	0.39120	0.56425	-1.0000

>ADDITIONAL PRESSURE RATIOS , EJECTOR INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	14.174	0.99259	0.39551	0.57048	0.39800
112	14.166	0.99189	0.39523	0.57008	0.43180
122	14.156	0.99119	0.39495	0.56967	0.44900
127	14.174	0.99259	0.39551	0.57048	0.48600
137	14.124	0.98910	0.39412	0.56847	0.52200
142	14.019	0.98176	0.39120	0.56425	0.58800
-152	14.246	0.99748	0.39746	0.57329	-1.0000
-157	14.249	0.99783	0.39763	0.57349	-1.0000

>ADDITIONAL PRESSURE RATIOS , CWL UPPER FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	14.246	0.99748	0.39746	0.57329	-1.0000
-157	14.249	0.99783	0.39760	0.57349	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
167	14.249	0.99783	0.39760	0.57349	0.79300
172	14.244	0.99748	0.39746	0.57329	0.84430

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
182	13.435	0.94087	0.37490	0.54075	0.79300
187	13.246	0.92760	0.36961	0.53312	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

IC-9) 625.76   FIC 624.90   SIGMA IC 2.2071   FTAPF 0.91364   DSM 0.048073   CFM 0.0028445

NASA-LEWIS   PRELIMINARY DATA   26/13/79   CANDEII   REC 10/26/79 23:13:10.235   FAT 8268I   PCM C856

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	7.6343	2.52261	0.18857	0.27405	0.72200
37	10.408	2.75727	0.27416	0.39843	0.62000
47	12.839	0.89545	0.32567	0.47328	0.91900
52	15.254	1.0687	0.38691	0.56229	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER E.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	18.306	1.2926	0.46634	0.67481	0.42200
67	14.398	1.0086	0.36515	0.53066	0.67300

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	9.3562	2.65552	0.23732	0.34499	0.50000
82	13.433	2.94115	0.34073	0.49517	0.58300
92	14.216	0.99802	0.36054	0.52404	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER NOZZLE

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.156	3.9913	0.35867	0.52183	-1.0000
-112	14.141	0.63902	0.35870	0.52128	-1.0000
-122	14.136	0.78043	0.35867	0.52110	-1.0000
-127	14.143	0.99218	0.35977	0.52202	-1.0000
-137	14.121	0.98938	0.35819	0.57056	-1.0000
-142	14.046	0.98414	0.35629	0.51779	-1.0000

>ADDITIONAL PRESSURE RATIOS , FLOW NOZZLE INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.156	0.99183	0.35908	0.52183	0.39800
112	14.141	0.99078	0.35470	0.52128	0.43100
122	14.136	0.99043	0.35867	0.52110	0.44905
127	14.161	0.99218	0.35920	0.52202	0.58400
137	14.121	0.98938	0.35819	0.52055	0.52200
142	14.046	0.98414	0.35629	0.51779	0.58000
152					1.0000
153					-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE EXIT

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-157	14.236	0.99647	0.36110	0.52478	-1.0000
-167	14.736	0.99742	0.36110	0.52478	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.736	0.99742	0.36110	0.52478	0.79300
172	14.736	0.99742	0.36110	0.52478	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.298	0.93171	0.33731	0.49020	0.79300
187	13.059	0.91423	0.33108	0.48101	0.84400

>OPTION 5, MEASURED THRUST PARAMETERS

FIC 718.08   SIGMA IC 1.0736   FVARF 0.73556   DSM 0.951800   DFS 0.303633
IC=11 720.77

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFII   REC 10/24/79 23:13:33.696   FAC RX6X1   PGM C034   RUG 1459

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	8.7417	0.61237	0.19677	0.28852	0.72200
37	13.894	0.97320	0.31274	0.45857	0.82000
47	11.148	0.78006	0.25094	0.36795	0.91900
52	15.611	1.0936	0.35139	0.51523	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	20.616	1.4442	0.46405	0.68042	0.42200
67	16.619	1.1642	0.37408	0.54850	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	10.669	0.74739	0.24015	0.35213	0.50800
82	14.987	1.0499	0.33734	0.49464	0.58300
92	14.223	0.99636	0.32016	0.46944	0.67000

>ADDITIONAL PRESSURE RATIOS , COFLOW SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.153	0.99147	0.31858	0.46713	-1.0000
-112	14.143	0.99077	0.31836	0.46680	-1.0000
-122	14.138	0.99042	0.31825	0.46664	-1.0000
-127	14.163	0.99217	0.31881	0.46746	-1.0000
-137	14.128	0.98972	0.31802	0.46621	-1.0000
-142	14.079	0.98622	0.31699	0.46466	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.153	0.99147	0.31858	0.46713	0.39800
112	14.143	0.99077	0.31836	0.46680	0.43100
122	14.138	0.99042	0.31825	0.46664	0.44900
127	14.163	0.99217	0.31881	0.46746	0.48600
137	14.128	0.98972	0.31802	0.46621	0.52200
142	14.079	0.98622	0.31699	0.46466	0.58800
152	14.268	0.99811	0.32072	0.47026	-1.0000
157	14.248	0.99811	0.32072	0.47026	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.268	0.99811	0.32072	0.47026	-1.0000
-157	14.248	0.99811	0.32072	0.47026	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.263	0.99846	0.32083	0.47043	0.79300
172	14.248	0.99811	0.32072	0.47026	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.449	0.94147	0.30252	0.44357	0.79300
187	13.210	0.92539	0.29735	0.43600	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS
(F-D) 854.72   FIC 853.57   SIGMA IC 2.1786   FTAPE 0.091133   DS4 0.060163   CF4 0.0029266

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CARDFIT   PFF 10/24/79 23:15:37.525   FAC RX6X1   PGM C036   RNG 1450

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WDPD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
37	0.7903	0.68622	0.19065	0.27456	0.72200
37	17.713	1.2364	0.33517	0.48260	0.82000
47	13.892	0.97381	0.27055	0.38963	0.91900
57	14.171	0.99340	0.27599	0.39746	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WDPD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	24.265	1.7009	0.47256	0.68055	0.42200
67	19.500	1.3669	0.37977	0.54691	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WDPD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	12.285	2.86117	0.23926	0.34456	0.50800
82	17.750	1.2092	0.33595	0.48381	0.54300
92	14.206	0.93585	0.27667	0.39844	0.67000

>ADDITIONAL PRESSURE RATIOS , EXHAUST SHROUD

AVD WDPD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	14.131	0.99060	0.27522	0.39634	-1.0000
112	14.116	0.98957	0.27492	0.39592	-1.0000
122	14.111	0.98921	0.27483	0.39578	-1.0000
127	14.141	0.99130	0.27541	0.39662	-1.0000
137	14.097	0.98816	0.27454	0.39536	-1.0000
147	14.052	0.98501	0.27366	0.39411	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WDPD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	14.131	0.99060	0.27522	0.39634	0.39800
112	14.116	0.98955	0.27492	0.39592	0.43100
122	14.111	0.98921	0.27483	0.39578	0.44900
127	14.141	0.99130	0.27541	0.39662	0.48600
137	14.097	0.98816	0.27454	0.39536	0.52200
147	14.052	0.98501	0.27366	0.39411	0.58800
157	14.241		0.27735	0.39942	-1.0000

>ADDITIONAL PRESSURE RATIOS , FLAT SURFACE PLUG

AVD WDPD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
152	14.241	0.99830	0.27735	0.39942	-1.0000
157	14.241	0.99830	0.27735	0.39942	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WDPD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
167	14.236	0.99795	0.27726	0.39928	0.79300
172	14.241	0.99830	0.27735	0.39942	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WDPD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
182	13.503	0.94653	0.26297	0.37871	0.79300
187	13.283	0.93114	0.25870	0.37255	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FLC 1064.8   SIGMA IF 2.4016   FTARE 0.31195   PCM 0.266895   CFM 0.002886R

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   REC 10/24/79 23:17:06.326   FAC RX6Y1   PGM C034   PRG 1461

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	10.901	0.76501	0.18317	0.26641	0.72200
37	16.375	1.1442	0.27396	0.39847	0.82000
47	16.944	1.1990	0.29469	0.41498	0.91900
52	12.394	0.86972	0.20824	0.30288	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	27.715	1.9449	0.46567	0.67730	0.42200
67	21.728	1.5247	0.36507	0.53099	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	14.170	0.99438	0.23809	0.34629	0.50800
82	20.017	1.4047	0.33632	0.48917	0.58300
92	14.195	0.99613	0.23859	0.34690	0.67000

>ADDITIONAL PRESSURE RATIOS , CENTER SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.105	0.98982	0.23699	0.34470	-1.0000
-112	14.095	0.98912	0.23683	0.34446	-1.0000
-122	14.090	0.98877	0.23674	0.34434	-1.0000
-127	14.125	0.99122	0.23733	0.34519	-1.0000
-137	14.090	0.98877	0.23674	0.34434	-1.0000
-142	14.055	0.98632	0.23616	0.34348	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.105	0.98982	0.23699	0.34470	0.39800
112	14.095	0.98912	0.23683	0.34446	0.43100
122	14.090	0.98877	0.23674	0.34434	0.44900
127	14.125	0.99122	0.23733	0.34519	0.48600
137	14.090	0.98877	0.23674	0.34434	0.52200
142	14.055	0.98632	0.23616	0.34348	0.58800
=152	14.235	0.99893	0.23917	0.34787	-1.0000
=157	14.240	0.99928	0.23926	0.34800	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.235	0.99893	0.23917	0.34787	-1.0000
-157	14.240	0.99928	0.23926	0.34800	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.235	0.99893	0.23917	0.34787	0.79300
172	14.235	0.99893	0.23917	0.34787	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.332	0.93555	0.22400	0.32590	0.79300
187	12.997	0.91139	0.21821	0.31739	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS
IF-DI 1302.9   FI5 1301.2   SIGMA IC 4.1027   FTAPE 0.55749   DSM 0.096351   CFM 0.0028319

323

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   REC 10/24/79 23:17:46.624   FAC 9X6Y1   PGM C034   PDG 1462

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	10.892	0.76410	0.19298	0.26593	0.72200
37	16.298	1.1433	0.27340	0.35792	0.82000
47	16.936	1.1981	0.28453	0.41359	1.91900
52	12.373	0.86803	0.20787	0.30210	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
52	27.706	1.9437	0.46547	0.67647	0.42200
67	21.717	1.5235	0.36485	0.53074	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	14.174	0.99433	0.23812	0.34606	0.50800
82	20.007	1.4036	0.33612	0.48869	0.58300
92	14.234	0.93643	0.23862	0.34679	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.104	0.98943	0.23694	0.34435	-1.0000
-112	14.094	0.98873	0.23678	0.34411	-1.0000
-122	14.084	0.98803	0.23661	0.34387	-1.0000
-127	14.129	0.99118	0.23736	0.34496	-1.0000
-137	14.089	0.98838	0.23669	0.34390	-1.0000
-142	14.049	0.98558	0.23602	0.34301	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.104	0.98943	0.23694	0.34435	0.39800
112	14.094	0.98873	0.23678	0.34411	0.43100
122	14.084	0.99803	0.23661	0.34387	0.46900
127	14.129	0.99118	0.23736	0.34496	0.48600
137	14.089	0.99838	0.23669	0.34390	0.52200
142	14.049	0.99558	0.23602	0.34301	0.58800
152	14.233	0.99853	0.23912	0.34752	-1.0000
157	14.233	0.99853	0.23912	0.34752	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.233	0.99853	0.23912	0.34752	-1.0000
-157	14.233	0.99853	0.23912	0.34752	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.238	0.99888	0.23921	0.34764	0.79300
172	14.233	0.99853	0.23912	0.34752	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.331	0.93520	0.22396	0.32548	0.79300
187	13.332	0.91211	0.21863	0.31745	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 1323.1   FIC 1301.6   SIGMA IC 2.7563   FTAPF 0.17594   DSM 0.069175   CFM 0.0028880

VACS-IFWIS   PRELIMINARY DATA   06/13/79   (ADDFII)   REC 10/24/79 23:19:19.307   FAC RK671   PG# C036   RDG 1463

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	9.7458	2.6874	2.1808	0.27298	0.72200
37	17.138	1.2015	0.33390	0.69181	0.42000
62	17.897	0.97423	0.27075	0.39067	0.91900
67	14.166	0.90312	0.27500	0.39025	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
42	24.235	1.6990	0.47216	0.69131	0.42200
67	10.472	1.3651	0.39937	0.54742	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.240	0.85813	0.23848	0.34412	0.58800
82	17.238	1.2064	0.33526	0.46377	0.58399
92	14.206	0.99591	0.27677	0.39937	0.67000

>ADDITIONAL PRESSURE RATIOS , EXTERNAL SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.116	0.98962	0.27502	0.39684	-1.0000
-112	14.111	0.98927	0.27492	0.39670	-1.0000
-122	14.106	0.98892	0.27483	0.39656	-1.0000
-127	14.116	0.99102	0.27541	0.39740	-1.0000
-137	14.096	0.98822	0.27463	0.39628	-1.0000
-142	14.056	0.98542	0.27385	0.39516	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.116	0.98962	0.27502	0.39684	0.39800
112	14.111	0.98927	0.27492	0.39670	0.43100
122	14.104	0.98802	0.27483	0.39656	0.44900
127	14.116	0.99102	0.27541	0.39740	0.48600
137	14.096	0.98822	0.27463	0.39628	0.52200
147	14.096	0.98542	0.27385	0.39516	0.58600

>ADDITIONAL PRESSURE RATIOS , FOREBODY FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-157	14.231	0.99836	0.27745	0.40035	-1.0000
-157	14.236	0.99801	0.27735	0.40021	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.236	0.99801	0.27735	0.40021	0.79300
177	14.231	0.99766	0.27726	0.40007	0.86400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
147	13.467	0.94591	0.26287	0.37922	0.79300
147	13.273	0.93052	0.25860	0.37315	0.86400

>OPTION 5 , MEASURED THRUST PARAMETERS

FG-O 1067.2   FG 1065.6   SIGMA LC 1.PC01   ETAFF 0.64610   DSM 0.950083   CFH 2.002988

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	8.6564	0.59226	0.19066	0.27925	0.72200
37	13.946	0.97675	0.31444	0.46054	0.82000
47	10.957	0.76741	0.24705	0.36183	0.91900
52	15.602	1.0928	0.35179	0.51523	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	20.566	1.4404	0.46369	0.67914	0.42200
67	16.326	1.1434	0.36810	0.53912	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	10.558	0.73944	0.23905	0.34865	0.50800
82	14.834	1.0389	0.33446	0.49986	0.58300
92	14.215	0.99562	0.32052	0.46943	0.67000

>ADDITIONAL PRESSURE RATIOS , FACTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.151	0.99107	0.31905	0.46729	-1.0000
-112	14.136	0.99002	0.31872	0.46680	-1.0000
-122	14.131	0.98967	0.31860	0.46663	-1.0000
-127	14.161	0.99177	0.31928	0.46762	-1.0000
-137	14.121	0.98898	0.31838	0.46630	-1.0000
-142	14.071	0.98548	0.31725	0.46466	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.151	0.99107	0.31905	0.46729	0.39800
112	14.136	0.99002	0.31872	0.46680	0.43100
122	14.131	0.98967	0.31860	0.46663	0.44900
127	14.161	0.99177	0.31928	0.46762	0.48600
137	14.121	0.98898	0.31838	0.46630	0.52200
142	14.071	0.98548	0.31725	0.46466	0.58800
-147	14.245	0.99726	0.32108	0.47026	-1.0000
-147	14.245	0.99771	0.32119	0.47042	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.240	0.99736	0.32108	0.47026	-1.0000
-157	14.245	0.99771	0.32119	0.47042	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.245	0.99771	0.32119	0.47042	0.79300
172	14.245	0.99771	0.32119	0.47042	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.437	0.93901	0.30229	0.44274	0.79300
187	13.178	0.92293	0.29712	0.43516	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) P53.97   FIC P52.62   SIGMA LC 1.3257   FTAPE 0.31113   DSM 0.040714   CFM 0.3030286

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CONDET1   PFC 10/24/79 23:71:34.275   FAC 9X6X1   PCP C034

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	7.3341	2.51357	0.18589	0.76903	0.72200
37	10.714	2.75025	0.27155	0.79433	0.82000
47	12.945	0.90647	0.32292	0.47644	0.91903
52	13.275	1.0696	0.28715	0.56221	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	18.349	1.2848	0.46504	0.67532	0.42200
67	14.497	1.0151	0.36747	0.53356	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	9.2763	2.64958	0.23511	0.34142	0.50800
87	13.424	2.94002	0.36023	0.46438	0.58300
92	16.207	0.99488	0.36098	0.52291	0.67000

>ADDITIONAL PRESSURE RATIOS , ECONOMY SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	14.147	0.9906	0.35857	0.52070	-1.0000
-112	14.137	0.98998	0.35831	0.52034	-1.0000
-122	14.132	0.98964	0.35819	0.52015	-1.0000
-127	14.157	0.99138	0.35882	0.52107	-1.0000
-137	14.108	0.98789	0.35756	0.51924	-1.0000
-142	14.028	0.98230	0.35553	0.51630	-1.0000

>ADDITIONAL PRESSURE RATIOS , ECONOMY INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	14.147	0.99069	0.35857	0.52070	0.39400
112	14.137	0.98998	0.35831	0.52034	0.43100
122	14.132	0.98964	0.35819	0.52015	0.44900
127	14.157	0.99138	0.35882	0.52107	0.46600
137	14.108	0.98789	0.35756	0.51924	0.57200
142	14.028	0.98230	0.35553	0.51630	0.58000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	14.232	0.99662	0.36072	0.52383	-1.0000
-157	14.232	0.99662	0.36072	0.52383	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
167	14.232	0.99662	0.36072	0.52383	0.79300
172	14.232	0.99662	0.36072	0.52383	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
187	13.270	0.92908	0.33656	0.48875	0.79300
197	13.025	0.91206	0.33011	0.47938	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
(F-D) 721.50   FLC 720.17   SIGMA IC 1.047R   STAPE 0.27875   DSP 0.758090   CFH 2.027R077

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFIT   PEC 10/24/79 23:22:52.119   FAC 9%6X1   PGM C034   PDG 1466

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	6.5399	0.45604	0.18202	0.26212	0.72200
37	9.8449	0.68966	0.27527	0.39641	0.82000
47	14.161	0.99204	0.39596	0.57021	0.91900
52	15.239	1.0675	0.42609	0.61360	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	16.765	1.1745	0.46877	0.67506	0.42200
67	13.099	0.91759	0.36624	0.52742	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	8.2076	0.57496	0.22949	0.33068	0.50800
82	19.908	1.3946	0.55663	0.80160	0.58300
92	14.236	0.99728	0.39805	0.57322	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.181	0.99343	0.39651	0.57101	-1.0000
-112	14.166	0.99239	0.39610	0.57041	-1.0000
-122	14.161	0.99204	0.39596	0.57021	-1.0000
-127	14.181	0.99343	0.39651	0.57101	-1.0000
-137	14.126	0.98959	0.39498	0.56880	-1.0000
-142	14.017	0.98190	0.39191	0.56438	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.181	0.99343	0.39651	0.57101	0.39800
112	14.166	0.99239	0.39610	0.57041	0.43100
122	14.161	0.99204	0.39596	0.57021	0.46900
127	14.181	0.99343	0.39651	0.57101	0.48600
137	14.126	0.98959	0.39498	0.56880	0.52200
142	14.017	0.98190	0.39191	0.56438	0.58800
147	14.251	0.99833	0.39847	0.57383	-1.0000
157	14.251	0.99833	0.39847	0.57383	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.251	0.99833	0.39847	0.57383	-1.0000
-157	14.251	0.99833	0.39847	0.57383	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.256	0.99868	0.39861	0.57403	0.79300
172	14.256	0.99868	0.39861	0.57403	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.429	0.94066	0.37545	0.54062	0.79300
187	13.229	0.92668	0.36987	0.53264	0.84400

SECTION 5 , MEASURED THRUST PARAMETERS
(F-D) 624.35   FIC 624.67   SIGMA IC 2.2812   FTAPF 0.62350   DSM 0.056033   CFM 0.002942R

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CAROFIT   REC 10/24/79 23:23:50.452   FAC RX6X1   PGM C034   PDG 1467

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	10.385	0.72629	0.34489	0.49319	0.72200
37	13.585	0.95014	0.45118	0.64570	0.82000
47	14.409	1.0077	0.47854	0.68432	0.91900
52	14.759	1.0322	0.49015	0.70091	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.404	1.0074	0.47838	0.68408	0.42200
67	12.368	0.86259	0.40911	0.57216	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	11.548	0.80767	0.38353	0.54845	0.50800
82	16.271	1.1380	0.54039	0.77274	0.58300
92	14.239	0.99588	0.47290	0.67625	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.196	0.99274	0.47141	0.67412	-1.0000
-112	14.179	0.99169	0.47091	0.67341	-1.0000
-122	14.174	0.99134	0.47075	0.67317	-1.0000
-127	14.189	0.99239	0.47125	0.67388	-1.0000
-137	14.120	0.98750	0.46893	0.67056	-1.0000
-142	13.960	0.97633	0.46362	0.66298	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.196	0.99274	0.47141	0.67412	0.39800
112	14.179	0.99169	0.47091	0.67341	0.43100
122	14.174	0.99134	0.47075	0.67317	0.44900
127	14.189	0.99239	0.47125	0.67388	0.48600
137	14.120	0.98750	0.46893	0.67056	0.52200
142	13.960	0.97633	0.46362	0.66298	0.58800
-152	14.254	0.99693	0.47340	0.67697	-1.0000
-157	14.249	0.99658	0.47324	0.67673	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.254	0.99693	0.47340	0.67697	-1.0000
-157	14.249	0.99658	0.47324	0.67673	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.254	0.99693	0.47340	0.67697	0.79300
172	14.254	0.99693	0.47340	0.67697	0.84600

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.545	0.94735	0.44986	0.64330	0.79300
187	13.446	0.94036	0.44654	0.63856	0.84600

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 479.78   FIC 475.34   SIGMA IC 1.2844   FTAPE-2.56161   DSP 0.0011721   CFM 0.0042920

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFII   REC 10/24/79 23:24:46.656   FAC RX6X1   PGM C034   PDG 146A

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.907	0.90276	0.49951	0.72323	0.72200
37	13.944	0.97530	0.53064	0.78134	0.82000
47	14.298	1.0091	0.55334	0.80118	0.91900
52	14.502	1.0144	0.56125	0.81263	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	13.745	0.96135	0.53103	0.77017	0.42200
67	13.151	0.91985	0.50896	0.73692	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.064	0.84382	0.46689	0.67601	0.50800
82	15.485	1.0831	0.59926	0.86766	0.58300
92	14.283	0.99902	0.55276	0.80024	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.248	0.99658	0.55141	0.79838	-1.0000
-112	14.238	0.99588	0.55103	0.79782	-1.0000
-122	14.233	0.99563	0.55084	0.79754	-1.0000
-127	14.243	0.99623	0.55127	0.79810	-1.0000
-137	14.198	0.99309	0.54948	0.79559	-1.0000
-142	14.059	0.99332	0.54408	0.78777	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.248	0.99658	0.55141	0.79838	0.39800
112	14.238	0.99588	0.55103	0.79782	0.43100
122	14.233	0.99553	0.55084	0.79754	0.44900
127	14.243	0.99623	0.55122	0.79810	0.48600
137	14.198	0.99309	0.54948	0.79559	0.52200
142	14.059	0.98332	0.54408	0.78777	0.58800
-152	14.298	1.0001	0.55334	0.80118	-1.0000
-157	14.293	0.99971	0.55315	0.80090	-1.0000

>ADDITIONAL PRESSURE RATIOS , CRW NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.298	1.0001	0.55334	0.80118	-1.0000
-157	14.293	0.99971	0.55315	0.80090	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.298	1.0001	0.55334	0.80118	0.79300
172	14.293	0.99971	0.55315	0.80090	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.705	0.95856	0.53038	0.76793	0.79300
187	13.615	0.95229	0.52691	0.76290	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 346.83   FLC 346.40   SIGMA LC 1.1155   FTAPF-0.57303   DSW 0.0029558   CFW 0.0039920

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CANNELL   PFC 10/25/79 00:35:23.815   FAC 9X6X1   PGM C036   RRG 1469

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	14.615	0.98159	0.54279	0.90866	0.72200
37	14.946	1.0037	0.55504	0.92916	0.82000
47	15.099	1.0135	0.56042	0.93816	0.91900
52	15.174	1.0192	0.56357	0.94344	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	14.785	0.99300	0.54910	0.91922	0.42200
67	14.660	0.98461	0.54446	0.91145	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	13.001	0.87321	0.48286	0.80833	0.50800
82	16.493	1.1285	0.62405	1.0447	0.58300
92	14.920	1.0021	0.55411	0.92760	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	14.475	0.97220	0.53760	0.89996	-1.0000
-112	14.385	0.96616	0.53426	0.89437	-1.0000
-122	14.385	0.96616	0.53426	0.89437	-1.0000
-127	14.665	0.98495	0.54465	0.91176	-1.0000
-137	14.650	0.98394	0.54409	0.91083	-1.0000
-142	14.460	0.97119	0.53704	0.89903	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	14.475	0.97220	0.53760	0.89996	0.39800
112	14.385	0.96616	0.53426	0.89437	0.43100
122	14.385	0.96616	0.53426	0.89437	0.46900
127	14.665	0.98495	0.54465	0.91176	0.44600
137	14.650	0.98394	0.54409	0.91083	0.52200
142	14.460	0.97119	0.53704	0.89903	0.58800
-152	14.936	1.0031	0.55467	0.92854	-1.0000
-157	14.929	1.0027	0.55440	0.92823	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	14.936	1.0031	0.55467	0.92854	-1.0000
-157	14.929	1.0027	0.55448	0.92823	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
167	14.920	1.0021	0.55411	0.92760	0.79300
172	14.915	1.0017	0.55392	0.92729	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
182	14.735	0.98964	0.54725	0.91611	0.79300
187	14.310	0.96113	0.53148	0.88971	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

TF-91 295.03   FLC 289.34   SIGMA LC 3.9153   FTAPE 2.7900   DSM 2.2882   CFG 0.0021273

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CANDFII   REC 10/25/79 00:36:50.886   FAC BX6X1   PGM C034   PDG 1470

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	13.899	0.93154	0.46317	0.73529	0.72200
37	15.037	1.0058	0.47851	0.79392	1.82000
47	15.407	1.0326	0.49125	0.81504	0.91900
52	15.641	1.0483	0.49873	0.82745	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.728	0.98708	0.46960	0.77913	0.42200
67	14.069	0.94291	0.44859	0.74427	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.696	0.85089	0.40481	0.67163	0.50800
82	17.114	1.1470	0.54568	0.90535	0.58300
92	14.953	1.0021	0.47676	0.79101	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.498	0.97102	0.46196	0.76645	-1.0000
-112	14.388	0.96433	0.45877	0.76117	-1.0000
-122	14.383	0.96399	0.45861	0.76090	-1.0000
-127	14.658	0.98239	0.46737	0.77543	-1.0000
-137	14.648	0.98172	0.46705	0.77490	-1.0000
-142	14.438	0.96767	0.46037	0.76381	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.498	0.97102	0.46196	0.76645	0.39800
112	14.388	0.96433	0.45877	0.76117	0.43100
122	14.383	0.96399	0.45861	0.76090	0.44900
127	14.658	0.98239	0.46737	0.77543	0.48600
137	14.648	0.98172	0.46705	0.77490	0.52200
142	14.438	0.96767	0.46037	0.76381	0.58800
-152	14.949	1.0018	0.47660	0.79079	-1.0000
-157	14.949	1.0018	0.47660	0.79079	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.958	1.0018	0.47660	0.79075	-1.0000
-157	14.949	1.0018	0.47660	0.79075	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.953	1.0021	0.47676	0.79101	0.79300
172	14.953	1.0021	0.47676	0.79101	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.803	0.99210	0.47199	0.78309	0.79300
187	14.393	0.96466	0.45893	0.76143	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

IF-01 434.40   FIC 429.36   SIGMA IF 4.0056   FTAPF 2.6839   DSW 2.3538   CFW 0.9321218

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFII   REC 10/25/79 00:37:44.460   FAC 8X6X1   PG= C034   PBG 1471

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	10.978	0.72916	0.29131	0.49857	0.72200
37	14.295	0.94481	0.37747	0.63306	0.82000
47	15.424	1.0339	0.41305	0.69276	0.91900
52	15.943	1.0700	0.42740	0.71606	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
52	15.244	1.0218	0.40923	0.68466	0.42200
67	12.402	0.83130	0.33212	0.55701	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	10.438	0.69968	0.27954	0.46882	0.50800
82	18.605	1.2471	0.49824	0.83562	0.58300
92	14.956	1.0024	0.40048	0.67165	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	14.525	0.97361	0.38897	0.65237	-1.0000
-112	14.450	0.96858	0.38697	0.64895	-1.0000
-122	14.460	0.96925	0.38723	0.64944	-1.0000
-127	14.739	0.98800	0.39472	0.66200	-1.0000
-137	14.734	0.98767	0.39459	0.66178	-1.0000
-142	14.599	0.97863	0.39098	0.65572	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	14.525	0.97361	0.38897	0.65236	0.39800
112	14.450	0.96858	0.38697	0.64895	0.43100
122	14.460	0.96925	0.38723	0.64944	0.44900
127	14.739	0.98800	0.39472	0.66200	0.48800
137	14.734	0.98767	0.39455	0.66178	0.52200
142	14.599	0.97863	0.39098	0.65572	0.58800
147	14.974	1.0037	0.40101	0.67255	-1.0000
157	14.964	1.0031	0.40074	0.67210	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	14.974	1.0037	0.40101	0.67255	-1.0000
-157	14.964	1.0031	0.40074	0.67210	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
167	14.964	1.0031	0.40074	0.67210	0.79300
172	14.959	1.0027	0.40061	0.67187	0.84400

>ADDITIONAL PRESSURE RATIOS , 40 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
182	14.804	0.99235	0.39646	0.66492	0.79300
187	14.405	0.96557	0.38576	0.64697	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
(F-D) 597.33   FIC 585.42   SIGMA IC 2.6362   FTAPE 2.3262   DSM 2.3797   CFM 0.0021209

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDE11   REC 10/25/79 00:39:00.213   FAC SRAR1   PGM CA94   RDG 1472

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	7.9260	0.47035	0.17046	0.28966	0.72200
37	11.973	0.80150	0.29047	0.49359	0.82000
47	15.309	1.0248	0.37141	0.63113	0.91900
52	16.233	1.0947	0.39310	0.66798	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	16.532	1.1067	0.40109	0.68157	0.42200
67	13.646	0.91352	0.33106	0.56257	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	9.8196	0.65736	0.23823	0.40482	0.50000
82	19.209	1.2859	0.46602	0.79191	0.58300
92	14.959	1.0014	0.36293	0.61672	2.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.520	0.97202	0.35233	0.59860	-1.0000
-112	14.450	0.96734	0.35057	0.59572	-1.0000
-122	14.470	0.96868	0.35105	0.59654	-1.0000
-127	14.740	0.98673	0.35760	0.60766	-1.0000
-137	14.765	0.98841	0.35820	0.60869	-1.0000
-142	14.705	0.98439	0.35675	0.60622	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.520	0.97202	0.35227	0.59860	0.39800
117	14.450	0.96734	0.35057	0.59572	0.43100
122	14.470	0.96868	0.35105	0.59654	0.46900
127	14.740	0.98673	0.35760	0.60766	0.48400
137	14.765	0.98841	0.35820	0.60869	0.52200
142	14.705	0.98439	0.35675	0.60622	0.58000
-152	14.969	1.0021	0.36317	0.61713	-1.0000
-157	14.969	1.0021	0.36317	0.61713	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.969	1.0021	0.36317	0.61713	-1.0000
-157	14.969	1.0021	0.36317	0.61713	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.979	1.0028	0.36341	0.61754	0.79300
172	14.979	1.0028	0.36341	0.61754	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.695	0.98372	0.35651	0.60581	0.79300
187	14.270	0.95531	0.34621	0.58831	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
TF=11.693.95   FIC 679.77   SIGMA IC 3.0632   FTAPF 2.7446   DSM 2.4306   CFM 3.022}151

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   PFC 10/25/79 00:40:25.300   FAC AV6VI   PGM C034   PNG 1473

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	9.1402	0.54381	0.17472	0.29817	0.72200
37	13.611	0.90927	0.29214	0.49855	0.82000
47	11.593	0.77446	0.24892	0.42463	0.91900
52	16.502	1.1024	0.35427	0.60446	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	18.719	1.2595	0.40179	0.68567	0.42200
67	15.543	1.0384	0.33362	0.56934	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	11.083	0.74042	0.23789	0.40597	3.50800
82	15.514	1.0367	0.33309	0.56843	0.58300
92	15.004	1.0024	0.32204	0.54959	0.67000

>ADDITIONAL PRESSURE RATIOS , FAREING SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.580	0.97399	0.31293	0.53404	-1.0000
-112	14.510	0.96932	0.31143	0.53148	-1.0000
-122	14.525	0.97032	0.31175	0.53202	-1.0000
-127	14.806	0.98901	0.31776	0.54227	-1.0000
-137	14.844	0.99168	0.31861	0.54373	-1.0000
-142	14.874	0.99368	0.31926	0.54483	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.580	0.97399	0.31293	0.53404	0.39800
112	14.510	0.96932	0.31143	0.53148	0.43100
122	14.525	0.97032	0.31175	0.53202	0.44900
127	14.806	0.98901	0.31776	0.54227	0.48600
137	14.844	0.99168	0.31861	0.54373	0.52200
142	14.874	0.99368	0.31926	0.54483	0.58800
-152	14.999	1.0020	0.32194	0.54960	-1.0000
-162	14.999	1.0020	0.32194	0.54960	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	14.999	1.0020	0.32194	0.54960	-1.0000
-157	14.999	1.0020	0.32194	0.54960	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	14.999	1.0020	0.32194	0.54960	0.79300
172	15.004	1.0024	0.32204	0.54959	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.645	0.97833	0.31433	0.53641	0.79300
187	14.180	0.94730	0.30436	0.51940	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

F5-01 827.44   FIG 815.90   SIGMA LC 4.2222   FTAPE 2.0972   DSW 2.4589   CFH 0.0021136

335

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   PEC 10/25/79 00:41:54.119   FAC 9X6X1   PGM C036   RDG 1474

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PL	PL/PTF	PL/PTP	X/DMAX
32	9.3385	0.61670	0.17068	0.29161	0.72230
37	16.473	1.0878	0.30108	0.51439	0.82000
47	13.573	0.89633	0.24808	0.42383	0.91900
52	16.942	1.1122	0.30783	0.52592	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	22.068	1.4573	0.40334	0.68909	0.42200
67	18.584	1.2273	0.33967	0.58031	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.019	0.85973	0.23795	0.40652	0.50800
82	18.260	1.2058	0.33374	0.57018	0.58300
92	15.145	1.0002	0.27682	0.47293	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.726	0.97248	0.26915	0.45983	-1.0000
-112	14.661	0.96820	0.26797	0.45781	-1.0000
-122	14.681	0.96951	0.26833	0.45843	-1.0000
-127	14.960	0.98797	0.27344	0.46716	-1.0000
-137	14.995	0.99028	0.27408	0.46825	-1.0000
-142	15.025	0.99226	0.27463	0.46919	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.726	0.97248	0.26915	0.45983	0.39800
112	14.661	0.96820	0.26797	0.45781	0.43100
122	14.681	0.96951	0.26833	0.45843	0.44900
127	14.960	0.98797	0.27344	0.46716	0.48600
137	14.995	0.99028	0.27409	0.46825	0.52200
142	15.025	0.99226	0.27463	0.46919	0.58800
-152	15.140	0.99984	0.27672	0.47277	-1.0000
-157	15.140	0.99984	0.27672	0.47277	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.140	0.99984	0.27672	0.47277	-1.0000
-157	15.140	0.99984	0.27672	0.47277	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.130	0.99918	0.27654	0.47246	0.79300
172	15.130	0.99918	0.27654	0.47246	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.681	0.99270	0.27198	0.46467	0.79300
187	14.461	0.95501	0.26432	0.45157	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 1049.8   FLC 1045.9   SIGMA LC 3.6832   FTAPF 2.3598   DSM 2.4319   CFM 0.0021153

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CANDEII   REC 10/25/79 00:43:13.303   FAC 9X6X1   PGM C034   PDG 1475

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	9.7335	0.64527	0.16241	0.27639	0.72200
37	17.416	1.1546	0.29059	0.49455	0.82000
47	15.039	0.99699	0.25093	0.42704	0.91900
52	16.937	1.1229	0.28259	0.49093	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	23.993	1.5943	0.39875	0.67862	0.42200
67	19.329	1.2814	0.32251	0.54896	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	14.250	0.94467	0.23776	0.40463	0.50800
82	20.043	1.3287	0.33442	0.56914	0.58300
92	15.129	1.0029	0.25243	0.42960	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.769	0.97911	0.24663	0.41939	-1.0000
-112	14.719	0.97580	0.24559	0.41797	-1.0000
-122	14.744	0.97745	0.24601	0.41868	-1.0000
-127	14.989	0.99368	0.25010	0.42563	-1.0000
-137	15.044	0.99732	0.25101	0.42719	-1.0000
-142	15.079	0.99964	0.25160	0.42818	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.769	0.97911	0.24643	0.41939	0.39800
112	14.719	0.97580	0.24559	0.41797	0.43100
122	14.744	0.97745	0.24601	0.41868	0.44900
127	14.989	0.99369	0.25010	0.42563	0.48600
137	15.044	0.99732	0.25101	0.42719	0.52200
142	15.079	0.99964	0.25160	0.42818	0.58800
-152	15.124	1.0026	0.25235	0.42946	-1.0000
-157	15.124	1.0026	0.25235	0.42946	-1.0000

>ADDITIONAL PRESSURE RATIOS , BAY NOZZLE PIAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.124	1.0026	0.25235	0.42946	-1.0000
-157	15.124	1.0026	0.25235	0.42946	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.124	1.0026	0.25235	0.42946	0.79300
172	15.129	1.0029	0.25243	0.42960	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.944	0.99070	0.24935	0.42435	0.79300
187	14.575	0.96620	0.24318	0.41385	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 1198.6   FIC 1194.2   SIGMA IC 2.6445   FTAPF 2.1461   DSM 2.3104   CFM 0.0021257

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   PEC 10/25/79 09:43:47.099   EAC RX6X1   PGM C036   PDG 1476

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	9.6896	0.64319	0.16204	0.27667	0.72200
37	17.332	1.1505	0.28586	0.49450	0.82000
47	14.950	0.99239	0.25002	0.42688	0.91900
52	16.938	1.1243	0.28326	0.48364	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	23.809	1.5805	0.39819	0.67985	0.42200
67	19.290	1.2798	0.32243	0.55051	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	14.291	0.94265	0.23749	0.40549	0.50800
82	19.984	1.3265	0.33421	0.57062	0.58300
92	15.100	1.0023	0.25252	0.43116	0.67900

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.740	0.97866	0.24651	0.42089	-1.0000
-112	14.685	0.97491	0.24559	0.41932	-1.0000
-122	14.720	0.97714	0.24618	0.42032	-1.0000
-127	14.970	0.99371	0.25035	0.42745	-1.0000
-137	15.015	0.99670	0.25110	0.42873	-1.0000
-142	15.055	0.99935	0.25177	0.42997	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.740	0.97866	0.24651	0.42089	0.39800
112	14.685	0.97491	0.24559	0.41932	0.43100
122	14.720	0.97714	0.24618	0.42032	0.44900
127	14.970	0.99371	0.25035	0.42745	0.48600
137	15.015	0.99670	0.25110	0.42873	0.52200
142	15.055	0.99935	0.25177	0.42997	0.58800
-152	15.100	1.0023	0.25252	0.43116	-1.0000
-157	15.105	1.0027	0.25261	0.43130	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.100	1.0023	0.25252	0.43116	-1.0000
-157	15.105	1.0027	0.25261	0.43130	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.105	1.0027	0.25261	0.43130	0.79300
172	15.110	1.0030	0.25269	0.43144	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.925	0.99073	0.24960	0.42616	0.79300
187	14.545	0.96553	0.24325	0.41533	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

TF-GJ 1104.4   FIC 1189.5   SIGMA IF 3.2666   FTAPF 2.6880   DFM 2.3015   CFM 0.0021264

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFIT   REC 10/25/79 00:46:01.975   FAC RX6X1   PGM C034   PPG 1477

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	9.4436	0.62192	0.17233	0.29495	0.72200
37	16.479	1.0856	0.30092	0.51486	0.82000
47	13.590	0.88937	0.24644	0.42179	0.91900
52	16.954	1.1103	0.30766	0.52657	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	22.146	1.4589	0.40427	0.69191	0.42200
67	18.663	1.2295	0.34069	0.58309	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	12.521	0.82482	0.22856	0.39118	0.50800
82	19.939	1.3115	0.36340	0.62196	0.58300
92	15.200	1.0013	0.27747	0.47488	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	14.795	0.97465	0.27008	0.46223	-1.0000
-112	14.735	0.97070	0.26898	0.46036	-1.0000
-122	14.750	0.97169	0.26925	0.46083	-1.0000
-127	15.025	0.98980	0.27427	0.46942	-1.0000
-137	15.060	0.99210	0.27491	0.47051	-1.0000
-142	15.075	0.99309	0.27518	0.47098	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	14.795	0.97465	0.27008	0.46223	0.39800
112	14.735	0.97070	0.26898	0.46036	0.43100
122	14.750	0.97169	0.26925	0.46083	0.44900
127	15.025	0.98980	0.27427	0.46942	0.48600
137	15.060	0.99210	0.27491	0.47051	0.52200
142	15.075	0.99309	0.27518	0.47098	0.58800
147	15.200	1.0013	0.27747	0.47488	-1.0000
152	15.200	1.0013	0.27747	0.47488	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	15.200	1.0013	0.27747	0.47488	-1.0000
-157	15.200	1.0013	0.27747	0.47488	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
167	15.205	1.0017	0.27756	0.47504	0.79300
172	15.205	1.0017	0.27756	0.47504	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
182	14.945	0.98453	0.27281	0.46692	0.79300
187	14.525	0.95687	0.26515	0.45380	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

| FG-01 1047.1 | FLC 1042.0 | SIGMA FC 3.2561 | FTARE 2.7148 | DSM 2.4368 | CFM 0.0021174 |

339

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFII   REC 10/25/79 00:47:42.025   FAC RV6X1   PGM F934   RDG 1478

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	8.1792	0.54123	0.17318	0.29630	0.72200
37	13.797	0.91295	0.29211	0.49980	0.82000
47	11.763	0.77838	0.24905	0.42613	0.91900
52	16.664	1.1027	0.35283	0.60368	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	18.917	1.2518	0.40053	0.68529	0.42200
67	15.700	1.0389	0.33241	0.56875	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	11.258	0.74498	0.23837	0.40784	0.50800
82	15.840	1.0482	0.33538	0.57382	0.59300
92	15.141	1.0019	0.32057	0.54848	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.741	0.97564	0.31211	0.53401	-1.0000
-112	14.691	0.97147	0.31084	0.53183	-1.0000
-122	14.691	0.97213	0.31105	0.53220	-1.0000
-127	14.956	0.98965	0.31665	0.54179	-1.0000
-137	14.986	0.99164	0.31729	0.54287	-1.0000
-162	15.016	0.99362	0.31792	0.54396	-1.0000

>ADDITIONAL PRESSURE RATIOS , ECPERGOV INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.741	0.97564	0.31211	0.53401	0.39800
112	14.691	0.97147	0.31084	0.53183	0.43100
122	14.691	0.97213	0.31105	0.53220	0.44900
127	14.956	0.98965	0.31665	0.54179	0.48600
137	14.986	0.99164	0.31729	0.54287	0.52200
142	15.016	0.99362	0.31792	0.54396	0.58800
-147	15.126	1.0009	0.32042	0.54746	-1.0000
-157	15.121	1.0006	0.32014	0.54776	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.126	1.0009	0.32074	0.54794	-1.0000
-157	15.121	1.0006	0.32014	0.54776	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.116	1.0002	0.32004	0.54758	0.79300
172	15.116	1.0002	0.32004	0.54758	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.751	0.97610	0.31232	0.53437	0.79300
187	14.311	0.94701	0.30301	0.51844	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

IF-01 834.09   FI7 828.92   SIGMA IC 4.0497   FTAPF 2.9474   DSM 2.3236   CFM 0.0021246

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDEII   REC 10/25/79 00:48:38.803   FAC RX6X1   PGM C034   RDG 1479

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	7.0720	0.46855	0.16964	0.28880	0.72200
37	12.348	0.79822	0.28839	0.49199	0.82000
47	15.447	1.0234	0.37052	0.63079	0.91900
52	16.356	1.0936	0.39234	0.66793	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	16.686	1.1055	0.40025	0.68140	0.42200
67	13.792	0.91378	0.33084	0.56323	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	9.7878	0.64847	0.23478	0.39970	0.50800
82	18.860	1.2495	0.45239	0.77017	0.58300
92	15.122	1.0019	0.36273	0.61752	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.712	0.97471	0.35290	0.60078	-1.0000
-112	14.637	0.96974	0.35110	0.59772	-1.0000
-122	14.657	0.97107	0.35158	0.59854	-1.0000
-127	14.922	0.98862	0.35793	0.60936	-1.0000
-137	14.942	0.98994	0.35841	0.61017	-1.0000
-142	14.877	0.98564	0.35685	0.60752	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.712	0.97471	0.35290	0.60078	0.39800
112	14.637	0.96974	0.35110	0.59772	0.43100
122	14.657	0.97107	0.35158	0.59854	0.44900
127	14.922	0.98862	0.35793	0.60936	0.48600
137	14.942	0.98994	0.35841	0.61017	0.52200
142	14.877	0.98564	0.35685	0.60752	0.58800
147	15.122	1.0019	0.36273	0.61752	-1.0000
152	15.127	1.0022	0.36289	0.61772	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.122	1.0019	0.36273	0.61752	-1.0000
-157	15.127	1.0022	0.36289	0.61772	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.122	1.0019	0.36273	0.61752	0.79300
172	15.117	1.0015	0.36261	0.61732	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.822	0.98200	0.35553	0.60527	0.79300
187	14.397	0.95385	0.34534	0.58792	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

TF-31 692.26   FIC 687.21   SIGMA IC 2.0581   FTARE 2.7582   DSM 2.2983   CFM 0.0921275

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFIT   REC 10/25/79 00:49:37.605   FAC RX6XI   PGM C034   PDG 1490

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.206	0.74187	0.29522	0.50183	0.72200
37	14.060	0.93080	0.37041	0.62963	0.82000
47	15.449	1.0228	0.40700	0.69184	0.91900
52	16.059	1.0631	0.42306	0.71914	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	15.224	1.0079	0.40108	0.68177	0.42200
67	12.446	0.82393	0.32788	0.55734	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	8.7163	0.57705	0.22963	0.39034	0.50800
82	21.789	1.4425	0.57404	0.97577	0.58300
92	15.144	1.0026	0.39897	0.67819	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.724	0.97480	0.38791	0.65939	-1.0000
-112	14.639	0.96918	0.38568	0.65559	-1.0000
-122	14.644	0.96951	0.38581	0.65581	-1.0000
-127	14.919	0.98770	0.39305	0.66812	-1.0000
-137	14.919	0.98770	0.39305	0.66812	-1.0000
-142	14.779	0.97844	0.38936	0.66185	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.724	0.97480	0.38791	0.65939	0.39800
112	14.639	0.96918	0.38568	0.65559	0.43100
122	14.644	0.96951	0.38581	0.65581	0.44900
127	14.919	0.98770	0.39305	0.66812	0.48600
137	14.919	0.98770	0.39305	0.66812	0.52200
142	14.779	0.97844	0.38936	0.66185	0.58900
-152	15.130	1.0022	0.39884	0.67704	-1.0000
-157	15.139	1.0023	0.39884	0.67796	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.130	1.0022	0.39884	0.67796	-1.0000
-157	15.139	1.0023	0.39884	0.67796	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.144	1.0026	0.39897	0.67819	0.79300
172	15.149	1.0029	0.39910	0.67841	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.974	0.99134	0.39450	0.67058	0.79300
187	14.569	0.96454	0.38383	0.65245	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 597.81   FLC 592.76   SIGMA LC 2.9412   FTAPF 2.6970   DSM 2.3523   CFM 0.0021221

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   REC 10/25/79 00:50:44.603   FAC 8X6X1   PGM C034   PRG 1491

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.306	0.93736	0.44354	0.74839	0.72200
37	15.270	1.0076	0.47677	0.80445	0.82000
47	15.655	1.0330	0.48879	0.82472	0.91900
52	15.882	1.0478	0.49581	0.83657	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.911	0.98384	0.46554	0.78550	0.42200
67	14.351	0.94692	0.44807	0.75602	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.697	0.83778	0.39643	0.66888	0.50800
82	17.863	1.1787	0.55774	0.94106	0.58300
92	15.190	1.0023	0.47428	0.80024	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.736	0.97230	0.46008	0.77629	-1.0000
-112	14.641	0.96604	0.45712	0.77129	-1.0000
-122	14.646	0.96637	0.45727	0.77155	-1.0000
-127	14.941	0.98582	0.46648	0.78708	-1.0000
-137	14.916	0.98417	0.46570	0.78577	-1.0000
-142	14.696	0.96967	0.45883	0.77418	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.736	0.97230	0.46008	0.77629	0.39800
112	14.641	0.96604	0.45712	0.77129	0.43100
122	14.646	0.96637	0.45727	0.77155	0.44900
127	14.941	0.98582	0.46648	0.78708	0.48600
137	14.916	0.98417	0.46570	0.78577	0.52200
142	14.696	0.96967	0.45883	0.77418	0.58800
-152	15.195	1.0026	0.47443	0.80051	-1.0000
-157	15.210	1.0030	0.47494	0.80077	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

VD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.195	1.0026	0.47443	0.80051	-1.0000
-157	15.210	1.0030	0.47454	0.80077	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.195	1.0026	0.47443	0.80051	0.79300
172	15.190	1.0023	0.47428	0.80024	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	15.056	0.99341	0.47007	0.79314	0.79300
187	14.641	0.96604	0.45712	0.77129	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
IF-D) 437.84   FLC 433.36   SIGMF IC 3.5553   FTAPF 2.4021   DSM 2.3752   CFM 0.3021202

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFIT   PFC 10/25/79 00:51:59.835   FAC RX6X1   PGM C036   PDG 14R2

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.851	0.98055	0.53949	0.91712	0.72200
37	15.143	1.0023	0.55147	0.93768	0.82000
47	15.310	1.0109	0.55615	0.94549	3.91900
52	15.390	1.0155	0.55873	0.94981	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.990	0.98979	0.54457	0.92575	0.42200
67	14.991	0.98253	0.54058	0.91897	2.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.077	0.86347	0.47508	0.80761	0.50900
82	16.893	1.1154	0.61370	1.0433	0.58300
92	15.185	1.0026	0.55165	0.93778	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.721	0.97198	0.53478	0.90910	-1.0000
-112	14.621	0.96538	0.53115	0.90293	-1.0000
-122	14.616	0.96505	0.53097	0.90262	-1.0000
-127	14.901	0.98385	0.54131	0.92020	-1.0000
-137	14.991	0.98253	0.54058	0.91897	-1.0000
-142	14.676	0.96901	0.53314	0.90632	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.721	0.97198	0.53478	0.90910	0.39800
112	14.621	0.96538	0.53115	0.90293	0.43100
122	14.616	0.96505	0.53097	0.90262	0.44900
127	14.901	0.98385	0.54131	0.92020	0.48600
137	14.991	0.98253	0.54058	0.91897	0.52200
142	14.676	0.96901	0.53314	0.90632	0.58800
152	15.140	1.0010	0.55054	0.93624	1.0000
157	15.165	1.0013	0.55092	0.93655	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.160	1.0010	0.55074	0.93624	-1.0000
-157	15.165	1.0013	0.55092	0.93655	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.165	1.0013	0.55092	0.93655	0.79300
172	15.165	1.0013	0.55092	0.93655	0.84600

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.365	0.98814	0.54367	0.92421	0.79300
187	14.541	0.96011	0.52824	0.89799	2.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 289.28   FIG 294.45   SIGMA IF 2.9193   FTARF 2.4537   DSM 2.3527   CFM 0.0021220

344

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFIL   REC 10/25/79 00:53:30.504   FAC RX6X1   PGM CO34   PRG 1483

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.329	0.94780	0.52363	0.75154	0.72200
37	15.323	1.0136	0.55907	0.80370	0.82000
47	15.663	1.0361	0.57239	0.82152	0.91909
52	15.859	1.0489	0.57951	0.83174	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

A D WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	15.098	0.99870	0.55175	0.79190	0.42200
67	14.573	0.96400	0.53258	0.76438	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.089	0.86582	0.47834	0.68653	0.50800
82	16.877	1.1164	0.61676	0.88520	0.58300
92	15.143	1.0017	0.55340	0.79426	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.708	0.97292	0.53751	0.77146	-1.0000
-112	14.618	0.96697	0.53422	0.76674	-1.0000
-122	14.673	0.96730	0.53660	0.76700	-1.0000
-127	14.893	0.98515	0.54427	0.78116	-1.0000
-137	14.883	0.98449	0.54390	0.78063	-1.0000
-142	14.698	0.97226	0.53714	0.77093	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.708	0.97292	0.53751	0.77146	0.39800
112	14.618	0.96697	0.53422	0.76674	0.43100
122	14.673	0.96730	0.53660	0.76700	0.44900
127	14.893	0.98515	0.54427	0.78116	0.48600
137	14.883	0.98449	0.54390	0.78063	0.52200
142	14.698	0.97226	0.53714	0.77093	0.58800
147	15.133	1.0013	0.55321	0.79400	1.0000
157	15.133	1.0010	0.55303	0.79374	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE PIPE

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.138	1.0013	0.55321	0.79400	-1.0000
-157	15.133	1.0010	0.55303	0.79374	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.133	1.0010	0.55303	0.79374	0.79300
172	15.138	1.0013	0.55321	0.79400	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	15.069	0.99672	0.55066	0.79033	0.79300
187	14.698	0.97226	0.53714	0.77093	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FG=D 252.10   FIC 347.02   SIGMA IC 3.7720   FTARF 2.7839   DSM 2.3028   CFM 0.9921262

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDEIT   REC 10/25/79 00:54:03.84A   FAC 9X6XI   PGM C036   PDG 1494

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.950	0.79049	0.37467	0.53410	0.72200
37	15.134	1.0014	0.47462	0.67659	0.82000
47	15.863	1.0493	0.49733	0.70896	0.91900
52	16.212	1.0724	0.50830	0.72459	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	15.488	1.0245	0.48559	0.69222	0.42200
67	13.379	0.88503	0.41948	0.59798	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.580	0.83214	0.39441	0.56224	0.50800
82	17.726	1.1726	0.55576	0.79225	0.58300
92	15.138	1.0014	0.47462	0.67659	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.688	0.97163	0.46052	0.65649	-1.0000
-112	14.599	0.96568	0.45770	0.65247	-1.0000
-122	14.599	0.96568	0.45770	0.65247	-1.0000
-127	14.873	0.98386	0.46637	0.66475	-1.0000
-137	14.858	0.98286	0.46585	0.66408	-1.0000
-142	14.624	0.96733	0.45849	0.65359	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.688	0.97163	0.46052	0.65649	0.39800
112	14.599	0.96568	0.45770	0.65247	0.43100
122	14.599	0.96568	0.45770	0.65247	0.46900
127	14.873	0.98386	0.46632	0.66475	0.48600
137	14.858	0.98286	0.46585	0.66408	0.52200
142	14.624	0.96733	0.45849	0.65359	0.58900
147	15.149	1.0020	0.47493	0.67703	-1.0000
152	15.153	1.0024	0.47509	0.67726	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.149	1.0020	0.47493	0.67703	-1.0000
-157	15.153	1.0024	0.47509	0.67726	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.149	1.0020	0.47493	0.67703	0.79300
172	15.149	1.0020	0.47493	0.67703	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	15.033	0.99463	0.47133	0.67190	0.79300
187	14.653	0.96931	0.45943	0.65493	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
IF-DI 492.95   FIC 497.95   SIGMA IC 3.3245   FTARF 2.6600   DSM 2.3348   CFM 0.0021235

346

MASS-1 FWIS   PRELIMINARY DATA   26/17/79   CANDEII   REC 10/25/79 20:56:26.787   EAC RX6X1   PCP C034   RDC 1485

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WDPD	PL	PL/PD	PL/PTE	PL/PTP	X/DMAX
32	6.8367	0.45119	0.17920	0.26200	0.72200
37	12.912	0.44551	0.33590	0.49284	0.82003
47	15.655	1.0232	0.41C67	0.60223	0.91906
52	16.752	1.1054	0.42027	0.64422	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WDPD	PL	PL/PD	PL/PTE	PL/PTP	X/DMAX
62	17.604	1.1618	0.46167	0.67719	0.42200
67	13.756	0.90745	0.36074	0.5291R	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WDPD	PL	PL/PD	PL/PTE	PL/PTP	X/DMAX
77	8.8773	0.58586	0.23281	0.34149	0.50600
A2	20.917	1.3834	0.54855	0.80463	0.58300
92	15.186	1.0022	0.39825	0.58416	0.67000

>ADDITIONAL PRESSURE RATIOS , FORE/BODY SHROUD

AVD WDPD	PL	PL/PD	PL/PTE	PL/PTP	X/DMAX
-107	14.761	0.97415	0.38711	0.56792	-1.0000
-112	14.681	0.96887	0.38501	0.56474	-1.0000
-122	14.681	0.96887	0.38501	0.56474	-1.0000
-127	14.951	0.98668	0.39209	0.57512	-1.0000
-137	14.951	0.97678	0.39209	0.57512	-1.0000
-142	14.801	0.97678	0.38816	0.56936	-1.0000

>ADDITIONAL PRESSURE RATIOS , FORE/BODY INLET

AVD WDPD	PL	PL/PD	PL/PTE	PL/PTP	X/DMAX
107	14.761	0.97415	0.38711	0.56782	0.35800
112	14.681	0.96887	0.38501	0.56474	0.43100
122	14.681	0.96887	0.38501	0.56474	0.44900
127	14.951	0.98668	0.39209	0.57512	0.48600
127	14.951	0.98668	0.39209	0.57512	0.52200
142	14.801	0.97678	0.38816	0.56936	0.58800

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE PLUG

AVD WDPD	PL	PL/PD	PL/PTE	PL/PTP	X/DMAX
-152	15.181	1.0019	0.39812	0.58397	-1.0000
-157	15.181	1.0019	0.39812	0.58397	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WDPD	PL	PL/PD	PL/PTE	PL/PTP	X/DMAX
167	15.191	1.0018	0.39812	0.58397	0.79300
172	15.176	1.0015	0.39798	0.58377	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WDPD	PL	PL/PD	PL/PTE	PL/PTP	X/DMAX
187	14.931	0.99536	0.39156	0.57435	0.79300
197	14.491	0.95634	0.38003	0.55744	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

IF-0) 649.59   FIG 644.79   SIGMA IE 4.1578   EVAPE 2.4134   DSP 2.3989   FEM 0.0021182

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CANOE11   REC 10/25/79 01:00:18.745   FAC RX6XL   PGM F034   PPG 1446

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	7.5697	0.49925	0.18086	0.26819	0.72200
37	11.211	0.73930	0.26784	0.39718	0.82000
47	15.055	0.99294	0.35969	0.53338	0.91900
52	16.669	1.0994	0.39826	0.59058	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	19.118	1.2609	0.45677	0.67734	0.42200
67	15.055	0.99294	0.35969	0.53338	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	9.8354	0.64869	0.23499	0.34846	0.50800
82	19.828	1.3077	0.47373	0.70248	0.58300
92	15.180	1.0012	0.36268	0.53781	3.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.755	0.97316	0.35253	0.52276	-1.0000
-112	14.695	0.96854	0.35085	0.52028	-1.0000
-122	14.695	0.96920	0.35109	0.52063	-1.0000
-127	14.980	0.98799	0.35799	0.53072	-1.0000
-137	15.000	0.98931	0.35838	0.53143	-1.0000
-142	14.940	0.98535	0.35695	0.52931	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.755	0.97316	0.35253	0.52276	0.39800
112	14.695	0.96854	0.35085	0.52028	0.43100
122	14.695	0.96920	0.35109	0.52063	0.44900
127	14.980	0.98799	0.35799	0.53072	0.48600
137	15.000	0.98931	0.35838	0.53143	0.52200
142	14.940	0.98535	0.35695	0.52931	0.58800
-152	15.180	1.0012	0.36268	0.53781	-1.0000
-157	15.185	1.0015	0.36289	0.53799	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.180	1.0012	0.36268	0.53781	-1.0000
-157	15.185	1.0015	0.36289	0.53799	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.180	1.0012	0.36268	0.53781	0.79300
172	15.180	1.0012	0.36268	0.53781	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.780	0.97480	0.35312	0.52364	0.79300
187	14.325	0.94480	0.34226	0.50753	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
(F-D) 744.78   FLC 741.61   SIGMA LC 4.0757   FTAPF 2.7628   DSM 2.4153   CFM 0.0021170

VAST-1 FWIS   PRELIMINARY DATA   06/13/79   CADDF11   PFC 10/25/79 01:01:29.662   FAF ANGT1   PGM C034   PAG 1647

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	8.9872	0.59317	0.19024	0.29130	0.72200
37	14.363	0.94799	0.30403	0.44971	0.82000
47	11.693	0.77110	0.24739	0.36560	2.91900
57	17.168	1.1318	0.36299	0.53680	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
52	21.696	1.4313	0.65905	0.67900	0.42200
67	17.168	1.1344	0.36382	0.53815	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	11.208	0.73975	0.23725	0.35092	0.50800
82	15.833	1.0650	0.33515	0.49573	0.58300
92	15.168	1.0011	0.32107	0.47491	0.47000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.768	0.97472	0.31261	0.46239	-1.0000
-112	14.708	0.97076	0.31134	0.46951	-1.0000
-122	14.723	0.97175	0.31165	0.46098	-1.0000
-127	14.998	0.98924	0.31726	0.46928	-1.0000
-137	15.318	0.99122	0.31790	0.47022	-1.0000
-152	15.053	0.99353	0.31864	0.47131	-1.0000

>ADDITIONAL PRESSURE RATIOS , PRIMARY INLET

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.768	0.97472	0.31761	0.46229	0.29800
112	14.708	0.97076	0.31134	0.46951	0.43100
122	14.723	0.97175	0.31165	0.46098	0.44900
177	14.998	0.98924	0.31726	0.46922	0.48600
142	15.053	0.99353	0.31864	0.47131	3.52200
					0.58800
					-1.0000
					-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-162	15.153	1.0001	0.32075	0.47644	-1.0000
-167	15.153	1.0001	0.32073	0.47644	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.168	0.99980	0.32065	0.47429	0.79300
172	15.168	0.99980	0.32065	0.47429	0.84600

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.743	2.97207	0.31228	0.44161	0.79300
187	14.283	2.94271	0.30234	0.44721	2.84400

>OPTION 5, MEASURED THRUST PARAMETERS
(F-D) 862.30   FLT 866.71   SIGMA 1C 2.8577   ETARF 1.7567   MKW 2.3740   EFW 0.002123R

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDETT   REC 10/25/79 01:03:47.284   FAC 9X6X1   PGS C036   RDG 1498

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	10.441	0.68940	0.19056	0.27667	0.72200
37	18.809	1.2419	0.34327	0.49839	0.82000
47	14.546	0.96040	0.26547	0.38543	0.91900
52	16.855	1.1129	0.30761	0.44661	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	25.796	1.7032	0.47079	0.68353	0.42200
67	20.948	1.3831	0.38231	0.55507	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.031	0.86040	0.23783	0.34529	0.50800
82	18.394	1.2145	0.33570	0.48740	0.58300
92	15.171	1.0017	0.27687	0.40198	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.796	0.97624	0.26985	0.39178	-1.0000
-112	14.731	0.97261	0.26884	0.39033	-1.0000
-122	14.741	0.97327	0.26903	0.39059	-1.0000
-127	15.006	0.99076	0.27386	0.39761	-1.0000
-137	15.051	0.99373	0.27468	0.39880	-1.0000
-142	15.081	0.99571	0.27523	0.39960	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.786	0.97624	0.26985	0.39178	0.39800
112	14.731	0.97261	0.26884	0.39033	0.43100
122	14.741	0.97327	0.26903	0.39059	0.44900
127	15.006	0.99076	0.27386	0.39761	0.48600
137	15.051	0.99373	0.27468	0.39880	0.52200
142	15.081	0.99571	0.27523	0.39960	0.55800
147	15.166	1.0013	0.27678	0.40185	-1.0000
-157	15.171	1.0017	0.27687	0.40198	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.166	1.0013	0.27678	0.40185	-1.0000
-157	15.171	1.0017	0.27687	0.40198	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.176	1.0020	0.27696	0.40211	0.79300
172	15.171	1.0017	0.27687	0.40198	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.996	0.99010	0.27368	0.39735	0.79300
187	14.606	0.96436	0.26656	0.38702	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

IF-01 1129.7   FIC 1125.1   SIGMA IC 2.7870   FTAPF 2.2465   DSM 2.3786   CFM 3.0321200

350

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   REC 10/25/.9 01:34:50.557   FAC RX6X1   PGM C034   #DG 1459

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	10.976	0.72345	0.18479	0.27066	0.72200
37	19.332	1.2743	0.32568	0.47674	0.82000
47	16.202	1.068C	0.27278	3.39655	0.91900
52	13.012	1.85765	0.21506	0.320P6	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	27.569	1.8172	0.46415	0.67984	0.42200
67	21.753	1.4338	0.36622	0.53641	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	14.117	0.93050	0.23767	0.34812	0.50800
82	19.957	1.3155	0.33600	0.49215	0.58300
92	15.212	1.0027	0.25611	0.37513	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

VD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.842	0.97830	0.24988	0.36600	-1.0000
-112	14.787	0.97468	0.24895	0.36465	-1.0000
-122	14.812	0.97637	0.24937	0.36526	-1.0000
-127	15.072	0.99347	0.25375	0.37168	-1.0000
-137	15.127	0.99709	0.25468	0.37303	-1.0000
-142	15.172	1.0001	0.25544	0.37414	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.842	0.97830	0.24988	0.36600	0.39800
112	14.787	0.97468	0.24895	0.36465	0.43100
122	14.812	0.97632	0.24937	0.36526	0.44900
127	15.072	0.99347	0.25375	0.37168	0.48600
132	15.127	0.99709	0.25469	0.37303	0.52200
142	15.172	1.0001	0.25544	0.37414	0.58800
152	15.207	1.0026	0.25603	0.37501	-1.0000
157	15.237	1.0024	0.25603	0.37501	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.207	1.0724	0.25603	0.37301	-1.0000
-157	15.237	1.0024	0.25603	0.37501	-1.0000

>ADDITIONAL PRESSURE RATIOS , 2 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.212	1.0027	0.25611	0.37513	0.79300
172	15.237	1.0024	0.25603	0.37501	0.84400

>ADDITIONAL PRESSURE RATIOS , 9 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.992	0.98810	0.25241	0.36970	0.79300
187	14.592	0.96116	0.24550	0.35959	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-0) 1256.8   FLC 1252.0   SIGMA LC 5.4858   FTAPE 2.3595   DSM 2.4144   CFM 0.0021172

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.345	0.72628	0.18521	0.27061	0.72200
37	19.371	1.2737	0.32482	0.47460	0.82000
47	16.256	1.0689	0.27258	0.39828	0.91900
52	13.091	0.86014	0.21934	0.32049	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	27.646	1.8179	0.46358	0.67735	0.42200
67	21.811	1.4342	0.36573	0.53438	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	14.221	0.93511	0.23846	0.34842	0.50800
82	20.106	1.3221	0.33714	0.49261	0.59300
92	15.244	1.0025	0.25565	0.37354	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.881	0.97851	0.24953	0.36459	-1.0000
-112	14.826	0.97490	0.24861	0.36325	-1.0000
-122	14.946	0.97621	0.24894	0.36374	-1.0000
-127	15.116	0.99397	0.25247	0.37035	-1.0000
-137	15.166	0.99725	0.25431	0.37158	-1.0000
-142	15.216	1.0005	0.25515	0.37280	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.881	0.97851	0.24953	0.36459	0.39800
112	14.826	0.97490	0.24861	0.36325	0.43100
122	14.946	0.97621	0.24894	0.36374	0.44900
127	15.116	0.99397	0.25247	0.37035	0.48600
137	15.166	0.99725	0.25431	0.37158	0.52200
142	15.216	1.0005	0.25515	0.37280	0.58800
147	15.241	1.1728	0.24712	0.37366	1.0000
157	15.246	1.0025	0.25565	0.37354	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.251	1.0028	0.25573	0.37366	-1.0000
-157	15.246	1.0025	0.25565	0.37354	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.241	1.0022	0.25556	0.37342	0.79300
172	15.246	1.0025	0.25565	0.37354	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	15.021	0.98772	0.25188	0.36803	0.79300
187	14.601	0.96010	0.24483	0.35773	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FE-DI 1269.3   FIC 1264.5   SIGMA IC 5.1514   FTAPF 2.6654   DSP 2.3803   CFM 0.9921192

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDFIT   REC 10/25/79 01:13:13.943   FAC RX6X1   PGM C034   PDG 1491

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	10.640	0.73106	0.19350	0.28101	0.72200
37	18.905	1.2456	0.34380	0.49930	0.82000
47	14.521	0.95674	0.26407	0.38350	0.91900
52	16.971	1.1116	0.30680	0.44556	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	25.929	1.7084	0.47154	0.68481	0.42200
67	20.855	1.3741	0.37926	0.55079	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.176	0.86812	0.23961	0.34798	0.50800
82	18.525	1.2206	0.33690	0.48926	0.58300
92	15.201	1.0015	0.27644	0.40146	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.811	0.97585	0.26934	0.39116	-1.0000
-112	14.756	0.97223	0.26834	0.38971	-1.0000
-122	14.776	0.97354	0.26871	0.39024	-1.0000
-127	15.041	0.99100	0.27353	0.39723	-1.0000
-137	15.091	0.99430	0.27444	0.39855	-1.0000
-142	15.126	0.99660	0.27507	0.39948	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.811	0.97585	0.26934	0.39116	0.39800
112	14.756	0.97223	0.26834	0.38971	0.43100
122	14.776	0.97354	0.26871	0.39024	0.44900
127	15.041	0.99100	0.27353	0.39723	0.48600
137	15.091	0.99430	0.27444	0.39855	0.52200
142	15.126	0.99660	0.27507	0.39948	0.58800
152	15.196	1.0012	0.27635	0.40133	1.0000
157	15.196	1.0012	0.27635	0.40133	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.196	1.0012	0.27635	0.40133	-1.0000
-157	15.196	1.0012	0.27635	0.40133	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.196	1.0012	0.27635	0.40133	0.79300
172	15.201	1.0015	0.27644	0.40146	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	15.026	0.99302	0.27325	0.39684	0.79300
187	14.661	0.96597	0.26662	0.38720	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

(F-0) 1136.6   FIC 1131.1   SIGMA IC 3.7347   FTARE 3.1152   DSM 2.3723   CFM 0.0021206

353

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	9.1781	0.60268	0.19299	0.28255	0.72200
37	14.441	0.94825	0.30365	0.44457	0.82000
47	11.935	0.78370	0.25096	0.36742	0.91900
52	17.296	1.1359	0.36369	0.53248	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
52	22.067	1.4490	0.46400	0.67934	0.42200
67	17.406	1.1430	0.36600	0.53586	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	11.360	0.74592	0.23886	0.34971	0.50800
82	15.991	1.0501	0.33325	0.49230	0.58300
92	15.256	1.0018	0.32079	0.46967	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	14.866	0.97616	0.31258	0.45766	-1.0000
-112	14.806	0.97222	0.31132	0.45581	-1.0000
-122	14.826	0.97354	0.31174	0.45642	-1.0000
-127	15.086	0.99061	0.31721	0.46443	-1.0000
-137	15.131	0.99357	0.31816	0.46582	-1.0000
-142	15.156	0.99521	0.31869	0.46659	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	14.866	0.97616	0.31259	0.45766	0.39800
112	14.806	0.97222	0.31132	0.45581	0.43100
122	14.826	0.97354	0.31174	0.45642	0.44900
127	15.086	0.99061	0.31721	0.46443	0.48600
137	15.131	0.99357	0.31816	0.46582	0.52200
142	15.156	0.99521	0.31869	0.46659	0.58800
-152	15.236	1.0005	0.32037	0.46905	-1.0000
-157	15.231	1.0001	0.32026	0.46890	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	15.236	1.0005	0.32037	0.46905	-1.0000
-157	15.231	1.0001	0.32026	0.46890	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
167	15.231	1.0001	0.32026	0.46890	0.79300
172	15.231	1.0001	0.32026	0.46890	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
182	14.841	0.97452	0.31236	0.45689	0.79300
187	14.371	0.94365	0.30218	0.44241	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

TF=01 934.52   FIG 895.60   SIGMA TC 2.6725   FTARE 7.5393   DSM 2.3725   CFM 0.0021205

354

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CANDELL   REC 10/25/79 01:15:27.092   FAC 8X6X1   PGM C034   RDG 1493

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	7.6535	0.50416	0.18269	0.26958	0.72200
37	11.292	0.74415	0.26965	0.39700	0.82000
47	14.997	0.98766	0.35790	0.52811	0.91900
52	16.522	1.0954	0.39693	0.58571	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER T.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	19.241	1.2680	0.45948	0.67801	0.42200
67	15.092	0.99458	0.36040	0.53191	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	9.8167	0.64692	0.23442	0.34591	0.50800
82	18.912	1.2463	0.45161	0.66638	0.58300
92	15.187	1.0008	0.36267	0.53515	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.777	0.97382	0.35288	0.52071	-1.0000
-112	14.707	0.96921	0.35121	0.51824	-1.0000
-122	14.712	0.96954	0.35133	0.51842	-1.0000
-127	14.982	0.98733	0.35778	0.52793	-1.0000
-137	14.997	0.98832	0.35813	0.52846	-1.0000
-142	14.952	0.98535	0.35706	0.52687	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.777	0.97382	0.35288	0.52071	0.39800
112	14.707	0.96921	0.35121	0.51824	0.43100
122	14.712	0.96954	0.35133	0.51842	0.44900
127	14.982	0.98733	0.35778	0.52793	0.48600
137	14.997	0.98832	0.35813	0.52846	0.52200
142	14.952	0.98535	0.35706	0.52687	0.58800
152	15.192	1.0005	0.36255	0.53498	-1.0000
157	15.172	0.99985	0.36231	0.53462	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.192	1.0005	0.36255	0.53498	-1.0000
-157	15.172	0.99985	0.36231	0.53462	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.192	1.0005	0.36255	0.53498	0.79300
172	15.187	1.0008	0.36267	0.53515	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.767	0.97316	0.35264	0.52035	0.79300
187	14.312	0.94318	0.34178	0.50432	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FG-D1 750.58   FIC 746.12   SIGMA LC 3.4301   FTAPF 2.1532   DSM 2.3091   CFM 0.0021260

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   REC 10/25/79 01:16:20.671   FAC 8X6X1   PGM C034   RDG 1494

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	6.9574	0.45276	0.18013	0.26266	0.72200
37	12.761	0.84254	0.33521	0.48878	0.82000
47	15.606	1.0304	0.40998	0.59776	0.91900
52	16.726	1.1044	0.43938	0.64066	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	17.651	1.1654	0.46367	0.67609	0.42200
67	13.736	0.90693	0.36083	0.52613	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	8.7090	0.57502	0.22877	0.33358	0.50800
82	21.681	1.4315	0.56953	0.83044	0.58300
92	15.166	1.0014	0.39840	0.58091	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.751	0.97395	0.38750	0.56501	-1.0000
-112	14.671	0.96867	0.38539	0.56195	-1.0000
-122	14.671	0.96867	0.38539	0.56195	-1.0000
-127	14.936	0.98617	0.39236	0.57210	-1.0000
-137	14.936	0.98617	0.39236	0.57210	-1.0000
-142	14.901	0.97726	0.38881	0.56692	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.751	0.97395	0.38750	0.56501	0.39800
112	14.671	0.96867	0.38539	0.56195	0.43100
122	14.671	0.96867	0.38539	0.56195	0.44900
127	14.936	0.98617	0.39236	0.57210	0.48600
137	14.936	0.98617	0.39236	0.57210	0.52200
142	14.901	0.97726	0.38881	0.56692	0.58800
152	15.174	1.0020	0.39868	0.58129	-1.0000
157	15.174	1.0020	0.39868	0.58129	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.176	1.0020	0.39866	0.58129	-1.0000
-157	15.176	1.0020	0.39866	0.58129	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.171	1.0017	0.39853	0.58110	0.79300
172	15.156	1.0007	0.39813	0.58052	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.891	0.98320	0.39117	0.57037	0.79300
187	14.456	0.95467	0.37975	0.55371	0.84400

SECTION 5 , MEASURED THRUST PARAMETERS

(F-D) 649.82   FLC 644.96   SIGMA IC 3.6496   FTARF 2.5718   DSM 2.2868   CFM 0.0021280

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   REC 10/25/79 01:17:17.506   FAC 9X6X1   PGM C034   RDG 1495

>ADDITIONAL PRESSURE RATIOS , PPIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.138	0.79935	0.38052	0.54585	0.72203
37	15.223	1.0025	0.47724	0.68457	0.82003
47	15.918	1.0483	0.49902	0.71582	0.91903
52	16.263	1.0710	0.50593	0.73134	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	15.473	1.0190	0.38507	0.69582	0.42200
67	13.458	0.88628	0.42191	0.60521	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.673	0.93458	0.39730	0.56991	0.??00
87	17.753	1.1691	0.55653	0.79832	0.58300
92	15.203	1.0012	0.47661	0.68368	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.763	0.97222	0.46282	0.66389	-1.0000
-112	14.663	0.96563	0.45968	0.65940	-1.0000
-122	14.658	0.96530	0.45953	0.65917	-1.0000
-127	14.933	0.98341	0.46815	0.67154	-1.0000
-137	14.913	0.98209	0.46752	0.67064	-1.0000
-142	14.683	0.96695	0.46031	0.66029	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.763	0.97222	0.46282	0.66389	0.39800
112	14.663	0.96563	0.45968	0.65940	0.43100
122	14.658	0.96530	0.45953	0.65917	0.44900
127	14.933	0.98341	0.46815	0.67154	0.48600
137	14.913	0.98209	0.46752	0.67064	0.52200
142	14.683	0.96695	0.46031	0.66029	0.58800
147	15.213	1.0018	0.47692	0.68413	-1.0000
152	15.213	1.0018	0.47692	0.68413	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.213	1.0018	0.47692	0.68413	-1.0000
-152	15.213	1.0018	0.47692	0.68413	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.203	1.0012	0.47661	0.68368	0.79300
172	15.203	1.0012	0.47661	0.68368	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	15.093	0.99329	0.47285	0.67828	0.79300
187	14.733	0.96926	0.46094	0.66110	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

| F-DJ 490.82 | FEC 485.78 | SIGMA IC 3.3927 | FTAPE 2.7131 | DSM 2.3158 | CFM 0.0021254 |

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   REC 10/25/79 01:18:31.511   FAC RX6X1   PGM C034   PDG 1496

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.514	0.95253	0.52704	0.76322	0.72200
37	15.459	1.0145	0.56136	0.81291	0.82000
47	15.774	1.0352	0.57279	0.82947	0.91900
52	15.964	1.0477	0.57969	0.83946	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	15.209	0.99814	0.55228	0.79976	0.42200
67	14.739	0.96730	0.53521	0.77505	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.204	0.86656	0.47948	0.69433	0.50800
82	17.029	1.1176	0.61835	0.89545	0.58300
92	15.259	1.0014	0.55409	0.80239	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.839	0.97386	0.53884	0.78031	-1.0000
-112	14.759	0.96861	0.53594	0.77610	-1.0000
-122	14.769	0.96927	0.53630	0.77663	-1.0000
-127	15.029	0.98633	0.54574	0.79030	-1.0000
-137	15.024	0.98600	0.54556	0.79003	-1.0000
-142	14.844	0.97419	0.53903	0.78057	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.839	0.97386	0.53884	0.78031	0.35800
112	14.759	0.96861	0.53594	0.77610	0.43100
122	14.769	0.96927	0.53630	0.77663	0.44900
127	15.029	0.98633	0.54574	0.79030	0.48600
137	15.024	0.98600	0.54556	0.79003	0.52200
142	14.844	0.97419	0.53903	0.78057	0.58800
-152	15.264	1.0017	0.55428	0.80265	-1.0000
-157	15.264	1.0017	0.55428	0.80265	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.264	1.0017	0.55428	0.80265	-1.0000
-157	15.264	1.0017	0.55428	0.80265	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
147	15.269	1.0021	0.55446	0.80292	0.79300
172	15.264	1.0017	0.55428	0.80265	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	15.194	0.99716	0.55173	0.79897	0.79300
187	14.824	0.97288	0.53820	0.77952	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
IF-D) 254.50   FIC 349.55   SIGMA IC 3.5549   FTAPF 2.5757   DSM 2.3779   CFM 0.2021292

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDEII   REC 10/25/79 01:19:46.747   FAC RX5X1   PGM C034   PDG 1497

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.464	0.95172	0.52477	0.76147	0.72200
37	15.409	1.0139	0.55905	0.81171	0.82000
47	15.729	1.0349	0.57066	0.82806	0.91900
52	15.919	1.0474	0.57755	0.83806	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	15.169	0.99810	0.55034	0.79858	0.42200
67	14.694	0.96685	0.53311	0.77358	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.145	0.86487	0.47688	0.69198	0.50800
82	16.974	1.1168	0.61582	0.89358	0.58300
92	15.229	1.0020	0.55252	0.80174	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.804	0.97409	0.53710	0.77937	-1.0000
-112	14.714	0.96817	0.53384	0.77463	-1.0000
-122	14.724	0.96883	0.53420	0.77516	-1.0000
-127	14.994	0.98659	0.54403	0.78937	-1.0000
-137	14.979	0.98560	0.54345	0.78858	-1.0000
-142	14.799	0.97376	0.53692	0.77910	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.804	0.97409	0.53710	0.77937	0.39800
112	14.714	0.96817	0.53384	0.77463	0.43100
122	14.724	0.96883	0.53420	0.77516	0.44900
127	14.994	0.98659	0.54400	0.78937	0.48600
137	14.979	0.98560	0.54345	0.78858	0.52200
142	14.799	0.97376	0.53692	0.77910	0.58800
-152	15.234	1.0024	0.55270	0.80200	-1.0000
-157	15.229	1.0020	0.55252	0.80174	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.234	1.0024	0.55270	0.80200	-1.0000
-157	15.229	1.0020	0.55252	0.80174	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.234	1.0024	0.55270	0.80200	0.79300
172	15.239	1.0027	0.55283	0.80226	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	15.159	0.99744	0.54998	0.79805	0.79300
187	14.799	0.97310	0.53656	0.77858	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

IF-D) 252.78   FIC 247.52   SIGMA IC 3.2947   FTARE 2.8410   DSM 2.3271   CFM 2.3021245

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   REC 10/25/79 01:21:12.569   FAC 9XAX1   PGM C034   RDG 1498

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.873	0.99113	0.54048	0.91746	0.72200
37	15.188	1.0019	0.55103	0.93689	0.82000
47	15.315	1.0105	0.55665	0.94491	0.91900
52	15.395	1.0154	0.55939	0.94954	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	14.995	0.98939	0.54502	0.92517	0.42200
67	14.888	0.98212	0.54102	0.91838	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.067	0.86204	0.47488	0.80610	0.50800
82	16.863	1.1124	0.61280	1.0402	0.58300
92	15.193	1.0022	0.55211	0.93720	0.67000

>ADDITIONAL PRESSURE RATIOS , FOREBODY SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.758	0.97355	0.53630	0.91036	-1.0000
-112	14.693	0.96860	0.53357	0.90574	-1.0000
-122	14.673	0.96704	0.53321	0.90512	-1.0000
-127	14.938	0.99542	0.54284	0.92147	-1.0000
-137	14.918	0.99410	0.54211	0.92023	-1.0000
-142	14.718	0.97091	0.53485	0.90790	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.758	0.97355	0.53630	0.91036	0.39800
112	14.693	0.96860	0.53357	0.90574	0.43100
122	14.673	0.96704	0.53321	0.90512	0.44900
127	14.938	0.99542	0.54284	0.92147	0.48600
137	14.918	0.99410	0.54211	0.92023	0.52200
142	14.718	0.97091	0.53485	0.90790	0.58800
-147	15.193	1.0018	0.55143	0.93604	-1.0000
-157	15.188	1.0019	0.55143	0.93604	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.189	1.0016	0.55175	0.93658	-1.0000
-157	15.188	1.0019	0.55103	0.93689	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.188	1.0019	0.55103	0.93689	0.79300
172	15.193	1.0022	0.55211	0.93720	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
192	14.978	0.98806	0.54430	0.92394	0.79300
197	14.553	0.96002	0.52885	0.89772	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(F-D) 300.29   FIC 295.61   SIGMA IC 3.3725   FTARE 2.3396   DSM 2.2712   CFM 0.0021203

NOZZLE TYPE	P&W BASE EJECTOR NOZZLE (MODEL C)
FLIGHT CONDITIONS	TAKEOFF
NOZZLE CONFIGURATION	C3
PRIMARY-NOZZLE PLUG	SPLIT PLUG (EXTENDED)
FLOW SPLITTER	ISENTROPIC SPLITTER
FAN NOZZLE	SHORT FLAP
CLAMSHELL POSITION	21 DEG
EJECTOR INLET OPENING	MIDWAY

RDG	MO	PTF/PTP	PTF/PO	PTP/PO	OMEGA	PTS/PTF	COF	COP	CF1	ETA1	ETA1.INT	CFP1	CFP2	F9
1499	0.366	1.70	1.82	1.07	0.000	0.547	0.963	0.715	0.8862	0.8862	0.8897	0.8897	0.8895	******
1500	0.369	1.70	2.11	1.24	0.000	0.475	0.966	0.842	0.8946	0.8586	0.9004	0.9004	0.9028	******
1501	0.363	1.70	2.51	1.48	0.000	0.399	0.966	0.939	0.8793	0.8793	0.8805	0.8835	0.8835	******
1502	0.362	1.70	2.76	1.63	0.000	0.364	0.967	0.947	0.8737	0.8737	0.8747	0.8747	0.8776	******
1503	0.362	1.70	3.11	1.83	0.000	0.324	0.972	0.945	0.8659	0.8659	0.8667	0.8667	0.8694	******
1504	0.367	1.70	3.??	2.13	0.000	0.281	0.971	0.926	0.8951	0.8951	0.8958	0.8958	0.8979	******
1505	0.362	1.73	2.	2.29	0.000	0.258	0.972	0.948	0.9030	0.9030	0.9036	0.9036	0.9056	******
1506	0.361	1.71	3.45	2.33	0.000	0.256	0.971	0.952	0.9015	0.9015	0.9021	0.9021	0.9040	******
1507	0.366	1.71	3.63	2.12	0.000	0.280	0.968	0.924	0.8971	0.8971	0.8978	0.8978	0.8999	******
1508	0.366	1.71	3.10	1.82	0.000	0.325	0.970	0.945	0.8656	0.8656	0.8665	0.8665	0.8692	******
1509	0.359	1.71	2.77	1.62	0.000	0.363	0.967	0.948	0.8725	0.8725	0.8735	0.8735	0.8766	******
1510	0.361	1.70	2.51	1.48	0.000	0.400	0.967	0.943	0.8817	0.8817	0.8829	0.8829	0.8859	******
1511	0.365	1.69	2.11	1.25	0.000	0.475	0.965	0.845	0.9014	0.9014	0.9031	0.9031	0.9056	******
1512	0.366	1.70	1.82	1.07	0.000	0.546	0.965	0.721	0.8920	0.8920	0.8945	0.8945	0.8951	******
1513	0.357	1.45	1.81	1.25	0.000	0.552	0.965	0.867	0.8973	0.8973	0.8993	0.8993	0.9023	******
1514	0.363	1.43	2.11	1.47	0.000	0.477	0.967	0.935	0.9051	0.9051	0.9066	0.9066	0.9102	******
1515	0.366	1.46	2.52	1.73	0.000	0.399	0.968	0.979	0.8878	0.8878	0.8890	0.8890	0.8924	******
1516	0.361	1.47	2.76	1.87	0.000	0.365	0.967	0.878	0.8803	0.8803	0.8812	0.8812	0.8843	******
1517	0.359	1.47	3.12	2.12	0.000	0.325	0.969	0.979	0.8705	0.8705	0.8713	0.8713	0.8739	******
1518	0.353	1.46	3.53	2.42	0.000	0.288	0.969	0.967	0.8931	0.8931	0.8938	0.8938	0.8960	******
1519	0.362	1.46	3.91	2.67	0.000	0.262	0.971	0.966	0.9026	0.9026	0.9032	0.9032	0.9052	******
1520	0.362	1.47	3.95	2.69	0.000	0.260	0.970	0.968	0.9014	0.9014	0.9019	0.9019	0.9039	******
1521	0.359	1.45	3.61	2.49	0.000	0.292	0.968	0.958	0.9012	0.9012	0.9019	0.9019	0.9040	******
1522	0.363	1.47	3.12	2.12	0.000	0.325	0.969	0.979	0.8711	0.8711	0.8719	0.8719	0.8745	******
1523	0.364	1.47	2.77	1.88	0.000	0.365	0.969	0.978	0.8787	0.8787	0.8797	0.8797	0.8827	******
1524	0.364	1.46	2.52	1.72	0.000	0.400	0.968	0.978	0.8865	0.8865	0.8876	0.8876	0.8910	******
1525	0.361	1.44	2.11	1.47	0.000	0.476	0.968	0.934	0.9074	0.9074	0.9089	0.9089	0.9125	******
1526	0.359	1.45	1.82	1.25	0.000	0.551	0.965	0.871	0.9016	0.9016	0.9036	0.9036	0.9065	******
1527	0.353	1.45	1.81	1.25	0.000	0.552	0.965	0.870	0.9038	0.9038	0.9058	0.9058	0.9088	******

361

DATA-ELEMENTS   PRELIMINARY DATA   06/13/79   CARDETT   DEC 10/25/79 02:11:49.27   FAC RK6E1   PGM C036   PPG 2699

>ADDITIONAL PRESSURE RATIOS , PRIMARY DUCT

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
22	15.529	1.0278	0.56404	0.56142	3.72200
27	15.659	1.0364	0.56877	0.56947	3.87000
47	15.70?	1.0397	0.57058	0.07256	3.91900
5?	15.724	1.0607	0.5711?	0.07369	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	15.589	1.0318	0.56622	0.56514	0.42200
67	15.524	1.0275	0.56296	0.56111	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.549	0.89677	0.49213	0.83883	0.50800
9?	17.364	1.1493	0.63069	1.0750	0.54303
92	15.159	1.0033	0.55061	0.93851	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.739	0.97554	0.53535	0.91251	-1.0000
-112	14.675	0.97125	0.53299	0.90849	-1.0000
-122	14.699	0.9728?	0.53390	0.91004	-1.0000
-127	14.964	0.99043	0.54352	0.92644	-1.0000
-137	14.978	0.99143	0.54407	0.92737	-1.0000
-142	14.899	0.98613	0.54116	0.92247	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.739	0.97554	0.53535	0.91251	0.39800
112	14.674	0.97124	0.53290	0.90840	0.43100
1??	14.699	0.97286	0.53390	0.91004	0.44000
127	14.964	0.99043	0.54352	0.92644	0.48600
137	14.979	0.99143	0.54407	0.92737	0.52200
142	14.969	0.98613	0.54116	0.92247	0.58809
15?	15.144	1.0022	0.55004	0.93759	1.0000
15?	15.144	1.0022	0.55004	0.93759	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.144	1.0023	0.55006	0.93759	-1.0000
-157	15.144	1.0023	0.55006	0.93759	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.134	1.0017	0.54970	0.93697	0.79300
172	15.139	1.0020	0.54989	0.93772	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
187	14.154	0.93682	0.51412	2.87620	0.79300
192	13.838	0.91308	0.50157	0.85603	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FF(-)) 206.31   FLF 282.91   SIGMA IF 2.7797   STARF 2.6978   DFM 0.202176

FFM 0.202176   DSM 2.4956

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CARDETI   REC 10/25/79 02:12:48.539   FAC 3X6X1   PGM C034   PDG 1500

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	16.338	1.0585	0.50266	0.85341	0.72200
37	16.582	1.0944	0.51973	0.88240	3.82000
47	16.697	1.1020	0.52334	0.88851	0.91900
52	16.657	1.0994	0.52208	0.88625	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	16.412	1.0832	0.51441	0.87336	0.42200
67	16.163	1.0667	0.50658	0.86006	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.489	0.89023	0.42277	0.71777	0.50800
82	18.321	1.2092	0.57424	0.97406	0.58300
92	15.169	1.0011	0.47541	0.80714	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.808	0.97731	0.46413	0.78700	-1.0000
-112	14.748	0.97336	0.46225	0.78480	-1.0000
-122	14.773	0.97530	0.46303	0.78613	-1.0000
-127	15.043	0.99282	0.47149	0.80049	-1.0000
-137	15.078	0.99513	0.47259	0.80235	-1.0000
-142	15.023	0.99150	0.47086	0.79943	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.808	0.97731	0.46413	0.78700	0.39800
112	14.748	0.97336	0.46225	0.78480	0.43100
122	14.773	0.97530	0.46303	0.78613	0.44500
127	15.043	0.99282	0.47149	0.80049	0.48600
137	15.078	0.99513	0.47259	0.80235	0.52200
142	15.023	0.99150	0.47086	0.79943	0.58800
-152	15.179	1.0017	0.47572	0.80767	-1.0000
-157	15.173	1.0014	0.47556	0.80740	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.179	1.0017	0.47572	0.80767	-1.0000
-157	15.173	1.0014	0.47556	0.80740	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.193	1.0021	0.47588	0.80794	0.79300
172	15.183	1.0024	0.47603	0.80820	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.979	0.92256	0.43812	0.74384	0.79300
187	13.644	0.90045	0.42763	0.72602	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

(F-D) 409.16   FLC 403.01   SIGMA IC 4.1922   FTARE 2.8103   DSM 2.6613   CEM 2.0021146

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTE	PL/PTP	X/DMAX
32	16.099	1.0659	0.42447	0.72052	0.72200
37	17.483	1.1708	0.44423	0.79147	0.82000
47	17.988	1.1613	0.47427	0.80506	0.91900
52	17.903	1.1854	0.47703	0.80126	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTE	PL/PTP	X/DMAX
62	16.544	1.1152	0.44410	0.75385	0.42200
67	15.745	1.0424	0.41511	0.70464	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTE	PL/PTP	X/DMAX
77	8.8062	2.58305	0.23218	0.39412	0.50800
82	21.641	1.4329	0.57058	0.96854	0.58300
92	15.135	1.3021	0.39904	0.67236	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTE	PL/PTP	X/DMAX
-107	15.025	0.99479	0.39614	0.67244	-1.0000
-112	15.115		0.39851	0.67664	-1.0000
-122	15.165		0.39683	0.67870	-1.0000
-127	15.125	1.0047	0.40009	0.67915	-1.0000
-137	15.130	1.0017	0.39891	0.67915	-1.0000
-1??	15.199	0.99974	0.39812	0.67579	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTE	PL/PTP	X/DMAX
107	15.025	0.99478	0.39614	0.67244	0.39800
117	15.115	1.0007	0.39851	0.67664	0.43100
122	15.165	1.0040	0.39993	0.67870	0.44900
127	15.125	1.0047	0.40009	0.67915	0.58600
137	15.130	1.0017	0.39891	0.67713	0.52200
147	15.100	0.99974	0.39812	0.67579	0.58800

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTE	PL/PTP	X/DMAX
-152	15.125	1.0015	0.39828	0.67691	-1.0000
-157	15.125	1.0014	0.39878	0.67679	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTE	PL/PTP	X/DMAX
167	15.130	1.0017	0.39891	0.67713	0.79300
177	15.125	1.0014	0.39878	0.67691	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTE	PL/PTP	X/DMAX
187	13.005	2.92662	0.34900	0.62634	0.79300
197	12.915	2.97132	0.26680	0.62278	0.84400

SECTION 5 , MEASURED THRUST PARAMETERS
... SEC-81   SIGMA IF 2.2299   FTAPF 1.9449   DSM 2.3625   CFM 1.0021711

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   REC 10/25/79 02:14:14.835   FAC 9X6X1   PGM C034   PDG 1502

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVG WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
32	16.427	1.0893	0.39400	0.67001	0.72200
37	18.625	1.2350	0.44674	0.75968	0.82000
47	18.973	1.2579	0.45591	0.77375	0.91900
52	18.800	1.2466	0.45093	0.76682	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVG WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
62	17.736	1.1761	0.42540	0.72341	0.42200
67	16.097	1.0674	0.38609	0.65656	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVG WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
77	9.8693	0.65443	0.23672	0.40255	0.50800
82	21.423	1.4206	0.51385	0.87381	0.58300
92	15.998	1.0011	0.36212	0.61580	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVG WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-107	15.358	0.99847	0.36116	0.61417	-1.0000
-112	15.158	1.0051	0.36356	0.61824	-1.0000
-122	15.178	1.0064	0.36404	0.61906	-1.0000
-127	15.143	1.0041	0.36320	0.61763	-1.0000
-137	15.358	0.99847	0.36116	0.61417	-1.0000
-142	15.033	0.99681	0.36056	0.61315	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVG WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
107	15.058	0.99847	0.36116	0.61417	0.39800
112	15.158	1.0051	0.36356	0.61824	0.43100
122	15.178	1.0064	0.36404	0.61906	0.44900
127	15.143	1.0041	0.36320	0.61763	0.48600
137	15.058	0.99847	0.36116	0.61417	0.52200
142	15.033	0.99681	0.36056	0.61315	0.58800
-152	15.118	1.0024	0.36260	0.61661	-1.0000
-152	15.113	1.0021	0.36248	0.61641	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVG WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-152	15.118	1.0024	0.36260	0.61661	-1.0000
-152	15.113	1.0021	0.36248	0.61641	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVG WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
167	15.109	1.0018	0.36236	0.61620	0.79300
172	15.109	1.0018	0.36236	0.61620	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVG WORD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
182	14.018	0.92954	0.33622	0.57177	0.79300
187	13.969	0.92623	0.33503	0.56973	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

FI-DI 657.33   FIC 651.94   SIGMA FC 3.2652   FTAPE 2.8468   DSM 2.3470   CFM 0.0021224

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   REC 10/25/79 02:15:43.826   FAC 8X6X1   PGM C034   PAG 1503

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	17.493	1.1566	0.37169	0.63238	0.72200
37	23.399	1.3490	0.43351	0.73757	0.82000
47	20.704	1.3692	0.43599	0.74860	0.91900
52	23.299	1.3417	0.43119	0.73360	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	19.749	1.3060	0.41970	0.71408	0.42200
67	17.945	1.1801	0.37923	0.64521	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	11.270	0.74526	0.23950	0.40747	0.50800
82	15.825	1.0472	0.3652	0.57254	0.58300
92	15.130	1.0006	0.32153	0.54705	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	15.165	1.0029	0.32228	0.54832	-1.0000
-112	15.255	1.0088	0.32419	0.55157	-1.0000
-122	15.255	1.0088	0.32419	0.55157	-1.0000
-127	15.190	1.0039	0.32260	0.54886	-1.0000
-137	15.070	0.99658	0.32026	0.54489	-1.0000
-142	15.120	0.99989	0.32132	0.54669	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	15.165	1.0029	0.32228	0.54832	0.39800
112	15.255	1.0088	0.32419	0.55157	0.43100
122	15.255	1.0088	0.32419	0.55157	0.44900
127	15.190	1.0039	0.32260	0.54886	0.48600
137	15.070	0.99658	0.32026	0.54489	0.52200
142	15.120	0.99989	0.32132	0.54669	0.58800
-152	15.130	1.0006	0.32153	0.54705	-1.0000
-157	15.130	1.0006	0.32153	0.54705	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.130	1.0006	0.32153	0.54705	-1.0000
-157	15.130	1.0006	0.32153	0.54705	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.130	1.0006	0.32153	0.54705	0.79300
177	15.145	1.0015	0.32195	0.54760	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.105	0.93277	0.29975	0.50999	0.79300
187	14.090	0.93178	0.29943	0.50945	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

(F-D) 785.30   FIG 780.54   SIGMA IG 3.6598   FTAPF 2.4068   DSM 2.3543   CFM 2.9921216

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
32	19.257	1.2744	0.35212	0.59963	0.72200
37	22.052	1.4593	0.40322	0.68665	0.82000
47	22.967	1.5132	0.41813	0.71202	0.91900
52	22.632	1.4977	0.41383	0.70471	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
62	23.437	1.5509	0.42855	0.72977	0.42200
67	22.092	1.4613	0.40377	0.68758	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
77	13.059	0.86409	0.23876	0.40659	0.50800
82	19.398	1.2175	0.33640	0.57286	0.58300
92	15.148	1.0024	0.27698	0.47167	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-107	15.074	0.99745	0.27561	0.46933	-1.0000
-112	15.148	1.0024	0.27698	0.47167	-1.0000
-122	15.198	1.0057	0.27789	0.47322	-1.0000
-127	15.203	1.0061	0.27799	0.47338	-1.0000
-137	15.138	1.0017	0.27680	0.47136	-1.0000
-142	15.093	0.99877	0.27597	0.46996	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
107	15.073	0.99745	0.27561	0.46933	0.39800
112	15.148	1.0024	0.27698	0.47167	0.43100
122	15.198	1.0057	0.27789	0.47322	0.44900
127	15.203	1.0061	0.27799	0.47338	0.48600
137	15.138	1.0017	0.27680	0.47136	0.52200
142	15.093	0.99877	0.27597	0.46996	0.58800
-152	15.163	1.0034	0.27725	0.47213	-1.0000
-157	15.163	1.0034	0.27725	0.47213	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
-152	15.163	1.0034	0.27725	0.47213	-1.0000
-157	15.163	1.0034	0.27725	0.47213	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
167	15.158	1.0031	0.27716	0.47198	0.79300
172	15.158	1.0031	0.27716	0.47198	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PD	PL/PTF	PL/PTP	X/DMAX
182	14.333	0.94848	0.26208	0.44629	0.79300
187	14.273	0.94451	0.26098	0.44442	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

FG-DI 895.26   FIC 994.25   SIGMA FC 4.0455   FTARE 2.6081   DSM 2.4095   CFM 0.0021176

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	20.299	1.3470	0.34027	0.58763	0.72200
37	23.188	1.5387	0.38870	0.67127	0.82000
47	24.452	1.6226	0.40990	0.70788	0.91900
52	24.242	1.6087	0.40628	0.70191	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	24.912	1.6531	0.41761	0.72120	0.42200
67	22.399	1.4863	0.37546	0.64841	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	14.195	0.94131	0.23779	0.41066	0.50800
82	20.059	1.3310	0.33625	0.58069	0.58300
92	15.120	1.0033	0.25346	0.43772	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	15.065	0.99969	0.25254	0.43613	-1.0000
-112	15.160	1.0060	0.25413	0.43888	-1.0000
-122	15.195	1.0083	0.25472	0.43989	-1.0000
-127	15.150	1.0053	0.25396	0.43859	-1.0000
-137	15.045	0.99836	0.25220	0.43555	-1.0000
-162	15.045	0.99836	0.25220	0.43555	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	15.065	0.99969	0.25254	0.43613	0.39800
112	15.160	1.0060	0.25413	0.43888	0.43100
122	15.195	1.0083	0.25472	0.43989	0.44900
127	15.150	1.0053	0.25396	0.43859	0.48600
137	15.045	0.99836	0.25220	0.43555	0.52200
142	15.045	0.99836	0.25220	0.43555	0.58800
152	15.120	1.0033	0.25346	0.43772	1.0000
157	15.125	1.0037	0.25345	0.43786	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.120	1.0033	0.25346	0.43772	-1.0000
-157	15.125	1.0037	0.25355	0.43786	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.120	1.0033	0.25346	0.43772	0.79300
172	15.110	1.0027	0.25329	0.43743	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.455	0.95922	0.24232	0.41847	0.79300
187	14.400	0.95557	0.24139	0.41689	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

(F-D) 1129.0   FIC 1133.2   SIGMA IC 3.8962   FTAPF 2.4507   DSM 2.3518   CFM 0.3321222

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	20.170	1.3392	0.33610	0.57443	0.72200
37	23.312	1.5478	0.38847	0.66392	0.82000
47	24.651	1.6367	0.41078	0.70205	0.91900
52	24.446	1.6231	0.40736	0.69622	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	25.061	1.6639	0.41761	0.71372	0.42200
67	22.393	1.4861	0.37298	0.63746	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	14.233	0.94477	0.23712	0.40526	0.50800
82	20.145	1.3375	0.33569	0.57372	0.58300
92	15.094	1.0022	0.25152	0.42987	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	15.074	1.0008	0.25119	0.42930	-1.0000
-112	15.164	1.0068	0.25269	0.43187	-1.0000
-122	15.174	1.0075	0.25286	0.43215	-1.0000
-127	15.114	1.0035	0.25186	0.43044	-1.0000
-137	15.019	0.99719	0.25027	0.42774	-1.0000
-142	15.014	0.99686	0.25019	0.42760	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	15.074	1.0008	0.25119	0.42930	0.39800
112	15.164	1.0068	0.25269	0.43187	0.43100
122	15.174	1.0075	0.25286	0.43215	0.44900
127	15.114	1.0035	0.25186	0.43044	0.48600
137	15.019	0.99719	0.25027	0.42774	0.52200
142	15.014	0.99686	0.25019	0.42760	0.58800
-152	15.089	1.0018	0.25166	0.43033	-1.0000
-157	15.094	1.0022	0.25152	0.42987	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.089	1.0018	0.25166	0.42973	-1.0000
-157	15.094	1.0022	0.25152	0.42987	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.094	1.0022	0.25152	0.42987	0.79300
172	15.094	1.0022	0.25152	0.42987	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.454	0.95970	0.24087	0.41166	0.79300
182	14.412	0.95738	0.24029	0.41066	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS
IF-DI 1143.4   FIC 1144.3   SIGMA IC 4.1131   ETAPF 2.9106   DSM 2.3366   CFM 1.9921232

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	19.266	1.2749	0.35158	0.60008	0.72200
37	21.956	1.4529	0.40066	0.68386	0.82000
47	22.826	1.5105	0.41654	0.71096	0.91900
52	22.606	1.4960	0.41253	0.70411	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
52	23.421	1.5499	0.42740	0.72949	0.42200
67	22.041	1.4586	0.40222	0.68651	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER C.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	13.075	0.86530	0.23862	0.40728	0.50800
82	18.411	1.2184	0.33598	0.57346	0.58300
92	15.151	1.0026	0.27649	0.47192	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	15.041	0.99536	0.27448	0.46849	-1.0000
-112	15.136	1.0016	0.27621	0.47145	-1.0000
-122	15.211	1.0066	0.27758	0.47379	-1.0000
-127	15.191	1.0053	0.27722	0.47316	-1.0000
-137	15.156	1.0030	0.27658	0.47207	-1.0000
-142	15.121	1.0007	0.27594	0.47098	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	15.041	0.99536	0.27448	0.46849	0.39800
112	15.136	1.0016	0.27621	0.47145	0.43100
122	15.211	1.0066	0.27758	0.47379	0.44900
127	15.191	1.0053	0.27722	0.47316	0.48600
137	15.156	1.0030	0.27658	0.47207	0.52200
142	15.121	1.0007	0.27594	0.47098	0.58800

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	15.161	1.0035	0.27667	0.47273	-1.0000
-157	15.151	1.0026	0.27649	0.47192	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
162	15.156	1.0030	0.27658	0.47207	0.79300
172	15.156	1.0030	0.27658	0.47207	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
182	14.326	0.94804	0.26143	0.44622	0.79300
187	14.216	0.94076	0.25942	0.44279	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FGD 1003.7   FID 996.03   SIGMA ID 5.4347   FTARE 2.2917   DSM 2.4076   CFM 0.0021173

R.24-5

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	17.408	1.1549	0.37200	0.63559	0.72200
37	21.368	1.3442	0.43232	0.73595	0.82000
42	20.683	1.3651	0.42571	0.75129	0.91900
52	20.293	1.3397	0.43121	0.73674	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
52	19.698	1.3001	0.41877	0.71551	0.42200
67	17.828	1.1767	0.37902	0.64758	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	11.262	0.74327	0.23942	0.40906	0.50800
82	15.838	1.0433	0.33607	0.57420	0.58300
92	15.198	1.0031	0.32310	0.55204	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	15.228	1.0050	0.32374	0.55313	-1.0000
-112	15.318	1.0110	0.32565	0.55640	-1.0000
-122	15.333	1.0120	0.32597	0.55695	-1.0000
-127	15.243	1.0060	0.32406	0.55368	-1.0000
-137	15.123	0.99811	0.32150	0.54932	-1.0000
-142	15.159	1.0004	0.32225	0.55059	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	15.228	1.0050	0.32374	0.55313	0.39800
112	15.318	1.0110	0.32561	0.55640	0.43100
122	15.333	1.0120	0.32597	0.55695	0.44900
127	15.243	1.0060	0.32406	0.55368	0.48600
137	15.123	0.99811	0.32150	0.54932	0.52200
142	15.159	1.0004	0.32225	0.55059	0.58800
152	15.183	1.0021	0.32278	0.55150	-1.0000
157	15.198	1.0024	0.32289	0.55168	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.183	1.0021	0.32278	0.55150	-1.0000
-157	15.198	1.0024	0.32289	0.55168	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.183	1.0021	0.32278	0.55150	0.79300
172	15.193	1.0021	0.32278	0.55150	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.137	0.93309	0.30056	0.51353	0.79300
192	14.117	0.93177	0.30013	0.51291	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

(F-D) 780.60   FIC 775.33   SIGMA IC 4.2880   FTAPE 2.4461   DSM 2.4030   CFM 0.0021176

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	16.430	1.0982	0.39282	0.67924	0.72200
37	18.622	1.2340	0.44545	0.76005	0.82000
47	18.375	1.2575	0.45395	0.77454	0.91900
52	18.735	1.2456	0.44964	0.76719	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	17.725	1.1746	0.42404	0.72351	0.42200
67	16.113	1.0676	0.38540	0.65758	0.67900

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	9.7973	0.64927	0.23439	0.39991	0.50800
82	21.491	1.4235	0.51388	0.87680	0.58300
92	15.115	1.0017	0.36159	0.61696	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	15.085	0.99967	0.36087	0.61573	-1.0000
-112	15.175	1.0056	0.36303	0.61941	-1.0000
-122	15.160	1.0046	0.36267	0.61879	-1.0000
-127	15.140	1.0033	0.36219	0.61798	-1.0000
-137	15.045	0.99702	0.35992	0.61410	-1.0000
-142	15.020	0.99536	0.35932	0.61308	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	15.085	0.99967	0.36087	0.61573	0.39800
112	15.175	1.0056	0.36303	0.61941	0.43100
122	15.160	1.0046	0.36267	0.61879	0.44900
127	15.140	1.0033	0.36219	0.61798	0.48600
137	15.045	0.99702	0.35992	0.61410	0.52200
142	15.020	0.99536	0.35932	0.61308	0.58800
-152	15.120	1.0020	0.36171	0.61716	-1.0000
-157	15.115	1.0017	0.36159	0.61696	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.120	1.0020	0.36171	0.61716	-1.0000
-157	15.115	1.0017	0.36159	0.61696	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.115	1.0017	0.36159	0.61696	0.79300
172	15.115	1.0017	0.36159	0.61696	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.124	0.92941	0.33551	0.57245	0.79300
187	13.794	0.92675	0.33455	0.57082	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FG-21 657.84   FIC 653.31   SIGMA FC 3.5707   FTABE 2.2184   DSM 2.3147   CFM 0.0021249

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	16.336	1.0623	0.42389	0.71953	0.72200
37	17.666	1.1703	0.46657	0.79156	0.82000
47	17.956	1.1902	0.47490	0.80500	0.91900
52	17.991	1.1945	0.47635	0.80119	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	16.776	1.1114	0.44345	0.75168	0.42200
67	15.666	1.0378	0.41411	0.70196	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	8.6397	0.57235	0.22838	0.38712	0.50800
82	22.575	1.4900	0.59489	1.0084	0.58300
92	15.121	1.0017	0.39971	0.67756	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	15.021	0.99510	0.39706	0.67306	-1.0000
-112	15.086	0.99941	0.39878	0.67597	-1.0000
-122	15.086	0.99941	0.39878	0.67597	-1.0000
-127	15.116	1.0014	0.39958	0.67731	-1.0000
-137	15.126	1.0021	0.39984	0.67776	-1.0000
-142	15.096	1.0001	0.39905	0.67642	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	15.021	0.99510	0.39706	0.67306	0.39800
112	15.086	0.99941	0.39878	0.67597	0.43100
122	15.086	0.99941	0.39878	0.67597	0.44900
127	15.116	1.0014	0.39958	0.67731	0.48600
137	15.126	1.0021	0.39984	0.67776	0.52200
142	15.096	1.0001	0.39905	0.67642	0.58800
152	15.111	1.0011	0.39966	0.67750	1.0300
157	15.121	1.0017	0.39971	0.67756	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.111	1.0011	0.39966	0.67709	-1.0000
-157	15.121	1.0017	0.39971	0.67756	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
162	15.126	1.0021	0.39984	0.67776	0.79300
172	15.126	1.0021	0.39984	0.67776	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	13.996	0.92720	0.36997	0.62713	0.79300
187	13.396	0.92058	0.36733	0.62265	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FE-01 566.97   FIC 559.75   SIGMA IC 4.0742   FTAPE 2.7868   DSM 2.3600   CFM 0.9921227

373

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	16.301	1.0573	0.50220	0.84892	0.72200
37	16.571	1.0950	0.52009	0.87917	0.82000
47	16.696	1.1026	0.52370	0.88527	3.91900
52	16.656	1.1006	0.52276	0.89368	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	16.391	1.0831	0.51444	0.86962	0.42200
67	16.136	1.0662	0.50644	0.85609	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	13.531	0.89406	0.42466	0.71785	0.50800
82	18.201	1.2027	0.57126	0.96565	0.58300
92	15.171	1.0025	0.47615	0.80688	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	14.806	0.97834	0.46464	0.78551	-1.0000
-112	14.756	0.97503	0.46312	0.78286	-1.0000
-122	14.776	0.97635	0.46375	0.78392	-1.0000
-127	15.066	0.99420	0.47222	0.79825	-1.0000
-137	15.091	0.99717	0.47364	0.80063	-1.0000
-142	15.046	0.99420	0.47222	0.79825	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	14.806	0.97834	0.46464	0.78551	0.39800
112	14.756	0.97503	0.46312	0.78286	0.43100
122	14.776	0.97635	0.46375	0.78392	0.44900
127	15.066	0.99420	0.47222	0.79825	0.48600
137	15.091	0.99717	0.47364	0.80063	0.52200
142	15.046	0.99420	0.47222	0.79825	0.58800
152	15.101	1.0021	0.47442	0.80543	1.0000
157	15.196	1.0025	0.47442	0.80543	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-152	15.181	1.0031	0.47466	0.80541	-1.0000
-157	15.196	1.0035	0.47662	0.80548	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
167	15.176	1.0028	0.47630	0.80514	0.79300
172	15.191	1.0031	0.47646	0.80541	0.84400

>ADDITIONAL PRESSURE RATIOS , 30 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
182	13.936	0.92414	0.43895	0.74199	0.79300
187	13.636	0.90100	0.42796	0.72342	0.84400

>STATION 5 , MEASURED THRUST PARAMETERS

(F-D) 411.06   FTS 406.02   SIGMA IC 3.5763   FTAPF 2.6696   DSM 2.3929   CFM 0.0021182

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADWELL   REC 10/25/79 02:26:30.657   FAC 8X6X1   PGM C036   PDG 1512

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.569	1.0265	0.56441	0.95982	0.72200
37	15.739	1.0358	0.56949	0.56846	0.82000
47	15.754	1.0398	0.57112	0.97123	0.91900
52	15.769	1.0397	0.57167	0.57216	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
53	15.624	1.0302	0.56641	0.96322	0.42200
63	15.559	1.0259	0.56405	0.95921	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.613	0.89758	0.49351	0.83924	0.50800
82	17.395	1.1469	0.63060	1.0724	0.58300
92	15.204	1.0025	0.55118	0.93731	2.67000

>ADDITIONAL PRESSURE RATIOS , FOREBODY SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.794	0.97543	0.53631	0.91202	-1.0000
-112	14.724	0.97081	0.53377	0.90771	-1.0000
-122	14.764	0.97345	0.53522	0.91017	-1.0000
-127	15.110	0.99027	0.54447	0.92590	-1.0000
-137	15.044	0.99102	0.54537	0.92744	-1.0000
-142	14.959	0.98631	0.54229	0.92220	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.794	0.97543	0.53631	0.91202	0.39800
112	14.724	0.97081	0.53377	0.90771	0.42100
122	14.764	0.97345	0.53522	0.91017	0.44900
127	15.019	0.99027	0.54447	0.92590	0.48600
137	15.044	0.99192	0.54537	0.92744	0.52200
142	14.959	0.98631	0.54229	0.92220	0.58800
152	15.204	1.0025	0.55118	0.93731	1.0000
152	15.204	1.0025	0.55118	0.93731	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.204	1.0025	0.55118	0.93731	-1.0000
-152	15.204	1.0025	0.55118	0.93731	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.204	1.0025	0.55118	0.93731	0.79300
172	15.204	1.0025	0.55118	0.93731	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.208	0.93683	0.51509	0.87594	0.79300
187	13.863	0.91408	0.50257	0.85466	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

(C-D) TPP.79   FIC 282.30   SIGMA IC 2.5607   FTARE 2.481P   DSM 2.4093   CFM 0.9921170

NASA-LEWIS   PRELIMINARY DATA   06/13/79   CADDELL   PEC 10/25/79 02:29:19.556   FAC RX6RI   PGM C934   PNG 1513

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.906	1.0452	0.57607	0.83712	0.72200
37	16.391	1.0932	0.59702	0.86758	0.82000
47	16.491	1.0998	0.60967	0.87287	0.91900
52	16.456	1.0982	0.59976	0.87155	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	16.256	1.0749	0.59247	0.86096	0.42200
67	15.991	1.0574	0.59281	0.84692	1.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.716	0.90696	0.49989	0.72642	0.50800
82	17.471	1.1553	0.63675	0.92530	0.58300
92	15.161	1.0025	0.55256	0.80296	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.816	0.97971	0.53998	0.78469	-1.0000
-112	14.766	0.97640	0.53816	0.78204	-1.0000
-122	14.791	0.97806	0.53907	0.78336	-1.0000
-127	15.066	0.99492	0.54837	0.79687	-1.0000
-137	15.076	0.99600	0.54046	0.79846	-1.0000
-142	15.046	0.99492	0.54837	0.79687	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.816	0.97971	0.53998	0.78469	0.39800
112	14.766	0.97640	0.53816	0.78204	0.43100
122	14.791	0.97806	0.53907	0.78336	0.44900
127	15.266	0.99492	0.54837	0.79687	0.48600
137	15.276	0.99600	0.54046	0.79846	0.52200
142	15.246	0.99492	0.54837	0.79687	0.58800
152	15.146	1.0029	0.55074	0.80323	1.0000
157	15.171	1.0032	0.55292	0.80349	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.166	1.0029	0.55274	0.80323	-1.0000
-157	15.171	1.0032	0.55292	0.80349	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.171	1.0032	0.55292	0.80349	0.79300
172	15.166	1.0029	0.55274	0.80323	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.171	0.93705	0.51647	0.75052	0.79300
187	13.951	0.91589	0.50481	0.73357	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS

FG=0] 332.29   FIC 327.55   SIGMA FC 4.5222   FTAPE 2.4420   DSM 2.2992   CFM 0.0021240

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.741	1.0409	0.49421	0.70857	0.72200
37	17.116	1.1318	0.53740	0.77049	0.82000
47	17.401	1.1507	0.54635	0.78332	0.91900
52	17.376	1.1490	0.54556	0.78220	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	16.896	1.1173	0.53049	0.76058	0.42200
67	16.021	1.0594	0.50301	0.72118	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.615	0.99029	0.42747	0.61289	0.50800
82	18.226	1.2052	0.57226	0.82047	0.58300
92	15.192	1.0038	0.47662	0.68336	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.855	0.98233	0.46642	0.66872	-1.0000
-112	14.910	0.97935	0.46500	0.66669	-1.0000
-122	14.825	0.99034	0.46547	0.66737	-1.0000
-127	15.080	0.99721	0.47368	0.67885	-1.0000
-137	15.125	1.0002	0.47490	0.68088	-1.0000
-142	15.105	0.99887	0.47427	0.67998	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.855	0.98233	0.46642	0.66872	0.39800
112	14.910	0.97935	0.46500	0.66669	0.43100
122	14.825	0.99034	0.46547	0.66737	0.44900
127	15.080	0.99721	0.47368	0.67885	0.48690
137	15.125	1.0002	0.47490	0.68088	0.52200
142	15.105	0.99887	0.47427	0.67998	0.58800
157	15.175	1.0035	0.47647	0.68313	1.0000
167	15.175	1.0035	0.47647	0.68313	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.175	1.0035	0.47647	0.68313	-1.0000
-157	15.175	1.0035	0.47647	0.68313	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.175	1.0035	0.47647	0.68313	0.79300
172	15.175	1.0035	0.47647	0.68313	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.125	0.93404	0.44349	0.63594	0.79300
187	13.849	0.91518	0.43453	0.62301	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

IF-D1 440.96   FIC 462.47   SIGMA IC 4.5114   FTAPE 3.1263   DSM 2.3631   CFS 0.0021209

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.345	0.94580	0.37545	0.54716	0.72200
37	17.830	1.1749	0.46639	0.67970	0.82000
47	18.339	1.2402	0.49230	0.71746	0.91900
52	19.754	1.2365	0.49086	0.71536	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	17.983	1.1788	0.46797	0.68199	0.42200
67	14.575	0.96098	0.38147	0.55594	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	8.7033	0.57383	0.22779	0.33197	0.50800
82	22.574	1.4884	0.59083	0.86104	0.58300
92	15.185	1.0012	0.39744	0.57920	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	15.130	0.99558	0.39521	0.57596	-1.0000
-112	15.153	0.99887	0.39652	0.57787	-1.0000
-122	15.220	1.0035	0.39835	0.58054	-1.0000
-127	15.215	1.0032	0.39822	0.58035	-1.0000
-137	15.175	1.0005	0.39717	0.57882	-1.0000
-142	15.125	0.99722	0.39587	0.57692	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	15.130	0.99558	0.39521	0.57596	0.39800
112	15.153	0.99887	0.39652	0.57787	0.43100
122	15.220	1.0035	0.39835	0.58054	0.44900
127	15.215	1.0032	0.39822	0.58035	0.48600
137	15.175	1.0005	0.39717	0.57882	0.52200
142	15.125	0.99722	0.39587	0.57692	0.58800
-152	15.185	1.0018	0.39770	0.57950	-1.0000
-157	15.195	1.0018	0.39770	0.57950	-1.0000

>ADDITIONAL PRESSURE RATIOS , CAM NOZZLE PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.185	1.0018	0.39770	0.57950	-1.0000
-157	15.195	1.0018	0.39770	0.57950	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.200	1.0022	0.39783	0.57978	0.79300
172	15.200	1.0022	0.39783	0.57978	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.710	0.96900	0.37192	0.54201	0.79300
187	14.380	0.92832	0.36851	0.53706	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

FF=D) 631.01   FIC 625.98   SIGMA IC 5.0252   FTAPF 2.7154   DSM 2.4129   CFM 0.0021167

380

NECA-LEMTS   PRELIMINARY DATA   06/12/79   CARDETT   FEC 10/25/79 22:33:23.603   FAC 996X1   PGM C034   DMG 1517

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.921	1.0543	0.33777	0.49504	0.72200
37	20.394	1.3306	0.42628	0.62858	0.82000
47	21.559	1.4276	0.45738	0.67443	0.91900
57	21.279	1.4091	0.45144	0.66567	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	21.694	1.4366	0.46024	0.67965	0.42200
67	17.442	1.1552	0.37003	0.54563	0.67033

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	11.173	0.73904	0.23703	0.34951	0.50800
82	15.801	1.0463	0.33522	0.49430	0.58300
92	15.131	1.0020	0.32100	0.47333	0.67000

>ADDITIONAL PRESSURE RATIOS , EXTERNAL SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	15.206	1.0069	0.32259	0.47568	-1.0000
-112	15.291	1.0126	0.32430	0.47834	-1.0000
-122	15.291	1.0126	0.32430	0.47834	-1.0000
-127	15.191	1.0059	0.32227	0.47521	-1.0000
-137	15.136	1.0023	0.32110	0.47349	-1.0000
-142	15.171	1.0046	0.32185	0.47458	-1.0000

>ADDITIONAL PRESSURE RATIOS , EXTERNAL INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	15.206	1.0069	0.32259	0.47568	0.39400
112	15.291	1.0126	0.32430	0.47834	0.43100
122	15.291	1.0126	0.32430	0.47834	0.44900
127	15.191	1.0059	0.32227	0.47521	0.48600
137	15.136	1.0023	0.32110	0.47349	0.52200
142	15.171	1.0046	0.32185	0.47458	0.58400
147	15.136	1.0023	0.32110	0.47349	-1.0000
152	15.191	1.0020	0.32100	0.47333	-1.0000

>ADDITIONAL PRESSURE RATIOS , EXTERNAL SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.136	1.0023	0.32110	0.47349	-1.0000
-157	15.131	1.0020	0.32100	0.47333	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.136	1.0023	0.32110	0.47349	0.79300
172	15.141	1.0026	0.32121	0.47364	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.250	0.94364	0.30232	0.44578	0.79300
187	14.235	0.94264	0.30200	0.44531	0.84400

>OPTIONS , MEASURED THRUST PARAMETERS
(F-T) 846.41   FIC 841.91   SIGMA IC 2.7353   FTEPF 2.2042   DSW 2.3103   CFW 0.3021251

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	11.432	0.75403	0.21378	0.31167	0.72200
37	22.935	1.5109	0.42832	0.62446	0.82000
47	26.216	1.5972	0.45282	0.66018	0.91900
52	23.520	1.5777	0.44730	0.65214	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	25.476	1.6803	0.47639	0.69454	0.42200
67	22.355	1.4745	0.41803	0.60966	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	12.698	0.83751	0.23744	0.34618	0.50800
82	17.919	1.1819	0.33509	0.48853	0.58700
92	15.179	1.0011	0.28384	0.41381	0.67902

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	15.169	1.0005	0.28365	0.41354	-1.0000
-112	15.264	1.0068	0.28543	0.41613	-1.0000
-122	15.284	1.0071	0.28580	0.41668	-1.0000
-127	15.229	1.0044	0.28477	0.41518	-1.0000
-137	15.144	0.99883	0.28318	0.41286	-1.0000
-142	15.149	0.99916	0.28328	0.41300	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	15.169	1.0005	0.28365	0.41354	0.39800
112	15.264	1.0068	0.28543	0.41613	0.42100
122	15.284	1.0081	0.28580	0.41668	0.44900
127	15.229	1.0044	0.28477	0.41518	0.48600
137	15.144	0.99883	0.28318	0.41286	0.52200
142	15.149	0.99916	0.28328	0.41300	0.58800
147	15.149	1.0005	0.28365	0.41354	0.72900
157	15.179	1.0011	0.28384	0.41381	-1.0000

>ADDITIONAL PRESSURE RATIOS , BOATTAIL PLUG

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.169	1.0005	0.28365	0.41354	-1.0000
-157	15.179	1.0011	0.28384	0.41381	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.184	1.0015	0.28393	0.41395	0.79300
172	15.174	1.0008	0.28374	0.41368	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVG WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.514	0.95727	0.27140	0.39568	0.79300
187	14.499	0.95629	0.27112	0.39527	0.84400

>ADDITIONAL PRESSURE RATIOS , MEASURED THRUST PARAMETERS

(F-DE) 1036.2	FIC 1033.4	SIGMA IC 6.5277	FTARE 3.4374	DSM 2.3289	CFN 0.9021239

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTE	PL/PTP	X/DMAX
32	12.684	0.83694	0.21412	0.31347	0.72200
37	23.157	1.5230	0.39052	0.57230	0.82000
47	26.124	1.7238	0.44101	0.64564	0.91900
52	25.947	1.7123	0.43805	0.64191	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTE	PL/PTP	X/DMAX
62	27.996	1.8497	0.47092	0.68943	0.42200
67	23.452	1.5475	0.39590	0.57960	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTE	PL/PTP	X/DMAX
77	14.135	0.93271	0.23862	0.34934	0.50800
82	19.924	1.3147	0.33635	0.49242	0.54300
92	15.206	1.0034	0.25670	0.37581	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTE	PL/PTP	DMAX
-107	15.251	1.0063	0.25746	0.37692	-1.0000
-112	15.326	1.0113	0.25973	0.37878	-1.0000
-122	15.321	1.0110	0.25864	0.37865	-1.0000
-127	15.251	1.0063	0.25746	0.37692	-1.0000
-137	15.171	1.0011	0.25611	0.37404	-1.0000
-142	15.186	1.0021	0.25636	0.37531	-1.0000

>ADDITIONAL PRESSURE RATIOS , EXTERNAL INLET

AVD WORD	PL	PL/PO	PL/PTE	PL/PTP	X/DMAX
107	15.251	1.0063	0.25746	0.37692	0.39800
112	15.326	1.0113	0.25973	0.37878	0.43100
122	15.321	1.0110	0.25864	0.37865	0.44900
127	15.251	1.0063	0.25746	0.37692	0.49600
137	15.171	1.0011	0.25611	0.37404	0.52200
142	15.196	1.0021	0.25636	0.37531	0.58800
152	15.231	1.0030	0.25661	0.37549	1.0000
157	15.206	1.0034	0.25670	0.37581	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTE	PL/PTP	X/DMAX
-152	15.231	1.0030	0.25661	0.37549	-1.0000
-157	15.206	1.0034	0.25670	0.37581	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG. SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTE	PL/PTP	X/DMAX
167	15.206	1.0034	0.25670	0.37581	0.79300
172	15.211	1.0037	0.25678	0.37593	0.84400

>ADDITIONAL PRESSURE RATIOS , 86 DEG. SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTE	PL/PTP	X/DMAX
182	14.726	0.97167	0.24859	0.36392	0.79300
187	14.726	0.97167	0.24859	0.36393	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

(F-D) 1223.0   FIC 1158.6   SIGMA IC 5.4523   FTARE 2.0345   DSM 2.3575   CFS 0.0021211

383

NASA-LEWIS   PRELIMINARY DATA   06/13/73   GENDELL   REC 10/25/75 02:40:13.493   FAC STAXI   PGM C036   RDC 1520

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.675	0.83527	0.21170	0.31064	0.72200
37	23.469	1.5466	0.39108	0.57517	0.82000
47	26.394	1.7397	0.44067	0.64661	0.91900
52	26.189	1.7258	0.43741	0.63183	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
62	28.044	1.8481	0.46840	0.68730	0.42200
67	23.470	1.5466	0.39148	0.57444	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	14.265	0.94006	0.23826	0.34961	0.50800
82	20.135	1.3268	0.33629	0.49345	0.58800
92	15.215	1.0027	0.25412	0.37299	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	15.270	1.0063	0.25504	0.37424	-1.0000
-112	15.340	1.0109	0.25621	0.37595	-1.0000
-122	15.340	1.0109	0.25621	0.37595	-1.0000
-127	15.255	1.0053	0.25479	0.37387	-1.0000
-137	15.165	0.99937	0.25329	0.37166	-1.0000
-142	15.210	1.0023	0.25404	0.37277	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	15.270	1.0063	0.25504	0.37424	0.39800
112	15.340	1.0109	0.25621	0.37595	0.43100
122	15.340	1.0109	0.25621	0.37595	0.44900
127	15.255	1.0053	0.25479	0.37387	0.48600
137	15.165	0.99937	0.25329	0.37166	0.52200
142	15.210	1.0023	0.25404	0.37277	0.58800
152	15.205	1.0020	0.25396	0.37266	1.0000
162	15.210	1.0023	0.25404	0.37277	1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.205	1.0020	0.25396	0.37264	-1.0000
-152	15.210	1.0023	0.25404	0.37277	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.205	1.0020	0.25396	0.37264	0.79300
172	15.200	1.0017	0.25387	0.37252	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.720	0.97005	0.24586	0.36076	0.79300
187	14.725	0.97038	0.24594	0.36088	0.84400

SECTION 5 , MEASURED THRUST PARAMETERS

FG-D) 1216.3   FIC 1211.7   SIGMA IG 4.5295   STAPF 2.3603   PSW 2.3603   FSW 0.3321393

NASA-LEWIS   PRELIMINARY DATA   06/12/79   CADDELL   PFC 10/25/79 02:42:34.307   FGC RV6VI   PGR C034   RDG 1521

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	12.102	0.79999	0.22131	0.32198	3.72203
37	22.306	1.5195	0.42036	0.61139	0.82303
47	24.612	1.6270	0.45009	0.65463	0.91900
52	24.352	1.6099	0.44533	0.64771	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	F	PL/PO	PL/PTF	PL/PTP	./DMAX
62	26.228	1.7338	0.47964	0.69761	0.42200
67	23.471	1.5483	0.42832	0.62296	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.052	0.86284	0.23869	0.34717	0.50800
82	18.445	1.2193	0.33731	0.49059	0.58300
92	15.153	1.0017	0.27712	0.40305	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	15.168	1.0027	0.27739	0.40345	-1.0000
-112	15.248	1.0080	0.27886	0.40558	-1.0000
-122	15.273	1.0097	0.27931	0.40625	-1.0000
-127	15.209	1.0054	0.27812	0.40452	-1.0000
-137	15.113	0.99990	0.27630	0.40189	-1.0000
-142	15.143	1.0011	0.27694	0.40279	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	15.168	1.0027	0.27739	0.40345	0.39800
112	15.248	1.0080	0.27886	0.40558	0.43100
122	15.273	1.0097	0.27931	0.40625	0.44900
127	15.209	1.0054	0.27812	0.40452	0.48680
137	15.113	0.99990	0.27630	0.40199	0.52700
142	15.143	1.0011	0.27694	0.40279	0.58800
-152	15.173	1.0031	0.27749	0.40359	-1.0000
-157	15.163	1.0024	0.27730	0.40332	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE FLAP

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.173	1.0031	0.27749	0.40359	-1.0000
-157	15.163	1.0024	0.27730	0.40332	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.163	1.0024	0.27730	0.40332	0.79300
172	15.163	1.0024	0.27730	0.40332	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.543	0.96139	0.26594	0.38682	0.79300
187	14.523	0.96007	0.26550	0.38629	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

IF=71 1074.8   FIC 1071.3   SICMA IC 3.6969   FTAPF 3.0971   DSW 2.3268   CFM 0.0021236

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
32	14.877	0.98098	0.35477	0.52251	0.72200
37	19.444	1.2162	0.43986	0.66778	0.82000
47	19.785	1.2346	0.47181	0.69497	0.91900
52	19.688	1.2990	0.46942	0.69136	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
62	19.355	1.2762	0.46155	0.67976	0.42200
67	15.393	1.3150	0.36706	0.54061	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
77	9.8629	0.65034	0.23520	0.34640	0.50800
82	21.196	1.3976	0.50565	0.74442	0.58300
92	15.202	1.0024	0.26253	0.53393	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-107	15.187	1.0014	0.36317	0.53340	-1.0000
-112	15.242	1.0064	0.26396	0.53694	-1.0000
-122	15.293	1.0084	0.36468	0.53709	-1.0000
-127	15.242	1.0051	0.36340	0.53523	-1.0000
-137	15.147	0.99879	0.36122	0.53200	-1.0000
-142	15.142	0.99946	0.36110	0.53182	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
107	15.187	1.0014	0.36217	0.53340	0.39800
112	15.242	1.0064	0.36396	0.53604	0.43100
122	15.293	1.0084	0.36468	0.53709	0.44900
127	15.242	1.0051	0.36340	0.53532	0.48600
137	15.147	0.99879	0.36122	0.53200	0.52200
142	15.142	0.99946	0.36110	0.53182	0.58800
147	15.147	0.9971	0.36241	0.53206	-1.0000
152	15.202	1.0014	0.36253	0.53393	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE LIP

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
-147	15.187	1.0021	0.36241	0.53375	-1.0000
-152	15.202	1.0024	0.36253	0.53393	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
157	15.207	1.0027	0.36265	0.53410	0.79300
177	15.207	1.0027	0.36265	0.53410	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/P0	PL/PTF	PL/PTP	X/DMAX
182	14.267	0.94073	0.34022	0.50107	0.79300
182	14.252	0.93974	0.33986	0.50054	0.84400

>OPTION 5 , MEASURED THRUST PARAMETERS
IF-DI 718.22   FIG 713.22   SIGMA IF 3.7438   FTARE 2.6279   DSW 2.3895   CSW 0.9921186

386

NASA-LEWIS   PRELIMINARY DATA   04/13/79   CAPPELLI   REC 10/25/79 02:45:23.982   FAC 8Y6VI   PGM C036   DDG 1524

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	14.392	0.94718	0.37635	0.55014	0.72200
37	17.973	1.1762	0.46726	0.68219	0.82000
47	18.819	1.2384	0.49297	0.71930	0.91900
52	18.763	1.2348	0.49063	0.71720	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
52	17.868	1.1759	0.46723	0.68299	0.42200
67	14.657	0.96463	0.38329	0.56027	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	8.7493	0.57581	0.22879	0.33444	0.50800
82	21.938	1.4438	0.57366	0.83857	0.58300
92	15.222	1.0018	0.39925	0.58187	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	15.177	0.99886	0.39688	0.58015	-1.0000
-112	15.277	1.0054	0.39949	0.58397	-1.0000
-122	15.287	1.0061	0.39975	0.58436	-1.0000
-127	15.262	1.0045	0.39910	0.58340	-1.0000
-137	15.197	0.99951	0.39714	0.58053	-1.0000
-142	15.147	0.99688	0.39609	0.57900	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	15.177	0.99886	0.39688	0.58015	0.39800
112	15.277	1.0054	0.39949	0.58397	0.43100
122	15.287	1.0061	0.39975	0.58436	0.44900
127	15.262	1.0045	0.39910	0.58340	0.48600
137	15.197	0.99951	0.39714	0.58053	0.52200
142	15.147	0.99688	0.39609	0.57900	0.58800
-152	15.222	1.0021	0.39919	0.58187	-1.0000
-153	15.232	1.0025	0.39925	0.58275	-1.0000

>ADDITIONAL PRESSURE RATIOS , FAN NOZZLE PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.232	1.0021	0.39919	0.58206	-1.0000
-153	15.237	1.0025	0.39832	0.58275	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.217	1.0015	0.39792	0.58164	0.74300
172	15.222	1.0018	0.39805	0.58187	0.84400

>ADDITIONAL PRESSURE RATIOS , 80 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.237	0.93698	0.37229	0.54421	0.79300
192	14.182	0.93336	0.37085	0.54211	0.84400

>SECTION 5 , MEASURED THRUST PARAMETERS

FG=H 622.06   FIC 624.11   SFCMP IC 2.5889   FTAPS 2.3615   DSM 2.3873   CFM 0.0021187

>ADDITIONAL PRESSURE RATIOS , PRIMARY PLUG

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
32	15.810	1.0407	0.49371	0.70952	0.72230
37	17.180	1.1309	0.53653	0.77102	0.82000
47	17.465	1.1496	0.54541	0.78382	0.91900
52	17.435	1.1477	0.54447	0.78247	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
52	16.945	1.1154	0.52916	0.76047	0.42200
67	16.085	1.0589	0.50230	0.72187	0.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
77	13.599	0.89513	0.42466	0.61030	0.50800
82	18.396	1.2103	0.57414	0.82512	0.58300
92	15.225	1.0021	0.47543	0.68326	0.67000

>ADDITIONAL PRESSURE RATIOS , EJECTOR SHROUD

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-107	14.890	0.98009	0.46497	0.66822	-1.0000
-112	14.860	0.97811	0.46403	0.66687	-1.0000
-122	14.890	0.98009	0.46497	0.66822	-1.0000
-127	15.125	0.99556	0.47231	0.67877	-1.0000
-137	15.160	0.99786	0.47340	0.68034	-1.0000
	15.145	0.99687	0.47293	0.67966	-1.0000

>ADDITIONAL PRESSURE RATIOS , ECPERCDY IPLEY

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
107	14.890	0.98009	0.46497	0.66822	0.39800
112	14.860	0.97811	0.46403	0.66687	0.43100
122	14.890	0.98009	0.46497	0.66822	0.44900
127	15.125	0.99556	0.47231	0.67877	0.48600
137	15.160	0.99786	0.47340	0.68034	0.52200
142	15.145	0.99687	0.47293	0.67966	0.58800
-152	15.225	1.0021	0.47543	0.68326	-1.0000
-157	15.230	1.0018	0.47524	0.68303	-1.0000

>ADDITIONAL PRESSURE RATIOS , EVICKLE-FIRE

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
-152	15.225	1.0021	0.47543	0.68326	-1.0000
-157	15.230	1.0018	0.47524	0.68303	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
167	15.215	1.0015	0.47512	0.68281	0.79300
172	15.210	1.0012	0.47496	0.68258	0.84400

>ADDITIONAL PRESSURE RATIOS , 90 DEG SHROUD LOCATION

AVD WORD	PL	PL/PO	PL/PTF	PL/PTP	X/DMAX
182	14.169	0.93267	0.44247	0.63580	0.79300
187	13.894	0.91390	0.43357	0.62309	0.84405

>OPTION 5 , MEASURED THRUST PARAMETERS

FF-DL 471.03   FIC 466.25   SIGMA IC 3.9370   FTAPF 2.6271   DF# 2.3503   CF# 0.0021210

PRELIMINARY DATA   24/13/70   CAPDETT   DFC 10/25/75 02:47:11.48P   EAT REGVT   PGR 603.   DPC 1926

>ADDITIONAL PRESSURE RATIOS , PRIMARY RING

AVD NDRD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
32	15.018	1.0441	0.57477	0.83296	3.72200
37	14.418	1.0437	0.50658	0.84457	3.82000
47	16.538	1.0997	0.59985	0.96931	3.91900
47	14.443	1.0540	0.50806	0.86800	1.0170

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER I.D.

AVD NDRD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
62	16.288	1.0752	0.59185	0.85772	0.42200
67	16.013	1.0572	0.58186	0.84323	3.67000

>ADDITIONAL PRESSURE RATIOS , FLOW SPLITTER O.D.

AVD NDRD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
77	13.711	0.90507	0.49823	0.72204	0.50800
82	17.454	1.1521	0.63421	0.91910	0.58300
82	15.177	1.0018	0.55150	0.74924	0.67000

AVD NDRD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-107	16.842	1.07971	0.53353	0.78158	-1.0000
-112	16.797	1.07674	0.53768	0.77921	-1.0000
-117	14.817	2.9780A	0.53861	0.78077	-1.0000
-127	15.058	0.90391	0.54711	0.79791	-1.0000
-137	15.107	0.93722	0.54805	0.78544	-1.0000
-142	15.087	0.90580	0.54827	0.78440	-1.0000

>ADDITIONAL PRESSURE RATIOS , FOREBODY INLET

AVD NDRD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
107	16.842	0.97971	0.53932	0.78158	0.16600
112	16.797	2.97674	0.537268	0.77921	2.43100
117	14.817	2.9780A	0.53861	0.78677	3.44900
127	15.057	0.90391	0.54713	0.79791	0.48600
137	15.107	0.93722	0.54805	0.78544	0.52200
142	15.087	0.90580	0.54827	0.78440	0.58800

AVD NDRD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
-152	15.122	1.0018	0.55158	0.78924	-1.0000
-152	15.182	1.0022	0.55168	0.78580	-1.0000

>ADDITIONAL PRESSURE RATIOS , 20 DFG SHROUD LOCATION

AVD NDRD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
147	15.177	1.0018	0.55172	0.78924	3.79300
172	15.177	1.0018	0.55150	0.78924	0.44400

>ADDITIONAL PRESSURE RATIOS , 80 DFG SHROUD LOCATION

AVD NDRD	PI	PI/PO	PI/PTF	PI/PTP	X/DMAX
102	14.107	2.93711	0.5154	0.74749	0.75200
172	13.802	0.91696	2.5067	0.73152	0.44403

POSITCH S. MEASURED THRUST PARAMETERS
ELP 212.71   SISPA LF 2.4211   STAPF 2.7069   PEW 0.001243